

**WARNING** Contains gas under pressure; may explode if heated. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May displace oxygen and cause rapid suffocation. **Prevention:** Obtain special instructions before use. DO NOT handle until all safety precautions have been read and understood. Avoid breathing spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. **Response:** IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If exposed or concerned: Get medical advice/attention. **Storage:** Store locked up. Protect from sunlight. Store in a well-ventilated place. **Disposal:** Dispose of contents/container to an approved waste disposal plant.



See the **SDS** for more info at/Voir la **FDS** pour plus d'info au: [wurth.ca](http://wurth.ca) or call/ou appelez: **1-800-263-5002**  
Manufactured for/Fabriqu e pour:

**Wurth Canada Limited/Limit e**  
345 Hanlon Creek Blvd, Guelph, ON, N1C 0A1

**ATTENTION** Contient un gaz sous pression; peut exploser sous l'effet de la chaleur. Peut provoquer une allergie cutan e. Susceptible de nuire   la fertilit  ou au f etus. Peut remplacer l'oxyg ne et causer une suffocation rapide. **Pr vention:** Se procurer les instructions avant utilisation. NE PAS manipuler avant d'avoir lu et compris toutes les pr cautions de s curit .  viter de respirer les pulv risations. Les v tements de travail contamin s ne devraient pas sortir du lieu de travail. Porter des gants de protection/des v tements de protection/ un  quipement de protection des yeux/du visage. **Intervention:** CONTACT AVEC LA PEAU: laver avec beaucoup d'eau. En cas d'irritation ou d' ruption cutan e: Consulter un m decin. Enlever les v tements contamin s et les laver avant r utilisation. En cas d'exposition prouv e ou suspect e: Consulter un m decin. **Entreposage:** Garder sous clef. Prot ger du rayonnement solaire. Stocker dans un endroit bien ventil . ** limination:**  liminer le contenu/le conteneur dans une installation d' limination des d chets agr e e.

**Not for retail sale/Pas pour la vente au d tail**  
**Made in USA/Fabriqu  aux  tats-Unis**

PME | 06.2019 | 892.76462 | V.4.0



## R-134A PERFORMANCE ENHANCER

## AMPLIFICATEUR DE PERFORMANCE R-134A

Net content/Contenu:

# 118 g (4.1 oz)

### **EN R-134A PERFORMANCE ENHANCER**

**Features:** An A/C system additive that provides faster cool-down rates and extends compressor life. Typical temperature reduction of 3 to 9 °C [37 to 48 °F]. Cleans and revitalizes A/C systems. Won't harm system components or recovery equipment. Compatible with mineral, ester and PAG oils.

**Uses:** For use with R-134a A/C systems only.

**Directions:** For use with charging hose (Art. No. 892.764305). Shake can well before use. Start vehicle engine and set A/C to maximum; the compressor must be engaged. Locate the blue LOW pressure service port and remove cap. Open charging hose valve fully to raise piercing pin and thread onto top of can. When ready, turn valve fully clockwise to pierce can. Once pierced, turning valve counter clockwise will allow product to flow. Before connecting to service port, open valve slightly and slowly fill hose with product to ensure air or moisture do not enter the system. Attach hose to LOW service port. Hold the can upside down and fully open the valve to dispense product into A/C system. Once can is empty, detach hose from service port and replace cover. Allow vehicle to run for at least 20 minutes to circulate product.

This information is based on our experience. Preliminary tests are advised before use. For more details, see the technical data sheet.

### **FR AMPLIFICATEUR DE PERFORMANCE R-134A**

**Caract ristiques:** Un additif pour syst mes d'A/C qui am liore la capacit  de refroidissement et prolonge la vie du compresseur. La r duction de la temp rature typique est de 3   9 °C [37   48 °F]. Nettoie et revitalise les syst mes A/C. Ne nuira pas les composants du syst me ou l' quipement de r cup ration. Compatible avec les huiles min rales, esters et PAG.

**Utilisations:** Pour une utilisation avec les syst mes d'A/C R-134a seulement.

**Mode d'emploi:** Utiliser avec le tuyau de remplissage (Art. No. 892.764305).

Bien agiter avant utilisation. D marrer le moteur du v hicule et r gler l'A/C sur max; le compresseur doit  tre engag e. Trouver le port de service bleue   pression basse et enlever le bouchon. Tourner la valve du tuyau de charge compl tement ouvert pour  lever la broche de percage. Enfiler le tuyau sur la canette. Lorsque vous  tes pr t, tourner le robinet compl tement dans le sens horaire pour percer la canette.

Une fois perc e, tourner la valve dans le sens antihoraire permettra le produit de s' couler. Avant de connecter au port de service, tourner la valve l g rement pour remplir le tuyau avec le produit pour assurer que l'air ou l'humidit  n'entrera pas dans le syst me. Fixer le tuyau au port de service   bas pression. Tenir la canette   l'envers et ouvrir compl tement la valve pour distribuer le produit dans le syst me. Une fois que la canette est vide, d tacher le tuyau du port de service et remplacer le couvercle. Laisser le v hicule en marche pendant au moins 20 minutes pour faire circuler le produit.

Cette information est bas e sur notre exp rience. Des tests pr c rables sont avis s avant l'utilisation. Pour plus de d tails, voir la fiche technique.

Art. 892.76462 083

