



ESK-50

Fast-acting epoxy resin

Résine époxy à action rapide

Art. 893.4801⁰⁸³



Net content/Contenu net:

50 mL (1.6 US fl oz)

PAF | 05/2022 | 893.4801 | V.6.0 (A) / V.7.0 (B) | WRMMS 2015

BONDING | COLLER | BONDING | COLLER

118 x 80,

10 mm overlap right

EN ESK-50

Uses: For adhering metals, a range of plastics, glass, ceramic, etc.

Directions: Surfaces must be free of dust, oil, grease or other contaminants. Use the included static mixing tube to ensure components are thoroughly mixed. Apply to surfaces to be bonded immediately after mixing. Press the bond uniformly until final strength is reached. **Open time:** 3.5 min **Working time:** 4 min **Curing time:** 60 min @ 23 °C (78 °F) **Final strength:** 48 h

Cautions: For work stoppages longer than 3 min, change the mixing tube.

This information is based on our experience. Preliminary tests are advised before use. For more details, see the technical data sheet.

**Not for retail sale/
Pas pour la vente au détail**

**Made in Switzerland/
Fabriqué en Suisse**

Imported by/Importé par:
Wurth Canada Limited/Limitée
345 Hanlon Creek Blvd, Guelph, ON, N1C 0A1

Read the Safety Data Sheet (SDS) before using this product.
/ Lire la Fiche de données de sécurité (FDS) avant d'utiliser ce produit.

Component A/Composant A



WARNING / ATTENTION

Component B/Composant B



DANGER / DANGER

BONDING | COLLER | BONDING | COLLER