

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

SECTION 1. IDENTIFICATION

Product name : SUPER RTV SILICONE, Red, 254 g
Product code : 893.3312
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Sealant
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 1
Skin sensitization : Sub-category 1A
Reproductive toxicity : Category 2
Specific target organ toxicity : Category 2 (Central nervous system, optic nerve)
- single exposure

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

Specific target organ toxicity : Category 2 (Blood, spleen)
- repeated exposure

GHS label elements

Hazard pictograms



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H317 May cause an allergic skin reaction.
H361d Suspected of damaging the unborn child.
H371 May cause damage to organs (Central nervous system, optic nerve).
H373 May cause damage to organs (Blood, spleen) through prolonged or repeated exposure.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P308 + P311 IF exposed or concerned: Call a doctor.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Calcium carbonate	Carbonic acid calcium salt	471-34-1	$\geq 10 - < 30$ *
Diiron trioxide	No data available	1309-37-1	$\geq 5 - < 10$ *
O,O',O''-(Methylsilyldyne)trioxime 2-pentanone	(4E,9E)-4,7,10-Trimethyl-7-[[[(E)-(pentan-2-ylidene)amino]oxy]-6,8-dioxa-5,9-diaza-7-silatri-deca-4,9-diene	37859-55-5	$\geq 1 - < 5$ *
Propane	Dimethylmethane	74-98-6	$\geq 1 - < 5$ *
2-Pentanone oxime	(E)-N-(pentan-2-ylidene)hydroxylamine	623-40-5	$\geq 1 - < 5$ *
2-Pentanone, O,O',O''-(ethenylsilyldyne)trioxime	No data available	58190-62-8	$\geq 1 - < 5$ *
(3-Aminopropyl)trimethoxysilane	Trimethoxyaminopropylsilane	13822-56-5	$\geq 1 - < 5$ *
Dimethylbis[(1-oxodecyl)oxy]stannane	Dimethyltindecaneate	68928-76-7	$\geq 0.1 - < 1$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/26/2023
5.0	08/30/2023	7749145-00009	Date of first issue: 01/27/2021

- In case of skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction. Suspected of damaging the unborn child. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
Metal oxides
Silicon oxides
Nitrogen oxides (NO_x)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/26/2023
5.0	08/30/2023	7749145-00009	Date of first issue: 01/27/2021

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapors/mists with a water spray jet. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation. If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing. Do not breathe spray. Do not swallow. Avoid contact with eyes. Wash skin thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

assessment
Keep away from water.
Protect from moisture.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.

Conditions for safe storage : Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases

Recommended storage temperature : 5 - 30 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium carbonate	471-34-1	TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA	10 mg/m ³ (Calcium carbonate)	CA AB OEL
		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m ³	CA BC OEL
		STEL	20 mg/m ³	CA BC OEL
Diiron trioxide	1309-37-1	TWA (Respirable)	5 mg/m ³	CA AB OEL
		TWA	5 mg/m ³	CA BC OEL

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version
5.0

Revision Date:
08/30/2023

SDS Number:
7749145-00009

Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

		(Fumes)	(Iron)	
		TWA (Dust)	5 mg/m ³ (Iron)	CA BC OEL
		STEL (Fumes)	10 mg/m ³ (Iron)	CA BC OEL
		TWAEV (fume and dust)	5 mg/m ³ (Iron)	CA QC OEL
		TWA (Respi- rable particu- late matter)	5 mg/m ³	ACGIH
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL
Dimethylbis[(1- oxoneodecyl)oxy]stannane	68928-76-7	TWA	0.1 mg/m ³ (Tin)	CA AB OEL
		STEL	0.2 mg/m ³ (Tin)	CA AB OEL
		TWAEV	0.1 mg/m ³ (Tin)	CA QC OEL
		STEV	0.2 mg/m ³ (Tin)	CA QC OEL
		TWA	0.1 mg/m ³ (Tin)	CA BC OEL
		STEL	0.2 mg/m ³ (Tin)	CA BC OEL
		TWA	0.1 mg/m ³ (Tin)	CA ON OEL
		TWA	0.1 mg/m ³ (Tin)	ACGIH
		STEL	0.2 mg/m ³ (Tin)	ACGIH

This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Calcium carbonate

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control param- eters / Permissible concentration	Basis
Methanol	67-56-1	TWA	200 ppm 262 mg/m ³	CA AB OEL
		STEL	250 ppm 328 mg/m ³	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	250 ppm	CA BC OEL
		STEV	250 ppm 328 mg/m ³	CA QC OEL
		TWAEV	200 ppm 262 mg/m ³	CA QC OEL
		TWA	200 ppm	ACGIH

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

		STEL	250 ppm	ACGIH
--	--	------	---------	-------

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : butyl-rubber

Break through time : > 480 min

Glove thickness : > 0.6 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

Appearance : aerosol

Propellant : Propane, Butane

Color : red

Odor : characteristic

Odor Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : No data available

Density : 1.25 g/cm³

Solubility(ies)
Water solubility : hydrolyzes

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/26/2023
5.0	08/30/2023	7749145-00009	Date of first issue: 01/27/2021

Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents. Hazardous decomposition products will be formed upon contact with water or humid air.
Conditions to avoid	:	Exposure to moisture. Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents Water

Hazardous decomposition products

Contact with water or humid air	:	2-Pentanone oxime Methyl Isobutyl Ketoxime Methanol
---------------------------------	---	---

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
---------------------	---	--

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

Components:

Calcium carbonate:

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Diiron trioxide:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:

- Acute oral toxicity : LD50 (Rat): 1,234 mg/kg
Method: OECD Test Guideline 425
- Acute dermal toxicity : LD50 (Rat): > 1,782 mg/kg
Remarks: Based on data from similar materials

Propane:

- Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min
Test atmosphere: gas

2-Pentanone oxime:

- Acute oral toxicity : LD50 (Rat): 1,133 mg/kg
Method: OECD Test Guideline 425
- Acute inhalation toxicity : LC50 (Rat): > 1.22 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

- Acute oral toxicity : LD50 (Rat): > 1,000 - < 2,000 mg/kg
Method: OECD Test Guideline 423
- Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: Directive 67/548/EEC, Annex V, B.3.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/26/2023
5.0	08/30/2023	7749145-00009	Date of first issue: 01/27/2021

Remarks: Based on data from similar materials

(3-Aminopropyl)trimethoxysilane:

Acute oral toxicity : LD50 (Rat, male): 3,030 mg/kg
Acute toxicity estimate (Humans): > 300 - 2,000 mg/kg
Method: Expert judgment
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat, female): > 0.145 mg/l
Exposure time: 6 h
Test atmosphere: vapor
Method: OECD Test Guideline 403
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit, male): 11,460 mg/kg

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Acute oral toxicity : LD50 (Rat): 190 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Calcium carbonate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Diiron trioxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Species : Rabbit
Result : No skin irritation

(3-Aminopropyl)trimethoxysilane:

Species : Rabbit

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

Method : OECD Test Guideline 404
Result : Skin irritation

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 431

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : No eye irritation

Components:

Calcium carbonate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Diiron trioxide:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

2-Pentanone oxime:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

(3-Aminopropyl)trimethoxysilane:

Species : Rabbit
Result : Irreversible effects on the eye
Remarks : Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Species : Bovine cornea
Method : OECD Test Guideline 437

Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Calcium carbonate:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

Diiron trioxide:

Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

2-Pentanone oxime:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

(3-Aminopropyl)trimethoxysilane:

Test Type : Maximization Test

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Test Type : Maurer optimisation test
Routes of exposure : Skin contact
Species : Guinea pig
Result : positive
Remarks : Based on data from similar materials

Assessment : Probability or evidence of high skin sensitization rate in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Calcium carbonate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Diiron trioxide:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

O,O',O''-(Methylsilylydyne)trioxime 2-pentanone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

2-Pentanone oxime:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive

Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 475
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

2-Pentanone, O,O',O''-(ethenylsilyldyne)trioxime:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

(3-Aminopropyl)trimethoxysilane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative
Remarks: Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Diiron trioxide:

Species : Rat
Application Route : Intraperitoneal injection
Exposure time : 790 - 914 days
Result : negative

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

Calcium carbonate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

2-Pentanone oxime:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

(3-Aminopropyl)trimethoxysilane:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.
Remarks: Based on data from similar materials

STOT-single exposure

May cause damage to organs (Central nervous system, optic nerve).

Components:

Propane:

Assessment : May cause drowsiness or dizziness.

(3-Aminopropyl)trimethoxysilane:

Routes of exposure : Ingestion
Target Organs : Central nervous system, optic nerve
Assessment : May cause damage to organs.
Remarks : Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Routes of exposure : Ingestion
Target Organs : Nervous system
Assessment : Shown to produce significant health effects in animals at concentrations of 300 mg/kg bw or less.
Remarks : Based on data from similar materials

STOT-repeated exposure

May cause damage to organs (Blood, spleen) through prolonged or repeated exposure.

Components:

2-Pentanone oxime:

Routes of exposure : Ingestion
Target Organs : Blood, spleen
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

(3-Aminopropyl)trimethoxysilane:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Routes of exposure : Ingestion
Target Organs : Nervous system
Assessment : Shown to produce significant health effects in animals at concentrations of 10 mg/kg bw or less.
Remarks : Based on data from similar materials

Repeated dose toxicity

Components:

Calcium carbonate:

Species : Rat
NOAEL : > 1,000 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 422

Propane:

Species : Rat
NOAEL : 7.214 mg/l
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

2-Pentanone oxime:

Species : Rat
NOAEL : 15 mg/kg
LOAEL : 50 mg/kg
Application Route : Ingestion
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Species : Rat
NOAEL : > 10 - 100 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

(3-Aminopropyl)trimethoxysilane:

Species : Rat
NOAEL : 100 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Species : Rat
NOAEL : < 10 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Calcium carbonate:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): 50 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC: 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Diiron trioxide:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 50,000 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to microorganisms : EC50: > 10,000 mg/l
Exposure time: 3 h

O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 88 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 32 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 21.5 mg/l
Exposure time: 28 d

2-Pentanone oxime:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 88 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 32 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

Toxicity to microorganisms : EC50: > 20 mg/l
Exposure time: 28 d

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 117 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 117 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 103 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 37 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC0: > 22.2 mg/l
Exposure time: 28 h
Remarks: Based on data from similar materials

(3-Aminopropyl)trimethoxysilane:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.
Remarks: Based on data from similar materials

EC10 (Desmodesmus subspicatus (green algae)): > 1 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 (activated sludge): > 100 mg/l

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 39 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 7.6 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 1.2 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Persistence and degradability

Components:

O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Propane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

2-Pentanone oxime:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 9 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

(3-Aminopropyl)trimethoxysilane:

Biodegradability : Result: Not readily biodegradable.
Method: Regulation (EC) No. 440/2008, Annex, C.4-A
Remarks: Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential

Components:

2-Pentanone oxime:

Partition coefficient: n-octanol/water : log Pow: 1.43

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Partition coefficient: n-octanol/water : log Pow: 1.25

(3-Aminopropyl)trimethoxysilane:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): < 500
Method: OECD Test Guideline 305C
Remarks: Based on data from similar materials

Partition coefficient: n-octanol/water : log Pow: -2.8
Remarks: Calculation

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Partition coefficient: n-octanol/water : log Pow: 5.503
Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version 5.0 Revision Date: 08/30/2023 SDS Number: 7749145-00009 Date of last issue: 07/26/2023
Date of first issue: 01/27/2021

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/26/2023
5.0	08/30/2023	7749145-00009	Date of first issue: 01/27/2021

ERG Code : 126
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 0.06 % / 0.7 g/l
Remarks: VOC content excluding water and exempt compounds

The ingredients of this product are reported in the following inventories:

DSL : This product contains one or several components that are not on the Canadian DSL nor NDSL.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV : Time-weighted average exposure value
CA QC OEL / STEV : Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER RTV SILICONE, Red, 254 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/26/2023
5.0	08/30/2023	7749145-00009	Date of first issue: 01/27/2021

- International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 08/30/2023
Date format : mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8