



Empack Spraytech Inc.
98 Walker Drive
Brampton, Ontario, L6T 4H6
Canada
905-792-6571

PRODUCT: Emzone Corrosion Guard (G21) - 400 g

CODE: P6-045021

SECTION 01: IDENTIFICATION

Manufacturer..... Empack Spraytech Inc.
Product Item Numbers..... P6-045021
Product Identity..... Emzone Corrosion Guard (G21) - 400 g
24 hour emergency telephone number..... CANUTEC: 1-613-996-6666.
Recommended Use..... Multi-purpose lubricant and rust inhibitor.

SECTION 02: HAZARD IDENTIFICATION



Label Elements:

Signal Word..... DANGER.
Hazard Classification:
Physical Hazards..... Flammable Aerosols - Category 2. Gases Under Pressure - Liquefied Gas.
Health Hazards..... Acute Toxicity Oral - Category 5. Aspiration Hazard - Category 1.
Environmental Hazards..... Not Classified.
Hazard Statement..... H223:Flammable aerosol. H229:Pressurised container: may burst if heated (2).
H280:Contains gas under pressure; may explode if heated (L). H303:May be harmful if swallowed. H304:May be fatal if swallowed and enters airways.
Precautionary Statements:
Prevention..... P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not pierce or burn, even after use.
Response..... P301+P317: IF SWALLOWED: Get medical help. P301+P316: IF SWALLOWED: Get emergency medical help immediately. P331:Do NOT induce vomiting.
Storage..... P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F.
P403:Store in a well ventilated place . P405: Store locked up.
Disposal..... P501:Dispose of contents/container in accordance with local, regional, national, and/or international regulations.
Hazard(s) not otherwise classified (HNOC) Use only as directed.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	10-30
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	10-30
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	10-30
Propane	74-98-6	7-13
Isobutane	75-28-5	5-10

SECTION 04: FIRST-AID MEASURES

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance. If breathing is difficult, give oxygen and get medical attention.
Eye Contact..... Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs. Get medical attention if irritation persists.
Skin Contact..... Immediately flush the contaminated skin with soap and water. If this chemical penetrates clothing, immediately remove the clothing and flush the skin with water. If irritation persists after washing, get medical attention . Remove contaminated clothing. Launder clothing before reuse. If irritation occurs consult with your doctor.
Ingestion..... Do not induce vomiting, get medical attention. Rinse mouth. Obtain medical advice.
Most important symptoms/effects, acute .. Aspiration hazard.
and delayed

PRODUCT: Emzone Corrosion Guard (G21) - 400 g**CODE: P6-045021****SECTION 04: FIRST-AID MEASURES**

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media..... Dry chemical powder. Carbon dioxide. Foam, water spray or fog.
 Unsuitable Extinguishing Media..... Do not use water jet as an extinguisher, as this will spread the fire.
 Specific Hazards Arising from the Chemical Contents under pressure. Pressurized container may explode when exposed to heat or flame.
 Special Protective Equipment and Precautions for Firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from immediate hazard area if it is safe to do.
 General Fire Hazards..... Flammable Aerosol.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures Methods and Materials for Containment and Cleaning Up Ensure adequate ventilation; avoid formation of dust. Wear protective equipment and keep unprotected persons away. Use respiratory protection against the effects of dust. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.
 Environmental Precautions..... Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling..... Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Keep away from heat, sparks, and open flames. Avoid contact with eyes. Avoid breathing vapours or spray mists of this product. Use with adequate ventilation.
 Conditions for Safe Storage including any Incompatibilities Store in a cool, dry, well-ventilated area away from incompatible substances. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10). Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Store locked up.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Propane	Not available	Not available	1,000 ppm	Not available	Not available	Not available
Isobutane	Not available	1,000 ppm	Not available	Not available	Not available	Not available
Appropriate Engineering Controls.....	Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved. Ground all equipment and cylinders before use.					
Individual Protection Measures:						
Eye/Face Protection.....	Prevent eye contact, wear safety glasses in the event that eye contact is possible.					
Skin Protection.....	Normally, no hand protection is required; however, prolonged or repeated contact with skin use chemical resistant gloves conforming to appropriate regulations. Observe the instructions regarding permeability and breakthrough time that are provided by the supplier of the gloves. Use rubber or latex gloves when there is a potential for prolonged or excessive skin contact.					
Respiratory Protection.....	Use approved NIOSH respirators for emergencies. Typical use of this product under normal conditions does not require the use of respiratory protection. If airborne concentrations are above the applicable exposure limits (listed below), use NIOSH approved respiratory protection .					
Thermal Hazards.....	None Known.					
General Hygiene Considerations.....	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.					

PRODUCT: Emzone Corrosion Guard (G21) - 400 g

CODE: P6-045021

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Physical State.....	Aerosol.
Physical Appearance.....	Spray mist.
Odour.....	Mild odour.
Odour Threshold (ppm).....	Not available.
pH.....	Not applicable.
Vapour Pressure (psig).....	Not available.
Vapour Density (Air=1).....	Not available.
Evaporation Rate (n-Butyl Acetate = 1).....	Not available.
Boiling Point liquid (°C).....	Not available.
Melting/Freezing Point (°C).....	Not available.
VOC Content.....	NMT 25.
Solubility in water.....	Negligible.
Specific Gravity.....	0.860-0.880.
Aerosol Flame Projection.....	>15 cm and <100 cm.
Flashback.....	No.
Auto Ignition Temperature (Propellant), °C	450°C (842°F). (Propellant).
Flash Point (°C), Method.....	-155.27°F (-104.039 °C) Closed Cup. (Propellant).
Lower Flammable Limit (% Vol).....	2.0. (Propellant).
Upper Flammable Limit (% Vol).....	9.5. (Propellant).
Note.....	NMT = Not More Than.

SECTION 10: STABILITY AND REACTIVITY

Reactivity.....	Product not reactive under normal conditions of use.
Chemical Stability.....	Stable at normal temperatures and pressures.
Possibility of Hazardous Reactions.....	Will not occur.
Conditions to Avoid.....	Avoid sources of heat and flame, and electrostatic charge.
Incompatible Materials.....	Avoid contacting with oxidizers.
Hazardous Decomposition Products.....	No hazardous decomposition products when stored and handled correctly.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
-------------	------	------

Propane	658 mg/L (Rat - 4 hrs)	Not available
Isobutane	658 mg/L (Rat - 4 hrs)	Not available

Information on Likely Routes of Exposure:

Routes of entry - Inhalation.....	Yes.
Routes of entry - Skin & Eye.....	Yes.
Routes of entry - Ingestion.....	Yes.
Routes of entry - Skin Absorption.....	No.
Symptoms Related to the Physical,	Irritant effects.
Chemical and Toxicological Characteristics	
Acute Toxicity.....	May be harmful if swallowed.
Skin Corrosion/Irritation.....	Not classified.
Serious Eye Damage/Eye Irritation.....	Not classified.
Respiratory or Skin Sensitization.....	Not classified.
Germ Cell Mutagenicity.....	No information is available, and no adverse effects are expected.
Carcinogenicity.....	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
Reproductive Toxicity.....	No information is available, and no adverse effects are expected.
STOT - Single Exposure.....	Not classified.
STOT - Repeated Exposure.....	Not classified.
Aspiration Hazard.....	Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.
Chronic Effects.....	Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity.....	May be dangerous for the environment. No data is available on the product itself. Should not be released into the environment.
Persistence and degradability	The product itself has not been tested.
Bioaccumulation Potential.....	The product itself has not been tested.
Mobility in Soil.....	The product itself has not been tested.
Other Adverse Effects.....	None Known.

PRODUCT: Emzone Corrosion Guard (G21) - 400 g

CODE: P6-045021

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, provincial and federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.
DOT (US-Road)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty., Consumer Commodity ORM-D.
IMDG (International- Marine)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.
IATA (International- Air)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

SECTION 15: REGULATORY INFORMATION

Canada Regulations:..... Refer to Section 2 for a WHMIS 2015 Classification for this product.
US Regulations:..... This product is not subject to warning label under California proposition-65.

SECTION 16: OTHER INFORMATION

Disclaimer..... The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.
Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.
NFPA Storage Level..... Level 2.
Prepared by Regulatory Affairs
Latest Revision 2024-04-02