

Empack Spraytech Inc. 98 Walker Drive Brampton, Ontario, L6T 4H6 Canada 905-792-6571

PRODUCT: Emzone G24 Tech Lube - 320 g (11.3 oz)

SECTION 01: IDENTIFICATION

Manufacturer..... Empack Spraytech Inc.

Product Item Numbers..... P6-045024

Product Identity......24 hour emergency telephone number..... Emzone G24 Tech Lube - 320 g (11.3 oz) CANUTEC: 1-613-996-6666.

Recommended Use.....

Garage door, cable lubricant, rust inhibitor.

SECTION 02: HAZARD IDENTIFICATION



Label Elements:

Signal Word.....

Hazard Classification:

Physical Hazards..... Flammable Aerosols - Category 1. Gases Under Pressure - Liquefied Gas.

Not Classified. Health Hazards..... Environmental Hazards..... Not Classified.

Hazard Statement..... H222:Extremely flammable aerosol (1). H229:Pressurized container: may burst if heated

(1). H280:Contains gas under pressure; may explode if heated (L).

Precautionary Statements:

P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Prevention.....

No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not

CODE: P6-045024

pierce or burn, even after use.

Response..... None

P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. Storage.....

P403:Store in a well ventilated place.

None

Hazard(s) not otherwise classified (HNOC) None Known.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS				
CHEMICAL NAME AND SYNONYMS	CAS#	WT. %		

Liquified petroleum gas (LPG) 68476-85-7 15-40

SECTION 04: FIRST-AID MEASURES

Inhalation.....

If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance. If breathing is difficult, give oxygen and get medical attention. Do not give adrenaline, epinephrine or similar drugs following exposure to this

product.

The product is not expected to be skin irritant. However, if irritation persists, wash the Skin Contact.....

contact skin area with soap and water. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the Eye Contact.....

upper and lower eyelids. Get medical attention if irritation persists.

Do not induce vomiting, get medical attention. Rinse mouth. Obtain medical advice. Ingestion.....

Most important symptoms/effects, acute ...

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain.

Provide general supportive measures and treat symptomatically. In case of shortness of

breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 05: FIRE-FIGHTING MEASURES

Special Protective Equipment and Precautions for Firefighters

Indication of immediate medical attention

and special treatment needed

and delayed

Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Specific Hazards Arising from the Chemical Contents under pressure. Pressurized container may explode when exposed to heat or flame.



PRODUCT: Emzone G24 Tech Lube - 320 g (11.3 oz)

SECTION 05: FIRE-FIGHTING MEASURES

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).

CODE: P6-045024

Methods and Materials for Containment .. and Cleaning Up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Environmental Precautions.....

Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling.....

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid contact with eyes, skin, and clothing. Avoid breathing vapour of this product. Avoid prolonged exposure. Use in well-ventilated areas.

Conditions for Safe Storage including any Incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

	ACGIH TL	v	OSHA PE	L	NIC	SH
INGREDIENTS	TWA ST	EL IPEL	L 01	EL	REL	

Appropriate Engineering Controls.....

Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved.

Individual Protection Measures:

Skin Protection.....

Chemical resistant gloves are recommended. Avoid contact with the skin. Wear

appropriate chemical resistant clothing.

Thermal Hazards..... None Known.

Routinely wash work clothing and protective equipment prior to use.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Form. Physical Appearance. Odor Odor Threshold (ppm) Relative Density/Specific Gravity Vapour Pressure (psig) Vapour Density (Air=1) pH Boiling Point (°C). Melting/Freezing Point (°C). Flash Point (°C), Method Evaporation Rate (n-Butyl Acetate = 1) Solubility in water Aerosol Ignition Distance Flashback	Spray mist. Petroleum-like. Not available. Not available. Not available. Not available. Not available. Not applicable. Not available. Not available. Not available. Insoluble. Insoluble. Ignition Distance of greater than or equal to 75 cm. No.
Aerosol Ignition DistanceFlashback	Ignition Distance of greater than or equal to 75 cm. No.
VOC Content	NMT 25.
Auto Ignition Temperature (°C)	
Lower Flammable Limit (% Vol)	1.8. (Propellant).

CODE: P6-045024

PRODUCT: Emzone G24 Tech Lube - 320 g (11.3 oz)

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

8.8. (Propellant). Upper Flammable Limit (% Vol)..... NMT = Not More Than. Note.....

SECTION 10: STABILITY AND REACTIVITY

Reactivity Product not reactive under normal conditions of use.

Chemical Stability..... Material is stable under normal conditions.

Possibility of Hazardous Reactions..... Will not occur.

Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge.

Incompatible Materials..... Strong oxidizing agents. Strong acids.

Carbon Oxides Hazardous Decomposition Products......

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS LC50 LD50

Information on Likely Routes of Exposure:

Yes. Yes. Routes of entry - Ingestion..... Yes. Routes of entry - Skin Absorption..... Nο

Symptoms Related to the Physical, Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred

Chemical and Toxicological Characteristics vision. Defatting of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Acute Toxicity..... No known significant effects.

Skin Corrosion/Irritation..... Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation....... Respiratory or Skin Sensitization..... Not classified. Not classified.

Germ Cell Mutagenicity..... No information is available, and no adverse effects are expected. Not classified as carcinogenic by ACGIH, IARC, OSHA or NTP. No information is available, and no adverse effects are expected.

Not classified. STOT - Repeated Exposure..... Not classified. Aspiration Hazard..... Not classified.

Chronic Effects..... No long term chronic effects are known or anticipated.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity..... May be dangerous for the environment. No data is available on the product itself. Should

not be released into the environment. Persistence and degradability The product itself has not been tested. Bioaccumulation Potential..... The product itself has not been tested. Mobility in Soil..... The product itself has not been tested.

Other Adverse Effects..... Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road).....

UN1950, AEROSOLS, Class 2.1, Ltd. Qty. UN1950, AEROSOLS, Class 2.1, Ltd. Qty., Consumer Commodity ORM-D. UN1950, AEROSOLS, Class 2.1, Ltd. Qty. UN1950, AEROSOLS, Class 2.1, Ltd. Qty. DOT (US-Road).....

IMDG (International- Marine).....

IATA (International- Air).....

SECTION 15: REGULATORY INFORMATION

Refer to Section 2 for a WHMIS 2015 Classification for this product. Canada Regulations:.... All ingredients listed appear on the Domestic Substances List (DSL). Canadian Environmental Protection Act ...

ÙS Regulations..... Environmental Protection Act: Constituents of this product are included on the TSCA

inventory.



CODE: P6-045024

PRODUCT: Emzone G24 Tech Lube - 320 g (11.3 oz)

SECTION 16: OTHER INFORMATION

Disclaimer	The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.
NFPA Storage Level	
Prepared by	Regulatory Affairs
Latest Revision	2024-03-22