

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/09/2023
1.1	11/22/2023	11293285-00002	Date of first issue: 11/09/2023

SECTION 1. IDENTIFICATION

Product name : FUEL INJECTOR CLEANER, 354 mL

Product code : 5861.111302

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:

CHEMTREC (24/7): 1-800-424-9300

Urgences liées au transport:

CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Cleaning agent
Automotive

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 3

Specific target organ toxicity : Category 3
- single exposure

Aspiration hazard : Category 1

GHS label elements

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version 1.1 Revision Date: 11/22/2023 SDS Number: 11293285-00002 Date of last issue: 11/09/2023
Date of first issue: 11/09/2023

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.

Precautionary Statements

: **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapors.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection and face protection.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
Storage:
P405 Store locked up.
Disposal:
P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Vapors may form explosive mixture with air.
Repeated exposure may cause skin dryness or cracking.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Naphtha (petroleum), hydrotreated heavy	Naphtha, hydrotreated heavy	64742-48-9	$\geq 80 - \leq 100$ *

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/09/2023
1.1	11/22/2023	11293285-00002	Date of first issue: 11/09/2023

Solvent naphtha (petroleum), light arom.	No data available	64742-95-6	$\geq 1 - < 5$ *
--	-------------------	------------	------------------

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control center immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
May cause drowsiness or dizziness.
Prolonged or repeated contact may dry skin and cause irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/09/2023
1.1	11/22/2023	11293285-00002	Date of first issue: 11/09/2023

Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NOx)

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version 1.1 Revision Date: 11/22/2023 SDS Number: 11293285-00002 Date of last issue: 11/09/2023
Date of first issue: 11/09/2023

- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not get on skin or clothing.
Avoid breathing mist or vapors.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases
Very acutely toxic substances and mixtures

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha (petroleum), hydrotreated heavy	64742-48-9	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version 1.1 Revision Date: 11/22/2023 SDS Number: 11293285-00002 Date of last issue: 11/09/2023
Date of first issue: 11/09/2023

		TWA	525 mg/m ³	CA ON OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH

Engineering measures : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/09/2023
1.1	11/22/2023	11293285-00002	Date of first issue: 11/09/2023

clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : amber, clear

Odor : solvent

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : 149 °C

Flash point : 38 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 0.832

Solubility(ies)
Water solubility : No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/09/2023
1.1	11/22/2023	11293285-00002	Date of first issue: 11/09/2023

Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	< 20.5 mm ² /s (40 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials		

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/09/2023
1.1	11/22/2023	11293285-00002	Date of first issue: 11/09/2023

Acute inhalation toxicity : LC50 (Rat): > 4,951 mg/m³
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Solvent naphtha (petroleum), light arom.:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy:

Species : Rabbit
Result : Mild skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Solvent naphtha (petroleum), light arom.:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/09/2023
1.1	11/22/2023	11293285-00002	Date of first issue: 11/09/2023

Solvent naphtha (petroleum), light arom.:

Species	:	Rabbit
Result	:	No eye irritation
Remarks	:	Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative
Remarks	:	Based on data from similar materials

Solvent naphtha (petroleum), light arom.:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative
Remarks	:	Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy:

Genotoxicity in vitro	:	Test Type: In vitro mammalian cell gene mutation test Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Ingestion Result: negative

Solvent naphtha (petroleum), light arom.:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative Test Type: In vitro mammalian cell gene mutation test Result: negative Remarks: Based on data from similar materials
-----------------------	---	--

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/09/2023
1.1	11/22/2023	11293285-00002	Date of first issue: 11/09/2023

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Intraperitoneal injection
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 105 weeks
Result : negative
Remarks : Based on data from similar materials

Solvent naphtha (petroleum), light arom.:

Species : Mouse
Application Route : Skin contact
Exposure time : 102 weeks
Result : negative
Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated heavy:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Solvent naphtha (petroleum), light arom.:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/09/2023
1.1	11/22/2023	11293285-00002	Date of first issue: 11/09/2023

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

May cause drowsiness or dizziness.

Components:

Naphtha (petroleum), hydrotreated heavy:

Assessment : May cause drowsiness or dizziness.

Solvent naphtha (petroleum), light arom.:

Assessment : May cause drowsiness or dizziness.
Remarks : Based on data from similar materials

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Naphtha (petroleum), hydrotreated heavy:

Species : Rat
NOAEL : 10,186 mg/m³
Application Route : inhalation (vapor)
Exposure time : 13 Weeks

Solvent naphtha (petroleum), light arom.:

Species : Rat
NOAEL : > 1 mg/kg
Application Route : inhalation (vapor)
Exposure time : 109 Weeks
Remarks : Based on data from similar materials

Species : Rat
NOAEL : > 600 mg/kg
Application Route : Skin contact
Exposure time : 28 Days
Remarks : Based on data from similar materials

Aspiration toxicity

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/09/2023
1.1	11/22/2023	11293285-00002	Date of first issue: 11/09/2023

Components:

Naphtha (petroleum), hydrotreated heavy:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Solvent naphtha (petroleum), light arom.:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Naphtha (petroleum), hydrotreated heavy:

Toxicity to fish	:	LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 30 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 22 - 46 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	:	EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
		NOELR (Pseudokirchneriella subcapitata (green algae)): 1 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: Based on data from similar materials

Solvent naphtha (petroleum), light arom.:

Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): > 1 - 10 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 1 - 10 mg/l Exposure time: 48 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/09/2023
1.1	11/22/2023	11293285-00002	Date of first issue: 11/09/2023

	Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	: EL50 (Raphidocelis subcapitata (freshwater green alga)): > 1 - 10 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
	NOELR (Raphidocelis subcapitata (freshwater green alga)): > 0.1 - 1 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOELR (Daphnia magna (Water flea)): > 1 mg/l Exposure time: 21 d Test substance: Water Accommodated Fraction Method: OECD Test Guideline 211 Remarks: Based on data from similar materials

Persistence and degradability

Components:

Naphtha (petroleum), hydrotreated heavy:

Biodegradability	: Result: Readily biodegradable. Biodegradation: 89 % Exposure time: 28 d Method: OECD Test Guideline 301F Remarks: Based on data from similar materials
------------------	--

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	: Do not dispose of waste into sewer. Dispose of in accordance with local regulations.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/09/2023
1.1	11/22/2023	11293285-00002	Date of first issue: 11/09/2023

Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number	: UN 1993
Proper shipping name	: FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated heavy, Solvent naphtha (petroleum), light arom.)
Class	: 3
Packing group	: III
Labels	: 3
Environmentally hazardous	: no

IATA-DGR

UN/ID No.	: UN 1993
Proper shipping name	: Flammable liquid, n.o.s. (Naphtha (petroleum), hydrotreated heavy, Solvent naphtha (petroleum), light arom.)
Class	: 3
Packing group	: III
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 366
Packing instruction (passenger aircraft)	: 355

IMDG-Code

UN number	: UN 1993
Proper shipping name	: FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated heavy, Solvent naphtha (petroleum), light arom.)
Class	: 3
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number	: UN 1993
Proper shipping name	: FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated heavy, Solvent naphtha (petroleum), light arom.)
Class	: 3

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/09/2023
1.1	11/22/2023	11293285-00002	Date of first issue: 11/09/2023

Packing group	:	III
Labels	:	3
ERG Code	:	128
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content	Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations VOC content: 94.60 %
---	--

The ingredients of this product are reported in the following inventories:

DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
-----	--

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA ON OEL	: Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	: 8-hour, time-weighted average
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA AB OEL / STEL	: 15-minute occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average
CA ON OEL / TWA	: Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV	: Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory con-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



FUEL INJECTOR CLEANER, 354 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/09/2023
1.1	11/22/2023	11293285-00002	Date of first issue: 11/09/2023

centration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/22/2023
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8