according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

SECTION 1. IDENTIFICATION

Product name : THROTTLE VALVE CLEANER, 440 g

Product code : 5861.113500

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd

GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:

CHEMTREC (24/7): 1-800-424-9300

Transport related emergencies:

CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou

exposition:

CHEMTREC (24/7): 1-800-424-9300

Urgences liées au transport:

CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use

Additive

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 1

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity

- single exposure

Category 3

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, eye protection and face protec-

tion.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel

unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical attention.

P337 + P313 If eye irritation persists: Get medical attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to tempera-

tures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

Substance / Mixture Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Acetone	2-Propanone	67-64-1	>= 30 - < 60 *
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Naphtha (petro- leum), hy- drotreated light	Not Assigned	>= 30 - < 60 *
Propan-2-ol	Isopropyl alco- hol	67-63-0	>= 5 - < 10 *
1-Methoxy-2-propanol	METHOXYISOP ROPANOL	107-98-2	>= 5 - < 10 *
Carbon dioxide	Carbonic anhy- dride	124-38-9	>= 5 - < 10 *
3-Butoxypropan-2-ol	2-Propanol, 1- butoxy-	5131-66-8	>= 1 - < 5 *

^{*} Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of contact, immediately flush skin with plenty of water In case of skin contact

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed If swallowed, DO NOT induce vomiting.

> Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms

and effects, both acute and

delayed

Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness.

Protection of first-aiders First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Flash back possible over considerable distance.

Vapors may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod-

ucts

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Remove all sources of ignition.
Use personal protective equipment.

ose personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

: Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapors/mists with a water spray

jeτ.

For large spills, provide diking or other appropriate contain-

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

ment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If advised by assessment of the local exposure potential, use

only in an area equipped with explosion-proof exhaust ventila-

tion.

Advice on safe handling : For outdoor use only

Do not get on skin or clothing.

Avoid breathing spray. Do not swallow.

Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.

Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Do not pierce or burn, even after use. Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides Oxidizing agents Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

> **Explosives** Gases

Recommended storage tem- : 0 - 40 °C

perature

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m ³	CA AB OEL
		STEL	750 ppm 1,800 mg/m³	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	250 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Not Assigned	STEL	1,000 ppm 3,500 mg/m³	CA AB OEL
		TWA	500 ppm 1,760 mg/m ³	CA AB OEL
		STEV	1,000 ppm 3,500 mg/m ³	CA QC OEL
		TWAEV	500 ppm 1,760 mg/m ³	CA QC OEL
		TWA	200 ppm	CA BC OEL
		TWA	500 ppm	ACGIH
		STEL	1,000 ppm	ACGIH
Propan-2-ol	67-63-0	STEL	400 ppm 984 mg/m³	CA AB OEL
		TWA 200 ppm 492 mg/m³		CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	200 ppm	CA QC OEL
		STEV	400 ppm	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
1-Methoxy-2-propanol	107-98-2	TWA	100 ppm 369 mg/m ³	CA AB OEL
		STEL	150 ppm 553 mg/m³	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/17/2023

 8.0
 10/18/2023
 10681697-00012
 Date of first issue: 04/03/2013

		TWAEV	100 ppm 369 mg/m³	CA QC OEL
		STEV	150 ppm 553 mg/m ³	CA QC OEL
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
Carbon dioxide	124-38-9	TWA	5,000 ppm 9,000 mg/m ³	CA AB OEL
	STE	STEL	30,000 ppm 54,000 mg/m ³	CA AB OEL
		TWA	5,000 ppm	CA BC OEL
		STEL	15,000 ppm	CA BC OEL
		30,000 ppm 54,000 mg/m ³	CA QC OEL	
		TWAEV	5,000 ppm 9,000 mg/m ³	CA QC OEL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra-tion	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work- week	40 mg/l	ACGIH BEI
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust venti-

lation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the re-

commended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Nitrile rubber Break through time : < 480 min

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 10/18/2023 10681697-00012 Date of first issue: 04/03/2013 8.0

Glove thickness 0.45 mm

Choose gloves to protect hands against chemicals depending Remarks

> on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of

workday.

Eye protection Wear the following personal protective equipment:

Safety goggles

Skin and body protection Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

If exposure to chemical is likely during typical use, provide Hygiene measures

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance aerosol

Propellant Carbon dioxide

Color colorless

Odor characteristic

Odor Threshold No data available

substance/mixture is non-soluble (in water) рΗ

Melting point/freezing point No data available

Initial boiling point and boiling : 55.8 °C

range

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

Flash point : -18 °C

Flash point is only valid for liquid portion in the aerosol can.

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

14.3 %(V)

Lower explosion limit / Lower

flammability limit

1.8 %(V)

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Density : 0.751 g/cm³ (20 °C)

Method: DIN 51757

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : 270 °C

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Extremely flammable aerosol.

Vapors may form explosive mixture with air.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Can react with strong oxidizing agents.

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:

Acetone:

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25.2 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

Exposure time: 6 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

1-Methoxy-2-propanol:

Acute oral toxicity : LD50 (Rat): 4,016 mg/kg

Acute inhalation toxicity : LC50 (Mouse): < 22.2 mg/l

Exposure time: 6 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Carbon dioxide:

Acute inhalation toxicity : LC50 (Rat): 40000 - 50000 ppm

Exposure time: 30 min Test atmosphere: vapor

3-Butoxypropan-2-ol:

Acute oral toxicity : LD50 (Rat): 3,300 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 3.52 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Causes skin irritation.

Components:

Acetone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Propan-2-ol:

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

Species : Rabbit

Result : No skin irritation

1-Methoxy-2-propanol:

Species : Rabbit

Result : No skin irritation

3-Butoxypropan-2-ol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Acetone:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Result : No eye irritation

Propan-2-ol:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

1-Methoxy-2-propanol:

Species : Rabbit

Result : No eye irritation

3-Butoxypropan-2-ol:

Species : Rabbit

Result : Irritation to eyes, reversing within 7 days

Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

Components:

Acetone:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Propan-2-ol:

Test Type : Buehler Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

1-Methoxy-2-propanol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

3-Butoxypropan-2-ol:

Test Type : Buehler Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Acetone:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Result: negative

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (vapor)

Method: OPPTS 870.5395

Result: negative

Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

1-Methoxy-2-propanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-

malian cells Result: equivocal

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro) Method: OECD Test Guideline 482

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

Result: negative

3-Butoxypropan-2-ol:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Acetone:

Species : Mouse
Application Route : Skin contact
Exposure time : 424 days
Result : negative

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Mouse
Application Route : Skin contact
Exposure time : 102 weeks
Result : negative

Propan-2-ol:

Species : Rat

Application Route : inhalation (vapor)
Exposure time : 104 weeks

Method : OECD Test Guideline 451

Result : negative

1-Methoxy-2-propanol:

Species : Rat

Application Route : inhalation (vapor)

Exposure time : 2 Years

Method : OECD Test Guideline 453

Result : negative

3-Butoxypropan-2-ol:

Species : Rat

Application Route : inhalation (vapor)

Exposure time : 2 Years

Method : OECD Test Guideline 453

Result : negative

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

1-Methoxy-2-propanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapor) Method: OECD Test Guideline 416

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (vapor)

Result: negative

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

3-Butoxypropan-2-ol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Skin contact Method: OECD Test Guideline 414

Result: negative

STOT-single exposure

May cause drowsiness or dizziness.

Components:

Acetone:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Propan-2-ol:

Assessment : May cause drowsiness or dizziness.

1-Methoxy-2-propanol:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Acetone:

Species : Rat

NOAEL : 900 mg/kg LOAEL : 1,700 mg/kg Application Route : Ingestion Exposure time : 90 Days

Species : Rat NOAEL : 45 mg/l

Application Route : inhalation (vapor)

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

Exposure time : 8 Weeks

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rat NOAEL : > 20 mg/l

Application Route : inhalation (vapor)

Exposure time : 13 Weeks

Propan-2-ol:

Species : Rat NOAEL : 12.5 mg/l

Application Route : inhalation (vapor) Exposure time : 104 Weeks

1-Methoxy-2-propanol:

Species : Rat
NOAEL : 919 mg/kg
Application Route : Ingestion
Exposure time : 35 Days

Species : Rat NOAEL : 1.1 mg/l

Application Route : inhalation (vapor)

Exposure time : 2 y

Method : OECD Test Guideline 453

Species : Rabbit
NOAEL : 1,838 mg/kg
Application Route : Skin contact
Exposure time : 90 Days

3-Butoxypropan-2-ol:

Species : Rat
NOAEL : 350 mg/kg
LOAEL : 1,000 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Method : OECD Test Guideline 408

Aspiration toxicity

Not classified based on available information.

Components:

Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Acetone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia pulex (Water flea)): 8,800 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000

mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): >= 79 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: 61,150 mg/l

Exposure time: 30 min Method: ISO 8192

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 4.5 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chron-

NOELR (Daphnia magna (Water flea)): 2.6 mg/l Exposure time: 21 d

ic toxicity)

Method: OECD Test Guideline 211

Propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l

Exposure time: 96 h

Toxicity to daphnia and other : aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 24 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 1,050 mg/l

Exposure time: 16 h

1-Methoxy-2-propanol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 6,812 mg/l

Exposure time: 96 h Method: DIN 38412

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 23,300 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Skeletonema costatum (marine diatom)): 6,745 mg/l

Exposure time: 72 h Method: ISO 10253

Toxicity to microorganisms : IC50: > 1,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Carbon dioxide:

Toxicity to fish : NOEC (Lepomis macrochirus (Bluegill sunfish)): > 100 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

NOEC (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

3-Butoxypropan-2-ol:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 560 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): >

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

plants 1,000 mg/l

Exposure time: 96 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 560

mg/l

Exposure time: 96 h

Toxicity to microorganisms : EC50: > 1,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Persistence and degradability

Components:

Acetone:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 91 % Exposure time: 28 d

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 77.05 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1.19 (BOD5)COD: 2.23BOD/COD: 53 %

1-Methoxy-2-propanol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 96 % Exposure time: 28 d

Method: OECD Test Guideline 301E

3-Butoxypropan-2-ol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 90 % Exposure time: 28 d

Method: OECD Test Guideline 301E

Bioaccumulative potential

Components:

Acetone:

Partition coefficient: n-

octanol/water

: log Pow: -0.27 - -0.23

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Partition coefficient: n- : log Pow: 4

octanol/water Remarks: Based on data from similar materials

Propan-2-ol:

Partition coefficient: n-

octanol/water

log Pow: 0.05

1-Methoxy-2-propanol:

Partition coefficient: n-

octanol/water

log Pow: < 1

Carbon dioxide:

Partition coefficient: n-

octanol/water

log Pow: 0.83

3-Butoxypropan-2-ol:

Partition coefficient: n-

octanol/water

log Pow: 1.2

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty

(including propellant)

SECTION 14. TRANSPORT INFORMATION

International Regulations

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 10/18/2023 10681697-00012 Date of first issue: 04/03/2013 8.0

UNRTDG

UN number UN 1950 Proper shipping name **AEROSOLS**

Class 2.1

Packing group Not assigned by regulation

Labels 2.1 Environmentally hazardous yes

IATA-DGR

UN/ID No. UN 1950

Aerosols, flammable Proper shipping name

Class

Packing group Not assigned by regulation

Labels Flammable Gas

Packing instruction (cargo 203

aircraft)

Packing instruction (passen: 203

ger aircraft)

IMDG-Code

UN number UN 1950 Proper shipping name **AEROSOLS**

(Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-

hexane)

Class 2.1

Packing group Not assigned by regulation

Labels 2.1 **EmS Code** F-D, S-U Marine pollutant yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number UN 1950 Proper shipping name **AEROSOLS**

Class

Packing group Not assigned by regulation

Labels 2.1 **ERG Code** 126

Marine pollutant yes(Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics,

<5% n-hexane)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds

(VOC) content

CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 -Guidelines for VOC in Consumer Products

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

VOC content: 94.32 % / 750 g/l

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average CA BC OEL / STEL : short-term exposure limit

CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified: Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation,

according to the Hazardous Products Regulations



THROTTLE VALVE CLEANER, 440 g

Version Revision Date: SDS Number: Date of last issue: 07/17/2023 8.0 10/18/2023 10681697-00012 Date of first issue: 04/03/2013

Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to :

compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 10/18/2023 Date format : mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8