

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

### SECTION 1. IDENTIFICATION

Product name : FPT BLACK GRAY, 340 g  
Product code : 5987.150046  
Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : 1-800-263-5002  
Telefax : 1-905-564-3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300

Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300

E-mail address : prodsafe@wurth.ca

#### Recommended use of the chemical and restrictions on use

Recommended use : Paint  
Coatings  
Restrictions on use : Not applicable

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 1  
Eye irritation : Category 2A  
Carcinogenicity : Category 2  
Specific target organ toxicity : Category 3  
- single exposure

#### GHS label elements

Hazard pictograms :   

Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.  
H229 Pressurized container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

### Precautionary Statements

#### Prevention:

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.

#### Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P337 + P313 If eye irritation persists: Get medical attention.

#### Storage:

P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

#### Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

### Other hazards

Repeated exposure may cause skin dryness or cracking.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Acetone	2-Propanone	67-64-1	$\geq 10 - < 30$ *
Propane	Dimethylmethane	74-98-6	$\geq 10 - < 30$ *
Butane	Butyl hydride	106-97-8	$\geq 5 - < 10$ *
Barium sulfate	Sulfuric acid, barium salt	7727-43-7	$\geq 5 - < 10$ *
Isobutyl acetate	Acetic acid, 2-methylpropyl ester	110-19-0	$\geq 5 - < 10$ *

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

2-(Propyloxy)ethanol	Ethanol, 2-propoxy-	2807-30-9	$\geq 5 - < 10$ *
n-Butyl acetate	Acetic acid, butyl ester	123-86-4	$\geq 1 - < 5$ *
2-Methoxy-1-methylethyl acetate	2-Propanol, 1-methoxy-, 2-acetate	108-65-6	$\geq 1 - < 5$ *
Titanium dioxide	Titanic anhydride	13463-67-7	$\geq 1 - < 5$ *
Pentan-2-one	Methyl propyl ketone	107-87-9	$\geq 1 - < 5$ *
Isobutyl methyl ketone	4-Methylpentan-2-one	108-10-1	$\geq 0.1 - < 1$ *

\* Actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Prolonged or repeated contact may dry skin and cause irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing : High volume water jet

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/25/2025
2.0	11/14/2025	11543097-00003	Date of first issue: 06/12/2025

---

media

- Specific hazards during fire fighting : Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides  
Metal oxides  
Sulfur oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing spray.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.  
Do not spray on an open flame or other ignition source.
- Conditions for safe storage : Store locked up.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Do not pierce or burn, even after use.  
Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases
- Recommended storage temperature : < 40 °C

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
 Date of first issue: 06/12/2025

Acetone	67-64-1	TWA	500 ppm 1,200 mg/m <sup>3</sup>	CA AB OEL
		STEL	750 ppm 1,800 mg/m <sup>3</sup>	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	250 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm 1,900 mg/m <sup>3</sup>	CA QC OEL
		STEL	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Barium sulfate	7727-43-7	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Inhalable)	5 mg/m <sup>3</sup>	CA BC OEL
		TWAEV (inhalable dust)	5 mg/m <sup>3</sup>	CA QC OEL
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH
Isobutyl acetate	110-19-0	TWA	150 ppm 713 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	150 ppm	CA QC OEL
		TWA	50 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
2-(Propyloxy)ethanol	2807-30-9	TWA	25 ppm 110 mg/m <sup>3</sup>	CA ON OEL
n-Butyl acetate	123-86-4	STEL	200 ppm 950 mg/m <sup>3</sup>	CA AB OEL
		TWA	150 ppm 713 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	150 ppm	CA QC OEL
		TWA	50 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
2-Methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWA	50 ppm 270 mg/m <sup>3</sup>	CA ON OEL
Titanium dioxide	13463-67-7	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Total	10 mg/m <sup>3</sup>	CA BC OEL

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

		dust)		
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
Pentan-2-one	107-87-9	TWA	200 ppm 705 mg/m <sup>3</sup>	CA AB OEL
		STEL	250 ppm 881 mg/m <sup>3</sup>	CA AB OEL
		TWA	150 ppm	CA BC OEL
		STEL	250 ppm	CA BC OEL
		STEV	150 ppm	CA QC OEL
		STEL	150 ppm	ACGIH
Isobutyl methyl ketone	108-10-1	TWA	50 ppm 205 mg/m <sup>3</sup>	CA AB OEL
		STEL	75 ppm 307 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		STEV	75 ppm	CA QC OEL
		TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Isobutyl methyl ketone	108-10-1	methyl isobutyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

**Engineering measures** : Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection  
Material : Nitrile rubber

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Propellant : Propane, Butane

Color : black  
gray

Odor : aromatic

Odor Threshold : No data available

pH : Solvent mixture; pH value determination not possible, no aqueous solution

Melting point/freezing point : No data available

Initial boiling point and boiling range : -44.5 °C

Flash point : -19 °C

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/25/2025
2.0	11/14/2025	11543097-00003	Date of first issue: 06/12/2025

---

Flash point is only valid for liquid portion in the aerosol can.

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Self-ignition : not auto-flammable

Upper explosion limit / Upper flammability limit : 10.9 %(V)

Lower explosion limit / Lower flammability limit : 1.7 %(V)

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 0.77 - 0.85  
Reference substance: Water

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.  
Vapors may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/25/2025
2.0	11/14/2025	11543097-00003	Date of first issue: 06/12/2025

---

Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

#### Components:

##### Acetone:

Acute oral toxicity	:	LD50 (Rat): 5,800 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 76 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	:	LD50 (Rabbit): 7,426 mg/kg

##### Propane:

Acute inhalation toxicity	:	LC50 (Rat): > 800000 ppm Exposure time: 15 min Test atmosphere: gas
---------------------------	---	---------------------------------------------------------------------------

##### Butane:

Acute inhalation toxicity	:	LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: vapor
---------------------------	---	----------------------------------------------------------------------

##### Barium sulfate:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
---------------------	---	---------------------------

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

### Isobutyl acetate:

Acute oral toxicity : LD50 (Rat): 13,413 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

LC50 (Rat): 21.2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 17,400 mg/kg

### 2-(Propyloxy)ethanol:

Acute oral toxicity : LD50 (Mouse): 3,089 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 1,337 mg/kg

### n-Butyl acetate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

### 2-Methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 (Rat, female): 5,155 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 9.34 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

### Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 425  
Remarks: The test was conducted according to guideline

Acute inhalation toxicity : LC50 (Rat): > 5.09 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---



Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: The test was conducted according to guideline

### **Pentan-2-one:**

Acute oral toxicity : LD50 (Rat): 1,600 - 3,200 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 25.5 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 436  
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: Based on data from similar materials

### **Isobutyl methyl ketone:**

Acute oral toxicity : LD50 (Rat): 2,080 mg/kg  
Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Expert judgment  
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

### **Skin corrosion/irritation**

Not classified based on available information.

### **Components:**

#### **Acetone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

#### **Barium sulfate:**

Species : reconstructed human epidermis (RhE)  
Method : OECD Test Guideline 439  
Remarks : Based on data from similar materials  
Result : No skin irritation

#### **Isobutyl acetate:**

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials  
Assessment : Repeated exposure may cause skin dryness or cracking.  
Remarks : Based on national or regional regulation.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

### 2-(Propyloxy)ethanol:

Species : Rabbit  
Result : No skin irritation

### n-Butyl acetate:

Species : Rabbit  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

### 2-Methoxy-1-methylethyl acetate:

Species : Rabbit  
Result : No skin irritation

### Titanium dioxide:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : The test was conducted equivalent or similar to guideline

### Pentan-2-one:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

### Isobutyl methyl ketone:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Components:

#### Acetone:

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Method : OECD Test Guideline 405

#### Barium sulfate:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/25/2025
2.0	11/14/2025	11543097-00003	Date of first issue: 06/12/2025

---

### Isobutyl acetate:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

### 2-(Propyloxy)ethanol:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days

### n-Butyl acetate:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

### 2-Methoxy-1-methylethyl acetate:

Species	:	Rabbit
Result	:	No eye irritation

### Titanium dioxide:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	The test was conducted according to guideline

### Pentan-2-one:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 7 days

### Isobutyl methyl ketone:

Species	:	Human
Result	:	Irritation to eyes, reversing within 21 days

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

### Components:

#### Acetone:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

### Barium sulfate:

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative  
Remarks : Based on data from similar materials

### Isobutyl acetate:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### 2-(Propyloxy)ethanol:

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### n-Butyl acetate:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

### 2-Methoxy-1-methylethyl acetate:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### Titanium dioxide:

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative  
Remarks : The test was conducted according to guideline

### Pentan-2-one:

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

Result : negative  
Remarks : Based on data from similar materials

### Isobutyl methyl ketone:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Acetone:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

#### Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

#### Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/25/2025
2.0	11/14/2025	11543097-00003	Date of first issue: 06/12/2025

---

Result: negative  
Remarks: Based on data from similar materials

### **Barium sulfate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

### **Isobutyl acetate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

### **2-(Propyloxy)ethanol:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

### **n-Butyl acetate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

### **2-Methoxy-1-methylethyl acetate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

### **Titanium dioxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: The test was conducted according to guideline

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: The test was conducted according to guideline

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
Remarks: The test was conducted according to guideline

Genotoxicity in vivo : Test Type: Transgenic rodent somatic cell gene mutation assay  
Species: Mouse (male)  
Application Route: Intravenous injection  
Method: OECD Test Guideline 488  
Result: negative  
Remarks: The test was conducted equivalent or similar to guideline

### **Pentan-2-one:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: Directive 67/548/EEC, Annex V, B.13/14.  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative  
Remarks: Based on data from similar materials

### Isobutyl methyl ketone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: equivocal

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative

### Carcinogenicity

Suspected of causing cancer.

### Components:

#### Acetone:

Species : Mouse  
Application Route : Skin contact  
Exposure time : 424 days  
Result : negative

#### Barium sulfate:

Species : Rat  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative  
Remarks : Based on data from similar materials

#### 2-Methoxy-1-methylethyl acetate:

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 453  
Result : negative  
Remarks : Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

### Isobutyl methyl ketone:

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : positive

Species : Mouse  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

### Reproductive toxicity

Not classified based on available information.

### Components:

#### Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

#### Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

#### Butane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/25/2025
2.0	11/14/2025	11543097-00003	Date of first issue: 06/12/2025

---

Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

### **Barium sulfate:**

Effects on fertility : Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative  
Remarks: Based on data from similar materials

### **Isobutyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OPPTS 870.3800  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Inhalation  
Result: negative  
Remarks: Based on data from similar materials

### **2-(Propyloxy)ethanol:**

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rabbit  
Application Route: inhalation (vapor)  
Result: negative

### **n-Butyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 416  
Result: negative

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### **2-Methoxy-1-methylethyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 416  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### **Titanium dioxide:**

Effects on fertility : Test Type: Extended one-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 443  
Result: negative  
Remarks: The test was conducted according to guideline

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative  
Remarks: The test was conducted according to guideline

### **Pentan-2-one:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 421  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 414  
Result: negative

### **Isobutyl methyl ketone:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/25/2025
2.0	11/14/2025	11543097-00003	Date of first issue: 06/12/2025

---

Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### STOT-single exposure

May cause drowsiness or dizziness.

#### Components:

##### **Acetone:**

Assessment : May cause drowsiness or dizziness.

##### **Propane:**

Assessment : May cause drowsiness or dizziness.

##### **Butane:**

Assessment : May cause drowsiness or dizziness.

##### **Isobutyl acetate:**

Assessment : May cause drowsiness or dizziness.  
Remarks : Based on data from similar materials

##### **n-Butyl acetate:**

Assessment : May cause drowsiness or dizziness.

##### **2-Methoxy-1-methylethyl acetate:**

Assessment : May cause drowsiness or dizziness.

##### **Isobutyl methyl ketone:**

Assessment : May cause drowsiness or dizziness.

### STOT-repeated exposure

Not classified based on available information.

#### Components:

##### **Barium sulfate:**

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

### Repeated dose toxicity

#### Components:

##### **Acetone:**

Species : Rat  
NOAEL : 900 mg/kg  
LOAEL : 1,700 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
NOAEL : 45 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 8 Weeks

##### **Propane:**

Species : Rat  
NOAEL : 7.214 mg/l  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

##### **Butane:**

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

##### **Barium sulfate:**

Species : Rat  
NOAEL : 61.1 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

##### **Isobutyl acetate:**

Species : Rat  
NOAEL : > 100 mg/kg  
Application Route : Ingestion  
Exposure time : 92 Days  
Remarks : Based on data from similar materials

Species : Rat  
NOAEL : > 2.4 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

### 2-(Propyloxy)ethanol:

Species : Rat  
LOAEL : 195 mg/kg  
Application Route : Ingestion  
Exposure time : 6 Weeks

### n-Butyl acetate:

Species : Rat  
NOAEL : 2.4 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days

### 2-Methoxy-1-methylethyl acetate:

Species : Rat  
NOAEL :  $\geq 1,000$  mg/kg  
Application Route : Ingestion  
Exposure time : 41 - 45 Days  
Method : OECD Test Guideline 422

Species : Rat  
NOAEL :  $> 1$  mg/l  
Application Route : inhalation (vapor)  
Exposure time : 2 y  
Method : OECD Test Guideline 453  
Remarks : Based on data from similar materials

Species : Rabbit  
NOAEL :  $> 200$  mg/kg  
Application Route : Skin contact  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

### Titanium dioxide:

Species : Rat  
NOAEL :  $\geq 1,000$  mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408  
Remarks : The test was conducted according to guideline

### Pentan-2-one:

Species : Rat  
NOAEL : 5.28 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks  
Method : OECD Test Guideline 413

### Isobutyl methyl ketone:

Species : Rat

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/25/2025
2.0	11/14/2025	11543097-00003	Date of first issue: 06/12/2025

---

NOAEL	:	250 mg/kg
LOAEL	:	1,000 mg/kg
Application Route	:	Ingestion
Exposure time	:	13 Weeks
Species	:	Rat
NOAEL	:	4.106 mg/l
Application Route	:	inhalation (vapor)
Exposure time	:	14 Weeks

### Aspiration toxicity

Not classified based on available information.

### Components:

#### Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

#### Pentan-2-one:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

#### Isobutyl methyl ketone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### Acetone:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia pulex (Water flea)): 8,800 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): >= 79 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to microorganisms	:	EC50: 61,150 mg/l Exposure time: 30 min Method: ISO 8192

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

### Barium sulfate:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l  
Exposure time: 48 h  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): > 1 mg/l  
Exposure time: 21 d  
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC50: > 600 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials
- NOEC: > 600 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials

### Isobutyl acetate:

- Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): 16.6 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 24.6 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

NOELR (Pseudokirchneriella subcapitata (green algae)): 196 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23.2 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC10 (Pseudomonas putida): 487 mg/l  
Exposure time: 6 h

### **2-(Propyloxy)ethanol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 5,000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 5,000 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : IC50: > 1,000 mg/l  
Exposure time: 16 h

### **n-Butyl acetate:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp. (Water flea)): 44 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/25/2025
2.0	11/14/2025	11543097-00003	Date of first issue: 06/12/2025

---

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23.2 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

### 2-Methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l  
Exposure time: 48 h  
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): > 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

NOEC (Raphidocelis subcapitata (freshwater green alga)): >= 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 100 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC10 (activated sludge): > 1,000 mg/l  
Exposure time: 30 min

### Titanium dioxide:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: The test was conducted according to guideline  
Based on transformation/dissolution testing and data from soluble metal compounds

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: The test was conducted according to guideline

Toxicity to algae/aquatic plants : EL50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l  
Exposure time: 72 h

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: The test was conducted according to guideline

NOELR (Raphidocelis subcapitata (freshwater green alga)):  
>= 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: The test was conducted according to guideline

Toxicity to microorganisms : NOEC (activated sludge): >= 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: The test was conducted according to guideline

### **Pentan-2-one:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1,240 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 110 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 150 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 73.77 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

### **Isobutyl methyl ketone:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 179 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 200 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 30 mg/l  
Exposure time: 21 d

### **Persistence and degradability**

#### **Components:**

#### **Acetone:**

Biodegradability : Result: Readily biodegradable.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

Biodegradation: 91 %  
Exposure time: 28 d

### Propane:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

### Butane:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

### Isobutyl acetate:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 81 %  
Exposure time: 20 d

### 2-(Propyloxy)ethanol:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 20 d

### n-Butyl acetate:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

### 2-Methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

### Pentan-2-one:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 70 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

### Isobutyl methyl ketone:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version 2.0      Revision Date: 11/14/2025      SDS Number: 11543097-00003      Date of last issue: 06/25/2025  
Date of first issue: 06/12/2025

---

### Bioaccumulative potential

#### Components:

##### **Acetone:**

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

##### **Butane:**

Partition coefficient: n-octanol/water : log Pow: 2.31

##### **Barium sulfate:**

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)  
Bioconcentration factor (BCF): < 500

Partition coefficient: n-octanol/water : log Pow: -1.03  
Remarks: Calculation

##### **Isobutyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2.3

##### **2-(Propyloxy)ethanol:**

Partition coefficient: n-octanol/water : log Pow: 0.673

##### **n-Butyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2.3

##### **2-Methoxy-1-methylethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1.2

##### **Pentan-2-one:**

Partition coefficient: n-octanol/water : log Pow: 0.857

##### **Isobutyl methyl ketone:**

Partition coefficient: n-octanol/water : log Pow: 1.9

##### **Mobility in soil**

No data available

##### **Other adverse effects**

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Do not dispose of waste into sewer.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/25/2025
2.0	11/14/2025	11543097-00003	Date of first issue: 06/12/2025

Contaminated packaging : Dispose of in accordance with local regulations.  
: Please ensure aerosol cans are sprayed completely empty (including propellant)  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
Environmentally hazardous : no

##### IATA-DGR

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

##### IMDG-Code

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### TDG

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
ERG Code : 126

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/25/2025
2.0	11/14/2025	11543097-00003	Date of first issue: 06/12/2025

Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### The ingredients of this product are reported in the following inventories:

CA. DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

### Canadian lists

|| No substances are subject to CEPA Section 84 Ministerial Conditions.

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AllC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory con-

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FPT BLACK GRAY, 340 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/25/2025
2.0	11/14/2025	11543097-00003	Date of first issue: 06/12/2025

---

centration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/14/2025  
Date format : mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8