

SAFETY DATA SHEET

Revision Date 28-Oct-2016

Revision Number 0

This document complies with the US OSHA Hazard Communication Standard (29 CFR 1910.1200), Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR), and Mexico's NMX-R-019-SC-2011.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier		
Product Name	Sudz Off (Detergent Removable) All Colors	
Other means of identification		
Part Number	Black (44985, 91985), Blue (44938, 91938), Green (44371, 91371), Red (44939, 91939), White (44146, 91146), Yellow (44694, 91694)	
Formula Code	Z985 (Black), X938 (Blue), Y371 (Green), X939 (Red), Z146 (White), Z694 (Yellow)	
UN-Number	UN1263	
Synonyms	None	
Recommended use of the chemical and restrictions on use		
Recommended Use	Solvent based marker	
Uses advised against	No information available	
Supplier's details		
Manufacturer ITW Permatex Canada 1-35 Brownridge Road Halton Hills, ON, L7G 0C6 Canada	Supplier Wurth Canada Limited 345 Hanlon Creek Blvd Guelph, ON N1C 0A1 905 564-6225 prodsafe@wurth.ca	
Emergency telephone number		
Emergency Telephone Number	613 996-6666 (CANUTEC)	
Classification	2. HAZARDS IDENTIFICATION	

This product is considered hazardous according to the criteria set within the US OSHA Hazard Communication Standard (29 CFR 1910.1200), Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR), and Mexico's NMX-R-019-SC-2011.

Acute	Oral	Toxicity

Category 4

Acute Dermal Toxicity	Category 4
Serious Eye Damage/Eye Irritation	Category 1
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3
Flammable liquids	Category 3

Label Elements

Danger



Hazard Statements

Harmful if swallowed Harmful in contact with skin Causes serious eye damage May cause drowsiness or dizziness Flammable liquid and vapor.

Physical and Health Hazards Not Otherwise Classified Not applicable.

Precautionary Statements

Prevention

- Wear protective gloves/protective clothing/eye protection/face protection.
- · Wash face, hands and any exposed skin thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Keep away from heat/sparks/open flames/hot surfaces No smoking.
- Keep container tightly closed.
- · Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- · Take precautionary measures against static discharge.
- Keep cool.

General Advice

• Specific measures (see supplemental first aid instructions on this label)

Eyes

• IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

• Immediately call a POISON CENTER or doctor/physician.

Skin

- · Call a POISON CENTER or doctor/physician if you feel unwell.
- Wash contaminated clothing before reuse.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion

• IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Rinse mouth.

Fire

• In case of fire: Use CO2, dry chemical, or foam for extinction.

Storage

- Store in a well-ventilated place. Keep container tightly closed.
- Store locked up.

Disposal

• Dispose of contents/container to an approved waste disposal plant.

Other information

62.2166% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Hazardous Material Information Review Act registry number (HMIRA registry #)	
Propanol	71-23-8	92.14	-	-
Titanium dioxide	13463-67-7	32.34	-	-
Diacetone alcohol	123-42-2	11.51	-	-
Silicon dioxide	7631-86-9	5	-	-
Aluminum hydroxide	21645-51-2	3.33	-	-

4. FIRST AID MEASURES

Description of necessary first-aid measures

General Advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.		
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Immediate medical attention is required.		
Skin Contact	Flush with cool water. If skin irritation persists, call a physician.		
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.		
Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Consult a physician if necessary.		
Protection of First-aiders	Use personal protective equipment. Remove all sources of ignition.		
Most important symptoms/effects, acute and delayed			
Most Important Symptoms/Effects	Serious eye irritation or damage. Drowsiness. Dizziness.		
Indication of immediate medical att	Indication of immediate medical attention and special treatment needed, if necessary		
Notes to Physician	Treat symptomatically.		
5. FIRE-FIGHTING MEASURES			
Suitable Extinguishing Media	Carbon dioxide (CO 2). Foam. Dry chemical.		
Unsuitable Extinguishing Media	No information available.		
Specific Hazards Arising from the Chemical	Flammable. Keep product and empty container away from heat and sources of ignition. Risk of ignition. Vapors may travel to source of ignition and flash back.		

Explosion Data Sensitivity to Mechanical Impac Sensitivity to Static Discharge	t None. Yes.		
Protective Equipment and Precautions for Firefighters	Wear self contained breathing apparatus for fire fighting if necessary. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.		
	6. ACCIDENTAL RELEASE MEASURES		
Personal precautions, protective eq	uipment and emergency procedures		
Personal Precautions	Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Stop leak if you can do it without risk. Take precautionary measures against static discharges.		
Environmental Precautions			
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.		
Methods and materials for containment and cleaning up			
Methods for Containment	Prevent further leakage or spillage if safe to do so.		
Methods for Cleaning Up	Small spillage: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Large spillage: Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product.		
	7. HANDLING AND STORAGE		
Precautions for safe handling			
Handling	Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.		
Conditions for safe storage, includi	ng any incompatibilities		
Storage	Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children. Keep container closed when not in use. Keep away from incompatible materials.		

Incompatible Products

Strong oxidizing agents. Strong reducing agents. Strong alkalis. Strong acids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Propanol	TWA: 100 ppm	TWA: 200 ppm	IDLH: 800 ppm
71-23-8		TWA: 500 mg/m ³	TWA: 200 ppm
		(vacated) TWA: 200 ppm	TWA: 500 mg/m ³
		(vacated) TWA: 500 mg/m ³	STEL: 250 ppm
		(vacated) STEL: 250 ppm	STEL: 625 mg/m ³
		(vacated) STEL: 625 mg/m ³	-
Titanium dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³
13463-67-7		(vacated) TWA: 10 mg/m ³ total	-

			dust	
Г	Diacetone alcohol	TWA: 50 ppm	TWA: 50 ppm	IDLH: 1800 ppm
	123-42-2		TWA: 240 mg/m ³	TWA: 50 ppm
			(vacated) TWA: 50 ppm	TWA: 240 mg/m ³
			(vacated) TWA: 240 mg/m ³	_
Γ	Silicon dioxide	10 mg/m ³	20 mppcf TWA; ((80)/(% SiO2)	IDLH: 3000 mg/m ³
	7631-86-9		mg/m ³)	TWA: 6 mg/m ³
Γ	Aluminum hydroxide	TWA: 1 mg/m ³ respirable	-	-
	21645-51-2	particulate matter		

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).		
Appropriate engineering controls			
Engineering Measures	Showers Eyewash stations Ventilation systems		
Individual protection measures, such as personal protective equipment			
Eye/Face Protection Skin and Body Protection Respiratory Protection	Goggles. If splashes are likely to occur, wear: Chemical splash goggles. Chemical resistant gloves. Risk of contact: Boots. Apron. No special protective equipment required. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.		
Hygiene Measures	When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.		

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid.	Appearance	Varies, Thin viscosity,
Odor	Alcohol.	Odor Threshold	No information available.
<u>Property</u>	<u>Values</u>	<u>Remarks/ - N</u>	
pH	No data available	None known	
Melting Point/Range	No data available	None known	
Boiling Point/Boiling Range	97.22 °C / 207 °F	None known	
Flash Point	25 °C / 77 °F	Tag closed cu	
Evaporation rate	1.3 (BuAc = 1)	None known	
Flammability (solid, gas) Flammability Limits in Air upper flammability limit	No data available 13.7	None known	
lower flammability limit Vapor Pressure Vapor Density Specific Gravity	2.1 No data available > 1 (air = 1) No data available	None known None known None known	
Water Solubility	70-80%	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octand	bl/water No data available	None known	
Autoignition Temperature	No data available	None known	
Decomposition Temperature	No data available	None known	
Viscosity	No data available	None known	
Flammable Properties Explosive Properties	No data available	nmable; may be ignited by heat	, sparks or flames.
Oxidizing Properties <u>Other information</u>	No data available		

VOC Content (%)	Z985 Black: 88% X939 Red: 92.12%
	X938 Blue: 89.65%
	Z146 White: 49.16%
	Y371 Green: 91.25%
	Z694 Yellow: 49.22%
VOC (g/l)	Z985 Black: 791 g/L
	X939 Red: 771 g/L
	X938 Blue: 737 g/L
	Z146 White: 564 g/L
	Y371 Green: 750 g/L
	Z694 Yellow: 568 g/L

10. STABILITY AND REACTIVITY

Reactivity	No data available.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Incompatible products.
Incompatible materials	Strong oxidizing agents. Strong reducing agents. Strong alkalis. Strong acids.

Hazardous decomposition products Carbon oxides. Smoke Soot.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Inhalation	May cause drowsiness and dizziness. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal
Eye Contact	Causes serious eye damage.
Skin Contact	Harmful in contact with skin.
Ingestion	Harmful if swallowed.

Numerical measures of toxicity - Product

Unknown acute toxicity62.2166% of the mixture consists of ingredient(s) of unknown toxicity.The following values are calculated based on chapter 3.1 of the GHS document:LD50 Oral725 mg/kg; Acute toxicity estimateLD50 Dermal1600 mg/kg; Acute toxicity estimate mg/L

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Propanol	= 1870 mg/kg (Rat)	= 4049 mg/kg (Rabbit)	> 13548 ppm (Rat)4 h	
Titanium dioxide	> 10000 mg/kg (Rat)	-	-	
Diacetone alcohol	> 4 g/kg (Rat)	= 13630 mg/kg (Rabbit) = 13500	> 7.23 g/m³ (Rat)8 h	
		mg/kg (Rabbit)		
Silicon dioxide	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	>2.2 mg/L (Rat)4 h	
Aluminum hydroxide	> 5000 mg/kg (Rat)	-	-	

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Respiratory or Skin Sensitization Germ Cell Mutagenicity Carcinogenicity

No information available. No information available. This product contains titanium dioxide which is classified as an IARC 2B carcinogen based

on laboratory studies where animals were exposed to titanium dioxide dust. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B	-	-
Silicon dioxide		Group 3		

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to its Carcinogenicity to Humans

Reproductive Toxicity STOT - single exposure STOT - repeated exposure	No information available. May cause drowsiness and dizziness No information available.
Chronic Toxicity	Avoid repeated exposure. May cause adverse liver effects. May cause adverse effects on
	the bone marrow and blood-forming system.
Target Organ Effects	Liver. Kidney. Respiratory system. Eyes. Skin. Central nervous system (CNS). Blood.
	Gastrointestinal tract (GI). Lungs.
Aspiration Hazard	No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Propanol		LC50 96 h: = 4480 mg/L	EC50 = 17700 mg/L 5 min	EC50 48 h: 3339 - 3977
71-23-8		flow-through (Pimephales	EC50 = 45000 mg/L 5 h	mg/L Static (Daphnia
		promelas)	EC50 = 8686 mg/L 15 min	magna) EC50 48 h: = 3642
			EC50 = 980 mg/L 12 h	mg/L (Daphnia magna)
Diacetone alcohol		LC50 96 h: = 420 mg/L		EC50 24 h: = 8750 mg/L
123-42-2		(Lepomis macrochirus) LC50		(Daphnia magna)
		96 h: = 420 mg/L static		
		(Lepomis macrochirus)		
Silicon dioxide	EC50 72 h: = 440 mg/L	LC50 96 h: = 5000 mg/L		EC50 48 h: = 7600 mg/L
7631-86-9	(Pseudokirchneriella	static (Brachydanio rerio)		(Ceriodaphnia dubia)
	subcapitata)			

Persistence and Degradability No information available.

Bioaccumulation

Chemical Name	Log Pow
Propanol	0.34
Diacetone alcohol	1.03

Mobility

No information available.

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with local/regional/national regulations.

Contaminated Packaging Do not re-use empty containers.

US EPA Waste Number D001 U239 This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Propanol	Toxic
	Ignitable

14. TRANSPORT INFORMATION

DOT

UN-Number Proper shipping name Hazard Class Packing Group Description Emergency Response Guide Number	UN1263 Paint 3 III UN1263, Paint, 3, III 128
TDG UN-Number Proper Shipping Name Hazard Class Packing Group Description	UN1263 Paint 3 III UN1263, Paint, 3, III
MEX UN-Number Proper Shipping Name Hazard Class Packing Group Description	UN1263 Paint 3 III UN1263, Paint, 3, III
IATA_ UN-Number Proper Shipping Name Hazard Class Packing Group ERG Code Description	UN1263 Paint 3 III 3L UN1263, Paint, 3, III
IMDG/IMO UN-Number Proper Shipping Name Hazard Class Packing Group EmS No. Description	UN1263 Paint 3 III F-E, S-E UN1263, Paint, 3, III, (25°C c.c.)

15. REGULATORY INFORMATION

International Regulations

Ozone depleting substances Persistent Organic Pollutants Hazardous Waste The Rotterdam Convention (Prior Informed Consent) International Convention for the Prevention of Pollution from Ships (MARPOL)	Not applicable Not applicable Not applicable Not applicable
International Inventories TSCA	Complies

DSL

Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories	
Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

<u>CERCLA</u>

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65	
Titanium dioxide	13463-67-7	Carcinogen	
Quartz	14808-60-7	Carcinogen	

U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Propanol	Х	Х	Х		Х
Titanium dioxide	Х	Х	Х		Х
Diacetone alcohol	Х	Х	Х		Х
Silicon dioxide	Х	Х	Х		
Xanthylium,9-(2-carboxyphe nyl)-3,6-bis(diethyl amino)-, hydrogenbis[3-[(4,5-dihydro- 3-methyl-5	Х		X	Х	

U.S. EPA Label Information EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION Health Hazard 3 Flammability 3 Instability 0 **Physical and Chemical** NFPA Hazards -Health Hazard 3 Flammability 3 Physical Hazard 0 Personal Protection X HMIS **Prepared By** Product Stewardship 23 British American Blvd. Latham, NY 12110

	1-800-572-6501
Issuing Date	28-Oct-2016
Revision Date	28-Oct-2016
Revision Note	Initial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text. End of Safety Data Sheet