

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version 2.3 Revision Date: 08/22/2023 SDS Number: 10294674-00006 Date of last issue: 07/28/2023
Date of first issue: 11/25/2021

SECTION 1. IDENTIFICATION

Product name : SIG 3000, Super impact grease, 397 g
Product code : 889.0402
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Skin sensitization : Category 1

GHS label elements

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version 2.3 Revision Date: 08/22/2023 SDS Number: 10294674-00006 Date of last issue: 07/28/2023
Date of first issue: 11/25/2021

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

Precautionary Statements :

Prevention:

P261 Avoid breathing dust, fume, gas, mist, vapors or spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy naphthenic	No data available	64742-52-5	$\geq 30 - < 60$ *
Distillates (petroleum), hydrotreated light naphthenic	Baseoil - unspecified	64742-53-6	$\geq 30 - < 60$ *
Antimony, dialkyl dithiocarbamate	Antimony Diamyldithiocarbamate	15890-25-2	$\geq 1 - < 5$ *
Quartz	Crystallized silicon dioxide	14808-60-7	$\geq 0.1 - < 1$ *
Barium dinonyl naphthalenesulphonate	Naphthalenesulfonic acid, dinonyl-, barium salt (2:1)	25619-56-1	$\geq 0.1 - < 1$ *

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.3	08/22/2023	10294674-00006	Date of first issue: 11/25/2021

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)
Sulfur oxides

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.3	08/22/2023	10294674-00006	Date of first issue: 11/25/2021

Metal oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.
Avoid breathing dust, fume, gas, mist, vapors or spray.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version 2.3 Revision Date: 08/22/2023 SDS Number: 10294674-00006 Date of last issue: 07/28/2023
Date of first issue: 11/25/2021

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Antimony, dialkyl dithiocarbamate	15890-25-2	TWA	0.5 mg/m ³ (antimony)	CA AB OEL
		TWAEV	0.5 mg/m ³ (antimony)	CA QC OEL
		TWA	0.5 mg/m ³ (antimony)	CA BC OEL
		TWA	0.5 mg/m ³ (antimony)	ACGIH
		Quartz	14808-60-7	TWA (Respirable particulates)
TWA (Respirable fraction)	0.1 mg/m ³	CA ON OEL		
TWAEV (respirable dust)	0.1 mg/m ³	CA QC OEL		
TWA (Respirable)	0.025 mg/m ³ (Silica)	CA BC OEL		
TWA (Respirable particulate)	0.025 mg/m ³ (Silica)	ACGIH		

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version 2.3 Revision Date: 08/22/2023 SDS Number: 10294674-00006 Date of last issue: 07/28/2023
Date of first issue: 11/25/2021

		late matter)		
--	--	--------------	--	--

This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Quartz

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection

Material : Chemical-resistant gloves

Remarks : For prolonged or repeated contact use protective gloves. Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version 2.3 Revision Date: 08/22/2023 SDS Number: 10294674-00006 Date of last issue: 07/28/2023
Date of first issue: 11/25/2021

Appearance : gel

Color : dark green

Odor : oily

Odor Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : Decomposes without melting.

Initial boiling point and boiling range : No data available

Flash point : 204 °C
Solvent

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : Not applicable

Lower explosion limit / Lower flammability limit : Not applicable

Vapor pressure : < 0.01 hPa (20 °C)
negligible

Relative vapor density : Not applicable

Density : 1 g/cm³ (20 °C)

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : Not applicable

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : > 10000 mm²/s (40 °C)

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version 2.3 Revision Date: 08/22/2023 SDS Number: 10294674-00006 Date of last issue: 07/28/2023
Date of first issue: 11/25/2021

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version 2.3 Revision Date: 08/22/2023 SDS Number: 10294674-00006 Date of last issue: 07/28/2023
Date of first issue: 11/25/2021

Distillates (petroleum), hydrotreated light naphthenic:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Antimony, dialkyl dithiocarbamate:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Quartz:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Barium dinonyl naphthalenesulphonate:

- Acute oral toxicity : LD50 (Rat): > 300 - 2,000 mg/kg
Remarks: Based on data from similar materials
- Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgment
Remarks: Based on national or regional regulation.
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

- Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated light naphthenic:

- Species : Rabbit
Result : No skin irritation

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version 2.3 Revision Date: 08/22/2023 SDS Number: 10294674-00006 Date of last issue: 07/28/2023
Date of first issue: 11/25/2021

Antimony, dialkyl dithiocarbamate:

Species : Rabbit
Result : No skin irritation

Barium dinonyl naphthalenesulphonate:

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated light naphthenic:

Species : Rabbit
Result : No eye irritation

Antimony, dialkyl dithiocarbamate:

Species : Rabbit
Result : No eye irritation

Barium dinonyl naphthalenesulphonate:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version 2.3 Revision Date: 08/22/2023 SDS Number: 10294674-00006 Date of last issue: 07/28/2023
Date of first issue: 11/25/2021

Distillates (petroleum), hydrotreated light naphthenic:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Antimony, dialkyl dithiocarbamate:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

Barium dinonyl naphthalenesulphonate:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : positive
Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitization in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cyto-genetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated light naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cyto-genetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version 2.3 Revision Date: 08/22/2023 SDS Number: 10294674-00006 Date of last issue: 07/28/2023
Date of first issue: 11/25/2021

Result: negative

Antimony, dialkyl dithiocarbamate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: positive
Remarks: Based on data from similar materials

Barium dinonyl naphthalenesulphonate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks
Method : OECD Test Guideline 451
Result : negative

Distillates (petroleum), hydrotreated light naphthenic:

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks
Result : negative

Quartz:

Species : Humans
Application Route : inhalation (dust/mist/fume)

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version 2.3 Revision Date: 08/22/2023 SDS Number: 10294674-00006 Date of last issue: 07/28/2023
Date of first issue: 11/25/2021

Result : positive
Remarks : This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

Reproductive toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated light naphthenic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Skin contact
Result: negative

Antimony, dialkyl dithiocarbamate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Barium dinonyl naphthalenesulphonate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version 2.3 Revision Date: 08/22/2023 SDS Number: 10294674-00006 Date of last issue: 07/28/2023
Date of first issue: 11/25/2021

Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Components:

Quartz:

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Lungs
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rat
NOAEL : > 0.98 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated light naphthenic:

Species : Rabbit
NOAEL : 1,000 mg/kg
Application Route : Skin contact
Exposure time : 4 Weeks
Method : OECD Test Guideline 410

Antimony, dialkyl dithiocarbamate:

Species : Rat
NOAEL : 1,000 mg/kg
Application Route : Ingestion
Exposure time : 54 Days
Method : OECD Test Guideline 422

Quartz:

Species : Humans
LOAEL : 0.053 mg/m³
Application Route : Inhalation
Remarks : This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version 2.3 Revision Date: 08/22/2023 SDS Number: 10294674-00006 Date of last issue: 07/28/2023
Date of first issue: 11/25/2021

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated light naphthenic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d

Toxicity to microorganisms : NOEC (Photobacterium phosphoreum): > 2.17 mg/l
Exposure time: 4 d

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version 2.3 Revision Date: 08/22/2023 SDS Number: 10294674-00006 Date of last issue: 07/28/2023
Date of first issue: 11/25/2021

Antimony, dialkyl dithiocarbamate:

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

EL10 (Pseudokirchneriella subcapitata (green algae)): 34 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 0.02 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Quartz:

Ecotoxicology Assessment

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Barium dinonyl naphthalenesulphonate:

Toxicity to fish : LL50 (Cyprinus carpio (Carp)): > 100 mg/l
Exposure time: 98 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
No toxicity at the limit of solubility.

EL10 (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.3	08/22/2023	10294674-00006	Date of first issue: 11/25/2021

Toxicity to microorganisms : IC50: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Persistence and degradability

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Distillates (petroleum), hydrotreated light naphthenic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Antimony, dialkyl dithiocarbamate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 20 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Barium dinonyl naphthalenesulphonate:

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

Antimony, dialkyl dithiocarbamate:

Partition coefficient: n-octanol/water : log Pow: > 4
Method: Regulation (EC) No. 440/2008, Annex, A.8

Barium dinonyl naphthalenesulphonate:

Partition coefficient: n-octanol/water : log Pow: 23.3
Remarks: Calculation method

Mobility in soil

No data available

Other adverse effects

No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.3	08/22/2023	10294674-00006	Date of first issue: 11/25/2021

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.
-

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content : Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations
VOC content: < 1 %

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.3	08/22/2023	10294674-00006	Date of first issue: 11/25/2021

CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
--------------------------------------------------------------------	---	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Revision Date	:	08/22/2023
Date format	:	mm/dd/yyyy

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SIG 3000, Super impact grease, 397 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.3	08/22/2023	10294674-00006	Date of first issue: 11/25/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8