

**RTV SILICONE GASKET, Low volatility, Blue,  
300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1781291-00004	Date of first issue: 12/30/2009

---

**SECTION 1. IDENTIFICATION**

Product name : RTV SILICONE GASKET, Low volatility, Blue, 300 mL  
Product code : 890.00004  
Other means of identification : No data available

**Manufacturer or supplier's details**

Company name of supplier : Würth Canada Limited  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : +1 (905) 564 6225  
Telefax : +1 (905) 564 3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)  
  
Urgences impliquant un déversement, incendie, explosion ou exposition:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences liées au transport:  
CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)  
  
E-mail address : prodsafe@wurth.ca

**Recommended use of the chemical and restrictions on use**

Recommended use : Adhesives  
  
Restrictions on use : Not applicable

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Not a hazardous substance or mixture.

**GHS label elements**

Not a hazardous substance or mixture.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

**RTV SILICONE GASKET, Low volatility, Blue,  
300 mL**

Version 3.1      Revision Date: 09/21/2021      SDS Number: 1781291-00004      Date of last issue: 11/05/2020  
Date of first issue: 12/30/2009

Substance / Mixture : Mixture

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated middle	No data available	64742-46-7	$\geq 5 - < 10$ *
Diiron trioxide	No data available	1309-37-1	$\geq 1 - < 5$ *
Titanium dioxide	Titanic anhydride	13463-67-7	$\geq 0.1 - < 1$ *

\* Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.  
Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : None known.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically and supportively.

**SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides  
Metal oxides

**RTV SILICONE GASKET, Low volatility, Blue,  
300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1781291-00004	Date of first issue: 12/30/2009

---

Nitrogen oxides (NOx)

- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
- 

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the environment.
-

**RTV SILICONE GASKET, Low volatility, Blue,  
300 mL**

Version 3.1      Revision Date: 09/21/2021      SDS Number: 1781291-00004      Date of last issue: 11/05/2020  
Date of first issue: 12/30/2009

- Conditions for safe storage : Keep in properly labeled containers.  
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents
- Recommended storage temperature : 20 - 25 °C
- Storage period : 24 Months

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
Diiron trioxide	1309-37-1	STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Respirable)	5 mg/m <sup>3</sup>	CA AB OEL
		TWA (Fumes)	5 mg/m <sup>3</sup> (Iron)	CA BC OEL
		TWA (Dust)	5 mg/m <sup>3</sup> (Iron)	CA BC OEL
		STEL (Fumes)	10 mg/m <sup>3</sup> (Iron)	CA BC OEL
Titanium dioxide	13463-67-7	TWAEV (fume and dust)	5 mg/m <sup>3</sup> (Iron)	CA QC OEL
		TWA (Respirable particulate matter)	5 mg/m <sup>3</sup>	ACGIH
		TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA	10 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH

**These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.**

**RTV SILICONE GASKET, Low volatility, Blue,  
300 mL**

Version 3.1	Revision Date: 09/21/2021	SDS Number: 1781291-00004	Date of last issue: 11/05/2020 Date of first issue: 12/30/2009
----------------	------------------------------	------------------------------	-------------------------------------------------------------------

---

Titanium dioxide

**Engineering measures** : Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

**Personal protective equipment**

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

## Hand protection

Material : Latex gloves

Material : Nitrile rubber

Material : butyl-rubber

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:  
Safety glasses  
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.  
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : paste

Color : blue

Odor : Acetic acid

**RTV SILICONE GASKET, Low volatility, Blue,  
300 mL**

Version 3.1	Revision Date: 09/21/2021	SDS Number: 1781291-00004	Date of last issue: 11/05/2020 Date of first issue: 12/30/2009
----------------	------------------------------	------------------------------	-------------------------------------------------------------------

---

Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	> 100 °C Method: closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	1.007 (25 °C)
Density	:	1.007 g/cm <sup>3</sup>
Bulk density	:	1.007 kg/m <sup>3</sup>
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive

**RTV SILICONE GASKET, Low volatility, Blue,  
300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1781291-00004	Date of first issue: 12/30/2009

---

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Sublimation point : No data available

Particle size : Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated middle:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,000 mg/m<sup>3</sup>  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**Diiron trioxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

**Titanium dioxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

**RTV SILICONE GASKET, Low volatility, Blue,  
300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1781291-00004	Date of first issue: 12/30/2009

---

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated middle:**

Assessment : Repeated exposure may cause skin dryness or cracking.

**Diiron trioxide:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

**Titanium dioxide:**

Species : Rabbit  
Result : No skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated middle:**

Result : No eye irritation

**Diiron trioxide:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

**Titanium dioxide:**

Species : Rabbit  
Result : No eye irritation

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.



**RTV SILICONE GASKET, Low volatility, Blue,  
300 mL**

Version 3.1      Revision Date: 09/21/2021      SDS Number: 1781291-00004      Date of last issue: 11/05/2020  
Date of first issue: 12/30/2009

---

**Components:****Distillates (petroleum), hydrotreated middle:**

Test Type : Human repeat insult patch test (HRIPT)  
Routes of exposure : Skin contact  
Result : negative

**Diiron trioxide:**

Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

**Titanium dioxide:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Result : negative

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated middle:**

Genotoxicity in vitro : Test Type: In vitro sister chromatid exchange assay in mammalian cells  
Result: negative

**Diiron trioxide:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

**Titanium dioxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Components:****Diiron trioxide:**

Species : Rat  
Application Route : Intraperitoneal injection  
Exposure time : 790 - 914 days

**RTV SILICONE GASKET, Low volatility, Blue,  
300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1781291-00004	Date of first issue: 12/30/2009

---

Result : negative

**Titanium dioxide:**

Species : Rat  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years  
Method : OECD Test Guideline 453  
Result : positive  
Remarks : The mechanism or mode of action may not be relevant in humans.  
These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.

**Repeated dose toxicity****Components:****Titanium dioxide:**

Species : Rat  
NOAEL : 24,000 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days

Species : Rat  
NOAEL : 10 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 y

**Aspiration toxicity**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated middle:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**RTV SILICONE GASKET, Low volatility, Blue,  
300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1781291-00004	Date of first issue: 12/30/2009

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Distillates (petroleum), hydrotreated middle:**

- |                                                                        |   |                                                                                     |
|------------------------------------------------------------------------|---|-------------------------------------------------------------------------------------|
| Toxicity to fish                                                       | : | LC50 (Oncorhynchus mykiss (rainbow trout)): > 87,556 mg/l<br>Exposure time: 96 h    |
| Toxicity to daphnia and other aquatic invertebrates                    | : | EC50 (Daphnia magna (Water flea)): > 1,000 mg/l<br>Exposure time: 48 h              |
| Toxicity to algae/aquatic plants                                       | : | EC50 (Selenastrum capricornutum (green algae)): > 1,000 mg/l<br>Exposure time: 72 h |
| Toxicity to fish (Chronic toxicity)                                    | : | NOELR: > 1,000 mg/l<br>Exposure time: 28 d                                          |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOELR: 5 mg/l<br>Exposure time: 21 d                                                |
| Toxicity to microorganisms                                             | : | EC50: > 100 mg/l<br>Exposure time: 3 h                                              |

**Diiron trioxide:**

- |                                                     |   |                                                                                                         |
|-----------------------------------------------------|---|---------------------------------------------------------------------------------------------------------|
| Toxicity to fish                                    | : | LC50 (Danio rerio (zebra fish)): > 50,000 mg/l<br>Exposure time: 96 h                                   |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 100 mg/l<br>Exposure time: 48 h<br>Method: OECD Test Guideline 202 |
| Toxicity to microorganisms                          | : | EC50: > 10,000 mg/l<br>Exposure time: 3 h                                                               |

**Titanium dioxide:**

- |                                                     |   |                                                                                                                  |
|-----------------------------------------------------|---|------------------------------------------------------------------------------------------------------------------|
| Toxicity to fish                                    | : | LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l<br>Exposure time: 96 h<br>Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 100 mg/l<br>Exposure time: 48 h                                             |
| Toxicity to algae/aquatic plants                    | : | EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l<br>Exposure time: 72 h                                |
| Toxicity to microorganisms                          | : | EC50: > 1,000 mg/l<br>Exposure time: 3 h<br>Method: OECD Test Guideline 209                                      |

**RTV SILICONE GASKET, Low volatility, Blue,  
300 mL**

Version 3.1	Revision Date: 09/21/2021	SDS Number: 1781291-00004	Date of last issue: 11/05/2020 Date of first issue: 12/30/2009
----------------	------------------------------	------------------------------	-------------------------------------------------------------------

---

**Persistence and degradability****Components:****Distillates (petroleum), hydrotreated middle:**

Biodegradability : Result: Inherently biodegradable.

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

Not regulated as a dangerous good

**Special precautions for user**

Not applicable

---

**SECTION 15. REGULATORY INFORMATION****Volatile organic compounds** CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 -

**RTV SILICONE GASKET, Low volatility, Blue,  
300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1781291-00004	Date of first issue: 12/30/2009

**(VOC) content** Guidelines for VOC in Consumer Products  
VOC content: < 3 % / 30 g/l

**The ingredients of this product are reported in the following inventories:**

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

---

**SECTION 16. OTHER INFORMATION**
**Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation,

**RTV SILICONE GASKET, Low volatility, Blue,  
300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1781291-00004	Date of first issue: 12/30/2009

---

Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/21/2021  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8