

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version 3.1	Revision Date: 09/21/2021	SDS Number: 1780276-00005	Date of last issue: 11/05/2020 Date of first issue: 12/30/2009
----------------	------------------------------	------------------------------	---

SECTION 1. IDENTIFICATION

Product name : RTV SILICONE GASKET, High temperature, Red, 300 mL
Product code : 890.0005
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version 3.1 Revision Date: 09/21/2021 SDS Number: 1780276-00005 Date of last issue: 11/05/2020
Date of first issue: 12/30/2009

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated middle	No data available	64742-46-7	$\geq 5 - < 10$ *
Diiron trioxide	No data available	1309-37-1	$\geq 1 - < 5$ *
Aluminium powder (pyrophoric)	No data available	7429-90-5	$\geq 1 - < 5$ *
Titanium dioxide	Titanium(IV) oxide	13463-67-7	$\geq 0.1 - < 1$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Skin or eye contact with uncured photopolymer, vapors or condensate may result in skin or eye irritation, rash or allergic skin rashes.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1780276-00005	Date of first issue: 12/30/2009

- Hazardous combustion products : Carbon oxides
Metal oxides
Nitrogen oxides (NOx)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
-

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version 3.1 Revision Date: 09/21/2021 SDS Number: 1780276-00005 Date of last issue: 11/05/2020
Date of first issue: 12/30/2009

Keep away from water.
Protect from moisture.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

Recommended storage temperature : 20 - 25 °C

Storage period : 12 Months

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
Diiron trioxide	1309-37-1	TWA (Respirable)	5 mg/m ³	CA AB OEL
		TWA (Fumes)	5 mg/m ³ (Iron)	CA BC OEL
		TWA (Dust)	5 mg/m ³ (Iron)	CA BC OEL
		STEL (Fumes)	10 mg/m ³ (Iron)	CA BC OEL
		TWAEV (fume and dust)	5 mg/m ³ (Iron)	CA QC OEL
		TWA (Respirable particulate matter)	5 mg/m ³	ACGIH
Aluminium powder (pyrophoric)	7429-90-5	TWA (Dust)	10 mg/m ³	CA AB OEL
		TWAEV	10 mg/m ³	CA QC OEL
		TWAEV (Welding fumes)	5 mg/m ³ (Aluminum)	CA QC OEL
		TWA (Respirable)	1 mg/m ³ (Aluminum)	CA BC OEL
		TWA (Respi-	1 mg/m ³	ACGIH

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version 3.1 Revision Date: 09/21/2021 SDS Number: 1780276-00005 Date of last issue: 11/05/2020
Date of first issue: 12/30/2009

		able particu- late matter)	(Aluminum)	
Titanium dioxide	13463-67-7	TWA	10 mg/m ³	CA AB OEL
		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m ³	CA BC OEL
		TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Titanium dioxide

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection

Material : Latex gloves

Material : Nitrile rubber

Material : butyl-rubber

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:
Safety glasses
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1780276-00005	Date of first issue: 12/30/2009

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : dark gray, black, red

Odor : Acetic acid

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : > 100 °C
Method: Tag closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 1.007 g/cm³ (25 °C)

Bulk density : 1.007 kg/m³

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1780276-00005	Date of first issue: 12/30/2009

Solubility(ies)
Water solubility : No data available

Partition coefficient: n-
octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-
tions : Can react with strong oxidizing agents.
Hazardous decomposition products will be formed upon con-
tact with water or humid air.

Conditions to avoid : Exposure to moisture.

Incompatible materials : Oxidizing agents
Water

Hazardous decomposition
products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated middle:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version 3.1 Revision Date: 09/21/2021 SDS Number: 1780276-00005 Date of last issue: 11/05/2020
Date of first issue: 12/30/2009

Acute inhalation toxicity : LC50 (Rat): > 5,000 mg/m³
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Diiron trioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Aluminium powder (pyrophoric):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 0.888 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated middle:**

Assessment : Repeated exposure may cause skin dryness or cracking.

Diiron trioxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Aluminium powder (pyrophoric):

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Titanium dioxide:

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1780276-00005	Date of first issue: 12/30/2009

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated middle:**

Result : No eye irritation

Diiron trioxide:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Aluminium powder (pyrophoric):

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Titanium dioxide:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated middle:**

Test Type : Human repeat insult patch test (HRIPT)
Routes of exposure : Skin contact
Result : negative

Diiron trioxide:

Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Aluminium powder (pyrophoric):

Test Type : Draize Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1780276-00005	Date of first issue: 12/30/2009

Remarks : Based on data from similar materials

Titanium dioxide:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated middle:**

Genotoxicity in vitro : Test Type: In vitro sister chromatid exchange assay in mam-
malian cells
Result: negative

Diiron trioxide:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Aluminium powder (pyrophoric):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Result: negative

Carcinogenicity

Not classified based on available information.

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version 3.1 Revision Date: 09/21/2021 SDS Number: 1780276-00005 Date of last issue: 11/05/2020
Date of first issue: 12/30/2009

Components:**Diiron trioxide:**

Species : Rat
Application Route : Intraperitoneal injection
Exposure time : 790 - 914 days
Result : negative

Aluminium powder (pyrophoric):

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 1 Years
Result : negative

Titanium dioxide:

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Method : OECD Test Guideline 453
Result : positive
Remarks : The mechanism or mode of action may not be relevant in humans.
These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

Reproductive toxicity

Not classified based on available information.

Components:**Aluminium powder (pyrophoric):**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1780276-00005	Date of first issue: 12/30/2009

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity**Components:****Titanium dioxide:**

Species	:	Rat
NOAEL	:	24,000 mg/kg
Application Route	:	Ingestion
Exposure time	:	28 Days

Species	:	Rat
NOAEL	:	10 mg/m ³
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	2 y

Aspiration toxicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated middle:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Distillates (petroleum), hydrotreated middle:**

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 87,556 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Selenastrum capricornutum (green algae)): > 1,000 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOELR: > 1,000 mg/l Exposure time: 28 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOELR: 5 mg/l Exposure time: 21 d
Toxicity to microorganisms	:	EC50: > 100 mg/l Exposure time: 3 h

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1780276-00005	Date of first issue: 12/30/2009

Diiron trioxide:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 50,000 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to microorganisms : EC50: > 10,000 mg/l
Exposure time: 3 h

Aluminium powder (pyrophoric):

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0.135 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: No toxicity at the limit of solubility.
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 0.004 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: No toxicity at the limit of solubility.

Titanium dioxide:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l
Exposure time: 72 h
- Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Persistence and degradability**Components:****Distillates (petroleum), hydrotreated middle:**

- Biodegradability : Result: Inherently biodegradable.

Bioaccumulative potential

No data available

Mobility in soil

No data available

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1780276-00005	Date of first issue: 12/30/2009

Other adverse effectsNo data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

Not regulated as a dangerous good

Special precautions for userNot applicable

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: < 3 % / 30 g/l

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1780276-00005	Date of first issue: 12/30/2009

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
--	---	---

Revision Date	:	09/21/2021
Date format	:	mm/dd/yyyy

**RTV SILICONE GASKET, High temperature,
Red, 300 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/05/2020
3.1	09/21/2021	1780276-00005	Date of first issue: 12/30/2009

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8