

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version 5.0      Revision Date: 05/17/2024      SDS Number: 10697422-00012      Date of last issue: 12/18/2023  
Date of first issue: 01/25/2019

---

### SECTION 1. IDENTIFICATION

Product name : RUBBER PROFILE ADHESIVE, 250 mL  
Product code : 890.100014  
Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : +1 (905) 564 6225  
Telefax : +1 (905) 564 3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)  
  
Urgences impliquant un déversement, incendie, explosion ou exposition:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences liées au transport:  
CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)  
  
E-mail address : prodsafe@wurth.ca

#### Recommended use of the chemical and restrictions on use

Recommended use : Adhesives  
Restrictions on use : Not applicable

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 2  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Reproductive toxicity : Category 2  
Specific target organ toxicity : Category 3

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version 5.0      Revision Date: 05/17/2024      SDS Number: 10697422-00012      Date of last issue: 12/18/2023  
Date of first issue: 01/25/2019

---

- single exposure

### GHS label elements

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H361f Suspected of damaging fertility.

Precautionary Statements

: **Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical, ventilating and lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P261 Avoid breathing mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P332 + P313 If skin irritation occurs: Get medical attention.  
P337 + P313 If eye irritation persists: Get medical attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

**Storage:**

P403 + P233 + P235 Store in a well-ventilated place. Keep con-

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version 5.0      Revision Date: 05/17/2024      SDS Number: 10697422-00012      Date of last issue: 12/18/2023  
Date of first issue: 01/25/2019

tainer tightly closed. Keep cool.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

### Other hazards

Vapors may form explosive mixture with air.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Adhesives

### Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Butanone	Ethyl methyl ketone	78-93-3	$\geq 30 - < 60$ *
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Naphtha (petroleum), hydrotreated light	92128-66-0	$\geq 10 - < 30$ *
Acetone	2-Propanone	67-64-1	$\geq 10 - < 30$ *
Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich	Naphtha (petroleum), hydrotreated light	64742-49-0	$\geq 0.1 - < 1$ *

\* Actual concentration or concentration range is withheld as a trade secret

### Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0

## SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/18/2023
5.0	05/17/2024	10697422-00012	Date of first issue: 01/25/2019

- 
- |   |   |   |
|---|---|---|
| In case of eye contact                                      | : | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.<br>If easy to do, remove contact lens, if worn.<br>Get medical attention.          |
| If swallowed  | : | If swallowed, DO NOT induce vomiting.<br>Get medical attention.<br>Rinse mouth thoroughly with water.   |
| Most important symptoms and effects, both acute and delayed | : | Causes skin irritation.<br>Causes serious eye irritation.<br>May cause drowsiness or dizziness.<br>Suspected of damaging fertility.   |
| Protection of first-aiders                                  | : | First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8). |
| Notes to physician  | : | Treat symptomatically and supportively.   |

---

### SECTION 5. FIRE-FIGHTING MEASURES

- |  |   |   |
|--|---|---|
| Suitable extinguishing media                   | : | Water spray<br>Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical  |
| Unsuitable extinguishing media                 | : | High volume water jet   |
| Specific hazards during fire fighting          | : | Do not use a solid water stream as it may scatter and spread fire.<br>Flash back possible over considerable distance.<br>Vapors may form explosive mixtures with air.<br>Exposure to combustion products may be a hazard to health.             |
| Hazardous combustion products                  | : | Carbon oxides<br>Chlorine compounds   |
| Specific extinguishing methods                 | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.<br>Use water spray to cool unopened containers.<br>Remove undamaged containers from fire area if it is safe to do so.<br>Evacuate area. |
| Special protective equipment for fire-fighters | : | In the event of fire, wear self-contained breathing apparatus.<br>Use personal protective equipment.  |

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- |                                  |   |                                 |
|----------------------------------|---|---------------------------------|
| Personal precautions, protection | : | Remove all sources of ignition. |
|----------------------------------|---|---------------------------------|

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/18/2023
5.0	05/17/2024	10697422-00012	Date of first issue: 01/25/2019

---

- tive equipment and emergency procedures : Ventilate the area.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

- Technical measures : Ground and bond container and receiving equipment.  
See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing mist or vapors.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Non-sparking tools should be used.  
Keep container tightly closed.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version 5.0      Revision Date: 05/17/2024      SDS Number: 10697422-00012      Date of last issue: 12/18/2023  
Date of first issue: 01/25/2019

Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Self-reactive substances and mixtures  
Organic peroxides  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases  
Very acutely toxic substances and mixtures

Recommended storage temperature : > 0 °C

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
Butanone	78-93-3	TWA	200 ppm 590 mg/m <sup>3</sup>	CA AB OEL		
		STEL	300 ppm 885 mg/m <sup>3</sup>	CA AB OEL		
		TWA	50 ppm	CA BC OEL		
		STEL	100 ppm	CA BC OEL		
		TWAEV	50 ppm 150 mg/m <sup>3</sup>	CA QC OEL		
		STEV	100 ppm 300 mg/m <sup>3</sup>	CA QC OEL		
		TWA	200 ppm	ACGIH		
		STEL	300 ppm	ACGIH		
		Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	92128-66-0	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
				STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
TWAEV (Mist)	5 mg/m <sup>3</sup>			CA QC OEL		

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version 5.0      Revision Date: 05/17/2024      SDS Number: 10697422-00012      Date of last issue: 12/18/2023  
Date of first issue: 01/25/2019

		- Inhalable dust)		
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m <sup>3</sup>	CA AB OEL
		STEL	750 ppm 1,800 mg/m <sup>3</sup>	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	250 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich	64742-49-0	TWA	50 ppm 176 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 176 mg/m <sup>3</sup>	CA QC OEL
		TWA	50 ppm	ACGIH

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich	64742-49-0	2,5-Hexanedio- ne	Urine	End of shift	0.5 mg/l	ACGIH BEI

**Engineering measures** : Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version 5.0      Revision Date: 05/17/2024      SDS Number: 10697422-00012      Date of last issue: 12/18/2023  
Date of first issue: 01/25/2019

---

- Filter type : Self-contained breathing apparatus
- Hand protection  
Material : butyl-rubber  
Break through time : <= 15 min  
Glove thickness : 0.7 mm
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:  
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : amber
- Odor : solvent
- Odor Threshold : No data available
- pH : substance/mixture is non-soluble (in water)
- Melting point/freezing point : No data available



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/18/2023
5.0	05/17/2024	10697422-00012	Date of first issue: 01/25/2019

---

Initial boiling point and boiling range : 56 °C

Flash point : -17 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : 13 %(V)

Lower explosion limit / Lower flammability limit : 0.6 %(V)

Vapor pressure : 240 hPa (20 °C)

Relative vapor density : No data available

Density : 0.83 g/cm<sup>3</sup> (20 °C)

Solubility(ies)  
Water solubility : partly soluble

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : > 200 °C

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : 1,600 mPa.s ( 20 °C)  
Method: Brookfield

Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s ( 40 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/18/2023
5.0	05/17/2024	10697422-00012	Date of first issue: 01/25/2019

---

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Highly flammable liquid and vapor.  
Vapors may form explosive mixture with air.  
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

#### Components:

##### **Butanone:**

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 25.5 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 436  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25.2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/18/2023
5.0	05/17/2024	10697422-00012	Date of first issue: 01/25/2019

---

### Acetone:

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

### Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 259.354 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Remarks: Based on data from similar materials

### Skin corrosion/irritation

Causes skin irritation.

### Components:

#### Butanone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

### Acetone:

Assessment : Repeated exposure may cause skin dryness or cracking.

### Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich:

Result : Skin irritation

Remarks : Based on national or regional regulation.  
Based on data from similar materials

### Serious eye damage/eye irritation

Causes serious eye irritation.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version 5.0      Revision Date: 05/17/2024      SDS Number: 10697422-00012      Date of last issue: 12/18/2023  
Date of first issue: 01/25/2019

---

### Components:

#### **Butanone:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Method : OECD Test Guideline 405

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rabbit  
Result : No eye irritation

#### **Acetone:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Method : OECD Test Guideline 405

#### **Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich:**

Species : Rabbit  
Result : No eye irritation

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

### Components:

#### **Butanone:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

#### **Acetone:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version 5.0      Revision Date: 05/17/2024      SDS Number: 10697422-00012      Date of last issue: 12/18/2023  
Date of first issue: 01/25/2019

---

### Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich:

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Result : negative  
Remarks : Based on data from similar materials

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Butanone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

Test Type: Saccharomyces cerevisiae, gene mutation assay (in vitro)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OPPTS 870.5395  
Result: negative

#### Acetone:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version 5.0      Revision Date: 05/17/2024      SDS Number: 10697422-00012      Date of last issue: 12/18/2023  
Date of first issue: 01/25/2019

---

Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

### Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### Carcinogenicity

Not classified based on available information.

### Components:

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Mouse  
Application Route : Skin contact  
Exposure time : 102 weeks  
Result : negative

#### Acetone:

Species : Mouse  
Application Route : Skin contact  
Exposure time : 424 days  
Result : negative

### Reproductive toxicity

Suspected of damaging fertility.

### Components:

#### Butanone:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version 5.0      Revision Date: 05/17/2024      SDS Number: 10697422-00012      Date of last issue: 12/18/2023  
Date of first issue: 01/25/2019

---

Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Inhalation  
Method: OECD Test Guideline 414  
Result: negative

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich:

Effects on fertility : Test Type: Two-generation study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

### STOT-single exposure

May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version 5.0      Revision Date: 05/17/2024      SDS Number: 10697422-00012      Date of last issue: 12/18/2023  
Date of first issue: 01/25/2019

---

### Components:

#### **Butanone:**

Assessment : May cause drowsiness or dizziness.

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Assessment : May cause drowsiness or dizziness.

#### **Acetone:**

Assessment : May cause drowsiness or dizziness.

#### **Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich:**

Assessment : May cause drowsiness or dizziness.

### **STOT-repeated exposure**

Not classified based on available information.

### Components:

#### **Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich:**

Target Organs : Central nervous system

Assessment : May cause damage to organs through prolonged or repeated exposure.

### **Repeated dose toxicity**

### Components:

#### **Butanone:**

Species : Rat  
NOAEL : 14.84 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days  
Method : OECD Test Guideline 413

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rat  
NOAEL : > 20 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks

#### **Acetone:**

Species : Rat  
NOAEL : 900 mg/kg  
LOAEL : 1,700 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/18/2023
5.0	05/17/2024	10697422-00012	Date of first issue: 01/25/2019

---

NOAEL : 45 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 8 Weeks

### Aspiration toxicity

Not classified based on available information.

### Components:

#### Butanone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

#### Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### Butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 2,029 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 1,240 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version 5.0      Revision Date: 05/17/2024      SDS Number: 10697422-00012      Date of last issue: 12/18/2023  
Date of first issue: 01/25/2019

---

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.5 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 2.6 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

### Acetone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 8,800 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 79 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: 61,150 mg/l  
Exposure time: 30 min  
Method: ISO 8192

### Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich:

Toxicity to fish : LL50 : > 1 - 10 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version 5.0      Revision Date: 05/17/2024      SDS Number: 10697422-00012      Date of last issue: 12/18/2023  
Date of first issue: 01/25/2019

---

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3.88 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 55 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

### Persistence and degradability

#### Components:

##### **Butanone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 98 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 77.05 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **Acetone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 91 %  
Exposure time: 28 d

##### **Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 98 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

### Bioaccumulative potential

#### Components:

##### **Butanone:**

Partition coefficient: n-octanol/water : log Pow: 0.3

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Partition coefficient: n- : log Pow: 4

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version 5.0      Revision Date: 05/17/2024      SDS Number: 10697422-00012      Date of last issue: 12/18/2023  
Date of first issue: 01/25/2019

---

octanol/water      Remarks: Based on data from similar materials

### Acetone:

Partition coefficient: n-octanol/water      :    log Pow: -0.27 - -0.23

### Hydrocarbons, C6, n-alkanes, iso-alkanes, cyclics, n-hexane rich:

Partition coefficient: n-octanol/water      :    log Pow: 4  
Remarks: Based on data from similar materials

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues      :    Do not dispose of waste into sewer.  
Dispose of in accordance with local regulations.

Contaminated packaging      :    Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number      :    UN 1133  
Proper shipping name      :    ADHESIVES  
Class      :    3  
Packing group      :    II  
Labels      :    3  
Environmentally hazardous      :    no

#### IATA-DGR

UN/ID No.      :    UN 1133  
Proper shipping name      :    Adhesives  
Class      :    3  
Packing group      :    II  
Labels      :    Flammable Liquids  
Packing instruction (cargo aircraft)      :    364

---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/18/2023
5.0	05/17/2024	10697422-00012	Date of first issue: 01/25/2019

---

Packing instruction (passenger aircraft) : 353

### IMDG-Code

UN number : UN 1133  
Proper shipping name : ADHESIVES

Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-D  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### TDG

UN number : UN 1133  
Proper shipping name : ADHESIVES

Class : 3  
Packing group : II  
Labels : 3  
ERG Code : 128  
Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

### The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

---

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL : Canada. British Columbia OEL  
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/18/2023
5.0	05/17/2024	10697422-00012	Date of first issue: 01/25/2019

ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/17/2024  
Date format : mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBER PROFILE ADHESIVE, 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/18/2023
5.0	05/17/2024	10697422-00012	Date of first issue: 01/25/2019

---

safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8