

VULCANIZING TIRE CEMENT, 236 mL

Version Revision Date: SDS Number: Date of last issue: 11/20/2022
6.0 05/30/2023 10693503-00007 Date of first issue: 05/05/2017

SECTION 1. IDENTIFICATION

Product name : VULCANIZING TIRE CEMENT, 236 mL
Product code : 890.100019
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
 GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
 CHEMTREC (24/7): 1-800-424-9300
 Transport related emergencies:
 CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou
exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Sealant
 Rubber products

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable liquids : Category 2
Skin irritation : Category 2
Respiratory sensitization : Category 1
Skin sensitization : Category 1

VULCANIZING TIRE CEMENT, 236 mL

Version 6.0 Revision Date: 05/30/2023 SDS Number: 10693503-00007 Date of last issue: 11/20/2022
 Date of first issue: 05/05/2017

Specific target organ toxicity
 - single exposure : Category 3

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H336 May cause drowsiness or dizziness.

Precautionary Statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical, ventilating and lighting equipment.
 P242 Use non-sparking tools.
 P243 Take action to prevent static discharges.
 P261 Avoid breathing mist or vapors.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves, protective clothing, eye protection and face protection.
 P284 Wear respiratory protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
 P331 Do NOT induce vomiting.
 P333 + P313 If skin irritation or rash occurs: Get medical attention.
 P342 + P311 If experiencing respiratory symptoms: Call a doctor.
 P362 + P364 Take off contaminated clothing and wash it before reuse.

VULCANIZING TIRE CEMENT, 236 mL

Version 6.0 Revision Date: 05/30/2023 SDS Number: 10693503-00007 Date of last issue: 11/20/2022
 Date of first issue: 05/05/2017

Storage:

P403 + P233 + P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Heptane	n-Heptane	142-82-5	$\geq 80 - \leq 100$ *
Rubber, natural	No data available	9006-04-6	$\geq 10 - < 30$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
 If not breathing, give artificial respiration.
 If breathing is difficult, give oxygen.
 Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
 Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
 If vomiting occurs have person lean forward.
 Call a physician or poison control center immediately.
 Rinse mouth thoroughly with water.
 Never give anything by mouth to an unconscious person.

VULCANIZING TIRE CEMENT, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2022
6.0	05/30/2023	10693503-00007	Date of first issue: 05/05/2017

- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause drowsiness or dizziness.
Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
-

VULCANIZING TIRE CEMENT, 236 mL

Version 6.0 Revision Date: 05/30/2023 SDS Number: 10693503-00007 Date of last issue: 11/20/2022
Date of first issue: 05/05/2017

- Environmental precautions** : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up** : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures** : Ground and bond container and receiving equipment.
See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation** : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling** : Do not get on skin or clothing.
Avoid breathing mist or vapors.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

VULCANIZING TIRE CEMENT, 236 mL

Version 6.0 Revision Date: 05/30/2023 SDS Number: 10693503-00007 Date of last issue: 11/20/2022
 Date of first issue: 05/05/2017

- Conditions for safe storage : Keep in properly labeled containers.
 Store locked up.
 Keep tightly closed.
 Keep in a cool, well-ventilated place.
 Store in accordance with the particular national regulations.
 Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents
 Self-reactive substances and mixtures
 Organic peroxides
 Flammable solids
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures which in contact with water emit flammable gases
 Explosives
 Gases
 Very acutely toxic substances and mixtures

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
Heptane	142-82-5	TWA	400 ppm	CA BC OEL		
		STEL	500 ppm	CA BC OEL		
		TWA	400 ppm 1,640 mg/m ³	CA AB OEL		
		STEL	500 ppm 2,050 mg/m ³	CA AB OEL		
		TWAEV	400 ppm	CA QC OEL		
		STEV	500 ppm	CA QC OEL		
		TWA	400 ppm	ACGIH		
		STEL	500 ppm	ACGIH		
		Rubber, natural	9006-04-6	TWA	0.001 mg/m ³ (inhalable allergenic proteins)	CA AB OEL
				TWA (Inhalable)	0.001 mg/m ³ (inhalable allergenic proteins)	CA BC OEL
TWA (Inhalable particulate matter)	0.0001 mg/m ³ (inhalable allergenic proteins)			ACGIH		

- Engineering measures** : Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.
 Use explosion-proof electrical, ventilating and lighting

VULCANIZING TIRE CEMENT, 236 mL

Version 6.0 Revision Date: 05/30/2023 SDS Number: 10693503-00007 Date of last issue: 11/20/2022
Date of first issue: 05/05/2017

equipment.

Personal protective equipment

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Combined particulates and organic vapor type
- Hand protection
Material : Protective gloves
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!
- Eye protection : Wear the following personal protective equipment:
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : cloudy
- Odor : solvent

VULCANIZING TIRE CEMENT, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2022
6.0	05/30/2023	10693503-00007	Date of first issue: 05/05/2017

Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	93 °C
Flash point	:	0 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	6.7 %(V)
Lower explosion limit / Lower flammability limit	:	1.1 %(V)
Vapor pressure	:	48 hPa (20 °C)
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	0.77 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	immiscible
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	215 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

VULCANIZING TIRE CEMENT, 236 mL

Version 6.0 Revision Date: 05/30/2023 SDS Number: 10693503-00007 Date of last issue: 11/20/2022
Date of first issue: 05/05/2017

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Highly flammable liquid and vapor.
Vapors may form explosive mixture with air.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:**Heptane:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 73.5 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Rubber, natural:

Acute oral toxicity : LD50 (Rat): 2,043 - 2,210 mg/kg

VULCANIZING TIRE CEMENT, 236 mL

Version 6.0 Revision Date: 05/30/2023 SDS Number: 10693503-00007 Date of last issue: 11/20/2022
Date of first issue: 05/05/2017

Skin corrosion/irritation

Causes skin irritation.

Components:**Heptane:**

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Heptane:**

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Components:**Heptane:**

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Rubber, natural:

Assessment : Probability or evidence of skin sensitization in humans

Assessment : May cause sensitization by inhalation.

Germ cell mutagenicity

Not classified based on available information.

Components:**Heptane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

VULCANIZING TIRE CEMENT, 236 mL

Version 6.0 Revision Date: 05/30/2023 SDS Number: 10693503-00007 Date of last issue: 11/20/2022
Date of first issue: 05/05/2017

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:**Heptane:**

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:**Heptane:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

May cause drowsiness or dizziness.

Components:**Heptane:**

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

VULCANIZING TIRE CEMENT, 236 mL

Version 6.0 Revision Date: 05/30/2023 SDS Number: 10693503-00007 Date of last issue: 11/20/2022
Date of first issue: 05/05/2017

Repeated dose toxicity**Components:****Heptane:**

Species : Rat
NOAEL : 12.35 mg/l
Application Route : inhalation (vapor)
Exposure time : 90 Days

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:**Heptane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Heptane:**

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 4,924 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 0.2 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50: > 0.1 - 1 mg/l
plants Exposure time: 72 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): > 0.1 - 1 mg/l
aquatic invertebrates (Chronic toxicity) Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Rubber, natural:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 10,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to microorganisms : (activated sludge): > 10,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

VULCANIZING TIRE CEMENT, 236 mL

Version 6.0 Revision Date: 05/30/2023 SDS Number: 10693503-00007 Date of last issue: 11/20/2022
Date of first issue: 05/05/2017

Persistence and degradability**Components:****Heptane:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 %
Exposure time: 10 d

Bioaccumulative potential**Components:****Heptane:**

Partition coefficient: n-octanol/water : log Pow: 4.5

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.



Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 1206
Proper shipping name : HEPTANES
Class : 3
Packing group : II
Labels : 3

IATA-DGR

UN/ID No. : UN 1206
Proper shipping name : Heptanes
Class : 3

VULCANIZING TIRE CEMENT, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2022
6.0	05/30/2023	10693503-00007	Date of first issue: 05/05/2017

Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1206
Proper shipping name : HEPTANES
(Heptane, Methylcyclohexane)
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

UN number : UN 1206
Proper shipping name : HEPTANES
Class : 3
Packing group : II
Labels : 3
ERG Code : 128
Marine pollutant : yes(Heptane, Methylcyclohexane)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content : CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 75 %

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

VULCANIZING TIRE CEMENT, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2022
6.0	05/30/2023	10693503-00007	Date of first issue: 05/05/2017

CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
--	---	---

Revision Date	:	05/30/2023
Date format	:	mm/dd/yyyy

VULCANIZING TIRE CEMENT, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2022
6.0	05/30/2023	10693503-00007	Date of first issue: 05/05/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8