

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## EXHAUST ASSEMBLY PASTE, 140 g

Version 2.13      Revision Date: 10/31/2023      SDS Number: 11004717-00010      Date of last issue: 05/14/2023  
Date of first issue: 12/23/2009

---

### SECTION 1. IDENTIFICATION

Product name : EXHAUST ASSEMBLY PASTE, 140 g  
Product code : 890.100045  
Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : +1 (905) 564 6225  
Telefax : +1 (905) 564 3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)  
  
Urgences impliquant un déversement, incendie, explosion ou exposition:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences liées au transport:  
CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)  
  
E-mail address : prodsafe@wurth.ca

#### Recommended use of the chemical and restrictions on use

Recommended use : Sealing compound  
Restrictions on use : Not applicable

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

#### GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

#### Other hazards

None known.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## EXHAUST ASSEMBLY PASTE, 140 g

Version 2.13      Revision Date: 10/31/2023      SDS Number: 11004717-00010      Date of last issue: 05/14/2023  
Date of first issue: 12/23/2009

Substance / Mixture : Mixture

### Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Kaolin	Hydrated aluminum silicate	1332-58-7	>= 30 - < 60 *

\* Actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.  
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Not applicable  
Will not burn
- Unsuitable extinguishing media : Not applicable  
Will not burn
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Silicon oxides  
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## EXHAUST ASSEMBLY PASTE, 140 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/14/2023
2.13	10/31/2023	11004717-00010	Date of first issue: 12/23/2009

---

Evacuate area.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.  
Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

Recommended storage temperature : 15 - 30 °C

---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## EXHAUST ASSEMBLY PASTE, 140 g

Version 2.13      Revision Date: 10/31/2023      SDS Number: 11004717-00010      Date of last issue: 05/14/2023  
Date of first issue: 12/23/2009

perature

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Kaolin	1332-58-7	TWA (Respirable)	2 mg/m <sup>3</sup>	CA AB OEL
		TWA (Respirable)	2 mg/m <sup>3</sup>	CA BC OEL
		TWAEV (respirable dust)	2 mg/m <sup>3</sup>	CA QC OEL
		TWA (Respirable particulate matter)	2 mg/m <sup>3</sup>	ACGIH

**Engineering measures** : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

#### Personal protective equipment

**Respiratory protection** : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Particulates type

#### Hand protection

Material : Nitrile rubber  
Break through time : 30 min  
Glove thickness : 0.4 mm

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

**Eye protection** : Wear the following personal protective equipment: Safety glasses  
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded. Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

**Skin and body protection** : Skin should be washed after contact.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## EXHAUST ASSEMBLY PASTE, 140 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/14/2023
2.13	10/31/2023	11004717-00010	Date of first issue: 12/23/2009

---

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : gray

Odor : characteristic

Odor Threshold : No data available

pH : 10.5 (20 °C)  
Concentration: 100 %

Melting point/freezing point : No data available

Initial boiling point and boiling range : 100 °C

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Will not burn

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 1.71 g/cm<sup>3</sup> (20 °C)

Solubility(ies)  
Water solubility : partly soluble (20 °C)

Partition coefficient: n- : Not applicable

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## EXHAUST ASSEMBLY PASTE, 140 g

Version 2.13      Revision Date: 10/31/2023      SDS Number: 11004717-00010      Date of last issue: 05/14/2023  
Date of first issue: 12/23/2009

---

octanol/water

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : None known.

Conditions to avoid : None known.

Incompatible materials : Acids

Hazardous decomposition products : No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **Kaolin:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 2.07 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## EXHAUST ASSEMBLY PASTE, 140 g

Version 2.13      Revision Date: 10/31/2023      SDS Number: 11004717-00010      Date of last issue: 05/14/2023  
Date of first issue: 12/23/2009

---

Assessment: The substance or mixture has no acute inhalation toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity

: LD50 (Rat): > 5,000 mg/kg

Assessment: The substance or mixture has no acute dermal toxicity

Remarks: Based on data from similar materials

### Skin corrosion/irritation

Not classified based on available information.

#### Components:

##### **Kaolin:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

### Serious eye damage/eye irritation

Not classified based on available information.

#### Components:

##### **Kaolin:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

### Respiratory or skin sensitization

#### **Skin sensitization**

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT-single exposure**

Not classified based on available information.

#### **STOT-repeated exposure**

Not classified based on available information.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## EXHAUST ASSEMBLY PASTE, 140 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/14/2023
2.13	10/31/2023	11004717-00010	Date of first issue: 12/23/2009

---

### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### **Kaolin:**

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 30 d

#### **Persistence and degradability**

No data available

#### **Bioaccumulative potential**

No data available

#### **Mobility in soil**

No data available

#### **Other adverse effects**

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### **International Regulations**

#### **UNRTDG**

Not regulated as a dangerous good

#### **IATA-DGR**

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

#### **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

#### **Domestic regulation**



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## EXHAUST ASSEMBLY PASTE, 140 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/14/2023
2.13	10/31/2023	11004717-00010	Date of first issue: 12/23/2009

### **TDG**

Not regulated as a dangerous good

### **Special precautions for user**

Not applicable

## SECTION 15. REGULATORY INFORMATION

**Volatile organic compounds (VOC) content** CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products  
VOC content: 0 %

### **The ingredients of this product are reported in the following inventories:**

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

## SECTION 16. OTHER INFORMATION

### **Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL : Canada. British Columbia OEL  
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants  
ACGIH / TWA : 8-hour, time-weighted average  
CA AB OEL / TWA : 8-hour Occupational exposure limit  
CA BC OEL / TWA : 8-hour time weighted average  
CA QC OEL / TWA : Time-weighted average exposure value

AIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## EXHAUST ASSEMBLY PASTE, 140 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/14/2023
2.13	10/31/2023	11004717-00010	Date of first issue: 12/23/2009

---

Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/31/2023  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8