

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

SECTION 1. IDENTIFICATION

Product name : CONTACT SW, 395 g

Product code : 890.101102

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:

CHEMTREC (24/7): 1-800-424-9300

Urgences liées au transport:

CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Cleaning agent
Detergent

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 1

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity : Category 3
- single exposure

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

Specific target organ toxicity : Category 1 (Nervous system)
- repeated exposure

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs (Nervous system) through prolonged or repeated exposure.

Precautionary Statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, eye protection and face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical attention if you feel unwell.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
N-Heptane	n-Heptane	142-82-5	$\geq 80 - \leq 100$ *
1,1-Difluoroethane	Hydrofluorocarbon 152A	75-37-6	$\geq 10 - < 30$ *
Propan-2-ol	Isopropyl alcohol	67-63-0	$\geq 5 - < 10$ *
Carbon dioxide	Carbonic anhydride	124-38-9	$\geq 1 - < 5$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

- | | | |
|---|---|--|
| If swallowed | : | If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control center immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person. |
| Most important symptoms and effects, both acute and delayed | : | May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Causes damage to organs through prolonged or repeated exposure. |
| Protection of first-aiders | : | First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8). |
| Notes to physician | : | Treat symptomatically and supportively. |

SECTION 5. FIRE-FIGHTING MEASURES

- | | | |
|--|---|---|
| Suitable extinguishing media | : | Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : | High volume water jet |
| Specific hazards during fire fighting | : | Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. |
| Hazardous combustion products | : | Carbon oxides
Fluorine compounds |
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area. |
| Special protective equipment for fire-fighters | : | In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|----------------------------------|---|---------------------------------|
| Personal precautions, protection | : | Remove all sources of ignition. |
|----------------------------------|---|---------------------------------|

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

- | | | |
|---|---|---|
| tive equipment and emergency procedures | : | Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8). |
| Environmental precautions | : | Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | : | Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. |

SECTION 7. HANDLING AND STORAGE

- | | | |
|-------------------------|---|---|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation. |
| Advice on safe handling | : | For outdoor use only
Do not get on skin or clothing.
Do not breathe spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.
Keep away from heat, hot surfaces, sparks, open flames and |

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version 1.0 Revision Date: 03/08/2024 SDS Number: 11362870-00001 Date of last issue: -
Date of first issue: 03/08/2024

other ignition sources. No smoking.
Take precautionary measures against static discharges.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases

Recommended storage temperature : < 40 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
N-Heptane	142-82-5	TWA	400 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWA	400 ppm 1,640 mg/m ³	CA AB OEL
		STEL	500 ppm 2,050 mg/m ³	CA AB OEL
		TWAEV	400 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Propan-2-ol	67-63-0	STEL	400 ppm 984 mg/m ³	CA AB OEL
		TWA	200 ppm 492 mg/m ³	CA AB OEL
		TWA	200 ppm	CA BC OEL

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version 1.0 Revision Date: 03/08/2024 SDS Number: 11362870-00001 Date of last issue: -
Date of first issue: 03/08/2024

		STEL	400 ppm	CA BC OEL
		TWAEV	200 ppm	CA QC OEL
		STEV	400 ppm	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
Carbon dioxide	124-38-9	TWA	5,000 ppm 9,000 mg/m ³	CA AB OEL
		STEL	30,000 ppm 54,000 mg/m ³	CA AB OEL
		TWA	5,000 ppm	CA BC OEL
		STEL	15,000 ppm	CA BC OEL
		STEV	30,000 ppm 54,000 mg/m ³	CA QC OEL
		TWAEV	5,000 ppm 9,000 mg/m ³	CA QC OEL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection
Material : butyl-rubber

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version 1.0	Revision Date: 03/08/2024	SDS Number: 11362870-00001	Date of last issue: - Date of first issue: 03/08/2024
----------------	------------------------------	-------------------------------	--

- | | |
|--------------------------|--|
| Eye protection | : Wear the following personal protective equipment:
Safety goggles |
| Skin and body protection | : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc). |
| Hygiene measures | : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use. |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- | | |
|--|--------------------------------------|
| Appearance | : Aerosol containing a liquefied gas |
| Propellant | : 1,1-Difluoroethane, Carbon dioxide |
| Color | : colorless |
| Odor | : characteristic |
| Odor Threshold | : No data available |
| pH | : No data available |
| Melting point/freezing point | : No data available |
| Initial boiling point and boiling range | : Not applicable |
| Flash point | : Not applicable |
| Evaporation rate | : Not applicable |
| Flammability (solid, gas) | : Extremely flammable aerosol. |
| Upper explosion limit / Upper flammability limit | : No data available |

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Density	:	No data available
Solubility(ies) Water solubility	:	partly miscible
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

N-Heptane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 29.29 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

1,1-Difluoroethane:

Acute inhalation toxicity : LC50 (Rat): > 437500 ppm
Exposure time: 4 h
Test atmosphere: gas

Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l
Exposure time: 6 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Carbon dioxide:

Acute inhalation toxicity : LC50 (Rat): 40000 - 50000 ppm
Exposure time: 30 min
Test atmosphere: vapor

Skin corrosion/irritation

Causes skin irritation.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

Components:

N-Heptane:

Result : Skin irritation

Propan-2-ol:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

N-Heptane:

Result : Irritation to eyes, reversing within 21 days

Propan-2-ol:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Propan-2-ol:

Test Type : Buehler Test

Routes of exposure : Skin contact

Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

N-Heptane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

Method: OECD Test Guideline 473
Result: negative

1,1-Difluoroethane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

1,1-Difluoroethane:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 104 weeks
Result : negative

Propan-2-ol:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 104 weeks
Method : OECD Test Guideline 451
Result : negative

Reproductive toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

Components:

N-Heptane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Inhalation
Result: negative

1,1-Difluoroethane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (gas)
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT-single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

Components:

N-Heptane:

Assessment : May cause drowsiness or dizziness., May cause respiratory irritation.

1,1-Difluoroethane:

Assessment : May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

Propan-2-ol:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Causes damage to organs (Nervous system) through prolonged or repeated exposure.

Components:

N-Heptane:

Target Organs : Nervous system
Assessment : Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

N-Heptane:

Species : Rat, male
NOAEL : 12.47 mg/l
Application Route : Inhalation
Exposure time : 16 Weeks

Species : Rat
NOAEL : ≥ 12.35 mg/l
Application Route : Inhalation
Exposure time : 26 Weeks
Method : OECD Test Guideline 413

1,1-Difluoroethane:

Species : Rat
NOAEL : 100000 ppm
Application Route : inhalation (gas)
Exposure time : 14 Days

Propan-2-ol:

Species : Rat
NOAEL : 12.5 mg/l
Application Route : inhalation (vapor)
Exposure time : 104 Weeks

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

Components:

N-Heptane:

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

N-Heptane:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.5 mg/l
Exposure time: 48 h

LC50 (Mysidopsis bahia (opossum shrimp)): 0.1 mg/l
Exposure time: 96 h

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 24 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 1,050 mg/l
Exposure time: 16 h

Carbon dioxide:

Toxicity to fish : NOEC (Lepomis macrochirus (Bluegill sunfish)): > 100 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : NOEC (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Persistence and degradability

Components:

N-Heptane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 %
Exposure time: 10 d

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1,19 (BOD5)
COD: 2,23
BOD/COD: 53 %

Bioaccumulative potential

Components:

1,1-Difluoroethane:

Partition coefficient: n-octanol/water : log Pow: 0.75

Propan-2-ol:

Partition coefficient: n-octanol/water : log Pow: 0.05

Carbon dioxide:

Partition coefficient: n-octanol/water : log Pow: 0.83

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty (including propellant)

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
Environmentally hazardous	: yes

IATA-DGR

UN/ID No.	: UN 1950
Proper shipping name	: Aerosols, flammable
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: Flammable Gas
Packing instruction (cargo aircraft)	: 203
Packing instruction (passenger aircraft)	: 203

IMDG-Code

UN number	: UN 1950
Proper shipping name	: AEROSOLS (N-Heptane)
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
EmS Code	: F-D, S-U
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
ERG Code	: 126
Marine pollutant	: yes(N-Heptane)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

Volatile organic compounds (VOC) content Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations
VOC content: 75 % / 556.76 g/l

International Regulations

Montreal Protocol : 1,1-Difluoroethane

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA AB OEL / STEL	: 15-minute occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average
CA BC OEL / STEL	: short-term exposure limit
CA QC OEL / TWAEV	: Time-weighted average exposure value
CA QC OEL / STEV	: Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECL - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CONTACT SW, 395 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/08/2024	11362870-00001	Date of first issue: 03/08/2024

Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 03/08/2024
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8