

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

Version 2.0      Revision Date: 09/26/2025      SDS Number: 11570174-00002      Date of last issue: 08/18/2025  
Date of first issue: 08/18/2025

---

### SECTION 1. IDENTIFICATION

Product name : FOAMING WHEEL AND TIRE CLEANER, 539 g  
Product code : 890.102078  
Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : 1-800-263-5002  
Telefax : 1-905-564-3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
  
Urgences impliquant un déversement, incendie, explosion ou  
exposition: CHEMTREC (24/7): 1-800-424-9300

E-mail address : prodsafe@wurth.ca

#### Recommended use of the chemical and restrictions on use

Recommended use : Care product  
Restrictions on use : Not applicable

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 3

#### GHS label elements

Signal Word : Warning  
Hazard Statements : H229 Pressurized container: May burst if heated.  
Precautionary Statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P251 Do not pierce or burn, even after use.  
**Storage:**  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

#### Other hazards

None known.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

Version 2.0 Revision Date: 09/26/2025 SDS Number: 11570174-00002 Date of last issue: 08/18/2025 Date of first issue: 08/18/2025

### Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Petroleum gases, liquefied, sweetened	No data available	68476-86-8	>= 1 - < 5 *
4-Nonylphenol, branched, ethoxylated	Poly(oxy-1,2-ethanediyl), $\alpha$ -(4-nonylphenyl)- $\omega$ -hydroxy-, branched	127087-87-0	>= 1 - < 5 *
2-Butoxyethanol	1-Butoxy-2-hydroxyethanol	111-76-2	>= 1 - < 5 *

\* Actual concentration or concentration range is withheld as a trade secret

### Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)
4-Nonylphenol, branched, ethoxylated	68412-54-4

## SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : None known.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

## SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

Version 2.0      Revision Date: 09/26/2025      SDS Number: 11570174-00002      Date of last issue: 08/18/2025  
Date of first issue: 08/18/2025

---

Specific hazards during fire fighting	: Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Hazardous combustion products	: Carbon oxides
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
Environmental precautions	: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

## SECTION 7. HANDLING AND STORAGE

Technical measures	: See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	: Use only with adequate ventilation.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

Version  
2.0

Revision Date:  
09/26/2025

SDS Number:  
11570174-00002

Date of last issue: 08/18/2025  
Date of first issue: 08/18/2025

Advice on safe handling	: Do not get on skin or clothing. Avoid inhalation of vapor or mist. Do not swallow. Avoid contact with eyes. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take care to prevent spills, waste and minimize release to the environment.
Conditions for safe storage	: Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.
Materials to avoid	: Do not store with the following product types: Self-reactive substances and mixtures Organic peroxides Oxidizing agents Flammable solids Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures which in contact with water emit flammable gases Explosives Gases
Recommended storage temperature	: < 40 °C

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Petroleum gases, liquefied, sweetened	68476-86-8	TWAEV	800 ppm 1,900 mg/m <sup>3</sup>	CA QC OEL
		TWA	1,000 ppm	CA AB OEL
		STEL	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
2-Butoxyethanol	111-76-2	TWA	20 ppm 97 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		TWA	20 ppm	ACGIH

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra- tion	Basis

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

Version 2.0      Revision Date: 09/26/2025      SDS Number: 11570174-00002      Date of last issue: 08/18/2025  
Date of first issue: 08/18/2025

2-Butoxyethanol	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g creatinine	ACGIH BEI
-----------------	----------	-------------------------	-------	--	---------------------	-----------

**Engineering measures** : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection  
Material

: PVC

Material : Nitrile rubber

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment: Safety glasses

|| Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.

When using do not eat, drink or smoke.

Wash contaminated clothing before re-use.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a compressed gas

Propellant : Petroleum gases, liquefied, sweetened

Color : No data available

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling : Not applicable

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

Version 2.0	Revision Date: 09/26/2025	SDS Number: 11570174-00002	Date of last issue: 08/18/2025
			Date of first issue: 08/18/2025

---

range

Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: Not applicable
Relative vapor density	: Not applicable
Density	: 0.807 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: Not applicable
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, kinematic	: Not applicable
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Particle characteristics	
Particle size	: Not applicable

---

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	: None known.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

Version 2.0      Revision Date: 09/26/2025      SDS Number: 11570174-00002      Date of last issue: 08/18/2025  
Date of first issue: 08/18/2025

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

#### Components:

##### **Petroleum gases, liquefied, sweetened:**

Acute inhalation toxicity : Acute toxicity estimate: > 30000 ppm  
Exposure time: 4 h  
Test atmosphere: gas  
Method: Expert judgment  
Remarks: Based on data from similar materials

##### **4-Nonylphenol, branched, ethoxylated:**

Acute oral toxicity : LD50 (Rat): > 300 - 2,000 mg/kg  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

##### **2-Butoxyethanol:**

Acute oral toxicity : LD50 (Guinea pig): 1,200 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Expert judgment

Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg

##### **Skin corrosion/irritation**

Not classified based on available information.

#### Components:

##### **2-Butoxyethanol:**

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

Version	Revision Date:	SDS Number:	Date of last issue: 08/18/2025
2.0	09/26/2025	11570174-00002	Date of first issue: 08/18/2025

Species	:	Rabbit
Method	:	Directive 67/548/EEC, Annex V, B.4.
Result	:	Skin irritation

### **Serious eye damage/eye irritation**

Not classified based on available information.

#### **Components:**

##### **4-Nonylphenol, branched, ethoxylated:**

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days

##### **2-Butoxyethanol:**

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Method	:	OECD Test Guideline 405

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

#### **Components:**

##### **4-Nonylphenol, branched, ethoxylated:**

Test Type	:	Human repeat insult patch test (HRIPT)
Routes of exposure	:	Skin contact
Result	:	negative
Remarks	:	Based on data from similar materials

##### **2-Butoxyethanol:**

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

### **Germ cell mutagenicity**

Not classified based on available information.

#### **Components:**

##### **Petroleum gases, liquefied, sweetened:**

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Remarks: The test was conducted equivalent or similar to guideline
-----------------------	---	---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

Version 2.0	Revision Date: 09/26/2025	SDS Number: 11570174-00002	Date of last issue: 08/18/2025 Date of first issue: 08/18/2025
----------------	------------------------------	-------------------------------	---

---

Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: The test was conducted according to guideline

Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: The test was conducted according to guideline  
Based on data from similar materials

### 4-Nonylphenol, branched, ethoxylated:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

### 2-Butoxyethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells  
Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: Intraperitoneal injection  
Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

Version  
2.0

Revision Date:  
09/26/2025

SDS Number:  
11570174-00002

Date of last issue: 08/18/2025  
Date of first issue: 08/18/2025

---

### Carcinogenicity

Not classified based on available information.

### Components:

#### 4-Nonylphenol, branched, ethoxylated:

Species : Rat  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative  
Remarks : Based on data from similar materials

#### 2-Butoxyethanol:

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Result : negative

### Reproductive toxicity

Not classified based on available information.

### Components:

#### Petroleum gases, liquefied, sweetened:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: The test was conducted according to guideline  
Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 414  
Result: negative  
Remarks: The test was conducted according to guideline  
Based on data from similar materials

#### 2-Butoxyethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Mouse  
Application Route: Ingestion  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

Version  
2.0

Revision Date:  
09/26/2025

SDS Number:  
11570174-00002

Date of last issue: 08/18/2025  
Date of first issue: 08/18/2025

---

Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### STOT-single exposure

Not classified based on available information.

### Components:

#### **Petroleum gases, liquefied, sweetened:**

Assessment : May cause drowsiness or dizziness.  
Remarks : Based on data from similar materials

### STOT-repeated exposure

Not classified based on available information.

### Repeated dose toxicity

### Components:

#### **Petroleum gases, liquefied, sweetened:**

Species : Rat  
NOAEL : >250 ppm  
Application Route : inhalation (gas)  
Exposure time : 90 Days  
Method : OECD Test Guideline 413  
Remarks : The test was conducted equivalent or similar to guideline  
Based on data from similar materials

#### **4-Nonylphenol, branched, ethoxylated:**

Species : Rat  
LOAEL : > 100 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

### Components:

#### **4-Nonylphenol, branched, ethoxylated:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 0.1 - 1 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

Version 2.0	Revision Date: 09/26/2025	SDS Number: 11570174-00002	Date of last issue: 08/18/2025 Date of first issue: 08/18/2025
----------------	------------------------------	-------------------------------	---

Toxicity to daphnia and other aquatic invertebrates	: EC50 (Ceriodaphnia dubia (water flea)): > 0.1 - 1 mg/l Exposure time: 48 h Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	: ErC50 (Selenastrum capricornutum (green algae)): > 1 - 10 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
	EC10 (Selenastrum capricornutum (green algae)): > 1 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to fish (Chronic toxicity)	: NOEC (Oryzias latipes (Japanese medaka)): > 0.1 - 1 mg/l Exposure time: 100 d Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Mysidopsis bahia (opossum shrimp)): > 0.001 - 0.01 mg/l Exposure time: 28 d Remarks: Based on data from similar materials

### 2-Butoxyethanol:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 1,464 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 1,800 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: ErC50 (Pseudokirchneriella subcapitata (green algae)): 1,840 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
	EC10 (Pseudokirchneriella subcapitata (green algae)): 679 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOEC (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 21 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: EC10 (Daphnia magna (Water flea)): 134 mg/l Exposure time: 21 d Method: OECD Test Guideline 211

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

Version 2.0      Revision Date: 09/26/2025      SDS Number: 11570174-00002      Date of last issue: 08/18/2025  
Date of first issue: 08/18/2025

---

### Persistence and degradability

#### Components:

##### **4-Nonylphenol, branched, ethoxylated:**

Biodegradability : Result: Not readily biodegradable.  
Remarks: Based on data from similar materials

##### **2-Butoxyethanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 90.4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

### Bioaccumulative potential

#### Components:

##### **Petroleum gases, liquefied, sweetened:**

Partition coefficient: n-octanol/water : log Pow: < 4  
Remarks: Calculation

##### **4-Nonylphenol, branched, ethoxylated:**

Partition coefficient: n-octanol/water : log Pow: < 4

##### **2-Butoxyethanol:**

Partition coefficient: n-octanol/water : log Pow: 0.81

### **Mobility in soil**

No data available

### **Other adverse effects**

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

#### **Disposal methods**

Waste from residues : Do not dispose of waste into sewer.  
Dispose of in accordance with local regulations.

Contaminated packaging : Please ensure aerosol cans are sprayed completely empty (including propellant)  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

#### **International Regulations**

**UNRTDG**

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

Version 2.0      Revision Date: 09/26/2025      SDS Number: 11570174-00002      Date of last issue: 08/18/2025  
Date of first issue: 08/18/2025

---

UN number	:	UN 1950
Proper shipping name	:	AEROSOLS
Class	:	2.2
Packing group	:	Not assigned by regulation
Labels	:	2.2
Environmentally hazardous	:	yes

### IATA-DGR

UN/ID No.	:	UN 1950
Proper shipping name	:	Aerosols, non-flammable
Class	:	2.2
Packing group	:	Not assigned by regulation
Labels	:	Non-flammable, non-toxic Gas
Packing instruction (cargo aircraft)	:	203
Packing instruction (passenger aircraft)	:	203

### IMDG-Code

UN number	:	UN 1950
Proper shipping name	:	AEROSOLS (4-Nonylphenol, branched, ethoxylated)
Class	:	2.2
Packing group	:	Not assigned by regulation
Labels	:	2.2
EmS Code	:	F-D, S-U
Marine pollutant	:	yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### TDG

UN number	:	UN 1950
Proper shipping name	:	AEROSOLS
Class	:	2.2
Packing group	:	Not assigned by regulation
Labels	:	2.2
ERG Code	:	126
Marine pollutant	:	yes(4-Nonylphenol, branched, ethoxylated)

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

<b>Volatile organic compounds (VOC) content</b>	Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations VOC content: 4.72 % Remarks: VOC content excluding water and exempt compounds
---	--

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

Version 2.0      Revision Date: 09/26/2025      SDS Number: 11570174-00002      Date of last issue: 08/18/2025  
Date of first issue: 08/18/2025

### The ingredients of this product are reported in the following inventories:

CA. DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

### Canadian lists

|| No substances are subject to CEPA Section 84 Ministerial Conditions.

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average
CA BC OEL / STEL	: short-term exposure limit
CA QC OEL / TWAEV	: Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authori-

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## FOAMING WHEEL AND TIRE CLEANER, 539 g

---

Version	Revision Date:	SDS Number:	Date of last issue: 08/18/2025
2.0	09/26/2025	11570174-00002	Date of first issue: 08/18/2025

---

zation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/26/2025  
Date format : mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8