

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HEAVY DUTY PARTS WASH, 18.9 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/12/2025	11518829-00001	Date of first issue: 03/12/2025

SECTION 1. IDENTIFICATION

Product name : HEAVY DUTY PARTS WASH, 18.9 L

Product code : 890.107142

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : 1-800-263-5002

Telefax : 1-905-564-3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300

Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Degreasing agent

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 2

Skin irritation : Category 2

Specific target organ toxicity : Category 3
- single exposure

Aspiration hazard : Category 1

Physical hazards not otherwise classified : Category 1

GHS label elements

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HEAVY DUTY PARTS WASH, 18.9 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/12/2025	11518829-00001	Date of first issue: 03/12/2025

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H225 Highly flammable liquid and vapor.
May become electrostatically charged. Sparks may ignite liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.

Precautionary Statements

:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 Ground and bond container and receiving equipment.
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HEAVY DUTY PARTS WASH, 18.9 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/12/2025	11518829-00001	Date of first issue: 03/12/2025

Substance / Mixture : Substance

Substance name : Heptane

CAS-No. : 142-82-5

Common Name/Synonym : n-Heptane

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Heptane	n-Heptane	142-82-5	$\geq 80 - \leq 100$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control center immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause drowsiness or dizziness.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HEAVY DUTY PARTS WASH, 18.9 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/12/2025	11518829-00001	Date of first issue: 03/12/2025

- | | | |
|--|---|---|
| Suitable extinguishing media | : | Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : | High volume water jet |
| Specific hazards during fire fighting | : | Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health. |
| Hazardous combustion products | : | Carbon oxides |
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area. |
| Special protective equipment for fire-fighters | : | In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8). |
| Environmental precautions | : | Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | : | Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be |

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HEAVY DUTY PARTS WASH, 18.9 L

Version 1.0	Revision Date: 03/12/2025	SDS Number: 11518829-00001	Date of last issue: - Date of first issue: 03/12/2025
----------------	------------------------------	-------------------------------	--

pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- | | |
|-----------------------------|--|
| Technical measures | : Ground and bond container and receiving equipment.
Ensure all equipment is electrically grounded before beginning transfer operations.
This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical ignition source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity, it is necessary to provide an inert gas purge before beginning transfer operations.
Restrict flow velocity in order to reduce the accumulation of static electricity. |
| Local/Total ventilation | : Use explosion-proof electrical, ventilating and lighting equipment. |
| Advice on safe handling | : For outdoor use only
Do not get on skin or clothing.
Avoid breathing mist or vapors.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment. |
| Conditions for safe storage | : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition. |
| Materials to avoid | : Do not store with the following product types:
Strong oxidizing agents |

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HEAVY DUTY PARTS WASH, 18.9 L

Version 1.0 Revision Date: 03/12/2025 SDS Number: 11518829-00001 Date of last issue: -
Date of first issue: 03/12/2025

Self-reactive substances and mixtures
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases
Very acutely toxic substances and mixtures

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Heptane	142-82-5	TWA	400 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWA	400 ppm 1,640 mg/m ³	CA AB OEL
		STEL	500 ppm 2,050 mg/m ³	CA AB OEL
		TWAEV	400 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH

Engineering measures : Minimize workplace exposure concentrations.
Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Organic vapor Type

Hand protection
Material : Nitrile rubber

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the pro-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HEAVY DUTY PARTS WASH, 18.9 L

Version 1.0	Revision Date: 03/12/2025	SDS Number: 11518829-00001	Date of last issue: - Date of first issue: 03/12/2025
----------------	------------------------------	-------------------------------	--

- duct. Change gloves often!
- Eye protection : Wear the following personal protective equipment:
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : clear
- Odor : characteristic
- Odor Threshold : No data available
- pH : substance/mixture is non-soluble (in water)
- Melting point/freezing point : -91 °C
- Initial boiling point and boiling range : 98 °C
- Flash point : 22 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : Not applicable
- Flammability (liquids) : Ignitable (see flash point)
- Static-accumulating flammable liquid.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HEAVY DUTY PARTS WASH, 18.9 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/12/2025	11518829-00001	Date of first issue: 03/12/2025

Upper explosion limit / Upper flammability limit	: 7 %(V)
Lower explosion limit / Lower flammability limit	: 1.1 %(V)
Vapor pressure	: 53.5 hPa (20 °C)
Relative vapor density	: No data available
Relative density	: 0.684
Solubility(ies) Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: 223 °C
Decomposition temperature	: No data available
Viscosity Viscosity, kinematic	: < 20.5 mm ² /s (40 °C)
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	: Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Highly flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	: Handling operations that can promote accumulation of static charges. Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HEAVY DUTY PARTS WASH, 18.9 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/12/2025	11518829-00001	Date of first issue: 03/12/2025

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Heptane:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 73.5 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

Components:

Heptane:

Species	:	Rabbit
Result	:	Skin irritation
Remarks	:	Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Heptane:

Species	:	Rabbit
Result	:	No eye irritation
Remarks	:	Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HEAVY DUTY PARTS WASH, 18.9 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/12/2025	11518829-00001	Date of first issue: 03/12/2025

Respiratory sensitization

Not classified based on available information.

Components:

Heptane:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Heptane:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
-----------------------	---	--

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo	:	Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat Application Route: inhalation (vapor) Result: negative Remarks: Based on data from similar materials
----------------------	---	--

Carcinogenicity

Not classified based on available information.

Components:

Heptane:

Species	:	Rat
Application Route	:	inhalation (vapor)
Exposure time	:	2 Years
Result	:	negative
Remarks	:	Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Heptane:

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HEAVY DUTY PARTS WASH, 18.9 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/12/2025	11518829-00001	Date of first issue: 03/12/2025

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

May cause drowsiness or dizziness.

Components:

Heptane:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Heptane:

Species	: Rat
NOAEL	: 12.35 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 90 Days

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Heptane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be re-garded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Heptane:

Toxicity to fish	: LC50 (Gambusia affinis (Mosquito fish)): 4,924 mg/l
Exposure time:	96 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HEAVY DUTY PARTS WASH, 18.9 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/12/2025	11518829-00001	Date of first issue: 03/12/2025

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 0.2 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50: > 0.1 - 1 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): > 0.1 - 1 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Persistence and degradability

Components:

Heptane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 %
Exposure time: 10 d

Bioaccumulative potential

Components:

Heptane:

Partition coefficient: n-octanol/water : log Pow: 4.5

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HEAVY DUTY PARTS WASH, 18.9 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/12/2025	11518829-00001	Date of first issue: 03/12/2025

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number	: UN 1206
Proper shipping name	: HEPTANES
Class	: 3
Packing group	: II
Labels	: 3
Environmentally hazardous	: yes

IATA-DGR

UN/ID No.	: UN 1206
Proper shipping name	: Heptanes
Class	: 3
Packing group	: II
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 364
Packing instruction (passenger aircraft)	: 353

IMDG-Code

UN number	: UN 1206
Proper shipping name	: HEPTANES (Heptane)
Class	: 3
Packing group	: II
Labels	: 3
EmS Code	: F-E, <u>S-D</u>
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number	: UN 1206
Proper shipping name	: HEPTANES
Class	: 3
Packing group	: II
Labels	: 3
ERG Code	: 128
Marine pollutant	: yes(Heptane)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HEAVY DUTY PARTS WASH, 18.9 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/12/2025	11518829-00001	Date of first issue: 03/12/2025

Volatile organic compounds (VOC) content Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations
VOC content: 100 % / 684 g/l
Remarks: VOC content excluding water and exempt compounds

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA AB OEL / STEL	: 15-minute occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average
CA BC OEL / STEL	: short-term exposure limit
CA QC OEL / TWA EV	: Time-weighted average exposure value
CA QC OEL / STEV	: Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumu-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HEAVY DUTY PARTS WASH, 18.9 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/12/2025	11518829-00001	Date of first issue: 03/12/2025

lative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 03/12/2025
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8