according to the Hazardous Products Regulations



# **HEAVY DUTY PARTS WASH, 205 L**

Version Revision Date: SDS Number: Date of last issue: -

06/03/2025 11539861-00001 Date of first issue: 06/03/2025 1.0

## **SECTION 1. IDENTIFICATION**

Product name HEAVY DUTY PARTS WASH, 205 L

Product code 890.107205

Other means of identification: No data available

Manufacturer or supplier's details

Company name of supplier Würth Canada Limited/Limitée

345 Hanlon Creek Blvd Address

GUELPH, ON N1C 0A1

Telephone 1-800-263-5002

Telefax 1-905-564-3671

Emergency telephone Emergencies involving a spill, fire, explosion or exposure:

CHEMTREC (24/7): 1-800-424-9300

Urgences impliquant un déversement, incendie, explosion ou

exposition: CHEMTREC (24/7): 1-800-424-9300

E-mail address prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use Degreasing agent

Restrictions on use Not applicable

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids Category 2

Skin irritation Category 2

Specific target organ toxicity

- single exposure

Category 3

Aspiration hazard Category 1

Physical hazards not other-

Category 1

wise classified

#### **GHS** label elements

according to the Hazardous Products Regulations



# **HEAVY DUTY PARTS WASH, 205 L**

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2025 11539861-00001 Date of first issue: 06/03/2025

Hazard pictograms :







Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.

May become electrostatically charged. Sparks may ignite liquid

and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, protective clothing, eye protection

and face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel

unwell.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant

foam, dry chemical or carbon dioxide to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

Other hazards

Vapors may form explosive mixture with air.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

according to the Hazardous Products Regulations



# **HEAVY DUTY PARTS WASH, 205 L**

Version Revision Date: SDS Number: Date of last issue: -

06/03/2025 11539861-00001 Date of first issue: 06/03/2025 1.0

Substance / Mixture Substance

Substance name Heptane

CAS-No. 142-82-5

Common Name/Synonym n-Heptane

### Components

	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Heptane	n-Heptane	142-82-5	>= 80 - <= 100 *

Actual concentration or concentration range is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed If swallowed, DO NOT induce vomiting.

If vomiting occurs have person lean forward.

Call a physician or poison control center immediately.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

Most important symptoms

and effects, both acute and

delayed

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

Protection of first-aiders First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Treat symptomatically and supportively. Notes to physician

#### **SECTION 5. FIRE-FIGHTING MEASURES**

according to the Hazardous Products Regulations



# **HEAVY DUTY PARTS WASH, 205 L**

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2025 11539861-00001 Date of first issue: 06/03/2025

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not use a solid water stream as it may scatter and spread

fire.

Flash back possible over considerable distance. Vapors may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec: :

tive equipment and emer-

gency procedures

Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapors/mists with a water spray

jet.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be

according to the Hazardous Products Regulations



# **HEAVY DUTY PARTS WASH, 205 L**

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2025 11539861-00001 Date of first issue: 06/03/2025

pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : Ground and bond container and receiving equipment.

Ensure all equipment is electrically grounded before beginning

transfer operations.

This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical ignition source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity, it is necessary to provide an inert gas purge before

beginning transfer operations.

Restrict flow velocity in order to reduce the accumulation of

static electricity.

Local/Total ventilation : Use explosion-proof electrical, ventilating and lighting equip-

ment.

Advice on safe handling : For outdoor use only

Do not get on skin or clothing. Avoid breathing mist or vapors.

Do not swallow.

Avoid contact with eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Non-sparking tools should be used. Keep container tightly closed.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store locked up. Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

according to the Hazardous Products Regulations



# **HEAVY DUTY PARTS WASH, 205 L**

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2025 11539861-00001 Date of first issue: 06/03/2025

Self-reactive substances and mixtures

Organic peroxides Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases

Explosives Gases

Very acutely toxic substances and mixtures

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Heptane	142-82-5	TWA	400 ppm 1,640 mg/m <sup>3</sup>	CA AB OEL
		STEL	500 ppm 2,050 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	400 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	400 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH

**Engineering measures** : Minimize workplace exposure concentrations.

Use explosion-proof electrical, ventilating and lighting

equipment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the re-

commended guidelines, use respiratory protection.

Filter type : Organic vapor Type

Hand protection

Material : Nitrile rubber

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the pro-

according to the Hazardous Products Regulations



# **HEAVY DUTY PARTS WASH, 205 L**

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2025 11539861-00001 Date of first issue: 06/03/2025

duct. Change gloves often!

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : clear

Odor : characteristic

Odor Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : -91 °C

Initial boiling point and boiling :

range

98 °C

Flash point : 22 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Static-accumulating flammable liquid.

according to the Hazardous Products Regulations



# **HEAVY DUTY PARTS WASH, 205 L**

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2025 11539861-00001 Date of first issue: 06/03/2025

Upper explosion limit / Upper

flammability limit

7 %(V)

Lower explosion limit / Lower :

flammability limit

1.1 %(V)

Vapor pressure : 53.5 hPa (20 °C)

Relative vapor density : No data available

Relative density : 0.684

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : 223 °C

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : < 20.5 mm<sup>2</sup>/s ( 40 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size : Not applicable

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Highly flammable liquid and vapor.

Vapors may form explosive mixture with air. Can react with strong oxidizing agents.

Conditions to avoid : Handling operations that can promote accumulation of static

charges.

Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

according to the Hazardous Products Regulations



# **HEAVY DUTY PARTS WASH, 205 L**

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2025 11539861-00001 Date of first issue: 06/03/2025

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

## Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

## **Acute toxicity**

Not classified based on available information.

#### **Components:**

Heptane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 73.5 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

## Skin corrosion/irritation

Causes skin irritation.

## **Components:**

Heptane:

Species : Rabbit Result : Skin irritation

Remarks : Based on data from similar materials

#### Serious eye damage/eye irritation

Not classified based on available information.

#### **Components:**

Heptane:

Species : Rabbit

Result : No eye irritation

Remarks : Based on data from similar materials

## Respiratory or skin sensitization

### Skin sensitization

Not classified based on available information.

according to the Hazardous Products Regulations



# **HEAVY DUTY PARTS WASH, 205 L**

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2025 11539861-00001 Date of first issue: 06/03/2025

## Respiratory sensitization

Not classified based on available information.

#### Components:

Heptane:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

## Germ cell mutagenicity

Not classified based on available information.

#### **Components:**

Heptane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Remarks: Based on data from similar materials

### Carcinogenicity

Not classified based on available information.

## **Components:**

Heptane:

Species : Rat

Application Route : inhalation (vapor)

Exposure time : 2 Years
Result : negative

Remarks : Based on data from similar materials

## Reproductive toxicity

Not classified based on available information.

## **Components:**

## **Heptane:**

according to the Hazardous Products Regulations



# **HEAVY DUTY PARTS WASH, 205 L**

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2025 11539861-00001 Date of first issue: 06/03/2025

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Remarks: Based on data from similar materials

### STOT-single exposure

May cause drowsiness or dizziness.

## **Components:**

## Heptane:

Assessment : May cause drowsiness or dizziness.

### STOT-repeated exposure

Not classified based on available information.

#### Repeated dose toxicity

#### **Components:**

## Heptane:

Species : Rat

NOAEL : 12.35 mg/l

Application Route : inhalation (vapor)

Exposure time : 90 Days

#### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

## **Components:**

### Heptane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

## **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

#### **Components:**

#### Heptane:

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 4,924 mg/l

Exposure time: 96 h

according to the Hazardous Products Regulations



# **HEAVY DUTY PARTS WASH, 205 L**

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2025 11539861-00001 Date of first issue: 06/03/2025

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 0.2 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50: > 0.1 - 1 mg/l Exposure time: 72 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): > 0.1 - 1 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

### Persistence and degradability

## **Components:**

Heptane:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 70 % Exposure time: 10 d

#### Bioaccumulative potential

#### **Components:**

Heptane:

Partition coefficient: n-

octanol/water

log Pow: 4.5

## Mobility in soil

No data available

#### Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal methods**

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Empty containers retain residue and can be dangerous.

Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

according to the Hazardous Products Regulations



# **HEAVY DUTY PARTS WASH, 205 L**

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2025 11539861-00001 Date of first issue: 06/03/2025

#### **SECTION 14. TRANSPORT INFORMATION**

## **International Regulations**

**UNRTDG** 

UN number : UN 1206
Proper shipping name : HEPTANES

Class : 3
Packing group : II
Labels : 3
Environmentally hazardous : yes

**IATA-DGR** 

UN/ID No. : UN 1206 Proper shipping name : Heptanes

Class : 3 Packing group : II

Labels : Flammable Liquids

Packing instruction (cargo

aircraft)

Packing instruction (passen: 353

ger aircraft)

**IMDG-Code** 

UN number : UN 1206
Proper shipping name : HEPTANES

(Heptane)

364

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D

Marine pollutant : yes

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **Domestic regulation**

**TDG** 

UN number : UN 1206
Proper shipping name : HEPTANES

Class : 3
Packing group : II
Labels : 3
ERG Code : 128

Marine pollutant : yes(Heptane)

## Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

according to the Hazardous Products Regulations



# **HEAVY DUTY PARTS WASH, 205 L**

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2025 11539861-00001 Date of first issue: 06/03/2025

Volatile organic compounds

(VOC) content

Canada - Volatile Organic Compound Concentration Limits for

Certain Products Regulations VOC content: 100 % / 684 g/l

Remarks: VOC content excluding water and exempt com-

oounds

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).

### **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average CA BC OEL / STEL : short-term exposure limit

CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumu-

according to the Hazardous Products Regulations



# **HEAVY DUTY PARTS WASH, 205 L**

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2025 11539861-00001 Date of first issue: 06/03/2025

lative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety

**Data Sheet** 

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 06/03/2025 Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8