

Vers 2.1	sion	Revision Date: 05/28/2025		98 Number: 383234-00003	Date of last issue: 05/15/2025 Date of first issue: 04/24/2024
SEC		. IDENTIFICATION			
	Produc	t name	:	BRAKE AND PAF	RTS CLEANER, Low VOC, 18.9 L
	Produc	t code	:	890.108752	
	Other n	neans of identification	:	No data available	
	Manufa	acturer or supplier's c	leta	ils	
	Compa	ny name of supplier	:	Würth Canada Lir	nited/Limitée
	Addres	S	:	345 Hanlon Creek GUELPH, ON N1	-
	Telepho	one	:	1-800-263-5002	
	Telefax		:	1-905-564-3671	
	Emerge	ency telephone	:		lving a spill, fire, explosion or exposure: 7): 1-800-424-9300
					ant un déversement, incendie, explosion ou ITREC (24/7): 1-800-424-9300
	E-mail a	address	:	prodsafe@wurth.c	ca
	Recom	mended use of the cl	hen	nical and restriction	ons on use
	Recom	mended use	:	Cleaning agent Automotive Detergent	
	Restric	tions on use	:	Not applicable	

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids	:	Category 2
Eye irritation	:	Category 2A
Specific target organ toxicity - single exposure	:	Category 3
Aspiration hazard	:	Category 1

GHS label elements

according to the Hazardous Products Regulations



BRAKE AND PARTS CLEANER, Low VOC, 18.9 L

rsion	Revision Date: 05/28/2025	SDS Number: 11383234-00003	Date of last issue: 05/15/2025 Date of first issue: 04/24/2024
Hazar	d pictograms		
Signal	Word	: Danger	
Hazar	d Statements	H304 May be fa H319 Causes s	mmable liquid and vapor. atal if swallowed and enters airways. serious eye irritation. se drowsiness or dizziness.
Preca	utionary Statements	and other igniti P261 Avoid bre P264 Wash ski P271 Use only	ay from heat, hot surfaces, sparks, open flame on sources. No smoking. eathing mist or vapors. n thoroughly after handling. outdoors or in a well-ventilated area. tective gloves, protective clothing, eye protecti ction.
		CENTER. P303 + P361 + all contaminate P304 + P340 + and keep comf unwell. P305 + P351 + for several min to do. Continue P331 Do NOT P337 + P313 If P370 + P378 Ir	 SWALLOWED: Immediately call a POISON P353 IF ON SKIN (or hair): Take off immediated clothing. Rinse skin with water. P312 IF INHALED: Remove person to fresh a cortable for breathing. Call a doctor if you feel P338 IF IN EYES: Rinse cautiously with water utes. Remove contact lenses, if present and ear insing. induce vomiting. eye irritation persists: Get medical attention. in case of fire: Use water spray, alcohol-resistantical or carbon dioxide to extinguish.
		Storage: P405 Store loc	ked up.
		Disposal: P501 Dispose d disposal plant.	of contents and container to an approved wast

Repeated exposure may cause skin dryness or cracking.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture



Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2025
2.1	05/28/2025	11383234-00003	Date of first issue: 04/24/2024

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Acetone	2-Propanone	67-64-1	>= 80 - < 100 *
Naphtha (petroleum), hydrotreated light	Low boiling point hydrogen treated naphtha	64742-49-0	>= 5 - < 10 *
Propan-2-ol	Isopropyl alco- hol	67-63-0	>= 5 - < 10 *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	:	In the case of accident or if you feel unwell, seek medical ad- vice immediately. When symptoms persist or in all cases of doubt seek medical advice. If inhaled, remove to fresh air.
ii iiinaleu	•	Get medical attention if symptoms occur.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact	:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention.
If swallowed	:	If swallowed, DO NOT induce vomiting. If vomiting occurs have person lean forward. Call a physician or poison control center immediately. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute and delayed	:	May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause drowsiness or dizziness. Prolonged or repeated contact may dry skin and cause irrita- tion.
Protection of first-aiders	:	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
Notes to physician	:	Treat symptomatically and supportively.



BRAKE AND PARTS CLEANER, Low VOC, 18.9 L

Versior 2.1	n Revision Date: 05/28/2025		OS Number: 383234-00003	Date of last issue: 05/15/2025 Date of first issue: 04/24/2024
SECTI	ON 5. FIRE-FIGHTING ME	ASL	JRES	
Su	itable extinguishing media	:	Water spray Alcohol-resistant Carbon dioxide (0 Dry chemical	
	nsuitable extinguishing edia	:	High volume wate	er jet
	becific hazards during fire hting	:	fire. Flash back possil Vapors may form	d water stream as it may scatter and spread ble over considerable distance. explosive mixtures with air. bustion products may be a hazard to health.
Ha uc	azardous combustion prod- ts	:	Carbon oxides	
Sr od	becific extinguishing meth-	:	cumstances and Use water spray f	g measures that are appropriate to local cir- the surrounding environment. to cool unopened containers. ged containers from fire area if it is safe to do
	pecial protective equipment fire-fighters	:		e, wear self-contained breathing apparatus. tective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Remove all sources of ignition. Ventilate the area. Use personal protective equipment. Follow safe handling advice (see section 7) and personal pro- tective equipment recommendations (see section 8).
Environmental precautions	:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for	:	Non-sparking tools should be used.



according to the Hazardous Products Regulations

BRAKE AND PARTS CLEANER, Low VOC, 18.9 L

Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2025
2.1	05/28/2025	11383234-00003	Date of first issue: 04/24/2024
contai	nment and cleaning up	Suppress (knock jet. For large spills, p ment to keep ma pumped, store re Clean up remain bent. Local or national sal of this materia ployed in the clea which regulations Sections 13 and	rt absorbent material. down) gases/vapors/mists with a water spray provide diking or other appropriate contain- terial from spreading. If diked material can be covered material in appropriate container. ing materials from spill with suitable absor- regulations may apply to releases and dispo- al, as well as those materials and items em- anup of releases. You will need to determine s are applicable. 15 of this SDS provide information regarding ational requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation :	If sufficient ventilation is unavailable, use with local exhaust ventilation. Use explosion-proof electrical, ventilating and lighting equip- ment.
Advice on safe handling :	Do not get on skin or clothing. Avoid breathing mist or vapors. Do not swallow. Do not get in eyes. Wash skin thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as- sessment Non-sparking tools should be used. Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.
Conditions for safe storage :	Keep in properly labeled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.
Materials to avoid :	Do not store with the following product types: Strong oxidizing agents Self-reactive substances and mixtures Organic peroxides



Versior 2.1	n Revision Date: 05/28/2025		DS Number: 383234-00003	Date of last issue: 05/15/2025 Date of first issue: 04/24/2024
			Substances and I flammable gases Explosives Gases	s stances and mixtures mixtures which in contact with water emit
	ecommended storage tem- erature	:	< 50 °C	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m ³	CA AB OEL
		STEL	750 ppm 1,800 mg/m ³	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	250 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Naphtha (petroleum), hy- drotreated light	64742-49-0	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
Propan-2-ol	67-63-0	STEL	400 ppm 984 mg/m ³	CA AB OEL
		TWA	200 ppm 492 mg/m ³	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	200 ppm	CA QC OEL
		STEV	400 ppm	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra- tion	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at	40 mg/l	ACGIH BEI



sion	Revision Date: 05/28/2025			SDS Number: 11383234-00003		ast issue: 05/ irst issue: 04/			
						end of work- week			
Acetor	ie	67-64-1		Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGI BEI	
Engineering measures :		lf su ven Use	Minimize workplace exposure concentrations. If sufficient ventilation is unavailable, use with local exhaust ventilation. Use explosion-proof electrical, ventilating and lighting equipment.						
Perso	nal protective equ	ipment							
Respir	atory protection	:	sur con In ti	e assessmen nmended gui	t demonstra delines, use	entilation is no ates exposure e respiratory p on use a resp	es outside the protection.	e re-	
Filte	er type	:	Org	anic vapor T	уре				
	protection terial	:	but	/l-rubber					
Material :		:	Silver Shield(R) gloves						
Remarks :		Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to che- micals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the pro- duct. Change gloves often!							
Eye pr	otection	:	Wear the following personal protective equipment: Safety goggles						
Skin a	nd body protection	:	resi pote We If as atm prof Skin	stance data a ential. ar the followin ssessment de ospheres or tective clothir	and an asse ng personal emonstrates flash fires, i ng. st be avoide	e clothing bas essment of th I protective ed s that there is use flame reta ed by using in ots, etc).	e local expos quipment: a risk of exp ardant antista	sure Ilosive atic	



Ver 2.1	rsion Revision Date: SDS Number: 05/28/2025 11383234-00003			Date of last issue: 05/15/2025 Date of first issue: 04/24/2024				
	Hygiene measures		eye flushing sys king place. When using do i		nemical is likely during typical use, provide tems and safety showers close to the wor- not eat, drink or smoke. ated clothing before re-use.			
SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES								
	Appeara	nce	:	liquid				
	Color		:	colorless				
	Odor		:	acetone-like				
	Odor Th	reshold	:	No data available				
	рН		:	Solvent mixture; pH value determination not possible, r aqueous solution				
	Melting p	ooint/freezing point	:	-1817 °C				
	Initial boi range	ling point and boiling	:	56 °C				
	Flash po	int	:	-18 °C				
	Evaporat	tion rate	:	> 1 (Butyl Acetate=1.	0)			
	Flammat	oility (solid, gas)	:	Not applicable				
	Flammat	pility (liquids)	:	Ignitable (see flas	sh point)			
	Self-ignit	ion	:	465 - 560 °C				
	Upper ex flammab	xplosion limit / Upper ility limit	:	14.3 %(V)				
	Lower ex flammab	xplosion limit / Lower ility limit	:	2.5 %(V)				
	Vapor pr	essure	:	No data available)			
	Relative	vapor density	:	> 1 (Air = 1.0)				



Version 2.1	Revision Date: 05/28/2025		S Number: 383234-00003	Date of last issue: 05/15/2025 Date of first issue: 04/24/2024				
Relativ	ve density	:	0.780 - 0.800					
	lity(ies) tter solubility	:	: completely miscible					
	on coefficient: n- bl/water	:	Not applicable					
Autoig	nition temperature	:	: No data available					
Decon	nposition temperature	:	No data available					
Viscos Vis	ity cosity, kinematic	:	No data available					
Explos	sive properties	:	Not explosive					
Oxidiz	ing properties	:	The substance o	r mixture is not classified as oxidizing.				
Particl Particl	e characteristics e size	:	Not applicable					


SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reac- tions	:	Highly flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact





	Revision Date: 05/28/2025	SDS Number: 11383234-00003	Date of last issue: 05/15/2025 Date of first issue: 04/24/2024					
Acute	toxicity							
Not cla	assified based on ava	ailable information.						
<u>Comp</u>	onents:							
Aceto	ne:							
Acute	oral toxicity	: LD50 (Rat): 5,8	300 mg/kg					
Acute	inhalation toxicity	Exposure time	: LC50 (Rat): 76 mg/l Exposure time: 4 h Test atmosphere: vapor					
Acute	dermal toxicity	: LD50 (Rabbit):	7,426 mg/kg					
Napht	ha (petroleum), hyd	rotreated light:						
Acute	oral toxicity	: LD50 (Rat): >	5,000 mg/kg					
Acute	inhalation toxicity		4 h					
Acute	dermal toxicity		 LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mixture has no acute der toxicity 					
Propa	ın-2-ol:							
-	oral toxicity	: LD50 (Rat): > \$	5,000 mg/kg					
Acute	inhalation toxicity	: LC50 (Rat): > 2 Exposure time Test atmosphe	6 h					
Acute	dermal toxicity	: LD50 (Rabbit):	> 5,000 mg/kg					
Not cla	corrosion/irritation assified based on ava conents:	ilable information.						
Aceto								

according to the Hazardous Products Regulations



BRAKE AND PARTS CLEANER, Low VOC, 18.9 L

Vers 2.1	sion	Revision Date: 05/28/2025	-	0S Number: 383234-00003	Date of last issue: 05/15/2025 Date of first issue: 04/24/2024
	Propan-2-ol: Species Result		:	Rabbit No skin irritation	
		s eye damage/eye irri s serious eye irritation.	tati	on	
	Compo	onents:			
	Aceton Species Result Method	5	:	Rabbit Irritation to eyes, r OECD Test Guide	eversing within 21 days line 405
	Naphth	a (petroleum), hydro	trea	ted light:	
	Species Result Method		:	Rabbit No eye irritation OECD Test Guide	line 405
	Propan	i-2-ol:			
	Species Result	5	:	Rabbit Irritation to eyes, r	eversing within 21 days
	Respira	atory or skin sensitiz	atio	n	
		ensitization ssified based on availa	ble	information.	
	-	atory sensitization ssified based on availa	ble	information.	
	Compo				
	Aceton Test Ty Routes Species Result	pe of exposure		Maximization Test Skin contact Guinea pig negative	t
	Test Ty	of exposure	:	ted light: Buehler Test Skin contact Guinea pig OECD Test Guide negative	eline 406

Propan-2-ol:

Test Type	: Buehler Test
Routes of exposure	: Skin contact



ersion 1	Revision Date: 05/28/2025	SDS Number:Date of last issue: 05/15/202511383234-00003Date of first issue: 04/24/2024							
Speci Metho Resul	bd	 Guinea pig OECD Test Guideline 406 negative 							
	cell mutagenicity lassified based on av	ailable information.							
Com	oonents:								
Aceto	one:								
Geno	toxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative							
		Test Type: Bacterial reverse mutation assay (AMES) Result: negative							
		Test Type: Chromosome aberration test in vitro Result: negative							
Geno	toxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Ingestion Result: negative							
Naph	tha (petroleum), hy	drotreated light:							
Geno	toxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative							
Geno	toxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Intraperitoneal injection Method: OPPTS 870.5395 Result: negative							
Propa	an-2-ol:								
-	toxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative							
		Test Type: In vitro mammalian cell gene mutation test Result: negative							
Geno	toxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative							



ersion 1	Revision Date: 05/28/2025		DS Number: 383234-00003	Date of last issue: 05/15/2025 Date of first issue: 04/24/2024		
	inogenicity					
Not c	lassified based on availa	able	information.			
<u>Com</u>	ponents:					
Acete	one:					
Speci		:	Mouse			
	cation Route	:	Skin contact			
Expo: Resu	sure time It		424 days negative			
	tha (petroleum), hydro	trea				
Speci		÷	Mouse			
	cation Route sure time	÷	Skin contact 102 weeks			
Metho		:	OECD Test Guide	aline 451		
Resu		:	negative			
Prop	an-2-ol:					
Speci			Rat			
•	cation Route	:	inhalation (vapor)			
	sure time	÷	104 weeks			
Meth		: OECD Test Guideline 451				
Resu	lt	:	negative			
Repr	oductive toxicity					
•	lassified based on availa	able	information.			
Com	ponents:					
Acete	one:					
Effec	ts on fertility	:	Test Type: One-g	eneration reproduction toxicity study		
	,		Species: Rat	, , , ,		
			Application Route	: Ingestion		
			Result: negative			
Effec	ts on fetal development	:		o-fetal development		
			Species: Rat			
			Application Route Result: negative	: inhalation (vapor)		
New	4h = (= 4 = 1 =)	4	ted light-			
	tha (petroleum), hydro		-	operation reproduction toxicity study		
Ellec	ts on fertility	•	Species: Rat	eneration reproduction toxicity study		
				: inhalation (vapor)		
			Method: OECD To			
			Result: negative			
Effect	ts on fetal development	:		vo-fetal development		
			Species: Rat			
			13 / 20			



Version 2.1	Revision Date: 05/28/2025		0S Number: 383234-00003	Date of last issue: 05/15/2025 Date of first issue: 04/24/2024	
				e: inhalation (vapor) Test Guideline 414	
Prop	an-2-ol:				
-	ts on fertility	:	Test Type: Two-g Species: Rat Application Route Result: negative	generation reproduction toxicity study e: Ingestion	
Effec	Effects on fetal development		Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Result: negative		
STO	Γ-single exposure				
May	cause drowsiness or dizz	zine	SS.		
<u>Com</u>	ponents:				
Acet	one:				
Asse	ssment	:	May cause drows	siness or dizziness.	
Naph	ntha (petroleum), hydro	trea	ted light:		
-	ssment	:	-	siness or dizziness.	
Prop	an-2-ol:				
Asse	ssment	:	May cause drows	siness or dizziness.	
STO	F-repeated exposure				
Not c	lassified based on availa	ble	information.		
Repe	ated dose toxicity				
Com	ponents:				
Acet	one:				
	EL	: : : : : : : : : : : : : : : : : : : :	Rat 900 mg/kg 1,700 mg/kg Ingestion 90 Days		
		: : :	Rat 45 mg/l inhalation (vapor) 8 Weeks)	

according to the Hazardous Products Regulations



BRAKE AND PARTS CLEANER, Low VOC, 18.9 L

Version 2.1	Revision Date: 05/28/2025		OS Number: 383234-00003	Date of last issue: 05/15/2025 Date of first issue: 04/24/2024
Naph	itha (petroleum), hyd	drotrea	ated light:	
Speci	ies	:	Rat	
NOA	EL	:	> 20 mg/l	
Appli	cation Route	:	inhalation (vapo	r)
Expo	sure time	:	13 Weeks	
Metho	od	:	OPPTS 870.346	65
Rema	arks	:	Based on data f	rom similar materials
Prop	an-2-ol:			
_	_		_	

: Rat
: 12.5 mg/l
: inhalation (vapor)
: 104 Weeks

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Naphtha (petroleum), hydrotreated light:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Acetone:

Autono.		
Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia pulex (Water flea)): 8,800 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other	:	NOEC (Daphnia magna (Water flea)): >= 79 mg/l



Versio 2.1	n	Revision Date: 05/28/2025		S Number: 383234-00003	Date of last issue: 05/15/2025 Date of first issue: 04/24/2024
	quatic toxici	invertebrates (Chron- ty)		Exposure time: 21 Method: OECD Te	
Т	oxicity	to microorganisms	:	EC50: 61,150 mg/ Exposure time: 30 Method: ISO 8192) min
N	laphth	a (petroleum), hydrot	trea	ted light:	
Т	oxicity	to fish	:	Exposure time: 96 Method: OECD Te	
		to daphnia and other invertebrates	:	Exposure time: 48 Method: OECD Te	
	oxicity lants	to algae/aquatic	:	EC50 (Pseudokiro 1,000 mg/l Exposure time: 72 Method: OECD Te	
				NOEC (Pseudokir - 0.1 mg/l Exposure time: 72 Method: OECD Te	
a		to daphnia and other invertebrates (Chron- ty)	:	NOEC (Daphnia n Exposure time: 21 Method: OECD Te	
Р	ropan	-2-ol:			
	-	to fish	:	LC50 (Pimephales Exposure time: 96	s promelas (fathead minnow)): 9,640 mg/l 5 h
		to daphnia and other invertebrates	:	EC50 (Daphnia m Exposure time: 24	agna (Water flea)): > 10,000 mg/l l h
Т	oxicity	to microorganisms	:	EC50 (Pseudomo Exposure time: 16	nas putida): > 1,050 mg/l 3 h
Ρ	ersist	ence and degradabili	ty		
<u>c</u>	ompo	nents:			
Α	ceton	e:			
В	liodegr	adability	:	Result: Readily bid Biodegradation: 9 Exposure time: 28	91 %



Vers 2.1	sion	Revision Date: 05/28/2025		9S Number: 383234-00003	Date of last issue: 05/15/2025 Date of first issue: 04/24/2024
	-	a (petroleum), hydro radability	trea :	Result: Readily bi Biodegradation: 7 Exposure time: 28	77%
	Propan Biodegi BOD/C	radability	:	Result: rapidly de	-
	Bioacc	umulative potential		COD: 2,23 BOD/COD: 53 %	
	Compo				
	Aceton Partition octanol	n coefficient: n-	:	log Pow: -0.27(0.23
	-	na (petroleum), hydro n coefficient: n- /water	trea :	t ed light: log Pow: > 4 Remarks: Expert j	udgment
	Propar Partition octanol	n coefficient: n-	:	log Pow: 0.05	
		y in soil a available			
	•	adverse effects a available			
SEC	SECTION 13. DISPOSAL CONSIDERATIONS				
	Dispos	al methods			
		from residues	:	Do not dispose of	waste into sewer.
				Dispose of in acco	ordance with local regulations.
	Contarr	ninated packaging	:		should be taken to an approved waste ecycling or disposal.



Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2025
2.1	05/28/2025	11383234-00003	Date of first issue: 04/24/2024

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG UN number Proper shipping name Class Packing group Labels Environmentally hazardous	:	UN 1993 FLAMMABLE LIQUID, N.O.S. (Acetone, Propan-2-ol) 3 II 3 no
IATA-DGR UN/ID No. Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passen- ger aircraft)	:	UN 1993 Flammable liquid, n.o.s. (Acetone, Propan-2-ol) 3 II Flammable Liquids 364 353
IMDG-Code UN number Proper shipping name Class Packing group Labels EmS Code Marine pollutant	:	UN 1993 FLAMMABLE LIQUID, N.O.S. (Acetone, Propan-2-ol) 3 II 3 F-E, <u>S-E</u> no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG		
UN number	:	UN 1993
Proper shipping name	:	FLAMMABLE LIQUID, N.O.S.
		(Acetone, Propan-2-ol)
Class	:	3
Packing group	:	II
Labels	:	3
ERG Code	:	128
Marine pollutant	:	no
-		



Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2025
2.1	05/28/2025	11383234-00003	Date of first issue: 04/24/2024

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds	Canada - Volatile Organic Compound Concentration Limits for
(VOC) content	Certain Products Regulations
(100) 000000	VOC content: < 10 %

The ingredients of this product are reported in the following inventories:

	0	•	
DSL		:	All chemical substances in this product comply with the CEPA
			1999 and NSNR and are on or exempt from listing on the
			Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH ACGIH BEI CA AB OEL	:	USA. ACGIH Threshold Limit Values (TLV) ACGIH - Biological Exposure Indices (BEI) Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safe- ty, Schedule 1, Part 1: Permissible exposure values for air- borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International



Version	Revision Date:	SDS Number:	Date of last issue: 05/15/2025
2.1	05/28/2025	11383234-00003	Date of first issue: 04/24/2024

Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NOM - Official Mexican Norm: NTP - National Toxicology Program: NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
Revision Date	:	05/28/2025

Revision Date	•	05/26/2025
Date format	:	mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8