

**BEAD SEALER, High strength, 946 mL**

Version            Revision Date:            SDS Number:            Date of last issue: 11/11/2022  
3.2                05/29/2023                10693491-00007            Date of first issue: 10/06/2011

---

**SECTION 1. IDENTIFICATION**

Product name                                : BEAD SEALER, High strength, 946 mL  
Product code                                : 890.122000  
Other means of identification            : No data available

**Manufacturer or supplier's details**

Company name of supplier                : Würth Canada Limited  
Address                                        : 345 Hanlon Creek Blvd  
    GUELPH, ON N1C 0A1  
Telephone                                     : +1 (905) 564 6225  
Telefax                                        : +1 (905) 564 3671  
Emergency telephone                      : Emergencies involving a spill, fire, explosion or exposure:  
    CHEMTREC (24/7): 1-800-424-9300  
    Transport related emergencies:  
    CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)  
  
    Urgences impliquant un déversement, incendie, explosion ou  
    exposition:  
    CHEMTREC (24/7): 1-800-424-9300  
    Urgences liées au transport:  
    CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)  
  
E-mail address                                : prodsafe@wurth.ca

**Recommended use of the chemical and restrictions on use**

Recommended use                            : Sealant  
  
Restrictions on use                           : Not applicable

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Flammable liquids                           : Category 2  
Skin irritation                                : Category 2  
Eye irritation                                 : Category 2B  
Respiratory sensitization                 : Category 1  
Skin sensitization                            : Category 1

**BEAD SEALER, High strength, 946 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
3.2	05/29/2023	10693491-00007	Date of first issue: 10/06/2011

---

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 3  
- single exposure

Specific target organ toxicity : Category 2 (Central nervous system)  
- repeated exposure

**GHS label elements**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.  
H315 + H320 Causes skin and eye irritation.  
H317 May cause an allergic skin reaction.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H336 May cause drowsiness or dizziness.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements :

**Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.  
P284 Wear respiratory protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P333 + P313 If skin irritation or rash occurs: Get medical attention.

**BEAD SEALER, High strength, 946 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
3.2	05/29/2023	10693491-00007	Date of first issue: 10/06/2011

P337 + P313 If eye irritation persists: Get medical attention.  
 P342 + P311 If experiencing respiratory symptoms: Call a doctor.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.  
 P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.

**Disposal:**

P501 Dispose of contents and container to an approved waste disposal plant.

**Other hazards**

Vapors may form explosive mixture with air.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture  
 Chemical nature : Adhesives

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Toluene	Benzene, methyl-	108-88-3	$\geq 60 - < 80$ *
Heptane	n-Heptane	142-82-5	$\geq 30 - < 60$ *
Rubber, natural	No data available	9006-04-6	$\geq 5 - < 10$ *

\* Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
 When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
 If not breathing, give artificial respiration.  
 If breathing is difficult, give oxygen.  
 Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
 Get medical attention.  
 Wash clothing before reuse.

**BEAD SEALER, High strength, 946 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
3.2	05/29/2023	10693491-00007	Date of first issue: 10/06/2011

---

- Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin and eye irritation.  
May cause an allergic skin reaction.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause drowsiness or dizziness.  
Suspected of damaging the unborn child.  
May cause damage to organs through prolonged or repeated exposure.  
Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

**BEAD SEALER, High strength, 946 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
3.2	05/29/2023	10693491-00007	Date of first issue: 10/06/2011

---

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Ventilate the area.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
- 

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not get on skin or clothing.  
Do not breathe mist or vapors.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-
-

**BEAD SEALER, High strength, 946 mL**

Version 3.2      Revision Date: 05/29/2023      SDS Number: 10693491-00007      Date of last issue: 11/11/2022  
 Date of first issue: 10/06/2011

essment

Non-sparking tools should be used.

Keep container tightly closed.

Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.  
 Store locked up.  
 Keep tightly closed.  
 Keep in a cool, well-ventilated place.  
 Store in accordance with the particular national regulations.  
 Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
 Strong oxidizing agents  
 Self-reactive substances and mixtures  
 Organic peroxides  
 Flammable solids  
 Pyrophoric liquids  
 Pyrophoric solids  
 Self-heating substances and mixtures  
 Substances and mixtures which in contact with water emit flammable gases  
 Explosives  
 Gases  
 Very acutely toxic substances and mixtures

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Toluene	108-88-3	TWA	50 ppm 188 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
Heptane	142-82-5	TWA	20 ppm	ACGIH
		TWA	400 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWA	400 ppm 1,640 mg/m <sup>3</sup>	CA AB OEL
		STEL	500 ppm 2,050 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	400 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL

**BEAD SEALER, High strength, 946 mL**

Version 3.2      Revision Date: 05/29/2023      SDS Number: 10693491-00007      Date of last issue: 11/11/2022  
 Date of first issue: 10/06/2011

		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Rubber, natural	9006-04-6	TWA	0.001 mg/m <sup>3</sup> (inhalable aller- genic proteins)	CA AB OEL
		TWA (Inhal- able)	0.001 mg/m <sup>3</sup> (inhalable aller- genic proteins)	CA BC OEL
		TWA (Inha- lable particu- late matter)	0.0001 mg/m <sup>3</sup> (inhalable aller- genic proteins)	ACGIH

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra- tion	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work- week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

**Engineering measures** : Minimize workplace exposure concentrations.  
 If sufficient ventilation is unavailable, use with local exhaust ventilation.  
 Use explosion-proof electrical, ventilating and lighting equipment.

**Personal protective equipment**

Respiratory protection : If adequate local exhaust ventilation is not available or expo-  
 sure assessment demonstrates exposures outside the re-  
 commended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection  
 Material : Solvent-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

**BEAD SEALER, High strength, 946 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
3.2	05/29/2023	10693491-00007	Date of first issue: 10/06/2011

---

on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

- Eye protection : Wear the following personal protective equipment:  
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Contaminated work clothing should not be allowed out of the workplace.  
Wash contaminated clothing before re-use.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Color : black
- Odor : solvent
- Odor Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : 99 °C
- Flash point : -9 °C

Method: Tag closed cup



**BEAD SEALER, High strength, 946 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
3.2	05/29/2023	10693491-00007	Date of first issue: 10/06/2011

---

Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	7.0 %(V)
Lower explosion limit / Lower flammability limit	:	1.1 %(V)
Vapor pressure	:	48 hPa (20 °C)
Relative vapor density	:	No data available
Density	:	0.87 g/cm <sup>3</sup> (20 °C)
Solubility(ies) Water solubility	:	immiscible
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	246.1 - 260 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s ( 40 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Highly flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

## BEAD SEALER, High strength, 946 mL

Version 3.2      Revision Date: 05/29/2023      SDS Number: 10693491-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/06/2011

---

## SECTION 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

**Components:****Toluene:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Heptane:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 73.5 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

**Rubber, natural:**

Acute oral toxicity : LD50 (Rat): 2,043 - 2,210 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**BEAD SEALER, High strength, 946 mL**

Version 3.2      Revision Date: 05/29/2023      SDS Number: 10693491-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/06/2011

---

**Components:****Toluene:**

Species : Rabbit  
Method : Directive 67/548/EEC, Annex V, B.4.  
Result : Skin irritation

**Heptane:**

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

**Serious eye damage/eye irritation**

Causes eye irritation.

**Product:**

Result : Irritation to eyes, reversing within 7 days

**Components:****Toluene:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

**Heptane:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Components:****Toluene:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : Directive 67/548/EEC, Annex V, B.6.  
Result : negative

**Heptane:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

**BEAD SEALER, High strength, 946 mL**

Version 3.2      Revision Date: 05/29/2023      SDS Number: 10693491-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/06/2011

---

**Rubber, natural:**

Assessment : Probability or evidence of skin sensitization in humans  
Assessment : May cause sensitization by inhalation.

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Toluene:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: Intraperitoneal injection  
Result: negative  
Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 478  
Result: negative

**Heptane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials  
Test Type: Chromosome aberration test in vitro  
Result: negative  
Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

**Carcinogenicity**

Not classified based on available information.

**BEAD SEALER, High strength, 946 mL**

Version 3.2      Revision Date: 05/29/2023      SDS Number: 10693491-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/06/2011

---

**Components:****Toluene:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 103 weeks  
Result : negative

Species : Mouse  
Application Route : Skin contact  
Exposure time : 24 Months  
Result : negative

**Heptane:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Result : negative  
Remarks : Based on data from similar materials

**Reproductive toxicity**

Suspected of damaging the unborn child.

**Components:****Toluene:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 416  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

**Heptane:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

**BEAD SEALER, High strength, 946 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
3.2	05/29/2023	10693491-00007	Date of first issue: 10/06/2011

---

**STOT-single exposure**

May cause drowsiness or dizziness.

**Components:**

**Toluene:**

Assessment : May cause drowsiness or dizziness.

**Heptane:**

Assessment : May cause drowsiness or dizziness.

**STOT-repeated exposure**

May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

**Components:**

**Toluene:**

Routes of exposure : Inhalation  
Target Organs : Central nervous system  
Assessment : May cause damage to organs through prolonged or repeated exposure.

**Repeated dose toxicity**

**Components:**

**Toluene:**

Species : Rat  
LOAEL : 1.875 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 6 Months

Species : Rat  
NOAEL : 625 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks

**Heptane:**

Species : Rat  
NOAEL : 12.35 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days

**Aspiration toxicity**

Not classified based on available information.

**Components:**

**Toluene:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**BEAD SEALER, High strength, 946 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
3.2	05/29/2023	10693491-00007	Date of first issue: 10/06/2011

---

**Heptane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Experience with human exposure****Components:****Toluene:**

Inhalation : Target Organs: Central nervous system  
Symptoms: Neurological disorders

---

**SECTION 12. ECOLOGICAL INFORMATION**
**Ecotoxicity****Components:****Toluene:**

Toxicity to fish	:	LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	NOEC (Skeletonema costatum (marine diatom)): 10 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l Exposure time: 40 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Ceriodaphnia dubia (water flea)): 0.74 mg/l Exposure time: 7 d
Toxicity to microorganisms	:	EC50 (Nitrosomonas sp.): 84 mg/l Exposure time: 24 h

**Heptane:**

Toxicity to fish	:	LC50 (Gambusia affinis (Mosquito fish)): 4,924 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia magna (Water flea)): 0.2 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50: > 0.1 - 1 mg/l Exposure time: 72 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): > 0.1 - 1 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials

**BEAD SEALER, High strength, 946 mL**

Version 3.2      Revision Date: 05/29/2023      SDS Number: 10693491-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/06/2011

---

**Rubber, natural:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 10,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to microorganisms : (activated sludge): > 10,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

**Persistence and degradability****Components:****Toluene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 80 %  
Exposure time: 20 d

**Heptane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 70 %  
Exposure time: 10 d

**Bioaccumulative potential****Components:****Toluene:**

Bioaccumulation : Species: Leuciscus idus (Golden orfe)  
Bioconcentration factor (BCF): 90

Partition coefficient: n-octanol/water : log Pow: 2.73

**Heptane:**

Partition coefficient: n-octanol/water : log Pow: 4.5

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.  
  
Do not dispose of waste into sewer.



**BEAD SEALER, High strength, 946 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
3.2	05/29/2023	10693491-00007	Date of first issue: 10/06/2011

---

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

---

**SECTION 14. TRANSPORT INFORMATION**
**International Regulations**
**UNRTDG**

UN number : UN 1133  
Proper shipping name : ADHESIVES  
Class : 3  
Packing group : II  
Labels : 3

**IATA-DGR**

UN/ID No. : UN 1133  
Proper shipping name : Adhesives  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

**IMDG-Code**

UN number : UN 1133  
Proper shipping name : ADHESIVES  
(Heptane)  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-D  
Marine pollutant : yes

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation**
**TDG**

UN number : UN 1133  
Proper shipping name : ADHESIVES  
  
Class : 3  
Packing group : II  
Labels : 3  
ERG Code : 128  
Marine pollutant : yes(Heptane)

## BEAD SEALER, High strength, 946 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
3.2	05/29/2023	10693491-00007	Date of first issue: 10/06/2011

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

**Volatile organic compounds (VOC) content** CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products  
VOC content: 75 %

### The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median

**BEAD SEALER, High strength, 946 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
3.2	05/29/2023	10693491-00007	Date of first issue: 10/06/2011

---

Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/29/2023  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8