

**TIRE MOUNTING COMPOUND, Concentrated,  
11.3 kg**

Version 2.2	Revision Date: 09/14/2021	SDS Number: 408235-00005	Date of last issue: 11/02/2020 Date of first issue: 09/25/2018
----------------	------------------------------	-----------------------------	---

---

**SECTION 1. IDENTIFICATION**

Product name : TIRE MOUNTING COMPOUND, Concentrated, 11.3 kg

Product code : 890.1225

Other means of identification : No data available

**Manufacturer or supplier's details**

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences liées au transport:  
CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

**Recommended use of the chemical and restrictions on use**

Recommended use : Lubricant

Restrictions on use : Not applicable

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Skin irritation : Category 2

Eye irritation : Category 2A

**GHS label elements**

**TIRE MOUNTING COMPOUND, Concentrated,  
11.3 kg**

Version 2.2	Revision Date: 09/14/2021	SDS Number: 408235-00005	Date of last issue: 11/02/2020 Date of first issue: 09/25/2018
----------------	------------------------------	-----------------------------	---

Hazard pictograms

:



Signal Word

: Warning

Hazard Statements

: H315 Causes skin irritation.  
H319 Causes serious eye irritation.

Precautionary Statements

**Prevention:**  
P264 Wash skin thoroughly after handling.  
P280 Wear protective gloves, eye protection and face protection.

**Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of water.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P332 + P313 If skin irritation occurs: Get medical attention.  
P337 + P313 If eye irritation persists: Get medical attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Soaps, potassium	No data available	Not Assigned	$\geq 30 - < 60$ *
Glycerine	1,2,3-Propanetriol	56-81-5	$\geq 5 - < 10$ *
Potassium hydroxide	Caustic potash	1310-58-3	$\geq 0.5 - < 1$ *

\* Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.

**TIRE MOUNTING COMPOUND, Concentrated,  
11.3 kg**

Version 2.2	Revision Date: 09/14/2021	SDS Number: 408235-00005	Date of last issue: 11/02/2020 Date of first issue: 09/25/2018
----------------	------------------------------	-----------------------------	---

- Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
Causes serious eye irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

**TIRE MOUNTING COMPOUND, Concentrated,  
11.3 kg**

Version 2.2	Revision Date: 09/14/2021	SDS Number: 408235-00005	Date of last issue: 11/02/2020 Date of first issue: 09/25/2018
----------------	------------------------------	-----------------------------	---

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing vapors.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents

**TIRE MOUNTING COMPOUND, Concentrated,  
11.3 kg**

Version 2.2      Revision Date: 09/14/2021      SDS Number: 408235-00005      Date of last issue: 11/02/2020  
Date of first issue: 09/25/2018

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Glycerine	56-81-5	TWA (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Mist)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (Respirable mist)	3 mg/m <sup>3</sup>	CA BC OEL
		TWAEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
Potassium hydroxide	1310-58-3	(c)	2 mg/m <sup>3</sup>	CA AB OEL
		C	2 mg/m <sup>3</sup>	CA BC OEL
		C	2 mg/m <sup>3</sup>	CA QC OEL
		C	2 mg/m <sup>3</sup>	ACGIH

**Engineering measures** : Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

**Personal protective equipment**

**Respiratory protection** : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

**Filter type** : Organic vapor Type

**Hand protection**

**Material** : Chemical-resistant gloves

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

**Eye protection** : Wear the following personal protective equipment:  
Safety goggles

**Skin and body protection** : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

**Hygiene measures** : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.

**TIRE MOUNTING COMPOUND, Concentrated,  
11.3 kg**

Version 2.2	Revision Date: 09/14/2021	SDS Number: 408235-00005	Date of last issue: 11/02/2020 Date of first issue: 09/25/2018
----------------	------------------------------	-----------------------------	---

When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	paste
Color	:	clear, amber
Odor	:	slight
Odor Threshold	:	No data available
pH	:	10.5
Melting point/freezing point	:	< 0 °C
Initial boiling point and boiling range	:	> 60 °C
Flash point	:	> 100 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	1.02 g/cm <sup>3</sup> (20 °C)
Solubility(ies) Water solubility	:	completely miscible
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available

**TIRE MOUNTING COMPOUND, Concentrated,  
11.3 kg**

Version 2.2	Revision Date: 09/14/2021	SDS Number: 408235-00005	Date of last issue: 11/02/2020 Date of first issue: 09/25/2018
----------------	------------------------------	-----------------------------	---

Decomposition temperature	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Particle size	: Not applicable

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Can react with strong oxidizing agents.
Conditions to avoid	: None known.
Incompatible materials	: Oxidizing agents Acids
Hazardous decomposition products	: No hazardous decomposition products are known.

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Components:****Glycerine:**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity	: LD50 (Guinea pig): > 5,000 mg/kg

**Potassium hydroxide:**

Acute oral toxicity	: LD50 (Rat): 333 mg/kg
Acute inhalation toxicity	: Assessment: Corrosive to the respiratory tract.

**TIRE MOUNTING COMPOUND, Concentrated,  
11.3 kg**

Version	Revision Date:	SDS Number:	Date of last issue: 11/02/2020
2.2	09/14/2021	408235-00005	Date of first issue: 09/25/2018

---

**Skin corrosion/irritation**

Causes skin irritation.

**Components:****Glycerine:**

Species	:	Rabbit
Result	:	No skin irritation

**Potassium hydroxide:**

Species	:	Rabbit
Result	:	Corrosive after 3 minutes or less of exposure

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Components:****Soaps, potassium:**

Result	:	Irritation to eyes, reversing within 21 days
--------	---	--

**Glycerine:**

Species	:	Rabbit
Result	:	No eye irritation

**Potassium hydroxide:**

Species	:	Rabbit
Result	:	Irreversible effects on the eye

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Components:****Potassium hydroxide:**

Test Type	:	Intracutaneous test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Glycerine:**



**TIRE MOUNTING COMPOUND, Concentrated,  
11.3 kg**

Version 2.2	Revision Date: 09/14/2021	SDS Number: 408235-00005	Date of last issue: 11/02/2020 Date of first issue: 09/25/2018
----------------	------------------------------	-----------------------------	---

---

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

**Potassium hydroxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Components:****Glycerine:**

Species	: Rat
Application Route	: Ingestion
Exposure time	: 2 Years
Result	: negative

**Reproductive toxicity**

Not classified based on available information.

**Components:****Glycerine:**

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative
Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Result: negative

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.

**TIRE MOUNTING COMPOUND, Concentrated,  
11.3 kg**

Version	Revision Date:	SDS Number:	Date of last issue: 11/02/2020
2.2	09/14/2021	408235-00005	Date of first issue: 09/25/2018

---

**Repeated dose toxicity****Components:****Glycerine:**

Species	:	Rat
NOAEL	:	0.167 mg/l
LOAEL	:	0.622 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	13 Weeks

Species	:	Rat
NOAEL	:	8,000 - 10,000 mg/kg
Application Route	:	Ingestion
Exposure time	:	2 y

Species	:	Rabbit
NOAEL	:	5,040 mg/kg
Application Route	:	Skin contact
Exposure time	:	45 Weeks

**Aspiration toxicity**

Not classified based on available information.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Glycerine:**

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 54,000 mg/l
Exposure time:	:	96 h

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,955 mg/l
Exposure time:	:	48 h

Toxicity to microorganisms	:	NOEC (Pseudomonas putida): > 10,000 mg/l
Exposure time:	:	16 h
Method:	:	DIN 38 412 Part 8

**Persistence and degradability****Components:****Glycerine:**

Biodegradability	:	Result: Readily biodegradable.
Biodegradation:	:	92 %
Exposure time:	:	30 d
Method:	:	OECD Test Guideline 301D

**TIRE MOUNTING COMPOUND, Concentrated,  
11.3 kg**

Version 2.2	Revision Date: 09/14/2021	SDS Number: 408235-00005	Date of last issue: 11/02/2020 Date of first issue: 09/25/2018
----------------	------------------------------	-----------------------------	---

**Bioaccumulative potential****Components:****Glycerine:**

Partition coefficient: n-  
octanol/water : log Pow: -1.75

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

Not regulated as a dangerous good

**Special precautions for user**

Not applicable

---

**SECTION 15. REGULATORY INFORMATION****Volatile organic compounds  
(VOC) content**

CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 -  
Guidelines for VOC in Consumer Products  
VOC content: 0 % / 0 g/l

**TIRE MOUNTING COMPOUND, Concentrated,  
11.3 kg**

Version	Revision Date:	SDS Number:	Date of last issue: 11/02/2020
2.2	09/14/2021	408235-00005	Date of first issue: 09/25/2018

**The ingredients of this product are reported in the following inventories:**

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / C	: Ceiling limit
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA AB OEL / (c)	: ceiling occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average
CA BC OEL / C	: ceiling limit
CA QC OEL / TWA EV	: Time-weighted average exposure value
CA QC OEL / C	: Ceiling

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recom-

**TIRE MOUNTING COMPOUND, Concentrated,  
11.3 kg**

Version	Revision Date:	SDS Number:	Date of last issue: 11/02/2020
2.2	09/14/2021	408235-00005	Date of first issue: 09/25/2018

---

recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/14/2021  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8