

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version 1.0 Revision Date: 10/17/2025 SDS Number: 11587081-00001 Date of last issue: -
Date of first issue: 10/17/2025

SECTION 1. IDENTIFICATION

Product name : W-SOL, Residue remover, 946 mL
Product code : 890.132006
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : 1-800-263-5002
Telefax : 1-905-564-3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300

Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Cleaning agent
Solvent

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 3

Skin irritation : Category 2

Specific target organ toxicity : Category 3
- single exposure

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version 1.0 Revision Date: 10/17/2025 SDS Number: 11587081-00001 Date of last issue: -
Date of first issue: 10/17/2025

Precautionary Statements

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
tert-Butyl acetate	Acetic acid, 1,1-dimethylethyl ester	540-88-5	$\geq 60 - < 80$ *
Distillates (petroleum), light distillate hydrotreating process, low-boiling	No data available	68410-97-9	$\geq 10 - < 30$ *
Xylene	Dimethylbenzene	1330-20-7	$\geq 5 - < 10$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version 1.0 Revision Date: 10/17/2025 SDS Number: 11587081-00001 Date of last issue: -
Date of first issue: 10/17/2025

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control center immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/17/2025	11587081-00001	Date of first issue: 10/17/2025

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapors/mists with a water spray jet. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation. Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Do not get on skin or clothing. Avoid breathing mist or vapors. Do not swallow. Avoid contact with eyes. Wash skin thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version 1.0 Revision Date: 10/17/2025 SDS Number: 11587081-00001 Date of last issue: -
Date of first issue: 10/17/2025

- Non-sparking tools should be used.
Keep container tightly closed.
Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases
Very acutely toxic substances and mixtures
- Recommended storage temperature : 5 - 30 °C
Storage period : 6 Months

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
tert-Butyl acetate	540-88-5	TWA	200 ppm 950 mg/m ³	CA AB OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	150 ppm	CA QC OEL
		TWA	50 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	50 ppm	ACGIH
Xylene	1330-20-7	TWA	100 ppm 434 mg/m ³	CA AB OEL
		STEL	150 ppm 651 mg/m ³	CA AB OEL

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version 1.0 Revision Date: 10/17/2025 SDS Number: 11587081-00001 Date of last issue: -
Date of first issue: 10/17/2025

		TWAEV	100 ppm 434 mg/m ³	CA QC OEL
		STEV	150 ppm 651 mg/m ³	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g creatinine	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection

Material : butyl-rubber

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/17/2025	11587081-00001	Date of first issue: 10/17/2025

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : No data available

Odor : solvent

Odor Threshold : No data available

pH : Solvent mixture; pH value determination not possible, no aqueous solution

Melting point/freezing point : No data available

Initial boiling point and boiling range : 127 °C

Flash point : 24 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : 8.28 hPa (20 °C)
4.096 hPa (50 °C)

Relative vapor density : No data available

Relative density : 0.842

Solubility(ies)
Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : 421 °C

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/17/2025	11587081-00001	Date of first issue: 10/17/2025

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : 0.8 cP (20 °C)

Viscosity, kinematic : 0.95 mm²/s (20 °C)

< 20.5 mm²/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Flammable liquid and vapor.
Vapors may form explosive mixture with air.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/17/2025	11587081-00001	Date of first issue: 10/17/2025

Components:

tert-Butyl acetate:

Acute oral toxicity : LD50 (Rat): 4,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 15 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Distillates (petroleum), light distillate hydrotreating process, low-boiling:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.61 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): 27.571 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

tert-Butyl acetate:

Species : Rabbit

Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version 1.0 Revision Date: 10/17/2025 SDS Number: 11587081-00001 Date of last issue: -
Date of first issue: 10/17/2025

Distillates (petroleum), light distillate hydrotreating process, low-boiling:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Based on data from similar materials

Xylene:

Species : Rabbit
Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

tert-Butyl acetate:

Species : Rabbit
Result : No eye irritation

Distillates (petroleum), light distillate hydrotreating process, low-boiling:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Xylene:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

tert-Butyl acetate:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Distillates (petroleum), light distillate hydrotreating process, low-boiling:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/17/2025	11587081-00001	Date of first issue: 10/17/2025

Xylene:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Result	:	negative

Germ cell mutagenicity

Not classified based on available information.

Components:

tert-Butyl acetate:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
		Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
		Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (vapor) Method: OECD Test Guideline 474 Result: negative

Distillates (petroleum), light distillate hydrotreating process, low-boiling:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	:	Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat Application Route: Intraperitoneal injection Result: negative Remarks: Based on data from similar materials

Xylene:

Genotoxicity in vitro	:	Test Type: Chromosome aberration test in vitro Result: negative
		Test Type: In vitro sister chromatid exchange assay in mammalian cells Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version 1.0 Revision Date: 10/17/2025 SDS Number: 11587081-00001 Date of last issue: -
Date of first issue: 10/17/2025

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

tert-Butyl acetate:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

Distillates (petroleum), light distillate hydrotreating process, low-boiling:

Species : Mouse
Application Route : Skin contact
Exposure time : 102 weeks
Result : negative
Remarks : Based on data from similar materials

Xylene:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

tert-Butyl acetate:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapor)
Method: OPPTS 870.3650
Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/17/2025	11587081-00001	Date of first issue: 10/17/2025

Species: Rat
Application Route: inhalation (vapor)
Method: OPPTS 870.3650
Result: negative

Distillates (petroleum), light distillate hydrotreating process, low-boiling:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

STOT-single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

Components:

tert-Butyl acetate:

Assessment : May cause respiratory irritation.

Assessment : May cause drowsiness or dizziness.

Distillates (petroleum), light distillate hydrotreating process, low-boiling:

Assessment : May cause drowsiness or dizziness.

Xylene:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/17/2025	11587081-00001	Date of first issue: 10/17/2025

Repeated dose toxicity

Components:

tert-Butyl acetate:

Species	: Mouse
NOAEL	: 1.9 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 13 Weeks

Distillates (petroleum), light distillate hydrotreating process, low-boiling:

Species	: Rat
NOAEL	: > 20 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 13 Weeks
Method	: OPPTS 870.3465
Remarks	: Based on data from similar materials

Xylene:

Species	: Rat
LOAEL	: 150 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Distillates (petroleum), light distillate hydrotreating process, low-boiling:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

tert-Butyl acetate:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 240 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
------------------	--

Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 350 mg/l Exposure time: 48 h
---	--

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/17/2025	11587081-00001	Date of first issue: 10/17/2025

Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 16 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 2.3 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Distillates (petroleum), light distillate hydrotreating process, low-boiling:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 4.5 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOELR (Pimephales promelas (fathead minnow)): 2.6 mg/l
Exposure time: 14 d
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 204

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 2.6 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version 1.0 Revision Date: 10/17/2025 SDS Number: 11587081-00001 Date of last issue: -
Date of first issue: 10/17/2025

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h
- Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): > 0.1 - < 1 mg/l
Exposure time: 35 d
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials
- Toxicity to microorganisms : NOEC: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Persistence and degradability

Components:

tert-Butyl acetate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 50 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Distillates (petroleum), light distillate hydrotreating process, low-boiling:

Biodegradability : Result: Inherently biodegradable.
Biodegradation: 74.3 %
Exposure time: 28 d

Xylene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

tert-Butyl acetate:

Partition coefficient: n- : Pow: 1.64

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/17/2025	11587081-00001	Date of first issue: 10/17/2025

octanol/water

Xylene:

Partition coefficient: n-octanol/water : log Pow: 3.16
Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(tert-Butyl acetate, Distillates (petroleum), light distillate hydrotreating process, low-boiling)

Class : 3
Packing group : III
Labels : 3
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1993
Proper shipping name : Flammable liquid, n.o.s.
(tert-Butyl acetate, Distillates (petroleum), light distillate hydrotreating process, low-boiling)

Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/17/2025	11587081-00001	Date of first issue: 10/17/2025

UN number	:	UN 1993
Proper shipping name	:	FLAMMABLE LIQUID, N.O.S. (tert-Butyl acetate, Distillates (petroleum), light distillate hydrotreating process, low-boiling)
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number	:	UN 1993
Proper shipping name	:	FLAMMABLE LIQUID, N.O.S. (tert-Butyl acetate, Distillates (petroleum), light distillate hydrotreating process, low-boiling)
Class	:	3
Packing group	:	III
Labels	:	3
ERG Code	:	128
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content	Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations VOC content: 30 % / 252.52 g/l Category: Multi-purpose solvent - non-aerosol
---	---

The ingredients of this product are reported in the following inventories:

CA. DSL	:	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
---------	---	--

Canadian lists

No substances are subject to CEPA Section 84 Ministerial Conditions.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/17/2025	11587081-00001	Date of first issue: 10/17/2025

CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
--	---	---

Revision Date	:	10/17/2025
Date format	:	mm/dd/yyyy

SAFETY DATA SHEET

according to the Hazardous Products Regulations



W-SOL, Residue remover, 946 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/17/2025	11587081-00001	Date of first issue: 10/17/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8