

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

SECTION 1. IDENTIFICATION

Product name : DASHBOARD CLEANER, 263 g

Product code : 890.2221

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:

CHEMTREC (24/7): 1-800-424-9300

Urgences liées au transport:

CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Detergent

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1

Gases under pressure : Liquefied gas

Skin irritation : Category 2

Specific target organ toxicity : Category 3
- single exposure

DASHBOARD CLEANER, 263 g

Version 4.3 Revision Date: 05/10/2023 SDS Number: 10663185-00011 Date of last issue: 11/10/2022
 Date of first issue: 06/23/2017

GHS label elements

Hazard pictograms



Signal Word

: Danger

Hazard Statements

 : H222 Extremely flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.

Precautionary Statements

 : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
 P332 + P313 If skin irritation occurs: Get medical attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)

DASHBOARD CLEANER, 263 g

Version 4.3 Revision Date: 05/10/2023 SDS Number: 10663185-00011 Date of last issue: 11/10/2022
 Date of first issue: 06/23/2017

Naphtha (petroleum), hydrotreated light	Low boiling point hydrogen treated naphtha	64742-49-0	$\geq 30 - < 60$ *
Butane	Butyl hydride	106-97-8	$\geq 10 - < 30$ *
Propane	Dimethylmethane	74-98-6	$\geq 5 - < 10$ *
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	No data available	90622-57-4	$\geq 5 - < 10$ *
Isobutane	Propane, 2-methyl-	75-28-5	$\geq 5 - < 10$ *
Distillates (petroleum), hydrotreated heavy paraffinic	No data available	Not Assigned	$\geq 1 - < 5$ *
Dodecan-1-ol	1-Dodecanol	112-53-8	$\geq 1 - < 5$ *
Tetradecanol	Tetradecan-1-ol	112-72-1	$\geq 1 - < 5$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
 Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
 Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
 Get medical attention if symptoms occur.
 Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
 May cause drowsiness or dizziness.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- | | | |
|---------------------------------|---|--|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation. |
| Advice on safe handling | : | Do not get on skin or clothing.
Avoid breathing spray.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source. |
| Conditions for safe storage | : | Store locked up.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight. |
| Materials to avoid | : | Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases |
| Recommended storage temperature | : | > 5 - 40 °C |

DASHBOARD CLEANER, 263 g

Version 4.3 Revision Date: 05/10/2023 SDS Number: 10663185-00011 Date of last issue: 11/10/2022
 Date of first issue: 06/23/2017

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha (petroleum), hydrotreated light	64742-49-0	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm 1,900 mg/m ³	CA QC OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	90622-57-4	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
Isobutane	75-28-5	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Distillates (petroleum), hydrotreated heavy paraffinic	Not Assigned	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH

Engineering measures : Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

- Filter type : Self-contained breathing apparatus
- Hand protection
Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0.45 mm
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a liquefied gas
- Propellant : Propane, Butane, Isobutane
- Color : colorless
- Odor : No data available
- Odor Threshold : No data available
- pH : substance/mixture is non-soluble (in water)
- Melting point/freezing point : No data available

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

Initial boiling point and boiling range : > 60 °C

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : No data available

Density : 0.72 g/cm³ (20 °C)

Solubility(ies)
Water solubility : partly soluble

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.
Vapors may form explosive mixture with air.

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.

Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated light:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5.6 mg/l Exposure time: 4 h Test atmosphere: vapor Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

Butane:

Acute inhalation toxicity	:	LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: vapor
---------------------------	---	--

Propane:

Acute inhalation toxicity	:	LC50 (Rat): > 800000 ppm Exposure time: 15 min Test atmosphere: gas
---------------------------	---	---

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

Exposure time: 4 h
Test atmosphere: dust/mist
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Remarks: Based on data from similar materials

Isobutane:

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm
Exposure time: 4 h
Test atmosphere: gas

Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Dodecan-1-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 12 mg/l
Exposure time: 6 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Tetradecanol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 1.5 mg/l
Exposure time: 1 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:**Naphtha (petroleum), hydrotreated light:**

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: Skin irritation

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:

Species	: Rabbit
Result	: Mild skin irritation
Remarks	: Based on data from similar materials

Assessment	: Repeated exposure may cause skin dryness or cracking.
Remarks	: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species	: Rabbit
Result	: No skin irritation
Remarks	: Based on data from similar materials

Dodecan-1-ol:

Species	: Human
Result	: No skin irritation

Tetradecanol:

Species	: Human
Result	: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated light:**

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:

Species	: Rabbit
Result	: No eye irritation
Remarks	: Based on data from similar materials

DASHBOARD CLEANER, 263 g

Version 4.3 Revision Date: 05/10/2023 SDS Number: 10663185-00011 Date of last issue: 11/10/2022
Date of first issue: 06/23/2017

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Dodecan-1-ol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

Tetradecanol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated light:**

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

Dodecan-1-ol:

Test Type : Maximization Test
Routes of exposure : Skin contact

DASHBOARD CLEANER, 263 g

Version 4.3 Revision Date: 05/10/2023 SDS Number: 10663185-00011 Date of last issue: 11/10/2022
Date of first issue: 06/23/2017

Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Tetradecanol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated light:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: Intraperitoneal injection
Method: OPPTS 870.5395
Result: negative

Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Isobutane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Dodecan-1-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

Method: OECD Test Guideline 473
 Result: negative
 Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
 Result: negative
 Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
 Species: Mouse
 Application Route: Ingestion
 Method: OECD Test Guideline 474
 Result: negative

Tetradecanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Test Type: Chromosome aberration test in vitro
 Method: OECD Test Guideline 473
 Result: negative
 Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
 Result: negative
 Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:
Naphtha (petroleum), hydrotreated light:

Species : Mouse
 Application Route : Skin contact
 Exposure time : 102 weeks
 Method : OECD Test Guideline 451
 Result : negative

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Mouse
 Application Route : Skin contact
 Exposure time : 78 weeks
 Method : OECD Test Guideline 451
 Result : negative
 Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

DASHBOARD CLEANER, 263 g

Version 4.3 Revision Date: 05/10/2023 SDS Number: 10663185-00011 Date of last issue: 11/10/2022
Date of first issue: 06/23/2017

Reproductive toxicity

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated light:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 414
Result: negative

Butane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

DASHBOARD CLEANER, 263 g

Version 4.3 Revision Date: 05/10/2023 SDS Number: 10663185-00011 Date of last issue: 11/10/2022
Date of first issue: 06/23/2017

Isobutane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Distillates (petroleum), hydrotreated heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Dodecan-1-ol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

STOT-single exposure

May cause drowsiness or dizziness.

Components:**Naphtha (petroleum), hydrotreated light:**

Assessment : May cause drowsiness or dizziness.

DASHBOARD CLEANER, 263 g

Version 4.3 Revision Date: 05/10/2023 SDS Number: 10663185-00011 Date of last issue: 11/10/2022
Date of first issue: 06/23/2017

Butane:

Assessment : May cause drowsiness or dizziness.

Propane:

Assessment : May cause drowsiness or dizziness.

Isobutane:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity**Components:****Naphtha (petroleum), hydrotreated light:**

Species : Rat
NOAEL : > 20 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks
Method : OPPTS 870.3465
Remarks : Based on data from similar materials

Butane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Propane:

Species : Rat
NOAEL : 7.214 mg/l
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:

Species : Rat
NOAEL : > 1 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Species : Rat
NOAEL : > 300 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

DASHBOARD CLEANER, 263 g

Version 4.3 Revision Date: 05/10/2023 SDS Number: 10663185-00011 Date of last issue: 11/10/2022
Date of first issue: 06/23/2017

Isobutane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit
NOAEL : 1,000 mg/kg
Application Route : Skin contact
Exposure time : 4 Weeks
Method : OECD Test Guideline 410
Remarks : Based on data from similar materials

Species : Rat
NOAEL : > 980 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 4 Weeks

Dodecan-1-ol:

Species : Rat
NOAEL : > 2,000 mg/kg
Application Route : Ingestion
Exposure time : 41 - 45 Days

Aspiration toxicity

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated light:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Dodecan-1-ol:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Naphtha (petroleum), hydrotreated light:**

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 8.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.5 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Pseudokirchneriella subcapitata (green algae)): > 0.01 - 0.1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 16 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): > 1 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

Method: OECD Test Guideline 211

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202
 Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
 Exposure time: 21 d
 Method: OECD Test Guideline 211
 Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
 Exposure time: 10 min
 Method: DIN 38 412 Part 8
 Remarks: Based on data from similar materials

Dodecan-1-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1.01 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.765 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 0.66 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 0.085 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Daphnia magna (Water flea)): 0.013 mg/l
 Exposure time: 21 d
 Method: OECD Test Guideline 211

Toxicity to microorganisms : EC0 (Pseudomonas putida): > 10,000 mg/l
 Exposure time: 30 min

Tetradecanol:

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility.
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3.2 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 10 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
- EL10 (Desmodesmus subspicatus (green algae)): 2.9 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Daphnia magna (Water flea)): 0.0063 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Persistence and degradability**Components:****Naphtha (petroleum), hydrotreated light:**

- Biodegradability : Result: Readily biodegradable.
Biodegradation: 77 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Butane:

- Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Propane:

- Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:

- Biodegradability : Result: Not readily biodegradable.
Remarks: Based on data from similar materials

Isobutane:

- Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

DASHBOARD CLEANER, 263 g

Version 4.3 Revision Date: 05/10/2023 SDS Number: 10663185-00011 Date of last issue: 11/10/2022
Date of first issue: 06/23/2017

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Dodecan-1-ol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 79 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Tetradecanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 92 %
Exposure time: 28 d

Bioaccumulative potential**Components:****Naphtha (petroleum), hydrotreated light:**

Partition coefficient: n-octanol/water : log Pow: > 4
Remarks: Expert judgment

Butane:

Partition coefficient: n-octanol/water : log Pow: 2.31

Isobutane:

Partition coefficient: n-octanol/water : log Pow: 2.8

Dodecan-1-ol:

Partition coefficient: n-octanol/water : log Pow: >= 4
Remarks: Based on data from similar materials

Tetradecanol:

Partition coefficient: n-octanol/water : log Pow: 5.5

Mobility in soil

No data available

Other adverse effects

No data available

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with local regulations.
- Do not dispose of waste into sewer.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
- Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty (including propellant)

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

- UN number : UN 1950
- Proper shipping name : AEROSOLS
- Class : 2.1
- Packing group : Not assigned by regulation
- Labels : 2.1

IATA-DGR

- UN/ID No. : UN 1950
- Proper shipping name : Aerosols, flammable
- Class : 2.1
- Packing group : Not assigned by regulation
- Labels : Flammable Gas
- Packing instruction (cargo aircraft) : 203
- Packing instruction (passenger aircraft) : 203

IMDG-Code

- UN number : UN 1950
- Proper shipping name : AEROSOLS
(Naphtha (petroleum), hydrotreated light, Tetradecanol)
- Class : 2.1
- Packing group : Not assigned by regulation
- Labels : 2.1
- EmS Code : F-D, S-U
- Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

UN number	:	UN 1950
Proper shipping name	:	AEROSOLS
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
ERG Code	:	126
Marine pollutant	:	yes(Naphtha (petroleum), hydrotreated light, Tetradecanol)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**The ingredients of this product are reported in the following inventories:**

DSL	:	This product contains one or several components that are not on the Canadian DSL nor NDSL.
-----	---	--

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Or-

DASHBOARD CLEANER, 263 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/10/2022
4.3	05/10/2023	10663185-00011	Date of first issue: 06/23/2017

ganisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/10/2023
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8