according to the Hazardous Products Regulations



RIGID PLASTIC FIX, Component B

Version Revision Date: SDS Number: Date of last issue: 11/17/2022 2.0 12/18/2023 5247090-00006 Date of first issue: 11/04/2019

SECTION 1. IDENTIFICATION

Product name : RIGID PLASTIC FIX, Component B

Product code : 890.480132B

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd

GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:

CHEMTREC (24/7): 1-800-424-9300

Transport related emergencies:

CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou

exposition:

CHEMTREC (24/7): 1-800-424-9300

Urgences liées au transport:

CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Paints

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Corrosive to Metals : Category 1

Skin corrosion : Category 1

Serious eye damage : Category 1

GHS label elements

according to the Hazardous Products Regulations



RIGID PLASTIC FIX, Component B

Version Revision Date: SDS Number: Date of last issue: 11/17/2022 2.0 12/18/2023 5247090-00006 Date of first issue: 11/04/2019

Hazard pictograms

Signal Word : Danger

Hazard Statements : H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Precautionary Statements : Prevention:

P234 Keep only in original packaging.

P260 Do not breathe vapors.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves, protective clothing, eye protection

and face protection.

Response:

P301 + P330 + P331 + P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER. P303 + P361 + P353 + P310 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

Immediately call a POISON CENTER.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON

CENTER

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER.

P363 Wash contaminated clothing before reuse. P390 Absorb spillage to prevent material damage.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

Other hazards

Corrosive to the respiratory tract.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Amines

Components

Chemical name	Common	CAS-No.	Concentration (% w/w)
	Name/Synonym		

according to the Hazardous Products Regulations



RIGID PLASTIC FIX, Component B

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11/17/2022

 2.0
 12/18/2023
 5247090-00006
 Date of first issue: 11/04/2019

2,4,6-	Phenol, 2,4,6-	90-72-2	
Tris(dimethylaminomet	tris[(dimethylami		>= 10 - < 30 *
hyl)phenol	no)methyl]-		
Titanium dioxide	Titanic anhy-	13463-67-7	>= 5 - < 10 *
	dride		>= 5 - < 10

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention immediately. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention immediately.

If swallowed : If swallowed, DO NOT induce vomiting.

If vomiting occurs have person lean forward.

Call a physician or poison control center immediately.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

Corrosive to respiratory system. Causes serious eye damage.

Causes severe burns.

Causes digestive tract burns.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam

according to the Hazardous Products Regulations



RIGID PLASTIC FIX, Component B

Version Revision Date: SDS Number: Date of last issue: 11/17/2022 2.0 12/18/2023 5247090-00006 Date of first issue: 11/04/2019

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod- :

ucts

Sulfur oxides Carbon oxides

Nitrogen oxides (NOx)

Silicon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: : tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers)

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

according to the Hazardous Products Regulations



RIGID PLASTIC FIX, Component B

Version Revision Date: SDS Number: Date of last issue: 11/17/2022 12/18/2023 5247090-00006 Date of first issue: 11/04/2019 2.0

Technical measures See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Advice on safe handling Do not get on skin or clothing.

Do not breathe vapors.

Do not swallow.

Do not get in eyes. Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety

practice, based on the results of the workplace exposure assessment

Keep container tightly closed.

Keep away from metals. Store in original container or corrosi-

ve resistant and/or lined container. Keep only in original packaging.

Take care to prevent spills, waste and minimize release to the

environment.

Keep in properly labeled containers. Conditions for safe storage

Store in original container.

Store locked up. Keep tightly closed.

Store in accordance with the particular national regulations.

Materials to avoid Do not store with the following product types:

Strong oxidizing agents

Self-reactive substances and mixtures

Organic peroxides

Explosives

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis
		exposure)	concentration	
Titanium dioxide	13463-67-7	TWA	10 mg/m ³	CA AB OEL
		TWA (Total	10 mg/m ³	CA BC OEL
		dust)		
		TWA (respir-	3 mg/m³	CA BC OEL
		able dust		
		fraction)		
		TWAEV (to-	10 mg/m ³	CA QC OEL
		tal dust)	_	
		TWA (Respi-	2.5 mg/m ³	ACGIH
		rable particu-	(Titanium dioxide)	
		late matter)		

according to the Hazardous Products Regulations



RIGID PLASTIC FIX, Component B

Version Revision Date: SDS Number: Date of last issue: 11/17/2022 2.0 12/18/2023 5247090-00006 Date of first issue: 11/04/2019

This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Titanium dioxide

Engineering measures : Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the re-

commended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection

Material : PVA
Break through time : <= 300 min
Glove thickness : >= 0.08 mm

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of

workday.

Eye protection : Wear the following personal protective equipment:

Chemical resistant goggles must be worn.

If splashes are likely to occur, wear:

Face-shield

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : light yellow

according to the Hazardous Products Regulations



RIGID PLASTIC FIX, Component B

Version 2.0

Revision Date: 12/18/2023

SDS Number: 5247090-00006

Date of last issue: 11/17/2022 Date of first issue: 11/04/2019

Odor : sweet

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling :

range

No data available

Flash point : > 93 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper

flammability limit

7.0 %(V)

Lower explosion limit / Lower :

flammability limit

1.0 %(V)

Vapor pressure : 0.13 kPa (20 °C)

Relative vapor density : 7.59

Density : 1.10 g/cm³

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

according to the Hazardous Products Regulations



RIGID PLASTIC FIX, Component B

Version Revision Date: SDS Number: Date of last issue: 11/17/2022 12/18/2023 5247090-00006 Date of first issue: 11/04/2019 2.0

Metal corrosion rate Corrosive to metals

Particle size Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability Stable under normal conditions.

tions

Possibility of hazardous reac- : Can react with strong oxidizing agents.

May be corrosive to metals.

Conditions to avoid None known.

Incompatible materials Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Components:

2,4,6-Tris(dimethylaminomethyl)phenol:

: LD50 (Rat): 1,653 mg/kg Acute oral toxicity

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Titanium dioxide:

Acute oral toxicity LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity LC50 (Rat): > 6.82 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

according to the Hazardous Products Regulations



RIGID PLASTIC FIX, Component B

Version Revision Date: SDS Number: Date of last issue: 11/17/2022 2.0 12/18/2023 5247090-00006 Date of first issue: 11/04/2019

tion toxicity

Skin corrosion/irritation

Causes severe burns.

Components:

2,4,6-Tris(dimethylaminomethyl)phenol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Corrosive after 1 to 4 hours of exposure

Titanium dioxide:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-Tris(dimethylaminomethyl)phenol:

Species : Rabbit

Result : Irreversible effects on the eye

Titanium dioxide:

Species : Rabbit

Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

2,4,6-Tris(dimethylaminomethyl)phenol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : equivocal

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

according to the Hazardous Products Regulations



RIGID PLASTIC FIX, Component B

Version Revision Date: SDS Number: Date of last issue: 11/17/2022 2.0 12/18/2023 5247090-00006 Date of first issue: 11/04/2019

Titanium dioxide:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

2,4,6-Tris(dimethylaminomethyl)phenol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Titanium dioxide:

Species : Rat

Application Route : inhalation (dust/mist/fume)

Exposure time : 2 Years

Method : OECD Test Guideline 453

Result : positive

Remarks : The mechanism or mode of action may not be relevant in hu-

mans.

This substance(s) is not bioavailable and therefore does not

contribute to a dust inhalation hazard.

Carcinogenicity - Assess-

ment

Limited evidence of carcinogenicity in inhalation studies with

animals.

Reproductive toxicity

Not classified based on available information.

Components:

2,4,6-Tris(dimethylaminomethyl)phenol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

according to the Hazardous Products Regulations



RIGID PLASTIC FIX, Component B

Version Revision Date: SDS Number: Date of last issue: 11/17/2022 2.0 12/18/2023 5247090-00006 Date of first issue: 11/04/2019

Application Route: Ingestion

Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

2,4,6-Tris(dimethylaminomethyl)phenol:

Species : Rat
NOAEL : 15 mg/kg
Application Route : Ingestion
Exposure time : 43 Days

Method : OECD Test Guideline 422

Titanium dioxide:

Species : Rat

NOAEL : 24,000 mg/kg Application Route : Ingestion Exposure time : 28 Days

Species : Rat NOAEL : 10 mg/m³

Application Route : inhalation (dust/mist/fume)

Exposure time : 2 y

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2,4,6-Tris(dimethylaminomethyl)phenol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 180 mg/l

Exposure time: 96 h

according to the Hazardous Products Regulations



RIGID PLASTIC FIX, Component B

Version Revision Date: SDS Number: Date of last issue: 11/17/2022 12/18/2023 5247090-00006 Date of first issue: 11/04/2019 2.0

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 84 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 6.25 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC: 2 mg/l Toxicity to microorganisms

Exposure time: 28 d

Method: OECD Test Guideline 301D

Titanium dioxide:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l

Exposure time: 72 h

Toxicity to microorganisms EC50: > 1,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Persistence and degradability

Components:

2,4,6-Tris(dimethylaminomethyl)phenol:

Biodegradability Result: Not readily biodegradable.

> Biodegradation: 4 % Exposure time: 28 d

Method: OECD Test Guideline 301D

Bioaccumulative potential

Components:

2,4,6-Tris(dimethylaminomethyl)phenol:

Partition coefficient: n-

: log Pow: 0.219

Mobility in soil

octanol/water

No data available

Other adverse effects

No data available

according to the Hazardous Products Regulations



RIGID PLASTIC FIX, Component B

Version Revision Date: SDS Number: Date of last issue: 11/17/2022 2.0 12/18/2023 5247090-00006 Date of first issue: 11/04/2019

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 2735

Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.

no

(2,4,6-Tris(dimethylaminomethyl)phenol)

Class : 8
Packing group : III
Labels : 8

Environmentally hazardous

IATA-DGR

UN/ID No. : UN 2735

Proper shipping name : Amines, liquid, corrosive, n.o.s.

(2,4,6-Tris(dimethylaminomethyl)phenol)

Class : 8 Packing group : III

Labels : Corrosive Packing instruction (cargo : 856

aircraft)

Packing instruction (passen- : 852

ger aircraft)

IMDG-Code

UN number : UN 2735

Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.

(2,4,6-Tris(dimethylaminomethyl)phenol)

Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 2735

Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.

according to the Hazardous Products Regulations



RIGID PLASTIC FIX, Component B

Version Revision Date: SDS Number: Date of last issue: 11/17/2022 2.0 12/18/2023 5247090-00006 Date of first issue: 11/04/2019

(2,4,6-Tris(dimethylaminomethyl)phenol)

Class : 8
Packing group : III
Labels : 8
ERG Code : 153
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 -

(VOC) content Guidelines for VOC in Consumer Products

VOC content: 0 % / 0 g/l

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average

CA QC OEL / TWAEV : Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International

according to the Hazardous Products Regulations



RIGID PLASTIC FIX, Component B

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11/17/2022

 2.0
 12/18/2023
 5247090-00006
 Date of first issue: 11/04/2019

Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 12/18/2023 Date format : mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8