

JOINT AND SEAM SEALER, White, 300 mL

Version 1.9 Revision Date: 05/30/2023 SDS Number: 10778569-00007 Date of last issue: 11/17/2022
Date of first issue: 05/30/2017

SECTION 1. IDENTIFICATION

Product name : JOINT AND SEAM SEALER, White, 300 mL
Product code : 890.50010
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Sealant

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable liquids : Category 2
Skin irritation : Category 2
Reproductive toxicity : Category 2
Specific target organ toxicity : Category 3
- single exposure

JOINT AND SEAM SEALER, White, 300 mL

Version 1.9 Revision Date: 05/30/2023 SDS Number: 10778569-00007 Date of last issue: 11/17/2022
Date of first issue: 05/30/2017

Specific target organ toxicity : Category 2 (Central nervous system)
- repeated exposure

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical attention.
P332 + P313 If skin irritation occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal:
P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Vapors may form explosive mixture with air.

JOINT AND SEAM SEALER, White, 300 mL

Version 1.9 Revision Date: 05/30/2023 SDS Number: 10778569-00007 Date of last issue: 11/17/2022
 Date of first issue: 05/30/2017

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | Common Name/Synonym | CAS-No. | Concentration (% w/w) |
|-------------------------------|---------------------|-------------|-----------------------|
| Toluene | Benzene, methyl- | 108-88-3 | >= 30 - < 60 * |
| Limestone | Calcium carbonate | 1317-65-3 | >= 10 - < 30 * |
| White mineral oil (petroleum) | Paraffinum liquidum | 8042-47-5 | >= 10 - < 30 * |
| Silicon, amorphous | Silicon dioxide | 112945-52-5 | >= 1 - < 5 * |
| Titanium dioxide | Titanic anhydride | 13463-67-7 | >= 1 - < 5 * |

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
 Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
 Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
 Get medical attention.
 Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
 May cause drowsiness or dizziness.
 Suspected of damaging the unborn child.
 May cause damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

JOINT AND SEAM SEALER, White, 300 mL

Version 1.9 Revision Date: 05/30/2023 SDS Number: 10778569-00007 Date of last issue: 11/17/2022
Date of first issue: 05/30/2017

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.

JOINT AND SEAM SEALER, White, 300 mL

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11/17/2022 |
| 1.9 | 05/30/2023 | 10778569-00007 | Date of first issue: 05/30/2017 |

Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- | | | |
|-----------------------------|---|---|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation. Use explosion-proof electrical, ventilating and lighting equipment. |
| Advice on safe handling | : | Do not get on skin or clothing. Do not breathe vapors. Do not swallow. Avoid contact with eyes. Wash skin thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment Non-sparking tools should be used. Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. |
| Conditions for safe storage | : | Keep in properly labeled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition. |
| Materials to avoid | : | Do not store with the following product types: Strong oxidizing agents Self-reactive substances and mixtures Organic peroxides Flammable solids Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures which in contact with water emit flammable gases Explosives Gases |

JOINT AND SEAM SEALER, White, 300 mL

Version 1.9 Revision Date: 05/30/2023 SDS Number: 10778569-00007 Date of last issue: 11/17/2022
 Date of first issue: 05/30/2017

Very acutely toxic substances and mixtures

Storage period : 18 Months

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-------------------------------|-------------|-------------------------------------|--|-----------|
| Toluene | 108-88-3 | TWA | 50 ppm 188 mg/m ³ | CA AB OEL |
| | | TWA | 20 ppm | CA BC OEL |
| | | TWAEV | 20 ppm | CA QC OEL |
| | | TWA | 20 ppm | ACGIH |
| Limestone | 1317-65-3 | TWA | 10 mg/m ³ | CA AB OEL |
| | | TWAEV (total dust) | 10 mg/m ³ | CA QC OEL |
| | | TWA (Total dust) | 10 mg/m ³ | CA BC OEL |
| | | TWA (respirable dust fraction) | 3 mg/m ³ | CA BC OEL |
| | | STEL | 20 mg/m ³ | CA BC OEL |
| White mineral oil (petroleum) | 8042-47-5 | TWA (Mist) | 5 mg/m ³ | CA AB OEL |
| | | STEL (Mist) | 10 mg/m ³ | CA AB OEL |
| | | TWAEV (Mist) | 5 mg/m ³ | CA QC OEL |
| | | STEV (Mist) | 10 mg/m ³ | CA QC OEL |
| | | TWA (Mist) | 1 mg/m ³ | CA BC OEL |
| | | TWA (Inhalable particulate matter) | 5 mg/m ³ | ACGIH |
| Silicon, amorphous | 112945-52-5 | TWA (Respirable) | 1.5 mg/m ³ | CA BC OEL |
| | | TWA (Total) | 4 mg/m ³ | CA BC OEL |
| | | TWAEV (respirable dust) | 6 mg/m ³ | CA QC OEL |
| Titanium dioxide | 13463-67-7 | TWA | 10 mg/m ³ | CA AB OEL |
| | | TWA (Total dust) | 10 mg/m ³ | CA BC OEL |
| | | TWA (respirable dust fraction) | 3 mg/m ³ | CA BC OEL |
| | | TWAEV (total dust) | 10 mg/m ³ | CA QC OEL |
| | | TWA (Respirable particulate matter) | 2.5 mg/m ³ (Titanium dioxide) | ACGIH |

JOINT AND SEAM SEALER, White, 300 mL

Version 1.9 Revision Date: 05/30/2023 SDS Number: 10778569-00007 Date of last issue: 11/17/2022
 Date of first issue: 05/30/2017

This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Titanium dioxide

Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Sam-pling time | Permissible concentra-tion | Basis |
|------------|----------|--------------------|---------------------|--|----------------------------|-----------|
| Toluene | 108-88-3 | Toluene | In blood | Prior to last shift of work-week | 0.02 mg/l | ACGIH BEI |
| | | Toluene | Urine | End of shift (As soon as possible after exposure ceases) | 0.03 mg/l | ACGIH BEI |
| | | o-Cresol | Urine | End of shift (As soon as possible after exposure ceases) | 0.3 mg/g Creatinine | ACGIH BEI |

Engineering measures : Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.
 Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

JOINT AND SEAM SEALER, White, 300 mL

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11/17/2022 |
| 1.9 | 05/30/2023 | 10778569-00007 | Date of first issue: 05/30/2017 |

- Eye protection : Wear the following personal protective equipment:
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Color : white
- Odor : aromatic
- Odor Threshold : 1.7 - 40 ppm
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : 111 °C
- Flash point : 4 °C
Method: closed cup
- Evaporation rate : 2.24
- Flammability (solid, gas) : Not applicable
- Flammability (liquids) : Ignitable (see flash point)
- Upper explosion limit / Upper flammability limit : No data available

JOINT AND SEAM SEALER, White, 300 mL

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11/17/2022 |
| 1.9 | 05/30/2023 | 10778569-00007 | Date of first issue: 05/30/2017 |

| | | |
|--|---|--|
| Lower explosion limit / Lower flammability limit | : | No data available |
| Vapor pressure | : | No data available |
| Relative vapor density | : | > 1 |
| Density | : | 1.15 - 1.20 g/cm ³ (20 °C) |
| Solubility(ies) | : | |
| Water solubility | : | practically insoluble |
| Partition coefficient: n-octanol/water | : | Not applicable |
| Autoignition temperature | : | No data available |
| Decomposition temperature | : | No data available |
| Viscosity | : | |
| Viscosity, dynamic | : | > 200,000 mPa.s |
| Viscosity, kinematic | : | > 20.5 mm ² /s (40 °C) |
| Explosive properties | : | Not explosive |
| Oxidizing properties | : | The substance or mixture is not classified as oxidizing. |
| Particle size | : | Not applicable |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|--|
| Reactivity | : | Not classified as a reactivity hazard. |
| Chemical stability | : | Stable under normal conditions. |
| Possibility of hazardous reactions | : | Highly flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents. |
| Conditions to avoid | : | Heat, flames and sparks. |
| Incompatible materials | : | Oxidizing agents |
| Hazardous decomposition products | : | No hazardous decomposition products are known. |

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact

JOINT AND SEAM SEALER, White, 300 mL

Version 1.9 Revision Date: 05/30/2023 SDS Number: 10778569-00007 Date of last issue: 11/17/2022
Date of first issue: 05/30/2017

Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:**Toluene:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Limestone:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

JOINT AND SEAM SEALER, White, 300 mL

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11/17/2022 |
| 1.9 | 05/30/2023 | 10778569-00007 | Date of first issue: 05/30/2017 |

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Silicon, amorphous:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: Based on data from similar materials

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Causes skin irritation.

Components:**Toluene:**

Species : Rabbit
Method : Directive 67/548/EEC, Annex V, B.4.
Result : Skin irritation

Limestone:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

White mineral oil (petroleum):

Species : Rabbit
Result : No skin irritation

Silicon, amorphous:

Species : Rabbit
Method : OECD Test Guideline 404

JOINT AND SEAM SEALER, White, 300 mL

Version 1.9 Revision Date: 05/30/2023 SDS Number: 10778569-00007 Date of last issue: 11/17/2022
Date of first issue: 05/30/2017

Result : No skin irritation
Remarks : Based on data from similar materials

Titanium dioxide:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Toluene:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Limestone:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

White mineral oil (petroleum):

Species : Rabbit
Result : No eye irritation

Silicon, amorphous:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Titanium dioxide:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Toluene:**

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

JOINT AND SEAM SEALER, White, 300 mL

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11/17/2022 |
| 1.9 | 05/30/2023 | 10778569-00007 | Date of first issue: 05/30/2017 |

Method : Directive 67/548/EEC, Annex V, B.6.
 Result : negative

Limestone:

Test Type : Local lymph node assay (LLNA)
 Routes of exposure : Skin contact
 Species : Mouse
 Method : OECD Test Guideline 429
 Result : negative
 Remarks : Based on data from similar materials

White mineral oil (petroleum):

Test Type : Buehler Test
 Routes of exposure : Skin contact
 Species : Guinea pig
 Result : negative

Titanium dioxide:

Test Type : Local lymph node assay (LLNA)
 Routes of exposure : Skin contact
 Species : Mouse
 Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:
Toluene:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
 Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
 Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
 Species: Rat
 Application Route: Intraperitoneal injection
 Result: negative

Test Type: Rodent dominant lethal test (germ cell) (in vivo)
 Species: Mouse
 Application Route: inhalation (vapor)
 Method: OECD Test Guideline 478
 Result: negative

Limestone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative
 Remarks: Based on data from similar materials

JOINT AND SEAM SEALER, White, 300 mL

Version 1.9 Revision Date: 05/30/2023 SDS Number: 10778569-00007 Date of last issue: 11/17/2022
Date of first issue: 05/30/2017

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Silicon, amorphous:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Result: negative

Carcinogenicity

Not classified based on available information.

Components:**Toluene:**

Species : Rat
Application Route : inhalation (vapor)

JOINT AND SEAM SEALER, White, 300 mL

Version Revision Date: SDS Number: Date of last issue: 11/17/2022
1.9 05/30/2023 10778569-00007 Date of first issue: 05/30/2017

Exposure time : 103 weeks
Result : negative

Species : Mouse
Application Route : Skin contact
Exposure time : 24 Months
Result : negative

White mineral oil (petroleum):

Species : Rat
Application Route : Ingestion
Exposure time : 24 Months
Result : negative

Silicon, amorphous:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative
Remarks : Based on data from similar materials

Titanium dioxide:

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Method : OECD Test Guideline 453
Result : positive
Remarks : The mechanism or mode of action may not be relevant in humans.
This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:**Toluene:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: positive

JOINT AND SEAM SEALER, White, 300 mL

Version Revision Date: SDS Number: Date of last issue: 11/17/2022
1.9 05/30/2023 10778569-00007 Date of first issue: 05/30/2017

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

Limestone:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

White mineral oil (petroleum):

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Skin contact
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Silicon, amorphous:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

May cause drowsiness or dizziness.

Components:**Toluene:**

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

JOINT AND SEAM SEALER, White, 300 mL

Version 1.9 Revision Date: 05/30/2023 SDS Number: 10778569-00007 Date of last issue: 11/17/2022
Date of first issue: 05/30/2017

Components:**Toluene:**

Routes of exposure : Inhalation
Target Organs : Central nervous system
Assessment : May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity**Components:****Toluene:**

Species : Rat
LOAEL : 1.875 mg/l
Application Route : inhalation (vapor)
Exposure time : 6 Months

Species : Rat
NOAEL : 625 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Limestone:

Species : Rat
NOAEL : > 300 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 422
Remarks : Based on data from similar materials

White mineral oil (petroleum):

Species : Rat
LOAEL : 160 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
LOAEL : >= 1 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 4 Weeks
Method : OECD Test Guideline 412

Silicon, amorphous:

Species : Rat
NOAEL : 1.3 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Titanium dioxide:

Species : Rat

JOINT AND SEAM SEALER, White, 300 mL

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11/17/2022 |
| 1.9 | 05/30/2023 | 10778569-00007 | Date of first issue: 05/30/2017 |

| | | |
|-------------------|---|-----------------------------|
| NOAEL | : | 24,000 mg/kg |
| Application Route | : | Ingestion |
| Exposure time | : | 28 Days |
| Species | : | Rat |
| NOAEL | : | 10 mg/m ³ |
| Application Route | : | inhalation (dust/mist/fume) |
| Exposure time | : | 2 y |

Aspiration toxicity

Not classified based on available information.

Components:
Toluene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure
Components:
Toluene:

| | | |
|------------|---|---|
| Inhalation | : | Target Organs: Central nervous system Symptoms: Neurological disorders |
|------------|---|---|

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Components:
Toluene:

| | | |
|--|---|---|
| Toxicity to fish | : | LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l Exposure time: 48 h |
| Toxicity to algae/aquatic plants | : | NOEC (Skeletonema costatum (marine diatom)): 10 mg/l Exposure time: 72 h |
| Toxicity to fish (Chronic toxicity) | : | NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l Exposure time: 40 d |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOEC (Ceriodaphnia dubia (water flea)): 0.74 mg/l Exposure time: 7 d |
| Toxicity to microorganisms | : | EC50 (Nitrosomonas sp.): 84 mg/l Exposure time: 24 h |

Limestone:

JOINT AND SEAM SEALER, White, 300 mL

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11/17/2022 |
| 1.9 | 05/30/2023 | 10778569-00007 | Date of first issue: 05/30/2017 |

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
 Exposure time: 96 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 203
 Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : LL50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 202
 Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 14 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201
 Remarks: No toxicity at the limit of solubility.
 Based on data from similar materials
- EL10 (Desmodesmus subspicatus (green algae)): > 14 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201
 Remarks: No toxicity at the limit of solubility.
 Based on data from similar materials
- Toxicity to microorganisms : EC50: > 100 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209
 Remarks: Based on data from similar materials

White mineral oil (petroleum):

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l
 Exposure time: 28 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1,000 mg/l
 Exposure time: 21 d

Silicon, amorphous:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 10,000 mg/l

JOINT AND SEAM SEALER, White, 300 mL

Version 1.9 Revision Date: 05/30/2023 SDS Number: 10778569-00007 Date of last issue: 11/17/2022
Date of first issue: 05/30/2017

Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): 10,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Titanium dioxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Persistence and degradability**Components:****Toluene:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 20 d

White mineral oil (petroleum):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d

JOINT AND SEAM SEALER, White, 300 mL

Version 1.9 Revision Date: 05/30/2023 SDS Number: 10778569-00007 Date of last issue: 11/17/2022
Date of first issue: 05/30/2017

Bioaccumulative potential**Components:****Toluene:**

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 90

Partition coefficient: n-octanol/water : log Pow: 2.73

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 1133
Proper shipping name : ADHESIVES
Class : 3
Packing group : II
Labels : 3

IATA-DGR

UN/ID No. : UN 1133
Proper shipping name : Adhesives
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

JOINT AND SEAM SEALER, White, 300 mL

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11/17/2022 |
| 1.9 | 05/30/2023 | 10778569-00007 | Date of first issue: 05/30/2017 |

IMDG-Code

UN number : UN 1133
Proper shipping name : ADHESIVES

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

UN number : UN 1133
Proper shipping name : ADHESIVES

Class : 3
Packing group : II
Labels : 3
ERG Code : 128
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content : CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 35 % / 400 g/l

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-

JOINT AND SEAM SEALER, White, 300 mL

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11/17/2022 |
| 1.9 | 05/30/2023 | 10778569-00007 | Date of first issue: 05/30/2017 |

| | | |
|-------------------|--------------------|---------------------------------------|
| | borne contaminants | |
| ACGIH / TWA | : | 8-hour, time-weighted average |
| CA AB OEL / TWA | : | 8-hour Occupational exposure limit |
| CA AB OEL / STEL | : | 15-minute occupational exposure limit |
| CA BC OEL / TWA | : | 8-hour time weighted average |
| CA BC OEL / STEL | : | short-term exposure limit |
| CA QC OEL / TWAEV | : | Time-weighted average exposure value |
| CA QC OEL / STEV | : | Short-term exposure value |

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/30/2023
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS mate-

JOINT AND SEAM SEALER, White, 300 mL

| | | | |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11/17/2022 |
| 1.9 | 05/30/2023 | 10778569-00007 | Date of first issue: 05/30/2017 |

Material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8