

SAFETY DATA SHEET

according to the Hazardous Products Regulations



LOW TEMPERATURE SYNTHETIC GREASE, 397 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2022
1.5	06/18/2024	11017217-00006	Date of first issue: 10/26/2018

SECTION 1. IDENTIFICATION

Product name : LOW TEMPERATURE SYNTHETIC GREASE, 397 g

Product code : 890.602

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Other hazards

None known.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



LOW TEMPERATURE SYNTHETIC GREASE, 397 g

Version 1.5 Revision Date: 06/18/2024 SDS Number: 11017217-00006 Date of last issue: 11/12/2022
Date of first issue: 10/26/2018

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
White mineral oil (petroleum)	Paraffinum liquidum	8042-47-5	$\geq 10 - < 30$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : None known.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Fluorine compounds

SAFETY DATA SHEET

according to the Hazardous Products Regulations



LOW TEMPERATURE SYNTHETIC GREASE, 397 g

Version 1.5	Revision Date: 06/18/2024	SDS Number: 11017217-00006	Date of last issue: 11/12/2022 Date of first issue: 10/26/2018
----------------	------------------------------	-------------------------------	---

- | | |
|--|---|
| Specific extinguishing methods | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area. |
| Special protective equipment for fire-fighters | : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8). |
| Environmental precautions | : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. |

SECTION 7. HANDLING AND STORAGE

- | | |
|-----------------------------|---|
| Technical measures | : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : Use only with adequate ventilation. |
| Advice on safe handling | : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment. |
| Conditions for safe storage | : Keep in properly labeled containers.
Store in accordance with the particular national regulations. |
| Materials to avoid | : Do not store with the following product types: |

SAFETY DATA SHEET

according to the Hazardous Products Regulations



LOW TEMPERATURE SYNTHETIC GREASE, 397 g

Version 1.5 Revision Date: 06/18/2024 SDS Number: 11017217-00006 Date of last issue: 11/12/2022
Date of first issue: 10/26/2018

Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection
Material : Latex gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:
Safety glasses
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Skin and body protection : Skin should be washed after contact.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



LOW TEMPERATURE SYNTHETIC GREASE, 397 g

Version 1.5	Revision Date: 06/18/2024	SDS Number: 11017217-00006	Date of last issue: 11/12/2022 Date of first issue: 10/26/2018
----------------	------------------------------	-------------------------------	---

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Pasty solid
Color	: translucent, white
Odor	: mild
Odor Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: 220 °C Method: ASTM D 92, open cup
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	: Not applicable
Lower explosion limit / Lower flammability limit	: Not applicable
Vapor pressure	: Not applicable
Relative vapor density	: Not applicable
Density	: 0.89 g/cm ³ (20 °C)
Solubility(ies) Water solubility	: insoluble
Partition coefficient: n-	: Not applicable

SAFETY DATA SHEET

according to the Hazardous Products Regulations



LOW TEMPERATURE SYNTHETIC GREASE, 397 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2022
1.5	06/18/2024	11017217-00006	Date of first issue: 10/26/2018

octanol/water

Autoignition temperature : Not applicable

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : 800.000 mm²/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics
Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact

Ingestion

Eye contact

Acute toxicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

SAFETY DATA SHEET

according to the Hazardous Products Regulations



LOW TEMPERATURE SYNTHETIC GREASE, 397 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2022
1.5	06/18/2024	11017217-00006	Date of first issue: 10/26/2018

Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

White mineral oil (petroleum):

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

White mineral oil (petroleum):

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

White mineral oil (petroleum):

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

SAFETY DATA SHEET

according to the Hazardous Products Regulations



LOW TEMPERATURE SYNTHETIC GREASE, 397 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2022
1.5	06/18/2024	11017217-00006	Date of first issue: 10/26/2018

Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	24 Months
Result	:	negative

Reproductive toxicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Effects on fertility	:	Test Type: One-generation reproduction toxicity study
		Species: Rat
		Application Route: Skin contact
		Result: negative

Effects on fetal development	:	Test Type: Embryo-fetal development
		Species: Rat
		Application Route: Ingestion
		Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

White mineral oil (petroleum):

Species	:	Rat
LOAEL	:	160 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days

Species	:	Rat
LOAEL	:	>= 1 mg/l
Application Route	:	inhalation (dust/mist/fume)

SAFETY DATA SHEET

according to the Hazardous Products Regulations



LOW TEMPERATURE SYNTHETIC GREASE, 397 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2022
1.5	06/18/2024	11017217-00006	Date of first issue: 10/26/2018

Exposure time : 4 Weeks
Method : OECD Test Guideline 412

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

White mineral oil (petroleum):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : NOEC (Pseudokirchneriella subcapitata (green algae)): 100
plants mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox- : NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l
icity) Exposure time: 28 d

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 1,000 mg/l
aquatic invertebrates (Chron- Exposure time: 21 d
ic toxicity)

Persistence and degradability

Components:

White mineral oil (petroleum):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



LOW TEMPERATURE SYNTHETIC GREASE, 397 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2022
1.5	06/18/2024	11017217-00006	Date of first issue: 10/26/2018

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content

CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 -
Guidelines for VOC in Consumer Products
VOC content: < 1 %

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

SAFETY DATA SHEET

according to the Hazardous Products Regulations



LOW TEMPERATURE SYNTHETIC GREASE, 397 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2022
1.5	06/18/2024	11017217-00006	Date of first issue: 10/26/2018

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWAEV	:	Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
--	---	---

Revision Date	:	06/18/2024
Date format	:	mm/dd/yyyy

SAFETY DATA SHEET

according to the Hazardous Products Regulations



LOW TEMPERATURE SYNTHETIC GREASE, 397 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2022
1.5	06/18/2024	11017217-00006	Date of first issue: 10/26/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8