

PREMIUM GLASS CLEANER, 517 g

Version 1.3 Revision Date: 11/17/2022 SDS Number: 6284730-00004 Date of last issue: 06/09/2022
Date of first issue: 08/24/2020

SECTION 1. IDENTIFICATION

Product name : PREMIUM GLASS CLEANER, 517 g
Product code : 890.9026
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Cleaning agent
Detergent

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Eye irritation : Category 2A

GHS label elements

PREMIUM GLASS CLEANER, 517 g

Version 1.3 Revision Date: 11/17/2022 SDS Number: 6284730-00004 Date of last issue: 06/09/2022
 Date of first issue: 08/24/2020

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H319 Causes serious eye irritation.

Precautionary Statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P264 Wash skin thoroughly after handling.
 P280 Wear eye protection and face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313 If eye irritation persists: Get medical attention.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Propan-2-ol	Isopropyl alcohol	67-63-0	>= 5 - < 10 *
Isobutane	Propane, 2-methyl-	75-28-5	>= 5 - < 10 *
Propylene glycol n-propyl ether	1-propoxypropan-2-ol	1569-01-3	>= 1 - < 5 *
(2-Methoxymethylethoxy)propanol	PPG-2 Methyl ether	34590-94-8	>= 1 - < 5 *
3-Butoxypropan-2-ol	2-Propanol, 1-butoxy-	5131-66-8	>= 1 - < 5 *

* Actual concentration or concentration range is withheld as a trade secret

PREMIUM GLASS CLEANER, 517 g

Version Revision Date: SDS Number: Date of last issue: 06/09/2022
1.3 11/17/2022 6284730-00004 Date of first issue: 08/24/2020

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion prod- : Carbon oxides
-

PREMIUM GLASS CLEANER, 517 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.3	11/17/2022	6284730-00004	Date of first issue: 08/24/2020

ucts

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : For outdoor use only

PREMIUM GLASS CLEANER, 517 g

Version 1.3 Revision Date: 11/17/2022 SDS Number: 6284730-00004 Date of last issue: 06/09/2022
 Date of first issue: 08/24/2020

Do not get on skin or clothing.
 Avoid inhalation of vapor or mist.
 Do not swallow.
 Do not get in eyes.
 Wash skin thoroughly after handling.
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Take precautionary measures against static discharges.
 Take care to prevent spills, waste and minimize release to the environment.
 Do not spray on an open flame or other ignition source.

Conditions for safe storage : Keep in a cool, well-ventilated place.
 Store in accordance with the particular national regulations.
 Do not pierce or burn, even after use.
 Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:
 Self-reactive substances and mixtures
 Organic peroxides
 Oxidizing agents
 Flammable solids
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures which in contact with water emit flammable gases
 Explosives
 Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propan-2-ol	67-63-0	STEL	400 ppm 984 mg/m ³	CA AB OEL
		TWA	200 ppm 492 mg/m ³	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	200 ppm	CA QC OEL
		STEV	400 ppm	CA QC OEL
		TWA	200 ppm	ACGIH
Isobutane	75-28-5	STEL	400 ppm	ACGIH
		TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
(2-	34590-94-8	STEL	1,000 ppm	ACGIH
		TWA	100 ppm	CA AB OEL

PREMIUM GLASS CLEANER, 517 g

Version 1.3 Revision Date: 11/17/2022 SDS Number: 6284730-00004 Date of last issue: 06/09/2022
 Date of first issue: 08/24/2020

Methoxymethyl- lethoxy)propanol			606 mg/m ³	
		STEL	150 ppm 909 mg/m ³	CA AB OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWAEV	100 ppm 606 mg/m ³	CA QC OEL
		STEV	150 ppm 909 mg/m ³	CA QC OEL
		TWA	50 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra- tion	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work- week	40 mg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Neoprene
 Break through time : 40 - 180 min
 Glove thickness : 0.22 mm

Material : Nitrile rubber
 Break through time : 40 - 180 min
 Glove thickness : 0.22 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
 Safety goggles

PREMIUM GLASS CLEANER, 517 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.3	11/17/2022	6284730-00004	Date of first issue: 08/24/2020

- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a liquefied gas
- Propellant : Isobutane
- Color : clear, colorless
- Odor : ammoniacal
- Odor Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : -40 - 340 °C
- Flash point : Not applicable
- Evaporation rate : Not applicable
- Flammability (solid, gas) : Extremely flammable aerosol.
- Upper explosion limit / Upper flammability limit : 8.4 %(V)
- Lower explosion limit / Lower flammability limit : 1.8 %(V)
- Vapor pressure : 1,723.70 - 2,413.18 hPa (21 °C)

PREMIUM GLASS CLEANER, 517 g

Version 1.3 Revision Date: 11/17/2022 SDS Number: 6284730-00004 Date of last issue: 06/09/2022
Date of first issue: 08/24/2020

Relative vapor density : > 1

Density : 0.98 g/cm³

Solubility(ies)
Water solubility : completely soluble

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.
Vapors may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

PREMIUM GLASS CLEANER, 517 g

Version 1.3 Revision Date: 11/17/2022 SDS Number: 6284730-00004 Date of last issue: 06/09/2022
Date of first issue: 08/24/2020

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:**Propan-2-ol:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l
Exposure time: 6 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Isobutane:

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm
Exposure time: 4 h
Test atmosphere: gas

Propylene glycol n-propyl ether:

Acute oral toxicity : LD50 (Rat, female): 2,490 mg/kg

Acute inhalation toxicity : LC50 (Rat, male): > 8.43 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit, male): 3,775 mg/kg

(2-Methoxymethylethoxy)propanol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC0 (Rat): > 1.667 mg/l
Exposure time: 7 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): 9,510 mg/kg

3-Butoxypropan-2-ol:

Acute oral toxicity : LD50 (Rat): 3,300 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 3.52 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity

PREMIUM GLASS CLEANER, 517 g

Version 1.3 Revision Date: 11/17/2022 SDS Number: 6284730-00004 Date of last issue: 06/09/2022
Date of first issue: 08/24/2020

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:**Propan-2-ol:**

Species : Rabbit
Result : No skin irritation

Propylene glycol n-propyl ether:

Species : Rabbit
Result : No skin irritation

(2-Methoxymethylethoxy)propanol:

Species : Rabbit
Result : No skin irritation

3-Butoxypropan-2-ol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Propan-2-ol:**

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Propylene glycol n-propyl ether:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

(2-Methoxymethylethoxy)propanol:

Species : Rabbit
Result : No eye irritation

3-Butoxypropan-2-ol:

Species : Rabbit
Result : Irritation to eyes, reversing within 7 days
Method : OECD Test Guideline 405

PREMIUM GLASS CLEANER, 517 g

Version 1.3 Revision Date: 11/17/2022 SDS Number: 6284730-00004 Date of last issue: 06/09/2022
Date of first issue: 08/24/2020

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Propan-2-ol:**

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Propylene glycol n-propyl ether:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

(2-Methoxymethylethoxy)propanol:

Test Type : Human repeat insult patch test (HRIPT)
Routes of exposure : Skin contact
Species : Humans
Result : negative

3-Butoxypropan-2-ol:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Propan-2-ol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection

PREMIUM GLASS CLEANER, 517 g

Version 1.3 Revision Date: 11/17/2022 SDS Number: 6284730-00004 Date of last issue: 06/09/2022
Date of first issue: 08/24/2020

Result: negative

Isobutane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Propylene glycol n-propyl ether:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

(2-Methoxymethylethoxy)propanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: Saacharomyces cerevisiae, mitotic recombination
assay (in vitro)
Result: negative

3-Butoxypropan-2-ol:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

PREMIUM GLASS CLEANER, 517 g

Version 1.3 Revision Date: 11/17/2022 SDS Number: 6284730-00004 Date of last issue: 06/09/2022
Date of first issue: 08/24/2020

Carcinogenicity

Not classified based on available information.

Components:**Propan-2-ol:**

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 104 weeks
Method : OECD Test Guideline 451
Result : negative

(2-Methoxymethylethoxy)propanol:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 2 Years
Method : OECD Test Guideline 453
Result : negative
Remarks : Based on data from similar materials

3-Butoxypropan-2-ol:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 2 Years
Method : OECD Test Guideline 453
Result : negative
Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:**Propan-2-ol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Isobutane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the
reproduction/developmental toxicity screening test
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

PREMIUM GLASS CLEANER, 517 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.3	11/17/2022	6284730-00004	Date of first issue: 08/24/2020

reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Propylene glycol n-propyl ether:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: inhalation (vapor)
Result: negative

(2-Methoxymethylethoxy)propanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

3-Butoxypropan-2-ol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative

STOT-single exposure

Not classified based on available information.

PREMIUM GLASS CLEANER, 517 g

Version 1.3 Revision Date: 11/17/2022 SDS Number: 6284730-00004 Date of last issue: 06/09/2022
Date of first issue: 08/24/2020

Components:**Propan-2-ol:**

Assessment : May cause drowsiness or dizziness.

Isobutane:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity**Components:****Propan-2-ol:**

Species : Rat
NOAEL : 12.5 mg/l
Application Route : inhalation (vapor)
Exposure time : 104 Weeks

Isobutane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Propylene glycol n-propyl ether:

Species : Rat
NOAEL : 1.474 mg/l
Application Route : inhalation (vapor)
Exposure time : 90 Days

(2-Methoxymethylethoxy)propanol:

Species : Rat
NOAEL : 1.21 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks

Species : Rat
NOAEL : 1,000 mg/kg
Application Route : Ingestion
Exposure time : 4 Weeks

Species : Rabbit
NOAEL : 2,850 mg/kg
Application Route : Skin contact
Exposure time : 90 Days

PREMIUM GLASS CLEANER, 517 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.3	11/17/2022	6284730-00004	Date of first issue: 08/24/2020

3-Butoxypropan-2-ol:

Species	:	Rat
NOAEL	:	350 mg/kg
LOAEL	:	1,000 mg/kg
Application Route	:	Ingestion
Exposure time	:	13 Weeks
Method	:	OECD Test Guideline 408

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Propan-2-ol:**

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h
Toxicity to microorganisms	:	EC50 (Pseudomonas putida): > 1,050 mg/l Exposure time: 16 h

Propylene glycol n-propyl ether:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 3,440 mg/l Exposure time: 72 h
		NOEC (Pseudokirchneriella subcapitata (green algae)): 500 mg/l Exposure time: 72 h

(2-Methoxymethylethoxy)propanol:

Toxicity to fish	:	LC50 (Poecilia reticulata (guppy)): > 1,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,919 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): > 969 mg/l

PREMIUM GLASS CLEANER, 517 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.3	11/17/2022	6284730-00004	Date of first issue: 08/24/2020

Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 969 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): \geq 0.5 mg/l
Exposure time: 22 d

Toxicity to microorganisms : EC50 (Pseudomonas putida): 4,168 mg/l
Exposure time: 18 h

3-Butoxypropan-2-ol:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 560 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 96 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 560 mg/l
Exposure time: 96 h

Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Persistence and degradability
Components:
Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1.19 (BOD5)COD: 2.23BOD/COD: 53 %

Isobutane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Propylene glycol n-propyl ether:

PREMIUM GLASS CLEANER, 517 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.3	11/17/2022	6284730-00004	Date of first issue: 08/24/2020

Biodegradability : Result: Readily biodegradable.
Biodegradation: 91.5 %
Exposure time: 28 d
Method: OECD Test Guideline 301A

(2-Methoxymethylethoxy)propanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 76 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

3-Butoxypropan-2-ol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301E

Bioaccumulative potential**Components:****Propan-2-ol:**

Partition coefficient: n-octanol/water : log Pow: 0.05

Isobutane:

Partition coefficient: n-octanol/water : log Pow: 2.8

Propylene glycol n-propyl ether:

Partition coefficient: n-octanol/water : log Pow: 0.621
Remarks: Calculation

(2-Methoxymethylethoxy)propanol:

Partition coefficient: n-octanol/water : log Pow: 0.004

3-Butoxypropan-2-ol:

Partition coefficient: n-octanol/water : log Pow: 1.2

Mobility in soil

No data available

Other adverse effects

No data available

PREMIUM GLASS CLEANER, 517 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.3	11/17/2022	6284730-00004	Date of first issue: 08/24/2020

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)
-

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

- UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

IATA-DGR

- UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

- UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

- UN number : UN 1950
Proper shipping name : AEROSOLS

PREMIUM GLASS CLEANER, 517 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.3	11/17/2022	6284730-00004	Date of first issue: 08/24/2020

Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
ERG Code	:	126
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content	CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products VOC content: 20 % / 235.9 g/l
-------------------------------------------------	------------------------------------------------------------------------------------------------------------------------

The ingredients of this product are reported in the following inventories:

DSL	:	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
-----	---	--------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA

PREMIUM GLASS CLEANER, 517 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/09/2022
1.3	11/17/2022	6284730-00004	Date of first issue: 08/24/2020

- International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/17/2022
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8