

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06/03/2024	11397719-00001	Date of first issue: 06/03/2024

SECTION 1. IDENTIFICATION

Product name : SUPER SPRAY ADHESIVE, 320 g
Product code : 890.910055
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 2
Skin irritation : Category 2
Eye irritation : Category 2A
Specific target organ toxicity : Category 3
- single exposure

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version 1.0 Revision Date: 06/03/2024 SDS Number: 11397719-00001 Date of last issue: -
Date of first issue: 06/03/2024

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H223 Flammable aerosol.
H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary Statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, eye protection and face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical attention.

P337 + P313 If eye irritation persists: Get medical attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version 1.0 Revision Date: 06/03/2024 SDS Number: 11397719-00001 Date of last issue: -
Date of first issue: 06/03/2024

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Liquified petroleum gas (LPG)	Petroleum gases, liquefied	68476-85-7	$\geq 30 - < 60$ *
Acetone	2-Propanone	67-64-1	$\geq 10 - < 30$ *
Heptane	n-Heptane	142-82-5	$\geq 5 - < 10$ *
Heptane, branched, cyclic and linear	No data available	426260-76-6	$\geq 5 - < 10$ *
Methyl acetate	Acetic acid, methyl ester	79-20-9	$\geq 5 - < 10$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control center immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and : May be fatal if swallowed and enters airways.
Causes skin irritation.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06/03/2024	11397719-00001	Date of first issue: 06/03/2024

delayed : Causes serious eye irritation.
May cause drowsiness or dizziness.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06/03/2024	11397719-00001	Date of first issue: 06/03/2024

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : For outdoor use only
Do not get on skin or clothing.
Avoid breathing spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version 1.0 Revision Date: 06/03/2024 SDS Number: 11397719-00001 Date of last issue: -
Date of first issue: 06/03/2024

Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases

Recommended storage temperature : < 40 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Liquified petroleum gas (LPG)	68476-85-7	TWA	1,000 ppm	CA AB OEL
		STEL	1,500 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m ³	CA AB OEL
		STEL	750 ppm 1,800 mg/m ³	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	250 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Heptane	142-82-5	TWA	400 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWA	400 ppm 1,640 mg/m ³	CA AB OEL
		STEL	500 ppm 2,050 mg/m ³	CA AB OEL
		TWAEV	400 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Heptane, branched, cyclic and linear	426260-76-6	TWA	400 ppm 1,640 mg/m ³	CA AB OEL
		STEL	500 ppm 2,050 mg/m ³	CA AB OEL
		TWAEV	400 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	400 ppm	ACGIH

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version 1.0 Revision Date: 06/03/2024 SDS Number: 11397719-00001 Date of last issue: -
Date of first issue: 06/03/2024

		STEL	500 ppm	ACGIH
Methyl acetate	79-20-9	STEL	250 ppm 757 mg/m ³	CA AB OEL
		TWA	200 ppm 606 mg/m ³	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	250 ppm	CA BC OEL
		TWAEV	200 ppm 606 mg/m ³	CA QC OEL
		STEV	250 ppm 757 mg/m ³	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Rubber gloves

Material : Latex gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06/03/2024	11397719-00001	Date of first issue: 06/03/2024

- Eye protection : Wear the following personal protective equipment:
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a liquefied gas
- Propellant : Liquefied petroleum gas (LPG)
- Color : clear
- Odor : hydrocarbon-like
- Odor Threshold : No data available
- pH : Solvent mixture; pH value determination not possible, no aqueous solution
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : Not applicable
- Flash point : -82.8 °C
Method: closed cup
Propellant
- Evaporation rate : > 10
(Butyl Acetate=1.0)

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06/03/2024	11397719-00001	Date of first issue: 06/03/2024

Flammability (solid, gas)	:	Flammable aerosol.
Upper explosion limit / Upper flammability limit	:	8.8 %(V) Propellant
Lower explosion limit / Lower flammability limit	:	1.8 %(V) Propellant
Vapor pressure	:	<= 245.31 hPa
Relative vapor density	:	Not applicable
Relative density	:	No data available
Density	:	0.830 - 0.850 g/cm ³ (as liquid)
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	460 °C Propellant
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06/03/2024	11397719-00001	Date of first issue: 06/03/2024

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Liquified petroleum gas (LPG):

Acute inhalation toxicity : LC50 (Mouse): 520400 ppm
Exposure time: 2 h
Test atmosphere: gas
Remarks: Based on data from similar materials

Acetone:

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

Heptane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 73.5 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Heptane, branched, cyclic and linear:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06/03/2024	11397719-00001	Date of first issue: 06/03/2024

Acute inhalation toxicity : LC50 (Rat): > 10 - 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Methyl acetate:

Acute oral toxicity : LD50 (Rat): 6,482 mg/kg

Acute inhalation toxicity : LC50 (Rabbit): > 49.2 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Causes skin irritation.

Components:

Acetone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Heptane:

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Heptane, branched, cyclic and linear:

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Methyl acetate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version 1.0 Revision Date: 06/03/2024 SDS Number: 11397719-00001 Date of last issue: -
Date of first issue: 06/03/2024

Components:

Acetone:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

Heptane:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Heptane, branched, cyclic and linear:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Methyl acetate:

Species : Rabbit
Result : Irritation to eyes, reversing within 7 days
Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Acetone:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Heptane:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Heptane, branched, cyclic and linear:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version 1.0 Revision Date: 06/03/2024 SDS Number: 11397719-00001 Date of last issue: -
Date of first issue: 06/03/2024

Germ cell mutagenicity

Not classified based on available information.

Components:

Liquified petroleum gas (LPG):

- Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Acetone:

- Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
- Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
- Test Type: Chromosome aberration test in vitro
Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Heptane:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
- Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials
- Test Type: Chromosome aberration test in vitro
Result: negative
- Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: inhalation (vapor)
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06/03/2024	11397719-00001	Date of first issue: 06/03/2024

Remarks: Based on data from similar materials

Heptane, branched, cyclic and linear:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Methyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Liquified petroleum gas (LPG):

Species : Mouse
Application Route : inhalation (gas)
Exposure time : 103 weeks
Result : negative
Remarks : Based on data from similar materials

Acetone:

Species : Mouse
Application Route : Skin contact
Exposure time : 424 days
Result : negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version 1.0 Revision Date: 06/03/2024 SDS Number: 11397719-00001 Date of last issue: -
Date of first issue: 06/03/2024

Heptane:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

Methyl acetate:

Species : Rat
Application Route : Inhalation
Exposure time : 18 Months
Result : negative
Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Heptane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Heptane, branched, cyclic and linear:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06/03/2024	11397719-00001	Date of first issue: 06/03/2024

Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

May cause drowsiness or dizziness.

Components:

Liquified petroleum gas (LPG):

Assessment : May cause drowsiness or dizziness.

Acetone:

Assessment : May cause drowsiness or dizziness.

Heptane:

Assessment : May cause drowsiness or dizziness.

Heptane, branched, cyclic and linear:

Assessment : May cause drowsiness or dizziness.

Methyl acetate:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Liquified petroleum gas (LPG):

Species : Rat
NOAEL : 10000 ppm
Application Route : inhalation (gas)
Exposure time : 13 Weeks

Acetone:

Species : Rat
NOAEL : 900 mg/kg
LOAEL : 1,700 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
NOAEL : 45 mg/l
Application Route : inhalation (vapor)
Exposure time : 8 Weeks

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06/03/2024	11397719-00001	Date of first issue: 06/03/2024

Heptane:

Species	:	Rat
NOAEL	:	12.35 mg/l
Application Route	:	inhalation (vapor)
Exposure time	:	90 Days

Heptane, branched, cyclic and linear:

Species	:	Rat
NOAEL	:	12.35 mg/l
Application Route	:	inhalation (vapor)
Exposure time	:	90 Days
Remarks	:	Based on data from similar materials

Methyl acetate:

Species	:	Rat
NOAEL	:	1.057 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	28 Days
Method	:	OECD Test Guideline 412

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Heptane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Heptane, branched, cyclic and linear:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Acetone:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l
------------------	---	--

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version 1.0 Revision Date: 06/03/2024 SDS Number: 11397719-00001 Date of last issue: -
Date of first issue: 06/03/2024

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 8,800 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): \geq 79 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: 61,150 mg/l
Exposure time: 30 min
Method: ISO 8192

Heptane:

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 4,924 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 0.2 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50: $> 0.1 - 1$ mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): $> 0.1 - 1$ mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Heptane, branched, cyclic and linear:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): $> 0.1 - 1$ mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): $> 1 - 10$ mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): $> 10 - 100$ mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06/03/2024	11397719-00001	Date of first issue: 06/03/2024

NOELR (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 0.1 - 1 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Methyl acetate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 250 - 350 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,026.7 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 120 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Desmodesmus subspicatus (green algae)): > 120 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (Pseudomonas putida): 1,830 mg/l
Exposure time: 16 h

Persistence and degradability

Components:

Liquified petroleum gas (LPG):

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 %

Acetone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 28 d

Heptane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 %
Exposure time: 10 d

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06/03/2024	11397719-00001	Date of first issue: 06/03/2024

Heptane, branched, cyclic and linear:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Methyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Bioaccumulative potential

Components:

Liquified petroleum gas (LPG):

Partition coefficient: n-octanol/water : log Pow: 1.09

Acetone:

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

Heptane:

Partition coefficient: n-octanol/water : log Pow: 4.5

Heptane, branched, cyclic and linear:

Partition coefficient: n-octanol/water : log Pow: ≥ 4
Remarks: Based on data from similar materials

Methyl acetate:

Partition coefficient: n-octanol/water : log Pow: 0.18

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06/03/2024	11397719-00001	Date of first issue: 06/03/2024

Contaminated packaging : Please ensure aerosol cans are sprayed completely empty (including propellant)
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS
(Heptane, Heptane, branched, cyclic and linear)
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06/03/2024	11397719-00001	Date of first issue: 06/03/2024

Labels : 2.1
ERG Code : 126
Marine pollutant : yes(Heptane, Heptane, branched, cyclic and linear)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content : Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations
VOC content: < 55 %

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit
CA QC OEL / TWAEV : Time-weighted average exposure value
CA QC OEL / STEV : Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory con-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



SUPER SPRAY ADHESIVE, 320 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06/03/2024	11397719-00001	Date of first issue: 06/03/2024

centration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/03/2024
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8