

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version 2.1	Revision Date: 09/16/2021	SDS Number: 309425-00004	Date of last issue: 11/16/2020 Date of first issue: 09/14/2016
----------------	------------------------------	-----------------------------	---

SECTION 1. IDENTIFICATION

Product name : RTV SILICONE GASKET, High temperature, Red, 226 g
Product code : 890.9102
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Sealant

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Gases under pressure : Liquefied gas
Skin corrosion : Category 1C
Serious eye damage : Category 1
Simple Asphyxiant : Category 1

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version 2.1 Revision Date: 09/16/2021 SDS Number: 309425-00004 Date of last issue: 11/16/2020
Date of first issue: 09/14/2016

GHS label elements

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H280 Contains gas under pressure; may explode if heated.
H314 Causes severe skin burns and eye damage.
May displace oxygen and cause rapid suffocation.

Precautionary Statements

:

Prevention:

P260 Do not breathe spray.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P301 + P330 + P331 + P310 IF SWALLOWED: Rinse mouth.

Do NOT induce vomiting. Immediately call a POISON CENTER.

P303 + P361 + P353 + P310 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Corrosive to the respiratory tract.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version 2.1 Revision Date: 09/16/2021 SDS Number: 309425-00004 Date of last issue: 11/16/2020
Date of first issue: 09/14/2016

Distillates (petroleum), hydrotreated middle	No data available	64742-46-7	$\geq 5 - < 10$ *
1,1-Difluoroethane	Hydrofluorocarbon 152A	75-37-6	$\geq 1 - < 5$ *
Triacetoxyethylsilane	Silanetriol, 1-ethyl-, 1,1,1-triacetate	17689-77-9	$\geq 1 - < 5$ *
Methylsilanetriyl triacetate	Silanetriol, 1-methyl-, 1,1,1-triacetate	4253-34-3	$\geq 1 - < 5$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention immediately.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control center immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Causes serious eye damage.
Causes severe burns.
Gas reduces oxygen available for breathing.
Causes digestive tract burns.
Corrosive to respiratory system.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version 2.1	Revision Date: 09/16/2021	SDS Number: 309425-00004	Date of last issue: 11/16/2020 Date of first issue: 09/14/2016
----------------	------------------------------	-----------------------------	---

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
Silicon oxides
Fluorine compounds
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
-

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version 2.1	Revision Date: 09/16/2021	SDS Number: 309425-00004	Date of last issue: 11/16/2020 Date of first issue: 09/14/2016
----------------	------------------------------	-----------------------------	---

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Keep away from water.
Protect from moisture.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version 2.1 Revision Date: 09/16/2021 SDS Number: 309425-00004 Date of last issue: 11/16/2020
Date of first issue: 09/14/2016

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetic acid	64-19-7	TWA	10 ppm 25 mg/m ³	CA AB OEL
		STEL	15 ppm 37 mg/m ³	CA AB OEL
		TWA	10 ppm	CA BC OEL
		STEL	15 ppm	CA BC OEL
		TWAEV	10 ppm 25 mg/m ³	CA QC OEL
		STEV	15 ppm 37 mg/m ³	CA QC OEL
		TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
Respirator with combination filter for vapor/particulate (EN 141)

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version 2.1	Revision Date: 09/16/2021	SDS Number: 309425-00004	Date of last issue: 11/16/2020 Date of first issue: 09/14/2016
----------------	------------------------------	-----------------------------	---

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shieldSkin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Propellant : 1,1-Difluoroethane

Color : red

Odor : vinegar-like

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version 2.1	Revision Date: 09/16/2021	SDS Number: 309425-00004	Date of last issue: 11/16/2020 Date of first issue: 09/14/2016
----------------	------------------------------	-----------------------------	---

Flash point	:	> 100 °C
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	1.18
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents. Hazardous decomposition products will be formed upon contact with water or humid air.
Conditions to avoid	:	Exposure to moisture.

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/16/2020
2.1	09/16/2021	309425-00004	Date of first issue: 09/14/2016

Incompatible materials : Oxidizing agents
Water

Hazardous decomposition products

Contact with water or humid air : Acetic acid

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:**Distillates (petroleum), hydrotreated middle:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,000 mg/m³
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

1,1-Difluoroethane:

Acute inhalation toxicity : LC50 (Rat): > 437500 ppm
Exposure time: 4 h
Test atmosphere: gas

Triacetoxymethylsilane:

Acute oral toxicity : LD50 (Rat): 1,460 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Methylsilanetriyl triacetate:

Acute oral toxicity : LD50 (Rat): 1,600 mg/kg
Method: OECD Test Guideline 401

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/16/2020
2.1	09/16/2021	309425-00004	Date of first issue: 09/14/2016

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Skin corrosion/irritation

Causes severe burns.

Components:**Distillates (petroleum), hydrotreated middle:**

Assessment : Repeated exposure may cause skin dryness or cracking.

Triacetoxymethylsilane:

Species : Rabbit
Result : Corrosive after 3 minutes to 1 hour of exposure

Methylsilanetriyl triacetate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 1 to 4 hours of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Components:**Distillates (petroleum), hydrotreated middle:**

Result : No eye irritation

Triacetoxymethylsilane:

Result : Irreversible effects on the eye

Methylsilanetriyl triacetate:

Species : Rabbit
Result : Irreversible effects on the eye

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated middle:**

Test Type : Human repeat insult patch test (HRIPT)
Routes of exposure : Skin contact
Result : negative

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version 2.1 Revision Date: 09/16/2021 SDS Number: 309425-00004 Date of last issue: 11/16/2020
Date of first issue: 09/14/2016

Triacetoxymethylsilane:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Assessment : Does not cause skin sensitization.

Methylsilanetriyl triacetate:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated middle:**

Genotoxicity in vitro : Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative

1,1-Difluoroethane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Triacetoxymethylsilane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Methylsilanetriyl triacetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version 2.1	Revision Date: 09/16/2021	SDS Number: 309425-00004	Date of last issue: 11/16/2020 Date of first issue: 09/14/2016
----------------	------------------------------	-----------------------------	---

Result: negative

Carcinogenicity

Not classified based on available information.

Components:**1,1-Difluoroethane:**

Species	: Rat
Application Route	: inhalation (vapor)
Exposure time	: 104 weeks
Result	: negative

Reproductive toxicity

Not classified based on available information.

Components:**1,1-Difluoroethane:**

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: inhalation (gas) Result: negative Remarks: Based on data from similar materials
Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: inhalation (vapor) Result: negative

STOT-single exposure

Not classified based on available information.

Components:**1,1-Difluoroethane:**

Assessment	: May cause drowsiness or dizziness.
------------	--------------------------------------

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity**Components:****1,1-Difluoroethane:**

Species	: Rat
NOAEL	: 100000 ppm
Application Route	: inhalation (gas)
Exposure time	: 14 Days

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/16/2020
2.1	09/16/2021	309425-00004	Date of first issue: 09/14/2016

Aspiration toxicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated middle:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity**Components:****Distillates (petroleum), hydrotreated middle:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 87,556 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (Selenastrum capricornutum (green algae)): > 1,000
plants mg/l
Exposure time: 72 h

Toxicity to fish (Chronic tox- : NOELR: > 1,000 mg/l
icity) Exposure time: 28 d

Toxicity to daphnia and other : NOELR: 5 mg/l
aquatic invertebrates (Chron- Exposure time: 21 d
ic toxicity)

Toxicity to microorganisms : EC50: > 100 mg/l
Exposure time: 3 h

Triacetoxymethylsilane:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 251 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 168.7 mg/l
aquatic invertebrates Exposure time: 48 h
Remarks: Data from similar compositions

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 24.41
plants mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 18

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/16/2020
2.1	09/16/2021	309425-00004	Date of first issue: 09/14/2016

mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): \geq 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Methylsilanetriyl triacetate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 500 mg/l
Exposure time: 96 h
Method: Directive 67/548/EEC, Annex V, C.1.
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l
Exposure time: 48 h
Method: Directive 67/548/EEC, Annex V, C.2.
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): \geq 500 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.
Remarks: Based on data from similar materials

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 500 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Persistence and degradability
Components:
Distillates (petroleum), hydrotreated middle:

Biodegradability : Result: Inherently biodegradable.

Triacetoxymethylsilane:

Biodegradability : Result: Readily biodegradable.

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version 2.1	Revision Date: 09/16/2021	SDS Number: 309425-00004	Date of last issue: 11/16/2020 Date of first issue: 09/14/2016
----------------	------------------------------	-----------------------------	---

Biodegradation: 74 %
Exposure time: 21 d

Methylsilanetriyl triacetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 74 %
Exposure time: 21 d
Method: Directive 67/548/EEC Annex V, C.4.A.
Remarks: Based on data from similar materials

Bioaccumulative potential**Components:****1,1-Difluoroethane:**

Partition coefficient: n-
octanol/water : log Pow: 0.75

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.2
Subsidiary risk : 8
Packing group : Not assigned by regulation
Labels : 2.2 (8)

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, non-flammable, containing substances in Class 8,
Packing Group III

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/16/2020
2.1	09/16/2021	309425-00004	Date of first issue: 09/14/2016

Class	: 2.2
Subsidiary risk	: 8
Packing group	: Not assigned by regulation
Labels	: Non-flammable, non-toxic Gas, Corrosive
Packing instruction (cargo aircraft)	: 203
Packing instruction (passenger aircraft)	: 203

IMDG-Code

UN number	: UN 1950
Proper shipping name	: AEROSOLS

Class	: 2.2
Subsidiary risk	: 8
Packing group	: Not assigned by regulation
Labels	: 2.2 (8)
EmS Code	: F-D, S-U
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

UN number	: UN 1950
Proper shipping name	: AEROSOLS

Class	: 2.2
Subsidiary risk	: 8
Packing group	: Not assigned by regulation
Labels	: 2.2 (8)
ERG Code	: 126
Marine pollutant	: no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content	CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products VOC content: 3.6 % / 31 g/l
---	--

International Regulations

Montreal Protocol	: 1,1-Difluoroethane
-------------------	----------------------

The ingredients of this product are reported in the following inventories:

DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the
-----	---

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/16/2020
2.1	09/16/2021	309425-00004	Date of first issue: 09/14/2016

Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION
Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

**RTV SILICONE GASKET, High temperature,
Red, 226 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/16/2020
2.1	09/16/2021	309425-00004	Date of first issue: 09/14/2016

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/16/2021
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8