

FLEXIBLE PLASTIC FIX, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 10/27/2021
1.3	06/09/2022	5246561-00004	Date of first issue: 11/04/2019

SECTION 1. IDENTIFICATION

Product name : FLEXIBLE PLASTIC FIX, Component A

Product code : 891.480104A

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Resins

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

Reproductive toxicity : Category 1B

GHS label elements

FLEXIBLE PLASTIC FIX, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 10/27/2021
1.3	06/09/2022	5246561-00004	Date of first issue: 11/04/2019

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H360Df May damage the unborn child. Suspected of damaging fertility.

Precautionary Statements

:

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing vapors.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical attention.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

:

Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
---------------	---------------------	---------	-----------------------

FLEXIBLE PLASTIC FIX, Component A

Version 1.3 Revision Date: 06/09/2022 SDS Number: 5246561-00004 Date of last issue: 10/27/2021
 Date of first issue: 11/04/2019

Bisphenol A/ epichlorohydrin resin	Oxirane, 2,2'-[[1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer	25085-99-8	$\geq 30 - < 60$ *
Benzyl butyl phthalate	1,2-Benzenedicarboxylic acid, 1-butyl 2-(phenylmethyl) ester	85-68-7	$\geq 10 - < 30$ *
Nepheline Syenite	Anhydrous sodium potassium aluminum silicate	37244-96-5	$\geq 10 - < 30$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
 Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
 If easy to do, remove contact lens, if worn.
 Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
 Get medical attention.
 Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
 May cause an allergic skin reaction.
 Causes serious eye irritation.
 May damage the unborn child. Suspected of damaging fertility.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

FLEXIBLE PLASTIC FIX, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 10/27/2021
1.3	06/09/2022	5246561-00004	Date of first issue: 11/04/2019

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Silicon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
-

FLEXIBLE PLASTIC FIX, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 10/27/2021
1.3	06/09/2022	5246561-00004	Date of first issue: 11/04/2019

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe vapors.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Nepheline Syenite	37244-96-5	TWA (Total dust)	10 mg/m ³	CA ON OEL

- Engineering measures** : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise

FLEXIBLE PLASTIC FIX, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 10/27/2021
1.3	06/09/2022	5246561-00004	Date of first issue: 11/04/2019

Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection

Material : PVA
Break through time : ≤ 300 min
Glove thickness : ≥ 0.08 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : blue

Odor : sweet

FLEXIBLE PLASTIC FIX, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 10/27/2021
1.3	06/09/2022	5246561-00004	Date of first issue: 11/04/2019

Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	240 °C
Flash point	:	> 149 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	2 Pa (20 °C)
Relative vapor density	:	10.8
Density	:	1.10 g/cm ³
Solubility(ies) Water solubility	:	partly soluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
------------	---	----------------------------------------

FLEXIBLE PLASTIC FIX, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 10/27/2021
1.3	06/09/2022	5246561-00004	Date of first issue: 11/04/2019

Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
---------------------	---	----------------------------------------------------------------------

Components:**Bisphenol A/ epichlorohydrin resin:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity	:	LD50 (Rat): > 2,000 mg/kg Remarks: Based on data from similar materials

Benzyl butyl phthalate:

Acute oral toxicity	:	LD50 (Rat): 2,330 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:**Bisphenol A/ epichlorohydrin resin:**

Species	:	Rabbit
Result	:	Skin irritation

Benzyl butyl phthalate:

Species	:	Human
---------	---	-------

FLEXIBLE PLASTIC FIX, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 10/27/2021
1.3	06/09/2022	5246561-00004	Date of first issue: 11/04/2019

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Bisphenol A/ epichlorohydrin resin:**

Result : Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:**Bisphenol A/ epichlorohydrin resin:**

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: positive
Remarks	: Based on data from similar materials

Assessment : Probability or evidence of skin sensitization in humans

Benzyl butyl phthalate:

Test Type	: Human repeat insult patch test (HRIPT)
Routes of exposure	: Skin contact
Result	: negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Bisphenol A/ epichlorohydrin resin:**

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES)
	Method: OECD Test Guideline 471
	Result: negative
	Remarks: Based on data from similar materials

Genotoxicity in vivo	: Test Type: Rodent dominant lethal test (germ cell) (in vivo)
	Species: Mouse
	Application Route: Ingestion
	Result: negative
	Remarks: Based on data from similar materials

Benzyl butyl phthalate:

FLEXIBLE PLASTIC FIX, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 10/27/2021
1.3	06/09/2022	5246561-00004	Date of first issue: 11/04/2019

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative Test Type: In vitro mammalian cell gene mutation test Result: negative Test Type: Chromosome aberration test in vitro Result: negative
Genotoxicity in vivo	: Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Mouse Application Route: Intraperitoneal injection Result: equivocal Test Type: Mammalian bone marrow sister chromatid exchange Species: Mouse Application Route: Intraperitoneal injection Result: positive
Germ cell mutagenicity - Assessment	: Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Not classified based on available information.

Components:**Bisphenol A/ epichlorohydrin resin:**

Species	: Rat
Application Route	: Ingestion
Exposure time	: 24 month(s)
Method	: OECD Test Guideline 453
Result	: negative
Remarks	: Based on data from similar materials

Benzyl butyl phthalate:

Species	: Mouse
Application Route	: Ingestion
Exposure time	: 103 weeks
Result	: negative

Reproductive toxicity

May damage the unborn child. Suspected of damaging fertility.

Components:**Bisphenol A/ epichlorohydrin resin:**

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Method: OECD Test Guideline 416 Result: negative
----------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------

FLEXIBLE PLASTIC FIX, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 10/27/2021
1.3	06/09/2022	5246561-00004	Date of first issue: 11/04/2019

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Benzyl butyl phthalate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OPPTS 870.3800
Result: positive

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: positive

Reproductive toxicity - Assessment : Clear evidence of adverse effects on development, based on animal experiments., Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity**Components:****Bisphenol A/ epichlorohydrin resin:**

Species : Rat
NOAEL : 50 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

Benzyl butyl phthalate:

Species : Rat
NOAEL : 151 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Aspiration toxicity

Not classified based on available information.

FLEXIBLE PLASTIC FIX, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 10/27/2021
1.3	06/09/2022	5246561-00004	Date of first issue: 11/04/2019

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Bisphenol A/ epichlorohydrin resin:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1 - 10 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : ErC50 (Scenedesmus capricornutum (fresh water algae)): > 10 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials
- Toxicity to microorganisms : IC50: > 100 mg/l
Exposure time: 3 h
Remarks: Based on data from similar materials

Benzyl butyl phthalate:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.82 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Mysidopsis bahia (opossum shrimp)): > 0.74 mg/l
Exposure time: 48 h
Remarks: No toxicity at the limit of solubility.
- Toxicity to algae/aquatic plants : NOEC (Navicula pelliculosa (Freshwater diatom)): 0.17 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- ErC50 (Navicula pelliculosa (Freshwater diatom)): 0.66 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 0.0675 mg/l
Exposure time: 126 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Mysidopsis bahia (opossum shrimp)): 0.075 mg/l
Exposure time: 28 d

Nepheline Syenite:**Ecotoxicology Assessment**

- Chronic aquatic toxicity : No toxicity at the limit of solubility.

FLEXIBLE PLASTIC FIX, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 10/27/2021
1.3	06/09/2022	5246561-00004	Date of first issue: 11/04/2019

Persistence and degradability**Components:****Bisphenol A/ epichlorohydrin resin:**

Biodegradability : Result: Not readily biodegradable.
Remarks: Based on data from similar materials

Benzyl butyl phthalate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 81 %
Exposure time: 14 d
Method: OECD Test Guideline 301C

Bioaccumulative potential**Components:****Benzyl butyl phthalate:**

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)
Bioconcentration factor (BCF): 188 - 255

Partition coefficient: n-octanol/water : log Pow: 4.91

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Bisphenol A/ epichlorohydrin resin, Benzyl butyl phthalate)

Class : 9
Packing group : III
Labels : 9

FLEXIBLE PLASTIC FIX, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 10/27/2021
1.3	06/09/2022	5246561-00004	Date of first issue: 11/04/2019

IATA-DGR

UN/ID No.	: UN 3082
Proper shipping name	: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A/ epichlorohydrin resin, Benzyl butyl phthalate)
Class	: 9
Packing group	: III
Labels	: Miscellaneous
Packing instruction (cargo aircraft)	: 964
Packing instruction (passenger aircraft)	: 964
Environmentally hazardous	: yes

IMDG-Code

UN number	: UN 3082
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A/ epichlorohydrin resin, Benzyl butyl phthalate)
Class	: 9
Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

UN number	: UN 3082
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A/ epichlorohydrin resin, Benzyl butyl phthalate)
Class	: 9
Packing group	: III
Labels	: 9
ERG Code	: 171
Marine pollutant	: yes(Bisphenol A/ epichlorohydrin resin, Benzyl butyl phthalate)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content	CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products VOC content: 0 %
-------------------------------------------------	--------------------------------------------------------------------------------------------------------------

The ingredients of this product are reported in the following inventories:

DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the
-----	-----------------------------------------------------------------------------------------------------------------------

FLEXIBLE PLASTIC FIX, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 10/27/2021
1.3	06/09/2022	5246561-00004	Date of first issue: 11/04/2019

Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/09/2022
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be

FLEXIBLE PLASTIC FIX, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 10/27/2021
1.3	06/09/2022	5246561-00004	Date of first issue: 11/04/2019

considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8