

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

---

### SECTION 1. IDENTIFICATION

Product name : RUBBERIZED UNDERCOATING, Black, 1 L  
Product code : 892.075210  
Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : +1 (905) 564 6225  
Telefax : +1 (905) 564 3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)  
  
Urgences impliquant un déversement, incendie, explosion ou exposition:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences liées au transport:  
CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)  
  
E-mail address : prodsafe@wurth.ca

#### Recommended use of the chemical and restrictions on use

Recommended use : Solvent-borne coatings  
Restrictions on use : Not applicable

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 2  
Skin irritation : Category 2  
Carcinogenicity (Inhalation) : Category 1A  
Reproductive toxicity : Category 2  
Specific target organ toxicity : Category 3

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

---

- single exposure

Specific target organ toxicity : Category 2 (Central nervous system)  
- repeated exposure

Aspiration hazard : Category 1

### GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H350 May cause cancer by inhalation.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.

**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**  
P405 Store locked up.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

### Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

### Other hazards

Vapors may form explosive mixture with air.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
tert-Butyl acetate	Acetic acid, 1,1-dimethylethyl ester	540-88-5	$\geq 30 - < 60$ *
Toluene	Benzene, methyl-	108-88-3	$\geq 10 - < 30$ *
Limestone	Calcium carbonate	1317-65-3	$\geq 10 - < 30$ *
Solvent naphtha (petroleum), heavy aliphatic	Solvent naphtha (petroleum), heavy aliph.	64742-96-7	$\geq 1 - < 5$ *
Quartz	Silicon Dioxide	14808-60-7	$\geq 0.1 - < 1$ *

\* Actual concentration or concentration range is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
If vomiting occurs have person lean forward.  
Call a physician or poison control center immediately.  
Rinse mouth thoroughly with water.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
2.5	06/19/2024	4995956-00007	Date of first issue: 10/02/2019

---

- Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May cause cancer by inhalation.  
Suspected of damaging the unborn child.  
May cause damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Metal oxides  
Nitrogen oxides (NO<sub>x</sub>)  
Silicon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency measures : Remove all sources of ignition.  
Ventilate the area.
-

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

---

- gency procedures      Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions      :    Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up      :    Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

- Technical measures      :    See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation      :    If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling      :    Do not get on skin or clothing.  
Do not breathe mist or vapors.  
Do not swallow.  
Avoid contact with eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Non-sparking tools should be used.  
Keep container tightly closed.  
Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Self-reactive substances and mixtures  
Organic peroxides  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases  
Very acutely toxic substances and mixtures

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
tert-Butyl acetate	540-88-5	TWA	200 ppm 950 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	150 ppm	CA QC OEL
		TWA	50 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Toluene	108-88-3	TWA	50 ppm 188 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		TWA	20 ppm	ACGIH
Limestone	1317-65-3	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		STEL	20 mg/m <sup>3</sup>	CA BC OEL
Solvent naphtha (petroleum), heavy aliphatic	64742-96-7	TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	CA AB OEL
		TWAEV	200 mg/m <sup>3</sup>	CA QC OEL
Quartz	14808-60-7	TWA (Respirable particulates)	0.025 mg/m <sup>3</sup>	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m <sup>3</sup>	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m <sup>3</sup>	CA QC OEL
		TWA (Respirable)	0.025 mg/m <sup>3</sup> (Silica)	CA BC OEL
		TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI

**Engineering measures** : Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
2.5	06/19/2024	4995956-00007	Date of first issue: 10/02/2019

---

### Personal protective equipment

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Combined particulates and organic vapor type
- Hand protection
- Material : PVA
- Material : Nitrile rubber
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!
- Eye protection : Wear the following personal protective equipment:  
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : black
- Odor : solvent
- Odor Threshold : No data available



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
2.5	06/19/2024	4995956-00007	Date of first issue: 10/02/2019

---

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : 97 °C

Flash point : 4 °C  
Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : 6.9 %(V)

Lower explosion limit / Lower flammability limit : 0.5 %(V)

Vapor pressure : No data available

Relative vapor density : > 1

Relative density : 0.99

Density : 0.99 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : slightly soluble

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : > 232 °C

Decomposition temperature : The substance or mixture is not classified self-reactive.

Viscosity  
Viscosity, dynamic : 3,400 mPa.s  
Viscosity, kinematic : 3400 mm<sup>2</sup>/s

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

---

Particle size : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Highly flammable liquid and vapor.  
Vapors may form explosive mixture with air.  
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

#### Components:

##### **tert-Butyl acetate:**

Acute oral toxicity : LD50 (Rat): 4,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 15 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

---

### **Toluene:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

### **Limestone:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### **Solvent naphtha (petroleum), heavy aliphatic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.28 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Remarks: Based on data from similar materials

### **Quartz:**

Acute oral toxicity : LD50 (Rat): > 22,500 mg/kg

### **Skin corrosion/irritation**

Causes skin irritation.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

---

### Components:

#### **tert-Butyl acetate:**

Species : Rabbit  
Result : No skin irritation  
  
Assessment : Repeated exposure may cause skin dryness or cracking.

#### **Toluene:**

Species : Rabbit  
Method : Directive 67/548/EEC, Annex V, B.4.  
Result : Skin irritation

#### **Limestone:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

#### **Solvent naphtha (petroleum), heavy aliphatic:**

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

#### **Quartz:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

#### **Serious eye damage/eye irritation**

Not classified based on available information.

### Components:

#### **tert-Butyl acetate:**

Species : Rabbit  
Result : No eye irritation

#### **Toluene:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

#### **Limestone:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
2.5	06/19/2024	4995956-00007	Date of first issue: 10/02/2019

---

### **Solvent naphtha (petroleum), heavy aliphatic:**

Species	:	Rabbit
Result	:	No eye irritation
Remarks	:	Based on data from similar materials

### **Quartz:**

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

### **Components:**

#### **tert-Butyl acetate:**

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

#### **Toluene:**

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	Directive 67/548/EEC, Annex V, B.6.
Result	:	negative

#### **Limestone:**

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative
Remarks	:	Based on data from similar materials

### **Solvent naphtha (petroleum), heavy aliphatic:**

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative
Remarks	:	Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

---

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **tert-Butyl acetate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 474  
Result: negative

#### **Toluene:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: Intraperitoneal injection  
Result: negative

Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 478  
Result: negative

#### **Limestone:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
2.5	06/19/2024	4995956-00007	Date of first issue: 10/02/2019

---

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

### **Solvent naphtha (petroleum), heavy aliphatic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Rat  
Application Route: Intraperitoneal injection  
Result: negative  
Remarks: Based on data from similar materials

### **Carcinogenicity**

May cause cancer by inhalation.

### **Components:**

#### **tert-Butyl acetate:**

Species : Rat  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative  
Remarks : Based on data from similar materials

#### **Toluene:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 103 weeks  
Result : negative

Species : Mouse  
Application Route : Skin contact  
Exposure time : 24 Months  
Result : negative

#### **Quartz:**

Species : Humans  
Application Route : inhalation (dust/mist/fume)  
Result : positive

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

### **Reproductive toxicity**

Suspected of damaging the unborn child.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

---

### Components:

#### **tert-Butyl acetate:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OPPTS 870.3650  
Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OPPTS 870.3650  
Result: negative

#### **Toluene:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 416  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

#### **Limestone:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

#### **Solvent naphtha (petroleum), heavy aliphatic:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

---

Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 421  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

### STOT-single exposure

May cause respiratory irritation.  
May cause drowsiness or dizziness.

#### Components:

##### **tert-Butyl acetate:**

Assessment : May cause respiratory irritation.

Assessment : May cause drowsiness or dizziness.

##### **Toluene:**

Assessment : May cause drowsiness or dizziness.

##### **Solvent naphtha (petroleum), heavy aliphatic:**

Assessment : May cause drowsiness or dizziness.

### STOT-repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

#### Components:

##### **Toluene:**

Routes of exposure : Inhalation  
Target Organs : Central nervous system  
Assessment : May cause damage to organs through prolonged or repeated exposure.

##### **Quartz:**

Routes of exposure : inhalation (dust/mist/fume)  
Target Organs : Lungs  
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

### Repeated dose toxicity

#### Components:

##### **tert-Butyl acetate:**

Species : Mouse

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

---

NOAEL : 1.9 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks

### **Toluene:**

Species : Rat  
LOAEL : 1.875 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 6 Months

Species : Rat  
NOAEL : 625 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks

### **Limestone:**

Species : Rat  
NOAEL : > 300 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days  
Method : OECD Test Guideline 422  
Remarks : Based on data from similar materials

### **Solvent naphtha (petroleum), heavy aliphatic:**

Species : Rat  
NOAEL : 750 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

### **Quartz:**

Species : Humans  
LOAEL : 0.053 mg/m<sup>3</sup>  
Application Route : Inhalation

### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

### **Components:**

#### **Toluene:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **Solvent naphtha (petroleum), heavy aliphatic:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

---

### Experience with human exposure

#### Components:

##### **Toluene:**

Inhalation : Target Organs: Central nervous system  
Symptoms: Neurological disorders

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### **tert-Butyl acetate:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 240 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 350 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 16 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 2.3 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

##### **Toluene:**

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Skeletonema costatum (marine diatom)): 10 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l  
Exposure time: 40 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): 0.74 mg/l  
Exposure time: 7 d

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 84 mg/l  
Exposure time: 24 h

---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

---

### Limestone:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : LL50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 14 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: No toxicity at the limit of solubility.  
Based on data from similar materials
- EL10 (Desmodesmus subspicatus (green algae)): > 14 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: No toxicity at the limit of solubility.  
Based on data from similar materials
- Toxicity to microorganisms : EC50: > 100 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials

### Solvent naphtha (petroleum), heavy aliphatic:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 1.4 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL10 (Pseudokirchneriella subcapitata (green algae)): 1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 3

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

---

mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.48 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction

### **Quartz:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 508 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 731 mg/l  
Exposure time: 48 h  
Remarks: Based on data from similar materials

### **Persistence and degradability**

#### **Components:**

##### **tert-Butyl acetate:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 50 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

##### **Toluene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 80 %  
Exposure time: 20 d

##### **Solvent naphtha (petroleum), heavy aliphatic:**

Biodegradability : Result: Inherently biodegradable.

### **Bioaccumulative potential**

#### **Components:**

##### **tert-Butyl acetate:**

Partition coefficient: n-octanol/water : Pow: 1.64

##### **Toluene:**

Bioaccumulation : Species: Leuciscus idus (Golden orfe)  
Bioconcentration factor (BCF): 90

Partition coefficient: n- : log Pow: 2.73

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
2.5	06/19/2024	4995956-00007	Date of first issue: 10/02/2019

---

octanol/water

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 1139  
Proper shipping name : COATING SOLUTION  
Class : 3  
Packing group : II  
Labels : 3  
Environmentally hazardous : no

#### IATA-DGR

UN/ID No. : UN 1139  
Proper shipping name : Coating solution  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

#### IMDG-Code

UN number : UN 1139  
Proper shipping name : COATING SOLUTION  
  
Class : 3  
Packing group : II  
Labels : 3

---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version 2.5      Revision Date: 06/19/2024      SDS Number: 4995956-00007      Date of last issue: 11/11/2022  
Date of first issue: 10/02/2019

---

EmS Code : F-E, S-E  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### TDG

UN number : UN 1139  
Proper shipping name : COATING SOLUTION

Class : 3  
Packing group : II  
Labels : 3  
ERG Code : 127  
Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

**Volatile organic compounds (VOC) content** : CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products  
VOC content: 246.84 g/l

### The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

---

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL : Canada. British Columbia OEL  
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.  
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants  
ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
CA AB OEL / TWA : 8-hour Occupational exposure limit  
CA BC OEL / TWA : 8-hour time weighted average

---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
2.5	06/19/2024	4995956-00007	Date of first issue: 10/02/2019

CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <a href="http://echa.europa.eu/">http://echa.europa.eu/</a>
--	---	---

Revision Date	:	06/19/2024
Date format	:	mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## RUBBERIZED UNDERCOATING, Black, 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 11/11/2022
2.5	06/19/2024	4995956-00007	Date of first issue: 10/02/2019

---

intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8