according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/19/2024 11441374-00001 Date of first issue: 09/19/2024

SECTION 1. IDENTIFICATION

Product name : RODENT PROTECTION SPRAY, 158 g

Product code : 892.077150 Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd

GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225 Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:

CHEMTREC (24/7): 1-800-424-9300 Transport related emergencies:

CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou

exposition:

CHEMTREC (24/7): 1-800-424-9300

Urgences liées au transport:

CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 1

Skin irritation : Category 2

Specific target organ toxicity : Ca

- single exposure

Category 3

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/19/2024 11441374-00001 Date of first issue: 09/19/2024

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.

P332 + P313 If skin irritation occurs: Get medical attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common	CAS-No.	Concentration (% w/w)
	Name/Synonym		
Isobutane	Propane, 2- methyl-	75-28-5	>= 30 - < 60 *
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Naphtha (petro- leum), hy- drotreated light	92128-66-0	>= 10 - < 30 *
Propane	Dimethylme- thane	74-98-6	>= 5 - < 10 *
Distillates (petroleum), solvent-refined light paraffinic	Baseoil - un- specified	64741-89-5	>= 5 - < 10 *

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/19/2024 11441374-00001 Date of first issue: 09/19/2024

| Butane | Butyl hydride | 106-97-8 | >= 1 - < 5 *

Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes,	64742-49-0
cyclics, <5% n-hexane	

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse. Flush eyes with water as a precaution.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur.

Rinse mouth thoroughly with water.

Most important symptoms

and effects, both acute and

delayed

Causes skin irritation.

May cause drowsiness or dizziness.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Flash back possible over considerable distance.

Vapors may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod: :

ucts

Carbon oxides

Actual concentration or concentration range is withheld as a trade secret

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/19/2024 11441374-00001 Date of first issue: 09/19/2024

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emergency procedures

Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions

Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapors/mists with a water spray

jet.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material

can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventila-

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/19/2024 11441374-00001 Date of first issue: 09/19/2024

tion.

Advice on safe handling : Do not get on skin or clothing.

Avoid breathing spray.

Do not swallow.

Avoid contact with eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the

environment.

Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store

Store locked up.

Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Do not pierce or burn, even after use. Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases Explosives Gases

Recommended storage tem: :

- : < 40 °C

perature

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Isobutane	75-28-5	TWA	1,000 ppm	CA AB OEL
		STEL	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	92128-66-0	TWA (Mist)	5 mg/m³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m³	CA QC OEL

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/19/2024 11441374-00001 Date of first issue: 09/19/2024

Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL
Distillates (petroleum), solvent- refined light paraffinic	64741-89-5	TWA (Mist)	5 mg/m³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m³	CA QC OEL
		TWA (Mist)	1 mg/m³	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m³	ACGIH
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm 1,900 mg/m ³	CA QC OEL
		STEL	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH

Engineering measures : Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust

ventilation.

If advised by assessment of the local exposure potential, use

only in an area equipped with explosion-proof exhaust

ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or

exposure assessment demonstrates exposures outside the

recommended guidelines, use respiratory protection.

Filter type

Self-contained breathing apparatus

Hand protection

Material : Nitrile rubber Break through time : 480 min Glove thickness : 0.45 mm

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the

end of workday.

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

protective clothing.

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/19/2024 11441374-00001 Date of first issue: 09/19/2024

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Propellant : Isobutane, Propane, Butane

Color : brown

Odor : solvent

Odor Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : No data available

Initial boiling point and boiling

range

-40 °C

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

15 %(V)

Lower explosion limit / Lower :

flammability limit

0.6 %(V)

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Density : 0.81 g/cm³ (20 °C)

Method: DIN 51757

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : > 200 °C

Decomposition temperature : No data available

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

09/19/2024 11441374-00001 Date of first issue: 09/19/2024 1.0

Viscosity

Viscosity, kinematic Not applicable

Explosive properties Not explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size Not applicable

SECTION 10. STABILITY AND REACTIVITY

Not classified as a reactivity hazard. Reactivity Stable under normal conditions. Chemical stability Extremely flammable aerosol.

Possibility of hazardous reac-

Vapors may form explosive mixture with air.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Can react with strong oxidizing agents.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Isobutane:

Acute inhalation toxicity LC50 (Mouse): 260200 ppm

Exposure time: 4 h Test atmosphere: gas

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity LD50 (Rat): > 5,000 mg/kg

LC50 (Rat): > 25.2 mg/l Acute inhalation toxicity

> Exposure time: 4 h Test atmosphere: vapor

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/19/2024 11441374-00001 Date of first issue: 09/19/2024

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm

Exposure time: 15 min Test atmosphere: gas

Distillates (petroleum), solvent-refined light paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Skin corrosion/irritation

Causes skin irritation.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Distillates (petroleum), solvent-refined light paraffinic:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Result : No eye irritation

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/19/2024 11441374-00001 Date of first issue: 09/19/2024

Distillates (petroleum), solvent-refined light paraffinic:

Species : Rabbit

Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Distillates (petroleum), solvent-refined light paraffinic:

Test Type : Buehler Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Isobutane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay)

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/19/2024 11441374-00001 Date of first issue: 09/19/2024

Species: Rat

Application Route: inhalation (vapor)

Method: OPPTS 870.5395

Result: negative

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 474

Result: negative

Distillates (petroleum), solvent-refined light paraffinic:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Mouse
Application Route : Skin contact
Exposure time : 102 weeks
Result : negative

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/19/2024 11441374-00001 Date of first issue: 09/19/2024

Distillates (petroleum), solvent-refined light paraffinic:

Species : Mouse, female
Application Route : Skin contact
Exposure time : 18 Months

Method : OECD Test Guideline 451

Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Isobutane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Inhalation Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 422

Result: negative

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 422

Result: negative

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/19/2024 11441374-00001 Date of first issue: 09/19/2024

Butane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Application Route: inhalation (gas) Method: OECD Test Guideline 422

Result: negative

STOT-single exposure

May cause drowsiness or dizziness.

Components:

Isobutane:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Propane:

Assessment : May cause drowsiness or dizziness.

Butane:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Isobutane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)

Exposure time : 6 Weeks

Method : OECD Test Guideline 422

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rat NOAEL : > 20 mg/l

Application Route : inhalation (vapor)

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/19/2024 11441374-00001 Date of first issue: 09/19/2024

Exposure time : 13 Weeks

Propane:

Species : Rat
NOAEL : 7.214 mg/l
Application Route : inhalation (gas)

Exposure time : 6 Weeks

Method : OECD Test Guideline 422

Distillates (petroleum), solvent-refined light paraffinic:

Species : Rabbit
NOAEL : 1,000 mg/kg
Application Route : Skin contact
Exposure time : 4 Weeks

Method : OECD Test Guideline 410

Remarks : Based on data from similar materials

Species : Rat

NOAEL : $> 980 \text{ mg/m}^3$

Application Route : inhalation (dust/mist/fume)

Exposure time : 4 Weeks

Remarks : Based on data from similar materials

Butane:

Species : Rat

NOAEL : 9000 ppm

Application Route : inhalation (gas)

Exposure time : 6 Weeks

Method : OECD Test Guideline 422

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

09/19/2024 11441374-00001 Date of first issue: 09/19/2024 1.0

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 4.5 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1

mq/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5

ma/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOELR (Daphnia magna (Water flea)): 2.6 mg/l

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

Exposure time: 21 d

Method: OECD Test Guideline 211 ic toxicity)

Distillates (petroleum), solvent-refined light paraffinic:

Toxicity to fish LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

LL50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (green algae)): > 100

ma/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 10 mg/l

Persistence and degradability

Components:

Isobutane:

Biodegradability Result: Readily biodegradable.

Biodegradation: 100 % Exposure time: 385.5 h

Remarks: Based on data from similar materials

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/19/2024 11441374-00001 Date of first issue: 09/19/2024

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 77.05 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Propane:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 100 % Exposure time: 385.5 h

Remarks: Based on data from similar materials

Distillates (petroleum), solvent-refined light paraffinic:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Butane:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 100 % Exposure time: 385.5 h

Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

Isobutane:

Partition coefficient: n- : log Pow: 2.8

octanol/water

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Partition coefficient: n- : log Pow: 4

octanol/water Remarks: Based on data from similar materials

Butane:

Partition coefficient: n-

: log Pow: 2.31

octanol/water

Mobility in soil
No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

09/19/2024 11441374-00001 Date of first issue: 09/19/2024 1.0

Dispose of in accordance with local regulations.

Empty containers should be taken to an approved waste Contaminated packaging

handling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other

sources of ignition. They may explode and cause injury and/or

death.

If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty

(including propellant)

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number UN 1950 **AEROSOLS** Proper shipping name

Class 2.1

Packing group Not assigned by regulation

Labels 2.1 Environmentally hazardous no

IATA-DGR

UN/ID No. UN 1950

Proper shipping name Aerosols, flammable

Class 2.1

Packing group Not assigned by regulation

203

Labels Flammable Gas

Packing instruction (cargo

aircraft)

Packing instruction (passen: 203

ger aircraft)

IMDG-Code

UN number UN 1950 Proper shipping name **AEROSOLS**

Class 2.1

Packing group Not assigned by regulation

Labels 2.1 **EmS Code** F-D, S-U Marine pollutant no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number UN 1950 **AEROSOLS** Proper shipping name

Class 2.1

Packing group Not assigned by regulation

Labels 2.1 **ERG Code** 126

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/19/2024 11441374-00001 Date of first issue: 09/19/2024

Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average CA BC OEL / STEL : short-term exposure limit

CA QC OEL / TWAEV : Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New

according to the Hazardous Products Regulations



RODENT PROTECTION SPRAY, 158 g

Version Revision Date: SDS Number: Date of last issue: -

09/19/2024 11441374-00001 Date of first issue: 09/19/2024 1.0

Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date 09/19/2024 Date format mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8