

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

SECTION 1. IDENTIFICATION

Product name : GRAVEL GUARD, Beige, 550 g
Product code : 892.090101
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Coatings

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 1
Skin irritation : Category 2
|| Carcinogenicity (Inhalation) : Category 2
Reproductive toxicity : Category 2
Specific target organ toxicity : Category 3

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

- single exposure

Specific target organ toxicity : Category 2 (Central nervous system)
- repeated exposure

Simple Asphyxiant : Category 1

GHS label elements

Hazard pictograms



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer if inhaled.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure.
May displace oxygen and cause rapid suffocation.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical attention.
P332 + P313 If skin irritation occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version
3.0

Revision Date:
02/08/2024

SDS Number:
7315238-00006

Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | Common Name/Synonym | CAS-No. | Concentration (% w/w) |
|---|---------------------|------------|-----------------------|
| Toluene | Benzene, methyl- | 108-88-3 | $\geq 30 - < 60$ * |
| Propane | Dimethylmethane | 74-98-6 | $\geq 10 - < 30$ * |
| Solvent naphtha (petroleum), light aliph. | No data available | 64742-89-8 | $\geq 10 - < 30$ * |
| Limestone | Calcium carbonate | 1317-65-3 | $\geq 5 - < 10$ * |
| Isobutane | Propane, 2-methyl- | 75-28-5 | $\geq 5 - < 10$ * |
| Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] | Titanic anhydride | 13463-67-7 | $\geq 1 - < 5$ * |
| Methanol | Methyl alcohol | 67-56-1 | $\geq 0.1 - < 1$ * |

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Gas reduces oxygen available for breathing.
Causes skin irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer if inhaled.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure.
May displace oxygen and cause rapid suffocation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
Metal oxides
Nitrogen oxides (NO_x)
Silicon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12/11/2023 |
| 3.0 | 02/08/2024 | 7315238-00006 | Date of first issue: 11/04/2020 |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe spray.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

- assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.
- Conditions for safe storage : Store locked up.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases
- Recommended storage temperature : > 0 - 40 °C
- Storage period : 18 Months

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------|-----------|-------------------------------|--|-----------|
| Toluene | 108-88-3 | TWA | 50 ppm 188 mg/m ³ | CA AB OEL |
| | | TWA | 20 ppm | CA BC OEL |
| | | TWAEV | 20 ppm | CA QC OEL |
| Propane | 74-98-6 | TWA | 20 ppm | ACGIH |
| | | TWA | 1,000 ppm | CA AB OEL |
| | | TWAEV | 1,000 ppm 1,800 mg/m ³ | CA QC OEL |
| Limestone | 1317-65-3 | TWA | 10 mg/m ³ | CA AB OEL |
| | | TWAEV (total dust) | 10 mg/m ³ | CA QC OEL |
| | | TWA (Total dust) | 10 mg/m ³ | CA BC OEL |
| | | TWA (respir-) | 3 mg/m ³ | CA BC OEL |

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
 Date of first issue: 11/04/2020

| | | | | |
|--|------------|-------------------------------------|---|-----------|
| | | able dust fraction) | | |
| | | STEL | 20 mg/m ³ | CA BC OEL |
| Isobutane | 75-28-5 | TWA | 1,000 ppm | CA AB OEL |
| | | TWA | 1,000 ppm | CA BC OEL |
| | | STEL | 1,000 ppm | ACGIH |
| Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | TWA | 10 mg/m ³ | CA AB OEL |
| | | TWA (Total dust) | 10 mg/m ³ | CA BC OEL |
| | | TWA (respirable dust fraction) | 3 mg/m ³ | CA BC OEL |
| | | TWAEV (total dust) | 10 mg/m ³ | CA QC OEL |
| | | TWA (Respirable particulate matter) | 2.5 mg/m ³ (Titanium dioxide) | ACGIH |
| Methanol | 67-56-1 | TWA | 200 ppm 262 mg/m ³ | CA AB OEL |
| | | STEL | 250 ppm 328 mg/m ³ | CA AB OEL |
| | | TWA | 200 ppm | CA BC OEL |
| | | STEL | 250 ppm | CA BC OEL |
| | | STEV | 250 ppm 328 mg/m ³ | CA QC OEL |
| | | TWAEV | 200 ppm 262 mg/m ³ | CA QC OEL |
| | | TWA | 200 ppm | ACGIH |
| | | STEL | 250 ppm | ACGIH |

Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Sampling time | Permissible concentration | Basis |
|------------|----------|--------------------|---------------------|--|---------------------------|--------------|
| Toluene | 108-88-3 | Toluene | In blood | Prior to last shift of work-week | 0.02 mg/l | ACGIH BEI |
| | | Toluene | Urine | End of shift (As soon as possible after exposure ceases) | 0.03 mg/l | ACGIH BEI |
| | | o-Cresol | Urine | End of shift (As soon as possible) | 0.3 mg/g creatinine | ACGIH BEI |

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

| | | | | | | |
|----------|---------|----------|-------|--|---------|-----------|
| | | | | after exposure ceases) | | |
| Methanol | 67-56-1 | Methanol | Urine | End of shift (As soon as possible after exposure ceases) | 15 mg/l | ACGIH BEI |

Engineering measures : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

|| Material : Nitrile rubber

|| Material : Neoprene

|| Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

|| Eye protection : Wear the following personal protective equipment:
Safety glasses

|| Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the work area.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12/11/2023 |
| 3.0 | 02/08/2024 | 7315238-00006 | Date of first issue: 11/04/2020 |

king place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|--|---|---|
| Appearance | : | aerosol |
| Propellant | : | Propane, Isobutane |
| Color | : | beige |
| Odor | : | aromatic |
| Odor Threshold | : | No data available |
| pH | : | Solvent mixture; pH value determination not possible, no aqueous solution |
| Melting point/freezing point | : | No data available |
| Initial boiling point and boiling range | : | Not applicable |
| Flash point | : | 4 °C Flash point is only valid for liquid portion in the aerosol can. |
| Evaporation rate | : | > 1 (Butyl Acetate=1.0) |
| Flammability (solid, gas) | : | Extremely flammable aerosol. |
| Self-ignition | : | No data available |
| Upper explosion limit / Upper flammability limit | : | 7.1 %(V) |
| Lower explosion limit / Lower flammability limit | : | 1.2 %(V) |
| Vapor pressure | : | 2,620 - 3,450 hPa (20 °C) |
| Relative vapor density | : | > 1 (Air = 1.0) |
| Density | : | 0.955 - 0.970 g/cm ³ (20 °C) |

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12/11/2023 |
| 3.0 | 02/08/2024 | 7315238-00006 | Date of first issue: 11/04/2020 |

| | |
|--|---|
| | (as liquid) |
| Solubility(ies) | |
| Water solubility | : practically insoluble |
| Partition coefficient: n-octanol/water | : Not applicable |
| Autoignition temperature | : No data available |
| Decomposition temperature | : The substance or mixture is not classified self-reactive. |
| Viscosity | |
| Viscosity, dynamic | : > 100 cP (20 °C) |
| Viscosity, kinematic | : Not applicable |
| Explosive properties | : Not explosive |
| Oxidizing properties | : The substance or mixture is not classified as oxidizing. |
| Particle size | : Not applicable |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|--|
| Reactivity | : Not classified as a reactivity hazard. |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents. |
| Conditions to avoid | : Heat, flames and sparks. |
| Incompatible materials | : Oxidizing agents |
| Hazardous decomposition products | : No hazardous decomposition products are known. |

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

Acute toxicity

|| Not classified based on available information.

Product:

|| Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

|| Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

Toluene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min
Test atmosphere: gas

Solvent naphtha (petroleum), light aliph.:

|| Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.6 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Limestone:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Isobutane:

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm
Exposure time: 4 h
Test atmosphere: gas

Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Methanol:

Acute oral toxicity : Acute toxicity estimate (Humans): 300 mg/kg
Method: Expert judgment
LD50 (Rat, female): 12.25 ml/kg
Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment
Remarks: Based on national or regional regulation.
Acute dermal toxicity : Acute toxicity estimate (Humans): 300 mg/kg
Method: Expert judgment

Skin corrosion/irritation

Causes skin irritation.

Components:

Toluene:

Species : Rabbit

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

Method : Directive 67/548/EEC, Annex V, B.4.
Result : Skin irritation

Solvent naphtha (petroleum), light aliph.:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

Limestone:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]:

Species : Rabbit
Result : No skin irritation

Methanol:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Toluene:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Solvent naphtha (petroleum), light aliph.:

Species : Rabbit
Result : No eye irritation

Limestone:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]:

Species : Rabbit
Result : No eye irritation

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

Methanol:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Toluene:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : Directive 67/548/EEC, Annex V, B.6.
Result : negative

Solvent naphtha (petroleum), light aliph.:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Limestone:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative
Remarks : Based on data from similar materials

Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : negative

Methanol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Germ cell mutagenicity

Not classified based on available information.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

Components:

Toluene:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Intraperitoneal injection
Result: negative

Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: inhalation (vapor)
Method: OECD Test Guideline 478
Result: negative

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Solvent naphtha (petroleum), light aliph.:

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Inhalation
Result: negative

Limestone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Isobutane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Result: negative

Methanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

|| Suspected of causing cancer if inhaled.

Components:

Toluene:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 103 weeks

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

Result : negative

Species : Mouse
Application Route : Skin contact
Exposure time : 24 Months
Result : negative

Solvent naphtha (petroleum), light aliph.:

Species : Mouse
Application Route : Skin contact
Exposure time : 102 weeks
Result : negative

Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]:

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Method : OECD Test Guideline 453
Result : positive
Remarks : The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

Methanol:

Species : Mouse
Application Route : inhalation (vapor)
Exposure time : 18 Months
Result : negative

Reproductive toxicity

|| Suspected of damaging the unborn child.

Components:

Toluene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Solvent naphtha (petroleum), light aliph.:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Limestone:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Isobutane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 422
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Methanol:

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Mouse
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Result: positive
Remarks: The effects were seen only at maternally toxic doses.

STOT-single exposure

May cause drowsiness or dizziness.
May displace oxygen and cause rapid suffocation.

Components:

Toluene:

Assessment : May cause drowsiness or dizziness.

Propane:

Assessment : May cause drowsiness or dizziness.

Solvent naphtha (petroleum), light aliph.:

Assessment : May cause drowsiness or dizziness.

Isobutane:

Assessment : May cause drowsiness or dizziness.

Methanol:

Target Organs : Eye, Central nervous system
Assessment : Causes damage to organs.

STOT-repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

Components:

Toluene:

Routes of exposure : Inhalation
Target Organs : Central nervous system
Assessment : May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Toluene:

Species : Rat
LOAEL : 1.875 mg/l
Application Route : inhalation (vapor)
Exposure time : 6 Months

Species : Rat
NOAEL : 625 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Propane:

Species : Rat
NOAEL : 7.214 mg/l
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Solvent naphtha (petroleum), light aliph.:

Species : Rat
NOAEL : > 20 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks
Method : OPPTS 870.3465
Remarks : Based on data from similar materials

Limestone:

Species : Rat
NOAEL : > 300 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 422
Remarks : Based on data from similar materials

Isobutane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]:

Species : Rat
NOAEL : 24,000 mg/kg
Application Route : Ingestion
Exposure time : 28 Days

Species : Rat
NOAEL : 10 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 y

Methanol:

Species : Rat
NOAEL : 1.06 mg/l
Application Route : inhalation (vapor)
Exposure time : 90 Days

Aspiration toxicity

|| Not classified based on available information.

Components:

Toluene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Solvent naphtha (petroleum), light aliph.:

|| The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure

Components:

Toluene:

Inhalation : Target Organs: Central nervous system
Symptoms: Neurological disorders

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Toluene:

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l
Exposure time: 40 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): 0.74 mg/l
Exposure time: 7 d

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 84 mg/l
Exposure time: 24 h

Solvent naphtha (petroleum), light aliph.:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 8.2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.5 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 2.6 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Limestone:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : LL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 14 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

Remarks: No toxicity at the limit of solubility.
Based on data from similar materials

EL10 (Desmodesmus subspicatus (green algae)): > 14 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Methanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 15,400 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 22,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Oryzias latipes (Orange-red killifish)): 15,800 mg/l
Exposure time: 200 h

Toxicity to microorganisms : IC50: > 1,000 mg/l
Exposure time: 3 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

Persistence and degradability

Components:

Toluene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 20 d

Propane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Solvent naphtha (petroleum), light aliph.:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 77.07 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Isobutane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Methanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 95 %
Exposure time: 20 d

Bioaccumulative potential

Components:

Toluene:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 90

Partition coefficient: n-octanol/water : log Pow: 2.73

Solvent naphtha (petroleum), light aliph.:

Partition coefficient: n-octanol/water : log Pow: > 4
Remarks: Expert judgment

Isobutane:

Partition coefficient: n- : log Pow: 2.8

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

octanol/water

Methanol:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): < 10

Partition coefficient: n-octanol/water : log Pow: -0.77

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo) : 203

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

aircraft)

Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
ERG Code : 126
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content Canada - Volatile Organic Compound (VOC) Concentration Limits for Automotive Refinishing Products Regulations
VOC content: 76 - 78 % / <= 640 g/l

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

Version 3.0 Revision Date: 02/08/2024 SDS Number: 7315238-00006 Date of last issue: 12/11/2023
Date of first issue: 11/04/2020

2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit
CA QC OEL / TWAEV : Time-weighted average exposure value
CA QC OEL / STEV : Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 02/08/2024
Date format : mm/dd/yyyy

SAFETY DATA SHEET

according to the Hazardous Products Regulations



GRAVEL GUARD, Beige, 550 g

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12/11/2023 |
| 3.0 | 02/08/2024 | 7315238-00006 | Date of first issue: 11/04/2020 |

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8