

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

SECTION 1. IDENTIFICATION

Product name : ENAMEL ENGINE PAINT, Gloss Ford Blue, 340 g

Product code : 892.140016

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Paint

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1

Gases under pressure : Dissolved gas

Skin irritation : Category 2

Eye irritation : Category 2A

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 3
- single exposure

Specific target organ toxicity : Category 2 (Central nervous system, Kidney, Auditory system)
- repeated exposure

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs (Central nervous system, Kidney, Auditory system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical attention.
P332 + P313 If skin irritation occurs: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before

**ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g**

Version 3.1	Revision Date: 09/16/2021	SDS Number: 2053230-00004	Date of last issue: 11/17/2020 Date of first issue: 10/10/2017
----------------	------------------------------	------------------------------	---

reuse.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Repeated exposure may cause skin dryness or cracking.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Acetone	2-Propanone	67-64-1	27.28
Propane	Dimethylmethane	74-98-6	18.89
Butane	No data available	106-97-8	11.09
Solvent naphtha (petroleum), light aliphatic	No data available	64742-89-8	9.74
Isobutyl acetate	Acetic acid, 2-methylpropyl ester	110-19-0	7.08
Distillates (petroleum), hydrotreated light	No data available	64742-47-8	6.79
Toluene	Benzene, methyl-	108-88-3	4.09
Titanium dioxide	Titanic anhydride	13463-67-7	2.84
Propan-2-ol	Isopropyl alcohol	67-63-0	2.47
Xylene	Benzene, dimethyl-	1330-20-7	1.68
Barium sulfate	Sulfuric acid, barium salt	7727-43-7	1.31
2-Methoxy-1-methylethyl acetate	2-Propanol, 1-methoxy-, 2-acetate	108-65-6	1.12

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

- When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure.
Prolonged or repeated contact may dry skin and cause irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

- Hazardous combustion products : Carbon oxides
Metal oxides
Sulfur oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Do not breathe spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives

Recommended storage temperature : < 40 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m ³	CA AB OEL
		STEL	750 ppm 1,800 mg/m ³	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g

Version 3.1 Revision Date: 09/16/2021 SDS Number: 2053230-00004 Date of last issue: 11/17/2020
 Date of first issue: 10/10/2017

		TWAEV	500 ppm 1,190 mg/m ³	CA QC OEL
		STEV	1,000 ppm 2,380 mg/m ³	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm 1,900 mg/m ³	CA QC OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Isobutyl acetate	110-19-0	TWA	150 ppm 713 mg/m ³	CA AB OEL
		TWA	150 ppm	CA BC OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	150 ppm	CA QC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	200 mg/m ³ (total hydrocarbon vapor)	CA BC OEL
		TWA	200 mg/m ³ (total hydrocarbon vapor)	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
		TWA	525 mg/m ³	CA ON OEL
Toluene	108-88-3	TWA	50 ppm 188 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 188 mg/m ³	CA QC OEL
		TWA	20 ppm	ACGIH
Titanium dioxide	13463-67-7	TWA	10 mg/m ³	CA AB OEL
		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m ³	CA BC OEL
		TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH
Propan-2-ol	67-63-0	STEL	400 ppm 984 mg/m ³	CA AB OEL
		TWA	200 ppm 492 mg/m ³	CA AB OEL
		TWA	200 ppm	CA BC OEL

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g

Version 3.1 Revision Date: 09/16/2021 SDS Number: 2053230-00004 Date of last issue: 11/17/2020
 Date of first issue: 10/10/2017

		STEL	400 ppm	CA BC OEL
		TWAEV	400 ppm 983 mg/m ³	CA QC OEL
		STEV	500 ppm 1,230 mg/m ³	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
Xylene	1330-20-7	TWA	100 ppm 434 mg/m ³	CA AB OEL
		STEL	150 ppm 651 mg/m ³	CA AB OEL
		TWAEV	100 ppm 434 mg/m ³	CA QC OEL
		STEV	150 ppm 651 mg/m ³	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
Barium sulfate	7727-43-7	TWA	10 mg/m ³	CA AB OEL
		TWA (Inhalable)	5 mg/m ³	CA BC OEL
		TWAEV (inhalable dust)	5 mg/m ³	CA QC OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
2-Methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWA	50 ppm 270 mg/m ³	CA ON OEL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g

Version 3.1 Revision Date: 09/16/2021 SDS Number: 2053230-00004 Date of last issue: 11/17/2020
 Date of first issue: 10/10/2017

				possible after exposure ceases)		
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI
Xylene	1330-20-7	Methyl-hippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection
 Material : Nitrile rubber

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:
 Safety goggles

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340**g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : aerosol
- Propellant : Propane, Butane
- Color : blue
- Odor : aromatic
- Odor Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : -44 °C
- Flash point : -19 °C
Flash point is only valid for liquid portion in the aerosol can.
- Evaporation rate : Not applicable
- Flammability (solid, gas) : Extremely flammable aerosol.
- Upper explosion limit / Upper flammability limit : 10.9 %(V)
- Lower explosion limit / Lower flammability limit : 1.5 %(V)

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340**g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Vapor pressure	:	2,750 hPa
Relative vapor density	:	Not applicable
Relative density	:	0.77 - 0.85
Solubility(ies)	:	
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340

g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 40 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method

Components:**Acetone:**

Acute oral toxicity	:	LD50 (Rat): 5,800 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 76 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	:	LD50 (Rabbit): 7,426 mg/kg

Propane:

Acute inhalation toxicity	:	LC50 (Rat): > 800000 ppm Exposure time: 15 min Test atmosphere: gas
---------------------------	---	---

Butane:

Acute inhalation toxicity	:	LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: vapor
---------------------------	---	--

Solvent naphtha (petroleum), light aliphatic:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: vapor Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340

g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Assessment: The substance or mixture has no acute dermal toxicity

Remarks: Based on data from similar materials

Isobutyl acetate:

Acute oral toxicity : LD50 (Rat): 13,413 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

LC50 (Rat): 21.2 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 17,400 mg/kg

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.28 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Remarks: Based on data from similar materials

Toluene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Propan-2-ol:

**ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l
Exposure time: 6 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): 27.571 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg

Barium sulfate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

2-Methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC0 (Rat): 9.48 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:**Acetone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

Solvent naphtha (petroleum), light aliphatic:

Species : Rabbit
Result : No skin irritation

Isobutyl acetate:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Assessment : Repeated exposure may cause skin dryness or cracking.
Remarks : Based on harmonised classification in EU regulation
1272/2008, Annex VI

**ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Distillates (petroleum), hydrotreated light:

Species	:	Rabbit
Result	:	Skin irritation

Toluene:

Species	:	Rabbit
Method	:	Directive 67/548/EEC, Annex V, B.4.
Result	:	Skin irritation

Titanium dioxide:

Species	:	Rabbit
Result	:	No skin irritation

Propan-2-ol:

Species	:	Rabbit
Result	:	No skin irritation

Xylene:

Species	:	Rabbit
Result	:	Skin irritation

Barium sulfate:

Species	:	reconstructed human epidermis (RhE)
Method	:	OECD Test Guideline 439
Remarks	:	Based on data from similar materials
Result	:	No skin irritation

2-Methoxy-1-methylethyl acetate:

Species	:	Rabbit
Result	:	No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Acetone:**

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Method	:	OECD Test Guideline 405

Solvent naphtha (petroleum), light aliphatic:

Species	:	Rabbit
Result	:	No eye irritation

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340**g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Isobutyl acetate:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

Distillates (petroleum), hydrotreated light:

Species	:	Rabbit
Result	:	No eye irritation
Remarks	:	Based on data from similar materials

Toluene:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

Titanium dioxide:

Species	:	Rabbit
Result	:	No eye irritation

Propan-2-ol:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days

Xylene:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days

Barium sulfate:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

2-Methoxy-1-methylethyl acetate:

Species	:	Rabbit
Result	:	No eye irritation

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340

g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Components:**Acetone:**

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

Solvent naphtha (petroleum), light aliphatic:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative
Remarks	:	Based on data from similar materials

Isobutyl acetate:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

Distillates (petroleum), hydrotreated light:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative
Remarks	:	Based on data from similar materials

Toluene:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	Directive 67/548/EEC, Annex V, B.6.
Result	:	negative

Titanium dioxide:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Result	:	negative

Propan-2-ol:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340**g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Xylene:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Result	:	negative

Barium sulfate:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative
Remarks	:	Based on data from similar materials

2-Methoxy-1-methylethyl acetate:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Acetone:**

Genotoxicity in vitro	:	Test Type: In vitro mammalian cell gene mutation test Result: negative
-----------------------	---	---

	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
--	---	--

	:	Test Type: Chromosome aberration test in vitro Result: negative
--	---	--

Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Ingestion Result: negative
----------------------	---	--

Propane:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
-----------------------	---	--

Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 474
----------------------	---	--

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340**g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Result: negative

Butane:Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negativeGenotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials**Solvent naphtha (petroleum), light aliphatic:**Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negativeGenotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: Inhalation
Method: OPPTS 870.5395
Result: negative**Isobutyl acetate:**Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negativeTest Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materialsTest Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negativeGenotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials**Distillates (petroleum), hydrotreated light:**Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340

g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Toluene:

- Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
- Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
- Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Intraperitoneal injection
Result: negative
- Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: inhalation (vapor)
Method: OECD Test Guideline 478
Result: negative

Titanium dioxide:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
- Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Result: negative

Propan-2-ol:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
- Test Type: In vitro mammalian cell gene mutation test
Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Xylene:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
- Test Type: Chromosome aberration test in vitro
Result: negative
- Test Type: In vitro mammalian cell gene mutation test
Result: negative
- Test Type: In vitro sister chromatid exchange assay in mam-

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340

g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

malian cells
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Barium sulfate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

2-Methoxy-1-methylethyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Product:

Carcinogenicity - Assessment : No data available

Components:**Acetone:**

Species : Mouse
Application Route : Skin contact
Exposure time : 424 days
Result : negative

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340**g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Toluene:

Species	: Rat
Application Route	: inhalation (vapor)
Exposure time	: 103 weeks
Result	: negative

Species	: Mouse
Application Route	: Skin contact
Exposure time	: 24 Months
Result	: negative

Titanium dioxide:

Species	: Rat
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 2 Years
Method	: OECD Test Guideline 453
Result	: positive
Remarks	: The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment	: Limited evidence of carcinogenicity in inhalation studies with animals.
------------------------------	---

Propan-2-ol:

Species	: Rat
Application Route	: inhalation (vapor)
Exposure time	: 104 weeks
Method	: OECD Test Guideline 451
Result	: negative

Xylene:

Species	: Rat
Application Route	: Ingestion
Exposure time	: 103 weeks
Result	: negative

Barium sulfate:

Species	: Rat
Application Route	: Ingestion
Exposure time	: 2 Years
Result	: negative
Remarks	: Based on data from similar materials

2-Methoxy-1-methylethyl acetate:

Species	: Rat
Application Route	: inhalation (vapor)
Exposure time	: 2 Years
Result	: negative
Remarks	: Based on data from similar materials

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340**g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Reproductive toxicity

Suspected of damaging the unborn child.

Components:**Acetone:**

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Butane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Solvent naphtha (petroleum), light aliphatic:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340

g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Species: Rat
Application Route: inhalation (vapor)
Result: negative

Isobutyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OPPTS 870.3800
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Inhalation
Result: negative
Remarks: Based on data from similar materials

Toluene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340

g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Species: Rat
Application Route: inhalation (vapor)
Result: negative

Barium sulfate:

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

2-Methoxy-1-methylethyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

STOT-single exposure

May cause drowsiness or dizziness.

Components:**Acetone:**

Assessment : May cause drowsiness or dizziness.

Propane:

Assessment : May cause drowsiness or dizziness.

Butane:

Assessment : May cause drowsiness or dizziness.

Isobutyl acetate:

Assessment : May cause drowsiness or dizziness.
Remarks : Based on data from similar materials

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340**g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Distillates (petroleum), hydrotreated light:

Assessment : May cause drowsiness or dizziness.

Toluene:

Assessment : May cause drowsiness or dizziness.

Propan-2-ol:

Assessment : May cause drowsiness or dizziness.

Xylene:

Assessment : May cause respiratory irritation.

2-Methoxy-1-methylethyl acetate:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (Central nervous system, Kidney, Auditory system) through prolonged or repeated exposure.

Components:**Solvent naphtha (petroleum), light aliphatic:**

Target Organs	:	Central nervous system, Kidney
Assessment	:	Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Toluene:

Routes of exposure	:	Inhalation
Target Organs	:	Central nervous system
Assessment	:	May cause damage to organs through prolonged or repeated exposure.

Xylene:

Routes of exposure	:	inhalation (vapor)
Target Organs	:	Auditory system
Assessment	:	Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Barium sulfate:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340**g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Repeated dose toxicity**Components:****Acetone:**

Species	:	Rat
NOAEL	:	900 mg/kg
LOAEL	:	1,700 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days

Species	:	Rat
NOAEL	:	45 mg/l
Application Route	:	inhalation (vapor)
Exposure time	:	8 Weeks

Propane:

Species	:	Rat
NOAEL	:	7.214 mg/l
Application Route	:	inhalation (gas)
Exposure time	:	6 Weeks
Method	:	OECD Test Guideline 422

Butane:

Species	:	Rat
NOAEL	:	9000 ppm
Application Route	:	inhalation (gas)
Exposure time	:	6 Weeks
Method	:	OECD Test Guideline 422

Isobutyl acetate:

Species	:	Rat
NOAEL	:	> 100 mg/kg
Application Route	:	Ingestion
Exposure time	:	92 Days
Remarks	:	Based on data from similar materials

Species	:	Rat
NOAEL	:	> 2.4 mg/l
Application Route	:	inhalation (vapor)
Exposure time	:	13 Weeks
Remarks	:	Based on data from similar materials

Distillates (petroleum), hydrotreated light:

Species	:	Rat
NOAEL	:	750 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340**g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Toluene:

Species	: Rat
LOAEL	: 1.875 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 6 Months

Species	: Rat
NOAEL	: 625 mg/kg
Application Route	: Ingestion
Exposure time	: 13 Weeks

Titanium dioxide:

Species	: Rat
NOAEL	: 24,000 mg/kg
Application Route	: Ingestion
Exposure time	: 28 Days

Species	: Rat
NOAEL	: 10 mg/m ³
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 2 y

Propan-2-ol:

Species	: Rat
NOAEL	: 12.5 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 104 Weeks

Xylene:

Species	: Rat
LOAEL	: > 0.2 - 1 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 13 Weeks
Remarks	: Based on data from similar materials

Species	: Rat
LOAEL	: 150 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

Barium sulfate:

Species	: Rat
NOAEL	: 61.1 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days
Remarks	: Based on data from similar materials

2-Methoxy-1-methylethyl acetate:

Species	: Rat
NOAEL	: > 1,000 mg/kg

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340

g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Application Route : Ingestion
Exposure time : 41 - 45 Days
Method : OECD Test Guideline 422

Species : Mouse
NOAEL : 1.62 mg/l
Application Route : inhalation (vapor)
Exposure time : 2 y
Remarks : Based on data from similar materials

Species : Rabbit
NOAEL : > 1,838 mg/kg
Application Route : Skin contact
Exposure time : 90 Days
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Components:**Acetone:**

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Solvent naphtha (petroleum), light aliphatic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Distillates (petroleum), hydrotreated light:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Toluene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure**Components:****Toluene:**

Inhalation : Target Organs: Central nervous system
Symptoms: Neurological disorders

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Components:
Acetone:

- | | | |
|--|---|---|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia pulex (Water flea)): 8,800 mg/l
Exposure time: 48 h |
| Toxicity to algae/aquatic plants | : | NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOEC (Daphnia magna (Water flea)): >= 79 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211 |
| Toxicity to microorganisms | : | EC50: 61,150 mg/l
Exposure time: 30 min
Method: ISO 8192 |

Solvent naphtha (petroleum), light aliphatic:

- | | | |
|---|---|---|
| Toxicity to fish | : | LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials |
| Toxicity to daphnia and other aquatic invertebrates | : | EL50 (Daphnia magna (Water flea)): 4.5 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials |
| Toxicity to algae/aquatic plants | : | EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials |
| | | NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials |
| Toxicity to daphnia and other | : | NOELR (Daphnia magna (Water flea)): 2.6 mg/l |

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

aquatic invertebrates (Chronic toxicity) : Exposure time: 21 d
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 211
 Remarks: Based on data from similar materials

Isobutyl acetate:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): 16.6 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 24.6 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 196 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23.2 mg/l
 Exposure time: 21 d
 Method: OECD Test Guideline 211

Toxicity to microorganisms : EC10 (Pseudomonas putida): 487 mg/l
 Exposure time: 6 h

Distillates (petroleum), hydrotreated light:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l
 Exposure time: 96 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 203
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 1.4 mg/l
 Exposure time: 48 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 3 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

NOELR (Pseudokirchneriella subcapitata (green algae)): 1 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 0.48 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction

Toluene:

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l
Exposure time: 40 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): 0.74 mg/l
Exposure time: 7 d

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 84 mg/l
Exposure time: 24 h

Titanium dioxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

aquatic invertebrates Exposure time: 24 h

Toxicity to microorganisms : EC50 (*Pseudomonas putida*): > 1,050 mg/l
Exposure time: 16 h

Xylene:

Toxicity to fish : LC50 (*Oncorhynchus mykiss* (rainbow trout)): 13.5 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (*Daphnia magna* (Water flea)): > 1 - 10 mg/l
aquatic invertebrates Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic : EC50 (*Skeletonema costatum* (marine diatom)): 10 mg/l
plants Exposure time: 72 h

Toxicity to fish (Chronic tox- : NOEC (*Danio rerio* (zebra fish)): > 0.1 - < 1 mg/l
icity) Exposure time: 35 d
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EL10 (*Daphnia magna* (Water flea)): > 1 - 10 mg/l
aquatic invertebrates (Chron- Exposure time: 21 d
ic toxicity) Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Barium sulfate:

Toxicity to fish : LC50 (*Danio rerio* (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EC50 (*Daphnia magna* (Water flea)): > 10 - 100 mg/l
aquatic invertebrates Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic : NOEC (*Pseudokirchneriella subcapitata* (green algae)): > 1
plants mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

ErC50 (*Pseudokirchneriella subcapitata* (green algae)): > 100
mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): > 1 mg/l
 Exposure time: 33 d
 Method: OECD Test Guideline 210
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): > 1 mg/l
 Exposure time: 21 d
 Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 600 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209
 Remarks: Based on data from similar materials

NOEC: > 600 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209
 Remarks: Based on data from similar materials

2-Methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l
 Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (algae)): > 1,000 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 100 mg/l
 Exposure time: 21 d
 Method: OECD Test Guideline 211

Toxicity to microorganisms : EC10: > 1,000 mg/l
 Exposure time: 0.5 h

Persistence and degradability
Components:
Acetone:

Biodegradability : Result: Readily biodegradable.
 Biodegradation: 91 %

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340

g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Exposure time: 28 d

Propane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Butane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Solvent naphtha (petroleum), light aliphatic:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 60 %
Exposure time: 28 d
Remarks: Based on data from similar materials

Isobutyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 81 %
Exposure time: 20 d

Distillates (petroleum), hydrotreated light:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 58.6 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Toluene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 20 d

Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1.19 (BOD5)COD: 2.23BOD/COD: 53 %

Xylene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

**ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

2-Methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Bioaccumulative potential**Components:****Acetone:**

Partition coefficient: n- : log Pow: -0.27 - -0.23
octanol/water

Butane:

Partition coefficient: n- : log Pow: 2.31
octanol/water

Solvent naphtha (petroleum), light aliphatic:

Partition coefficient: n- : log Pow: > 4
octanol/water Remarks: Expert judgment

Isobutyl acetate:

Partition coefficient: n- : log Pow: 2.3
octanol/water

Toluene:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 90

Partition coefficient: n- : log Pow: 2.73
octanol/water

Propan-2-ol:

Partition coefficient: n- : log Pow: 0.05
octanol/water

Xylene:

Partition coefficient: n- : log Pow: 3.16
octanol/water Remarks: Calculation

Barium sulfate:

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)
Bioconcentration factor (BCF): < 500

Partition coefficient: n- : log Pow: -1.03

**ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

octanol/water Remarks: Calculation

2-Methoxy-1-methylethyl acetate:Partition coefficient: n- : log Pow: 1.2
octanol/water**Mobility in soil**

No data available

Other adverse effectsNo data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1**IATA-DGR**UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo : 203
aircraft)
Packing instruction (passen- : 203
ger aircraft)**IMDG-Code**UN number : UN 1950
Proper shipping name : AEROSOLS

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
g

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
EmS Code	:	F-D, S-U
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation
TDG

UN number	:	UN 1950
Proper shipping name	:	AEROSOLS

Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
ERG Code	:	126
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content	CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products VOC content: 45 % / 517.7 g/l
---	--

The ingredients of this product are reported in the following inventories:

DSL	:	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
-----	---	--

SECTION 16. OTHER INFORMATION
Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340
9

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/16/2021
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be

ENAMEL ENGINE PAINT, Gloss Ford Blue, 340**g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2020
3.1	09/16/2021	2053230-00004	Date of first issue: 10/10/2017

considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8