

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

---

### SECTION 1. IDENTIFICATION

Product name : HIGH-HEAT PAINT, Flat White, 425 g

Product code : 892.140026

Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée

Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1

Telephone : 1-800-263-5002

Telefax : 1-905-564-3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300

Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300

E-mail address : prodsafe@wurth.ca

#### Recommended use of the chemical and restrictions on use

Recommended use : Paint  
Coatings

Restrictions on use : Not applicable

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 1

Skin irritation : Category 2

Eye irritation : Category 2A

Carcinogenicity (Inhalation) : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 3  
- single exposure

Specific target organ toxicity : Category 2 (Central nervous system, Kidney, Auditory system)

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

- repeated exposure

### GHS label elements

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer if inhaled.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs (Central nervous system, Kidney, Auditory system) through prolonged or repeated exposure.

Precautionary Statements

: **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P332 + P313 If skin irritation occurs: Get medical attention.  
P337 + P313 If eye irritation persists: Get medical attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

### Storage:

P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version 1.0      Revision Date: 02/05/2025      SDS Number: 11508422-00001      Date of last issue: -  
Date of first issue: 02/05/2025

### Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Toluene	Benzene, methyl-	108-88-3	$\geq 10 - < 30$ *
Propane	Dimethylmethane	74-98-6	$\geq 10 - < 30$ *
Acetone	2-Propanone	67-64-1	$\geq 10 - < 30$ *
Butane	Butyl hydride	106-97-8	$\geq 10 - < 30$ *
Barium sulfate	Sulfuric acid, barium salt	7727-43-7	$\geq 5 - < 10$ *
Solvent naphtha (petroleum), light aliphatic	No data available	64742-89-8	$\geq 5 - < 10$ *
Titanium dioxide	Titanic anhydride	13463-67-7	$\geq 1 - < 5$ *
Xylene	Benzene, dimethyl-	1330-20-7	$\geq 1 - < 5$ *
2-Methoxy-1-methylethyl acetate	2-Propanol, 1-methoxy-, 2-acetate	108-65-6	$\geq 1 - < 5$ *
Distillates (petroleum), hydrotreated light	Isoparaffins petroleum hydrotreated HFP	64742-47-8	$\geq 1 - < 5$ *

\* Actual concentration or concentration range is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

- Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer if inhaled.  
Suspected of damaging the unborn child.  
May cause damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides  
Metal oxides  
Sulfur oxides  
Silicon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

Evacuate area.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.  
for fire-fighters Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.  
Do not breathe spray.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version 1.0      Revision Date: 02/05/2025      SDS Number: 11508422-00001      Date of last issue: -  
Date of first issue: 02/05/2025

Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.  
Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Do not pierce or burn, even after use.  
Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases

Recommended storage temperature : < 40 °C

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Toluene	108-88-3	TWA	50 ppm 188 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		TWA	20 ppm	ACGIH
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m <sup>3</sup>	CA QC OEL
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m <sup>3</sup>	CA AB OEL
		STEL	750 ppm	CA AB OEL

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version  
1.0

Revision Date:  
02/05/2025

SDS Number:  
11508422-00001

Date of last issue: -  
Date of first issue: 02/05/2025

			1,800 mg/m <sup>3</sup>	
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	250 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm 1,900 mg/m <sup>3</sup>	CA QC OEL
		STEL	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Barium sulfate	7727-43-7	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Inhalable)	5 mg/m <sup>3</sup>	CA BC OEL
		TWAEV (inhalable dust)	5 mg/m <sup>3</sup>	CA QC OEL
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH
Titanium dioxide	13463-67-7	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
Xylene	1330-20-7	TWA	100 ppm 434 mg/m <sup>3</sup>	CA AB OEL
		STEL	150 ppm 651 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	100 ppm 434 mg/m <sup>3</sup>	CA QC OEL
		STEV	150 ppm 651 mg/m <sup>3</sup>	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	20 ppm	ACGIH
2-Methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWA	50 ppm 270 mg/m <sup>3</sup>	CA ON OEL
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	CA BC OEL
		TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	CA AB OEL
		TWAEV	200 mg/m <sup>3</sup>	CA QC OEL
		TWA	525 mg/m <sup>3</sup>	CA ON OEL

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version 1.0      Revision Date: 02/05/2025      SDS Number: 11508422-00001      Date of last issue: -  
Date of first issue: 02/05/2025

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Xylene	1330-20-7	Methyl-hippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g cre-atinine	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

**Engineering measures** : Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version 1.0	Revision Date: 02/05/2025	SDS Number: 11508422-00001	Date of last issue: - Date of first issue: 02/05/2025
----------------	------------------------------	-------------------------------	--

Hand protection Material	:	Nitrile rubber
Remarks	:	Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!
Eye protection	:	Wear the following personal protective equipment: Safety goggles
Skin and body protection	:	Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Hygiene measures	:	If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aerosol containing a liquefied gas
Propellant	:	Propane, Butane
Color	:	white
Odor	:	aromatic
Odor Threshold	:	No data available
pH	:	Solvent mixture; pH value determination not possible, no aqueous solution
Melting point/freezing point	:	No data available

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

Initial boiling point and boiling range : -44 °C

Flash point : -19 °C

Flash point is only valid for liquid portion in the aerosol can.

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Self-ignition : not auto-flammable

Upper explosion limit / Upper flammability limit : 10.9 %(V)

Lower explosion limit / Lower flammability limit : 1.5 %(V)

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 0.77 - 0.85  
Reference substance: Water

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

Possibility of hazardous reactions : Extremely flammable aerosol.  
Vapors may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

#### Components:

##### **Toluene:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

##### **Propane:**

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm  
Exposure time: 15 min  
Test atmosphere: gas

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

---

### Acetone:

Acute oral toxicity	: LD50 (Rat): 5,800 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 76 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	: LD50 (Rabbit): 7,426 mg/kg

### Butane:

Acute inhalation toxicity	: LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: vapor
---------------------------	--

### Barium sulfate:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
---------------------	-----------------------------

### Solvent naphtha (petroleum), light aliphatic:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials
Acute inhalation toxicity	: LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: vapor Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials

### Titanium dioxide:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 6.82 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity

### Xylene:

Acute oral toxicity	: LD50 (Rat): 3,523 mg/kg Method: Directive 67/548/EEC, Annex V, B.1.
Acute inhalation toxicity	: LC50 (Rat): 27.571 mg/l Exposure time: 4 h

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg

### **2-Methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 (Rat, female): 5,155 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 9.34 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

### **Distillates (petroleum), hydrotreated light:**

Acute oral toxicity : LD50 (Rat): > 15,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.0 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### **Skin corrosion/irritation**

Causes skin irritation.

### **Components:**

#### **Toluene:**

Species : Rabbit  
Method : Directive 67/548/EEC, Annex V, B.4.  
Result : Skin irritation

#### **Acetone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

#### **Barium sulfate:**

Species : reconstructed human epidermis (RhE)  
Method : OECD Test Guideline 439  
Remarks : Based on data from similar materials

Result : No skin irritation

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

---

### **Solvent naphtha (petroleum), light aliphatic:**

Species	:	Rabbit
Result	:	No skin irritation

### **Titanium dioxide:**

Species	:	Rabbit
Result	:	No skin irritation

### **Xylene:**

Species	:	Rabbit
Result	:	Skin irritation

### **2-Methoxy-1-methylethyl acetate:**

Species	:	Rabbit
Result	:	No skin irritation

### **Distillates (petroleum), hydrotreated light:**

Assessment	:	Repeated exposure may cause skin dryness or cracking.
------------	---	---

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Components:**

#### **Toluene:**

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

#### **Acetone:**

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Method	:	OECD Test Guideline 405

#### **Barium sulfate:**

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

### **Solvent naphtha (petroleum), light aliphatic:**

Species	:	Rabbit
Result	:	No eye irritation

### **Titanium dioxide:**

Species	:	Rabbit
Result	:	No eye irritation

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

---

### Xylene:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days

### 2-Methoxy-1-methylethyl acetate:

Species	:	Rabbit
Result	:	No eye irritation

### Distillates (petroleum), hydrotreated light:

Species	:	Rabbit
Result	:	No eye irritation
Remarks	:	Based on data from similar materials

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

### Components:

#### Toluene:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	Directive 67/548/EEC, Annex V, B.6.
Result	:	negative

#### Acetone:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

#### Barium sulfate:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative
Remarks	:	Based on data from similar materials

#### Solvent naphtha (petroleum), light aliphatic:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative
Remarks	:	Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

---

### **Titanium dioxide:**

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Result	: negative

### **Xylene:**

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Result	: negative

### **2-Methoxy-1-methylethyl acetate:**

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

### **Distillates (petroleum), hydrotreated light:**

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative
Remarks	: Based on data from similar materials

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **Toluene:**

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative
-----------------------	---

	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
--	--

Genotoxicity in vivo	: Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat Application Route: Intraperitoneal injection Result: negative
----------------------	--

	: Test Type: Rodent dominant lethal test (germ cell) (in vivo) Species: Mouse Application Route: inhalation (vapor) Method: OECD Test Guideline 478 Result: negative
--	--



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

### Propane:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 474 Result: negative

### Acetone:

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative  Test Type: Bacterial reverse mutation assay (AMES) Result: negative  Test Type: Chromosome aberration test in vitro Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Ingestion Result: negative

### Butane:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

### Barium sulfate:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: Based on data from similar materials  Test Type: Chromosome aberration test in vitro Result: negative Remarks: Based on data from similar materials  Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
-----------------------	--

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

Remarks: Based on data from similar materials

### **Solvent naphtha (petroleum), light aliphatic:**

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Inhalation Method: OPPTS 870.5395 Result: negative

### **Titanium dioxide:**

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: In vivo micronucleus test Species: Mouse Result: negative

### **Xylene:**

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative  Test Type: Chromosome aberration test in vitro Result: negative  Test Type: In vitro mammalian cell gene mutation test Result: negative  Test Type: In vitro sister chromatid exchange assay in mammalian cells Result: negative
Genotoxicity in vivo	: Test Type: Rodent dominant lethal test (germ cell) (in vivo) Species: Mouse Application Route: Skin contact Result: negative

### **2-Methoxy-1-methylethyl acetate:**

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative  Test Type: Chromosome aberration test in vitro Result: negative  Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro) Result: negative
-----------------------	---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

### Distillates (petroleum), hydrotreated light:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro  
Species: Mouse  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

### Carcinogenicity

Suspected of causing cancer if inhaled.

### Components:

#### Toluene:

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 103 weeks  
Result : negative

Species : Mouse  
Application Route : Skin contact  
Exposure time : 24 Months  
Result : negative

#### Acetone:

Species : Mouse  
Application Route : Skin contact  
Exposure time : 424 days  
Result : negative

#### Barium sulfate:

Species : Rat  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative  
Remarks : Based on data from similar materials

#### Titanium dioxide:

Species : Rat  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years  
Method : OECD Test Guideline 453  
Result : positive  
Remarks : The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

---

### Xylene:

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	103 weeks
Result	:	negative

### 2-Methoxy-1-methylethyl acetate:

Species	:	Rat
Application Route	:	inhalation (vapor)
Exposure time	:	2 Years
Method	:	OECD Test Guideline 453
Result	:	negative
Remarks	:	Based on data from similar materials

### Distillates (petroleum), hydrotreated light:

Species	:	Rat
Application Route	:	inhalation (vapor)
Exposure time	:	105 weeks
Result	:	negative
Remarks	:	Based on data from similar materials

### Reproductive toxicity

Suspected of damaging the unborn child.

### Components:

#### Toluene:

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: inhalation (vapor) Method: OECD Test Guideline 416 Result: negative
----------------------	---	---

Effects on fetal development	:	Test Type: Embryo-fetal development Species: Rat Application Route: inhalation (vapor) Result: positive
------------------------------	---	--

Reproductive toxicity - Assessment	:	Some evidence of adverse effects on development, based on animal experiments.
------------------------------------	---	---

#### Propane:

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative
----------------------	---	--

Effects on fetal development	:	Test Type: Combined repeated dose toxicity study with the
------------------------------	---	---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

---

reproduction/developmental toxicity screening test

Species: Rat

Application Route: inhalation (gas)

Method: OECD Test Guideline 422

Result: negative

### Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### Butane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

### Barium sulfate:

Effects on fertility : Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative  
Remarks: Based on data from similar materials

### Solvent naphtha (petroleum), light aliphatic:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

---

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### **Xylene:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### **2-Methoxy-1-methylethyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 416  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### **Distillates (petroleum), hydrotreated light:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

### **STOT-single exposure**

May cause drowsiness or dizziness.

### **Components:**

#### **Toluene:**

Assessment : May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

### Propane:

Assessment : May cause drowsiness or dizziness.

### Acetone:

Assessment : May cause drowsiness or dizziness.

### Butane:

Assessment : May cause drowsiness or dizziness.

### Xylene:

Assessment : May cause respiratory irritation.

### 2-Methoxy-1-methylethyl acetate:

Assessment : May cause drowsiness or dizziness.

### STOT-repeated exposure

May cause damage to organs (Central nervous system, Kidney, Auditory system) through prolonged or repeated exposure.

### Components:

#### Toluene:

Routes of exposure : Inhalation  
Target Organs : Central nervous system  
Assessment : May cause damage to organs through prolonged or repeated exposure.

#### Barium sulfate:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

#### Solvent naphtha (petroleum), light aliphatic:

Target Organs : Central nervous system, Kidney  
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

#### Xylene:

Routes of exposure : inhalation (vapor)  
Target Organs : Auditory system  
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

### Repeated dose toxicity

### Components:

#### Toluene:

Species : Rat

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

LOAEL : 1.875 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 6 Months

Species : Rat  
NOAEL : 625 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks

### Propane:

Species : Rat  
NOAEL : 7.214 mg/l  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

### Acetone:

Species : Rat  
NOAEL : 900 mg/kg  
LOAEL : 1,700 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
NOAEL : 45 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 8 Weeks

### Butane:

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

### Barium sulfate:

Species : Rat  
NOAEL : 61.1 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

### Titanium dioxide:

Species : Rat  
NOAEL : 24,000 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days

Species : Rat  
NOAEL : 10 mg/m<sup>3</sup>



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 y

### Xylene:

Species : Rat  
LOAEL : > 0.2 - 1 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials

Species : Rat  
LOAEL : 150 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

### 2-Methoxy-1-methylethyl acetate:

Species : Rat  
NOAEL :  $\geq 1,000$  mg/kg  
Application Route : Ingestion  
Exposure time : 41 - 45 Days  
Method : OECD Test Guideline 422

Species : Rat  
NOAEL : > 1 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 2 y  
Method : OECD Test Guideline 453  
Remarks : Based on data from similar materials

Species : Rabbit  
NOAEL : > 200 mg/kg  
Application Route : Skin contact  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

### Distillates (petroleum), hydrotreated light:

Species : Rat  
NOAEL : > 10.4 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

### Aspiration toxicity

Not classified based on available information.

### Components:

#### Toluene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

### Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

### Solvent naphtha (petroleum), light aliphatic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### Distillates (petroleum), hydrotreated light:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### Experience with human exposure

#### Components:

##### Toluene:

Inhalation : Target Organs: Central nervous system  
Symptoms: Neurological disorders

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### Toluene:

Toxicity to fish	:	LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	NOEC (Skeletonema costatum (marine diatom)): 10 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l Exposure time: 40 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Ceriodaphnia dubia (water flea)): 0.74 mg/l Exposure time: 7 d
Toxicity to microorganisms	:	EC50 (Nitrosomonas sp.): 84 mg/l Exposure time: 24 h

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

### Acetone:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia pulex (Water flea)): 8,800 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): $\geq$ 79 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to microorganisms	:	EC50: 61,150 mg/l Exposure time: 30 min Method: ISO 8192

### Barium sulfate:

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l Exposure time: 48 h Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	:	NOEC (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
		ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): > 1 mg/l Exposure time: 21 d Remarks: Based on data from similar materials
Toxicity to microorganisms	:	EC50: > 600 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: Based on data from similar materials
		NOEC: > 600 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

Remarks: Based on data from similar materials

### **Solvent naphtha (petroleum), light aliphatic:**

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 4.5 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 2.6 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### **Titanium dioxide:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC50: > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

### **Xylene:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 mg/l  
Exposure time: 96 h

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l  
Exposure time: 72 h
- Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): > 0.1 - < 1 mg/l  
Exposure time: 35 d  
Method: OECD Test Guideline 210  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials
- Toxicity to microorganisms : NOEC: > 100 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials

### 2-Methoxy-1-methylethyl acetate:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l  
Exposure time: 48 h  
Method: Directive 67/548/EEC, Annex V, C.2.
- Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): > 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201
- NOEC (Raphidocelis subcapitata (freshwater green alga)): >= 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 100 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211
- Toxicity to microorganisms : EC10 (activated sludge): > 1,000 mg/l  
Exposure time: 30 min

### Distillates (petroleum), hydrotreated light:

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- NOELR (Pseudokirchneriella subcapitata (green algae)):  
1,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): > 1 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC50 (Pseudomonas putida): > 2 mg/l  
Exposure time: 5 h  
Remarks: Based on data from similar materials

### Persistence and degradability

#### Components:

##### **Toluene:**

- Biodegradability : Result: Readily biodegradable.  
Biodegradation: 80 %  
Exposure time: 20 d

##### **Propane:**

- Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

##### **Acetone:**

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 91 %  
Exposure time: 28 d

### Butane:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

### Solvent naphtha (petroleum), light aliphatic:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: > 60 %  
Exposure time: 28 d  
Remarks: Based on data from similar materials

### Xylene:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: > 70 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

### 2-Methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

### Distillates (petroleum), hydrotreated light:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 77.6 %  
Exposure time: 28 d

### Bioaccumulative potential

#### Components:

#### Toluene:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)  
Bioconcentration factor (BCF): 90

Partition coefficient: n-octanol/water : log Pow: 2.73

#### Acetone:

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

### Butane:

Partition coefficient: n-octanol/water : log Pow: 2.31

### Barium sulfate:

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)  
Bioconcentration factor (BCF): < 500

Partition coefficient: n-octanol/water : log Pow: -1.03  
Remarks: Calculation

### Solvent naphtha (petroleum), light aliphatic:

Partition coefficient: n-octanol/water : log Pow: > 4  
Remarks: Expert judgment

### Xylene:

Partition coefficient: n-octanol/water : log Pow: 3.16  
Remarks: Calculation

### 2-Methoxy-1-methylethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1.2

### Mobility in soil

No data available

### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues	: Do not dispose of waste into sewer.  Dispose of in accordance with local regulations.
Contaminated packaging	: Please ensure aerosol cans are sprayed completely empty (including propellant) Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
Environmentally hazardous	: no

##### IATA-DGR

UN/ID No.	: UN 1950
Proper shipping name	: Aerosols, flammable
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: Flammable Gas
Packing instruction (cargo aircraft)	: 203
Packing instruction (passenger aircraft)	: 203

##### IMDG-Code

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
EmS Code	: F-D, S-U
Marine pollutant	: no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### TDG

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
ERG Code	: 126
Marine pollutant	: no

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

### SECTION 15. REGULATORY INFORMATION

**The ingredients of this product are reported in the following inventories:**

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA ON OEL	: Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA AB OEL / STEL	: 15-minute occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average
CA BC OEL / STEL	: short-term exposure limit
CA ON OEL / TWA	: Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV	: Time-weighted average exposure value
CA QC OEL / STEV	: Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Develop-

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH-HEAT PAINT, Flat White, 425 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/05/2025	11508422-00001	Date of first issue: 02/05/2025

ment; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 02/05/2025  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8