

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

### SECTION 1. IDENTIFICATION

Product name : HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g  
Product code : 892.150025  
Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : 1-800-263-5002  
Telefax : 1-905-564-3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300

Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300

E-mail address : prodsafe@wurth.ca

#### Recommended use of the chemical and restrictions on use

Recommended use : Paint  
Restrictions on use : Not applicable

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 1  
Eye irritation : Category 2A  
Carcinogenicity : Category 2  
Reproductive toxicity : Category 1B  
Specific target organ toxicity - single exposure : Category 3  
Specific target organ toxicity - repeated exposure : Category 2 (Central nervous system, Kidney)

#### GHS label elements

Hazard pictograms :   

Signal Word : Danger

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

**Hazard Statements** : H222 Extremely flammable aerosol.  
H229 Pressurized container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H360D May damage the unborn child.  
H373 May cause damage to organs (Central nervous system, Kidney) through prolonged or repeated exposure.

**Precautionary Statements** : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.

**Response:**  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P337 + P313 If eye irritation persists: Get medical attention.

**Storage:**  
P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

**Disposal:**  
P501 Dispose of contents and container to an approved waste disposal plant.

### Other hazards

Repeated exposure may cause skin dryness or cracking.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
---------------	---------------------	---------	-----------------------

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

Acetone	2-Propanone	67-64-1	21.88
Propane	Dimethylmethane	74-98-6	15.81
Limestone	Calcium carbonate	1317-65-3	11.26
Butane	Butyl hydride	106-97-8	9.29
2-Methoxy-1-methylethyl acetate	2-Propanol, 1-methoxy-, 2-acetate	108-65-6	5.51
Toluene	Benzene, methyl-	108-88-3	4.81
Titanium dioxide	Titanic anhydride	13463-67-7	2.49
Isobutyl methyl ketone	4-Methylpentan-2-one	108-10-1	2.07
Pentan-2-one	Methyl propyl ketone	107-87-9	1.77
Isobutyl acetate	Acetic acid, 2-methylpropyl ester	110-19-0	1.65
Silica gel, precipitated, crystalline free	Amorphous precipitated silica	112926-00-8	1.51
2-(Propoxy)ethanol	Ethanol, 2-propoxy-	2807-30-9	1.25
Solvent naphtha (petroleum), light aliphatic	No data available	64742-89-8	1.09
Zirconium octoate	Hexanoic acid, 2-ethyl-, zirconium salt	22464-99-9	0.17

### SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

- 
- |   |   |  |
|---|---|--|
| Most important symptoms and effects, both acute and delayed | : | Prolonged or repeated contact may dry skin and cause irritation.<br>Causes serious eye irritation.<br>May cause drowsiness or dizziness.<br>Suspected of causing cancer.<br>May damage the unborn child.<br>May cause damage to organs through prolonged or repeated exposure. |
| Protection of first-aiders                                  | : | First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).  |
| Notes to physician  | : | Treat symptomatically and supportively.  |
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- |  |   |   |
|--|---|---|
| Suitable extinguishing media                   | : | Water spray<br>Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical  |
| Unsuitable extinguishing media                 | : | None known.   |
| Specific hazards during fire fighting          | : | Flash back possible over considerable distance.<br>Vapors may form explosive mixtures with air.<br>Exposure to combustion products may be a hazard to health.<br>If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. |
| Hazardous combustion products                  | : | Carbon oxides<br>Metal oxides   |
| Specific extinguishing methods                 | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.<br>Use water spray to cool unopened containers.<br>Remove undamaged containers from fire area if it is safe to do so.<br>Evacuate area.                   |
| Special protective equipment for fire-fighters | : | In the event of fire, wear self-contained breathing apparatus.<br>Use personal protective equipment.  |
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- |   |   |   |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Remove all sources of ignition.<br>Use personal protective equipment.<br>Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8). |
| Environmental precautions   | : | Avoid release to the environment.<br>Prevent further leakage or spillage if safe to do so.<br>Prevent spreading over a wide area (e.g., by containment or                               |
-

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

---

oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.  
Do not breathe spray.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep container tightly closed.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.  
Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Do not pierce or burn, even after use.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

Materials to avoid : Keep cool. Protect from sunlight.  
: Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases

Recommended storage temperature : < 40 °C

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m <sup>3</sup>	CA AB OEL
		STEL	750 ppm 1,800 mg/m <sup>3</sup>	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	250 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
Limestone	1317-65-3	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		STEL	20 mg/m <sup>3</sup>	CA BC OEL
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm 1,900 mg/m <sup>3</sup>	CA QC OEL
		STEL	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
2-Methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm	CA BC OEL

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version  
8.0

Revision Date:  
11/05/2025

SDS Number:  
10788988-00011

Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

		STEL	75 ppm	CA BC OEL
		TWA	50 ppm 270 mg/m <sup>3</sup>	CA ON OEL
Toluene	108-88-3	TWA	50 ppm 188 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		TWA	20 ppm	ACGIH
Titanium dioxide	13463-67-7	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
Isobutyl methyl ketone	108-10-1	TWA	50 ppm 205 mg/m <sup>3</sup>	CA AB OEL
		STEL	75 ppm 307 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		STEV	75 ppm	CA QC OEL
		TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
Pentan-2-one	107-87-9	TWA	200 ppm 705 mg/m <sup>3</sup>	CA AB OEL
		STEL	250 ppm 881 mg/m <sup>3</sup>	CA AB OEL
		TWA	150 ppm	CA BC OEL
		STEL	250 ppm	CA BC OEL
		STEV	150 ppm	CA QC OEL
		STEL	150 ppm	ACGIH
Isobutyl acetate	110-19-0	TWA	150 ppm 713 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	150 ppm	CA QC OEL
		TWA	50 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Silica gel, precipitated, crystalline free	112926-00-8	TWA (Respirable)	1.5 mg/m <sup>3</sup>	CA BC OEL
		TWA (Total)	4 mg/m <sup>3</sup>	CA BC OEL
2-(Propyloxy)ethanol	2807-30-9	TWA	25 ppm 110 mg/m <sup>3</sup>	CA ON OEL
Zirconium octoate	22464-99-9	TWA	5 mg/m <sup>3</sup> (Zirconium)	CA AB OEL
		STEL	10 mg/m <sup>3</sup>	CA AB OEL

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

			(Zirconium)	
		TWAEV	5 mg/m <sup>3</sup> (Zirconium)	CA QC OEL
		STEV	10 mg/m <sup>3</sup> (Zirconium)	CA QC OEL
		TWA	5 mg/m <sup>3</sup> (Zirconium)	CA BC OEL
		STEL	10 mg/m <sup>3</sup> (Zirconium)	CA BC OEL
		TWA	5 mg/m <sup>3</sup> (Zirconium)	ACGIH
		STEL	10 mg/m <sup>3</sup> (Zirconium)	ACGIH

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI
Isobutyl methyl ketone	108-10-1	methyl isobutyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

**Engineering measures** : Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Nitrile rubber

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : aerosol

Propellant : Propane, Butane

Color : blue

Odor : aromatic

Odor Threshold : No data available

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

---

pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	-44 °C
Flash point	:	-19 °C Flash point is only valid for liquid portion in the aerosol can.
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	10.9 %(V)
Lower explosion limit / Lower flammability limit	:	1.7 %(V)
Vapor pressure	:	2,750 hPa
Relative vapor density	:	Not applicable
Relative density	:	0.77 - 0.85
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	:	Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

Possibility of hazardous reactions : Extremely flammable aerosol.  
Vapors may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.  
Incompatible materials : Oxidizing agents  
Hazardous decomposition products : No hazardous decomposition products are known.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

#### Components:

##### Acetone:

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

##### Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm  
Exposure time: 15 min  
Test atmosphere: gas

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

### Limestone:

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### Butane:

- Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

### 2-Methoxy-1-methylethyl acetate:

- Acute oral toxicity : LD50 (Rat, female): 5,155 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 9.34 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

### Toluene:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

### Titanium dioxide:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 425

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

Acute inhalation toxicity : LC50 (Rat): > 5.09 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: The test was conducted according to guideline

### Isobutyl methyl ketone:

Acute oral toxicity : LD50 (Rat): 2,080 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Expert judgment

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

### Pentan-2-one:

Acute oral toxicity : LD50 (Rat): 1,600 - 3,200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25.5 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 436

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: Based on data from similar materials

### Isobutyl acetate:

Acute oral toxicity : LD50 (Rat): 13,413 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

LC50 (Rat): 21.2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 17,400 mg/kg

### Silica gel, precipitated, crystalline free:

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

---

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 0.69 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: Based on data from similar materials

### **2-(Propyloxy)ethanol:**

Acute oral toxicity : LD50 (Mouse): 3,089 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 1,337 mg/kg

### **Solvent naphtha (petroleum), light aliphatic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### **Zirconium octoate:**

Acute oral toxicity : LD50 (Rat): 2,043 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4.3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 436  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

### Skin corrosion/irritation

Not classified based on available information.

### Components:

#### Acetone:

Assessment : Repeated exposure may cause skin dryness or cracking.

#### Limestone:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

#### 2-Methoxy-1-methylethyl acetate:

Species : Rabbit  
Result : No skin irritation

#### Toluene:

Species : Rabbit  
Method : Directive 67/548/EEC, Annex V, B.4.  
Result : Skin irritation

#### Titanium dioxide:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : The test was conducted equivalent or similar to guideline

#### Isobutyl methyl ketone:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

#### Pentan-2-one:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

#### Isobutyl acetate:

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

Assessment : Repeated exposure may cause skin dryness or cracking.  
Remarks : Based on national or regional regulation.

### **Silica gel, precipitated, crystalline free:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

### **2-(Propyloxy)ethanol:**

Species : Rabbit  
Result : No skin irritation

### **Solvent naphtha (petroleum), light aliphatic:**

Species : Rabbit  
Result : No skin irritation

### **Zirconium octoate:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Components:**

#### **Acetone:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Method : OECD Test Guideline 405

#### **Limestone:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

#### **2-Methoxy-1-methylethyl acetate:**

Species : Rabbit  
Result : No eye irritation

#### **Toluene:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

### Titanium dioxide:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : The test was conducted according to guideline

### Isobutyl methyl ketone:

Species : Human  
Result : Irritation to eyes, reversing within 21 days

### Pentan-2-one:

Species : Rabbit  
Result : Irritation to eyes, reversing within 7 days

### Isobutyl acetate:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

### Silica gel, precipitated, crystalline free:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

### 2-(Propyloxy)ethanol:

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

### Solvent naphtha (petroleum), light aliphatic:

Species : Rabbit  
Result : No eye irritation

### Zirconium octoate:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

### Components:

#### **Acetone:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

#### **Limestone:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative  
Remarks : Based on data from similar materials

#### **2-Methoxy-1-methylethyl acetate:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### **Toluene:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : Directive 67/548/EEC, Annex V, B.6.  
Result : negative

#### **Titanium dioxide:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative  
Remarks : The test was conducted according to guideline

#### **Isobutyl methyl ketone:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### **Pentan-2-one:**

Test Type : Buehler Test  
Routes of exposure : Skin contact

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative  
Remarks : Based on data from similar materials

### **Isobutyl acetate:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### **2-(Propyloxy)ethanol:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### **Solvent naphtha (petroleum), light aliphatic:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

### **Zirconium octoate:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **Acetone:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo)

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

### Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

### Limestone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

### Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

### 2-Methoxy-1-methylethyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)

Result: negative

### **Toluene:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: Intraperitoneal injection  
Result: negative

Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 478  
Result: negative

### **Titanium dioxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: The test was conducted according to guideline

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: The test was conducted according to guideline

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
Remarks: The test was conducted according to guideline

Genotoxicity in vivo : Test Type: Transgenic rodent somatic cell gene mutation assay  
Species: Mouse (male)  
Application Route: Intravenous injection  
Method: OECD Test Guideline 488  
Result: negative  
Remarks: The test was conducted equivalent or similar to guideline

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

### Isobutyl methyl ketone:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative
- Test Type: In vitro mammalian cell gene mutation test  
Result: equivocal
- Test Type: Chromosome aberration test in vitro  
Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative

### Pentan-2-one:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: Directive 67/548/EEC, Annex V, B.13/14.  
Result: negative
- Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative
- Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative  
Remarks: Based on data from similar materials

### Isobutyl acetate:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative
- Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials
- Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

---

cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

### **Silica gel, precipitated, crystalline free:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

### **2-(Propyloxy)ethanol:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

### **Solvent naphtha (petroleum), light aliphatic:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Rat  
Application Route: Inhalation  
Method: OPPTS 870.5395  
Result: negative

### **Zirconium octoate:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

---

cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

### **Carcinogenicity**

Suspected of causing cancer.

### **Components:**

#### **Acetone:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 424 days  
Result : negative

#### **2-Methoxy-1-methylethyl acetate:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 453  
Result : negative  
Remarks : Based on data from similar materials

#### **Toluene:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 103 weeks  
Result : negative

Species : Mouse  
Application Route : Skin contact  
Exposure time : 24 Months  
Result : negative

#### **Isobutyl methyl ketone:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : positive

Species : Mouse  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : positive

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

### **Silica gel, precipitated, crystalline free:**

Species : Rat  
Application Route : Ingestion  
Exposure time : 103 weeks  
Result : negative  
Remarks : Based on data from similar materials

### **Reproductive toxicity**

May damage the unborn child.

### **Components:**

#### **Acetone:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

#### **Propane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

#### **Limestone:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

### **Butane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

### **2-Methoxy-1-methylethyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 416  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### **Toluene:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 416  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

### **Titanium dioxide:**

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

Effects on fertility : Test Type: Extended one-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 443  
Result: negative  
Remarks: The test was conducted according to guideline

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative  
Remarks: The test was conducted according to guideline

### **Isobutyl methyl ketone:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### **Pentan-2-one:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 421  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 414  
Result: negative

### **Isobutyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OPPTS 870.3800  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

---

Application Route: Inhalation  
Result: negative  
Remarks: Based on data from similar materials

### **Silica gel, precipitated, crystalline free:**

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

### **2-(Propyloxy)ethanol:**

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rabbit  
Application Route: inhalation (vapor)  
Result: negative

### **Solvent naphtha (petroleum), light aliphatic:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### **Zirconium octoate:**

Effects on fertility : Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: positive  
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Clear evidence of adverse effects on development, based on animal experiments.  
Remarks: Based on data from similar materials

### **STOT-single exposure**

May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

### Components:

#### **Acetone:**

Assessment : May cause drowsiness or dizziness.

#### **Propane:**

Assessment : May cause drowsiness or dizziness.

#### **Butane:**

Assessment : May cause drowsiness or dizziness.

#### **2-Methoxy-1-methylethyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **Toluene:**

Assessment : May cause drowsiness or dizziness.

#### **Isobutyl methyl ketone:**

Assessment : May cause drowsiness or dizziness.

#### **Isobutyl acetate:**

Assessment : May cause drowsiness or dizziness.  
Remarks : Based on data from similar materials

### **STOT-repeated exposure**

May cause damage to organs (Central nervous system, Kidney) through prolonged or repeated exposure.

### Components:

#### **Toluene:**

Routes of exposure : Inhalation  
Target Organs : Central nervous system  
Assessment : May cause damage to organs through prolonged or repeated exposure.

#### **Solvent naphtha (petroleum), light aliphatic:**

Target Organs : Central nervous system, Kidney  
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

### Repeated dose toxicity

#### Components:

##### **Acetone:**

Species : Rat  
NOAEL : 900 mg/kg  
LOAEL : 1,700 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
NOAEL : 45 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 8 Weeks

##### **Propane:**

Species : Rat  
NOAEL : 7.214 mg/l  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

##### **Limestone:**

Species : Rat  
NOAEL : > 300 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days  
Method : OECD Test Guideline 422  
Remarks : Based on data from similar materials

##### **Butane:**

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

##### **2-Methoxy-1-methylethyl acetate:**

Species : Rat  
NOAEL :  $\geq$  1,000 mg/kg  
Application Route : Ingestion  
Exposure time : 41 - 45 Days  
Method : OECD Test Guideline 422

Species : Rat  
NOAEL : > 1 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 2 y  
Method : OECD Test Guideline 453

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

Remarks : Based on data from similar materials

Species : Rabbit  
NOAEL : > 200 mg/kg  
Application Route : Skin contact  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

### **Toluene:**

Species : Rat  
LOAEL : 1.875 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 6 Months

Species : Rat  
NOAEL : 625 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks

### **Titanium dioxide:**

Species : Rat  
NOAEL :  $\geq 1,000$  mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408  
Remarks : The test was conducted according to guideline

### **Isobutyl methyl ketone:**

Species : Rat  
NOAEL : 250 mg/kg  
LOAEL : 1,000 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks

Species : Rat  
NOAEL : 4.106 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 14 Weeks

### **Pentan-2-one:**

Species : Rat  
NOAEL : 5.28 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks  
Method : OECD Test Guideline 413

### **Isobutyl acetate:**

Species : Rat

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

---

NOAEL : > 100 mg/kg  
Application Route : Ingestion  
Exposure time : 92 Days  
Remarks : Based on data from similar materials

Species : Rat  
NOAEL : > 2.4 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials

### **Silica gel, precipitated, crystalline free:**

Species : Rat  
NOAEL : > 4,500 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

### **2-(Propyloxy)ethanol:**

Species : Rat  
LOAEL : 195 mg/kg  
Application Route : Ingestion  
Exposure time : 6 Weeks

### **Zirconium octoate:**

Species : Rat  
NOAEL : 300 mg/kg  
Application Route : Ingestion  
Exposure time : 91 - 93 Days  
Remarks : Based on data from similar materials

### **Aspiration toxicity**

Not classified based on available information.

### **Components:**

#### **Acetone:**

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

#### **Toluene:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **Isobutyl methyl ketone:**

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

### **Pentan-2-one:**

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

### **Solvent naphtha (petroleum), light aliphatic:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### **Experience with human exposure**

#### **Components:**

##### **Toluene:**

Inhalation : Target Organs: Central nervous system  
Symptoms: Neurological disorders

## SECTION 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

#### **Components:**

##### **Acetone:**

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia pulex (Water flea)): 8,800 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): >= 79 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to microorganisms	:	EC50: 61,150 mg/l Exposure time: 30 min Method: ISO 8192

##### **Limestone:**

Toxicity to fish	:	LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	LL50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 14 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: No toxicity at the limit of solubility.  
Based on data from similar materials

EL10 (Desmodesmus subspicatus (green algae)): > 14 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: No toxicity at the limit of solubility.  
Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials

### **2-Methoxy-1-methylethyl acetate:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l  
Exposure time: 48 h  
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): > 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

NOEC (Raphidocelis subcapitata (freshwater green alga)): >= 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 100 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC10 (activated sludge): > 1,000 mg/l  
Exposure time: 30 min

### **Toluene:**

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

- Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l  
Exposure time: 48 h
- Toxicity to algae/aquatic plants : NOEC (Skeletonema costatum (marine diatom)): 10 mg/l  
Exposure time: 72 h
- Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l  
Exposure time: 40 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): 0.74 mg/l  
Exposure time: 7 d
- Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 84 mg/l  
Exposure time: 24 h

### Titanium dioxide:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: The test was conducted according to guideline  
Based on transformation/dissolution testing and data from soluble metal compounds
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: The test was conducted according to guideline
- Toxicity to algae/aquatic plants : EL50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: The test was conducted according to guideline
- NOELR (Raphidocelis subcapitata (freshwater green alga)): >= 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: The test was conducted according to guideline
- Toxicity to microorganisms : NOEC (activated sludge): >= 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: The test was conducted according to guideline

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

### Isobutyl methyl ketone:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 179 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 200 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 30 mg/l  
Exposure time: 21 d

### Pentan-2-one:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1,240 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 110 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 150 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 73.77 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

### Isobutyl acetate:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): 16.6 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 24.6 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 196 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

---

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23.2 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC10 (Pseudomonas putida): 487 mg/l  
Exposure time: 6 h

### **Silica gel, precipitated, crystalline free:**

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 10,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Scenedesmus subspicatus): > 10,000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

### **2-(Propyloxy)ethanol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 5,000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 5,000 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : IC50: > 1,000 mg/l  
Exposure time: 16 h

### **Solvent naphtha (petroleum), light aliphatic:**

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): 4.5 mg/l

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

- aquatic invertebrates      Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants      :    EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)      :    NOELR (Daphnia magna (Water flea)): 2.6 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials
- Zirconium octoate:**
- Toxicity to fish      :    LC50 (Oncorhynchus mykiss (rainbow trout)): 180 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates      :    EC50 (Daphnia magna (Water flea)): > 0.17 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: No toxicity at the limit of solubility.
- Toxicity to algae/aquatic plants      :    EC50 (Desmodesmus subspicatus (green algae)): 49.3 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials
- EC10 (Desmodesmus subspicatus (green algae)): 32 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)      :    NOEC (Daphnia magna (Water flea)): 25 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials
- Toxicity to microorganisms      :    EC50 (Pseudomonas putida): 112.1 mg/l  
Exposure time: 17 h  
Method: DIN 38 412 Part 8  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

---

### Persistence and degradability

#### Components:

##### **Acetone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 91 %  
Exposure time: 28 d

##### **Propane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

##### **Butane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

##### **2-Methoxy-1-methylethyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **Toluene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 80 %  
Exposure time: 20 d

##### **Isobutyl methyl ketone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **Pentan-2-one:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 70 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

##### **Isobutyl acetate:**

Biodegradability : Result: Readily biodegradable.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

---

Biodegradation: 81 %  
Exposure time: 20 d

### 2-(Propyloxy)ethanol:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 20 d

### Solvent naphtha (petroleum), light aliphatic:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: > 60 %  
Exposure time: 28 d  
Remarks: Based on data from similar materials

### Zirconium octoate:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 99 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301E  
Remarks: Based on data from similar materials

### Bioaccumulative potential

#### Components:

##### Acetone:

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

##### Butane:

Partition coefficient: n-octanol/water : log Pow: 2.31

##### 2-Methoxy-1-methylethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1.2

##### Toluene:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)  
Bioconcentration factor (BCF): 90

Partition coefficient: n-octanol/water : log Pow: 2.73

##### Isobutyl methyl ketone:

Partition coefficient: n-octanol/water : log Pow: 1.9

##### Pentan-2-one:

Partition coefficient: n-octanol/water : log Pow: 0.857

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

### Isobutyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2.3

### 2-(Propyloxy)ethanol:

Partition coefficient: n-octanol/water : log Pow: 0.673

### Solvent naphtha (petroleum), light aliphatic:

Partition coefficient: n-octanol/water : log Pow: > 4  
Remarks: Expert judgment

### Mobility in soil

No data available

### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.  
Please ensure aerosol cans are sprayed completely empty (including propellant)

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
Environmentally hazardous : no

#### IATA-DGR

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

### IMDG-Code

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### TDG

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
ERG Code : 126  
Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

**Volatile organic compounds (VOC) content** : CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products  
VOC content: 48 % / 433.5 g/l

### The ingredients of this product are reported in the following inventories:

CA. DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

### Canadian lists

|| No substances are subject to CEPA Section 84 Ministerial Conditions.

---

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version 8.0      Revision Date: 11/05/2025      SDS Number: 10788988-00011      Date of last issue: 06/26/2025  
Date of first issue: 12/07/2017

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AllC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH SOLIDS ENAMEL PAINT, Gloss Lift Blue, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/26/2025
8.0	11/05/2025	10788988-00011	Date of first issue: 12/07/2017

---

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/05/2025  
Date format : mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8