

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MULTIPURPOSE SILICONE, Neutral, Grey, 300 mL

Version 1.0 Revision Date: 11/28/2025 SDS Number: 11601280-00001 Date of last issue: -
Date of first issue: 11/28/2025

SECTION 1. IDENTIFICATION

Product name : MULTIPURPOSE SILICONE, Neutral, Grey, 300 mL
Product code : 892.560002
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : 1-800-263-5002
Telefax : 1-905-564-3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300

Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives and/or sealants
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Skin sensitization : Sub-category 1A
Carcinogenicity : Category 1B
Specific target organ toxicity : Category 2 (Blood)
- repeated exposure

GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.
H350 May cause cancer.
H373 May cause damage to organs (Blood) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MULTIPURPOSE SILICONE, Neutral, Grey, 300 mL

Version 1.0 Revision Date: 11/28/2025 SDS Number: 11601280-00001 Date of last issue: -
Date of first issue: 11/28/2025

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe vapors.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P308 + P313 IF exposed or concerned: Get medical attention.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
2-Propanone, 2,2',2''-[O,O',O''-(ethylsilyldyne)trioxime]	Ethyl-tris(acetonoxim)-silan	58190-57-1	$\geq 1 - < 5$ *
3-(2-Aminoethylamino)propyltrimethoxysilane	1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	1760-24-3	$\geq 0.1 - < 1$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MULTIPURPOSE SILICONE, Neutral, Grey, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/28/2025	11601280-00001	Date of first issue: 11/28/2025

If inhaled	:	If inhaled, remove to fresh air. Get medical attention.
In case of skin contact	:	In case of contact, immediately flush skin with soap and plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact	:	Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	:	If swallowed, DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	:	May cause an allergic skin reaction. May cause cancer. May cause damage to organs through prolonged or repeated exposure. No information available.
Protection of first-aiders	:	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
Notes to physician	:	Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Not applicable Will not burn
Unsuitable extinguishing media	:	Not applicable Will not burn
Specific hazards during fire fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion products	:	Carbon oxides Silicon oxides Nitrogen oxides (NOx)
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency measures	:	Use personal protective equipment. Follow safe handling advice (see section 7) and personal
---	---	--

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MULTIPURPOSE SILICONE, Neutral, Grey, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/28/2025	11601280-00001	Date of first issue: 11/28/2025

Further information on storage stability : Keep away from direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection

Material : butyl-rubber

Break through time : 120 - 480 min

Glove thickness : 0.5 - 1 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : gray

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MULTIPURPOSE SILICONE, Neutral, Grey, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/28/2025	11601280-00001	Date of first issue: 11/28/2025

Odor	:	characteristic
Odor Threshold	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	No data available
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Will not burn
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	1.30 - 1.36 g/cm ³
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics	:	
Particle size	:	Not applicable

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MULTIPURPOSE SILICONE, Neutral, Grey, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/28/2025	11601280-00001	Date of first issue: 11/28/2025

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : Hazardous decomposition products will be formed upon contact with water or humid air.

Conditions to avoid : Exposure to moisture.
Incompatible materials : Water

Hazardous decomposition products
Contact with water or humid air : Acetone oxime

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylydyne)trioxime]:

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: The test was conducted equivalent or similar to guideline
Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 1,000 - 2,000 mg/kg
Method: OECD Test Guideline 402
Remarks: The test was conducted equivalent or similar to guideline
Based on data from similar materials

3-(2-Aminoethylamino) propyltrimethoxysilane:

Acute oral toxicity : LD50 (Rat, female): 1,897 mg/kg
Method: OPPTS 870.1100

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MULTIPURPOSE SILICONE, Neutral, Grey, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/28/2025	11601280-00001	Date of first issue: 11/28/2025

Acute toxicity estimate (Humans): > 300 - 2,000 mg/kg
Method: Expert judgment
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): 1.49 - 2.44 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OPPTS 870.1300

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OPPTS 870.1200

Skin corrosion/irritation

Not classified based on available information.

Components:

2-Propanone, 2,2',2"-[O,O',O''-(ethylsilylidyne)trioxime]:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439
Result : No skin irritation
Remarks : The test was conducted according to guideline

3-(2-Aminoethylamino) propyltrimethoxysilane:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Mild skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

2-Propanone, 2,2',2"-[O,O',O''-(ethylsilylidyne)trioxime]:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : The test was conducted according to guideline

3-(2-Aminoethylamino) propyltrimethoxysilane:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MULTIPURPOSE SILICONE, Neutral, Grey, 300 mL

Version 1.0 Revision Date: 11/28/2025 SDS Number: 11601280-00001 Date of last issue: -
Date of first issue: 11/28/2025

Respiratory sensitization

Not classified based on available information.

Components:

2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime]:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : positive
Remarks : The test was conducted equivalent or similar to guideline
Based on data from similar materials

Assessment : Probability or evidence of skin sensitization in humans

3-(2-Aminoethylamino) propyltrimethoxysilane:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : positive

Assessment : Probability or evidence of high skin sensitization rate in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime]:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: The test was conducted according to guideline
Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: The test was conducted according to guideline
Based on data from similar materials

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: The test was conducted according to guideline
Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MULTIPURPOSE SILICONE, Neutral, Grey, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/28/2025	11601280-00001	Date of first issue: 11/28/2025

3-(2-Aminoethylamino) propyltrimethoxysilane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Method: OPPTS 870.5900
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

May cause cancer.

Components:

2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime]:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 26 Months
Method : OECD Test Guideline 453
Result : positive
Remarks : The test was conducted equivalent or similar to guideline
Based on data from similar materials

Carcinogenicity - Assessment : Sufficient evidence of carcinogenicity in animal experiments
Remarks: Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime]:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MULTIPURPOSE SILICONE, Neutral, Grey, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/28/2025	11601280-00001	Date of first issue: 11/28/2025

Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: The test was conducted according to guideline
Based on data from similar materials

3-(2-Aminoethylamino) propyltrimethoxysilane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

STOT-single exposure

Not classified based on available information.

Components:

2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime]:

Assessment : May cause drowsiness or dizziness.

3-(2-Aminoethylamino) propyltrimethoxysilane:

Routes of exposure : Ingestion
Target Organs : Central nervous system, optic nerve
Assessment : May cause damage to organs.
Remarks : Based on data from similar materials

STOT-repeated exposure

May cause damage to organs (Blood) through prolonged or repeated exposure.

Components:

2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime]:

Routes of exposure : Ingestion
Target Organs : Blood
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.
Remarks : Based on data from similar materials

3-(2-Aminoethylamino) propyltrimethoxysilane:

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Respiratory Tract
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MULTIPURPOSE SILICONE, Neutral, Grey, 300 mL

Version 1.0 Revision Date: 11/28/2025 SDS Number: 11601280-00001 Date of last issue: -
Date of first issue: 11/28/2025

Repeated dose toxicity

Components:

2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime]:

Species : Rat
LOAEL : > 10 - 100 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408
Remarks : The test was conducted according to guideline
Based on data from similar materials

3-(2-Aminoethylamino) propyltrimethoxysilane:

Species : Rat
NOAEL : >= 500 mg/kg
Application Route : Ingestion
Exposure time : 44 Days

Species : Rat
NOAEL : 0.015 mg/l
LOAEL : 0.045 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 13 Weeks
Method : OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime]:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: The test was conducted equivalent or similar to guideline
Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: The test was conducted according to guideline
Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MULTIPURPOSE SILICONE, Neutral, Grey, 300 mL

Version 1.0 Revision Date: 11/28/2025 SDS Number: 11601280-00001 Date of last issue: -
Date of first issue: 11/28/2025

- Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: The test was conducted according to guideline
Based on data from similar materials
- NOEC (Raphidocelis subcapitata (freshwater green alga)): > 1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: The test was conducted according to guideline
Based on data from similar materials
- Toxicity to microorganisms : EC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: The test was conducted according to guideline
Based on data from similar materials

3-(2-Aminoethylamino) propyltrimethoxysilane:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: Directive 67/548/EEC, Annex V, C.1.
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: Directive 67/548/EEC, Annex V, C.2.
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 10 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOEC (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): > 1 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC10 (Pseudomonas putida): > 1 mg/l
Exposure time: 16 h
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MULTIPURPOSE SILICONE, Neutral, Grey, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/28/2025	11601280-00001	Date of first issue: 11/28/2025

Persistence and degradability

Components:

2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime]:

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301B
Remarks: The test was conducted according to guideline
Based on data from similar materials

3-(2-Aminoethylamino) propyltrimethoxysilane:

Biodegradability : Result: Not readily biodegradable.
Method: Regulation (EC) No. 440/2008, Annex, C.4-A
Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime]:

Partition coefficient: n- : log Pow: 2.89
octanol/water Remarks: Calculation

3-(2-Aminoethylamino) propyltrimethoxysilane:

Partition coefficient: n- : log Pow: -3.3
octanol/water Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.
Contaminated packaging : Empty containers should be taken to an approved waste
handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MULTIPURPOSE SILICONE, Neutral, Grey, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/28/2025	11601280-00001	Date of first issue: 11/28/2025

MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/28/2025
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8