

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version 8.1 Revision Date: 09/16/2024 SDS Number: 10644891-00016 Date of last issue: 10/11/2023
Date of first issue: 01/29/2016

SECTION 1. IDENTIFICATION

Product name : VAKU HARDENER, 40 g
Product code : 892.600004
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : 1-800-263-5002
Telefax : 1-905-564-3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300
E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Hardener
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Organic peroxides : Type E
Skin sensitization : Category 1
Eye irritation : Category 2A

GHS label elements

Hazard pictograms :  

Signal Word : Warning

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version 8.1 Revision Date: 09/16/2024 SDS Number: 10644891-00016 Date of last issue: 10/11/2023
Date of first issue: 01/29/2016

Hazard Statements : H242 Heating may cause a fire.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary Statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P234 Keep only in original packaging.
P235 Keep cool.
P261 Avoid breathing dust, fume, gas, mist, vapors or spray.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:
P302 + P352 IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:
P403 Store in a well-ventilated place.
P410 Protect from sunlight.
P420 Store separately.

Disposal:
P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Dibenzoyl peroxide	Diphenylperoxyanhydride	94-36-0	$\geq 30 - < 50$
Dimethyl phthalate	1,2-Benzenedicarboxylic acid, 1,2-dimethyl	131-11-3	$\geq 25 - < 30$

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version 8.1 Revision Date: 09/16/2024 SDS Number: 10644891-00016 Date of last issue: 10/11/2023
Date of first issue: 01/29/2016

_____ ester _____

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Causes serious eye irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : The product burns violently.
Exposure to combustion products may be a hazard to health.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/11/2023
8.1	09/16/2024	10644891-00016	Date of first issue: 01/29/2016

- Hazardous combustion products : Carbon oxides
Silicon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Clear spills immediately.
Do not clean-up or dispose of, except under supervision of a specialist.
Take any precaution to avoid mixing with combustibles.
Keep substance wet using water spray.
Soak up with inert absorbent material.
Remove mechanically and with care (e.g. with clean polyethylene plastic shovel).
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Keep waste moist, cool and well-ventilated.
Isolate waste and do not reuse.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version 8.1 Revision Date: 09/16/2024 SDS Number: 10644891-00016 Date of last issue: 10/11/2023
Date of first issue: 01/29/2016

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not breathe decomposition products.
- Do not get on skin or clothing.
Avoid breathing dust, fume, gas, mist, vapors or spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Prevent pressure build-up. Confinement can rapidly increase rate of decomposition.
Protect from contamination.
Keep cool.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep away from clothing and other combustible materials.
Take precautionary measures against static discharges.
Keep only in original packaging.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store in original container.
Keep in a dry, cool and well-ventilated place.
Protect from sunlight.
Adhere to recommended storage temperature.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.
- Materials to avoid : Store away from other materials.
- Recommended storage temperature : 25 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version 8.1 Revision Date: 09/16/2024 SDS Number: 10644891-00016 Date of last issue: 10/11/2023
Date of first issue: 01/29/2016

Dibenzoyl peroxide	94-36-0	TWA	5 mg/m ³	CA AB OEL
		TWA	5 mg/m ³	CA BC OEL
		TWAEV	5 mg/m ³	CA QC OEL
		TWA	5 mg/m ³	ACGIH
Dimethyl phthalate	131-11-3	TWA	5 mg/m ³	CA AB OEL
		TWA	5 mg/m ³	CA BC OEL
		TWAEV	5 mg/m ³	CA QC OEL
		TWA	5 mg/m ³	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Benzoic acid	65-85-0	TWA (Inhalable fraction and vapor)	0.5 mg/m ³	ACGIH
Benzene	71-43-2	STEL	2.5 ppm 8 mg/m ³	CA AB OEL
		TWA	0.5 ppm 1.6 mg/m ³	CA AB OEL
		TWA	0.5 ppm	CA BC OEL
		STEL	2.5 ppm	CA BC OEL
		TWA	0.5 ppm	CA ON OEL
		STEL	2.5 ppm	CA ON OEL
		TWAEV	0.5 ppm	CA QC OEL
		STEV	2.5 ppm	CA QC OEL
		TWA	0.02 ppm	ACGIH
Biphenyl	92-52-4	TWA	0.2 ppm 1.3 mg/m ³	CA AB OEL
		TWA	0.2 ppm	CA BC OEL
		TWAEV	0.2 ppm 1.3 mg/m ³	CA QC OEL
		TWA	0.2 ppm	ACGIH

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/11/2023
8.1	09/16/2024	10644891-00016	Date of first issue: 01/29/2016

Material : Chloroprene
Break through time : ≥ 480 min
Glove thickness : ≥ 0.6 mm
Protective index : Class 6

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : colored

Odor : characteristic

Odor Threshold : No data available

pH : Solvent mixture; pH value determination not possible, no aqueous solution

Melting point/freezing point : $> 3,000$ °C

Initial boiling point and boiling : 100 °C

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/11/2023
8.1	09/16/2024	10644891-00016	Date of first issue: 01/29/2016

range

Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	Not applicable
Lower explosion limit / Lower flammability limit	:	Not applicable
Vapor pressure	:	23 hPa (20 °C)
Relative vapor density	:	Not applicable
Density	:	1.1 g/cm ³ (20 °C) Method: DIN 53217
Bulk density	:	20 - 200 kg/m ³ (20 °C)
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	555 °C Method: DIN 51794
Decomposition temperature	:	50 °C
Viscosity Viscosity, dynamic	:	10,000 mPa.s (20 °C)
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Available oxygen content	:	3.3 %
Particle characteristics Particle size	:	No data available

SECTION 10. STABILITY AND REACTIVITY

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/11/2023
8.1	09/16/2024	10644891-00016	Date of first issue: 01/29/2016

-
- | | | |
|------------------------------------|---|---|
| Reactivity | : | Heating may cause a fire. |
| Chemical stability | : | Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions. |
| Possibility of hazardous reactions | : | Oxidizing material can cause a reaction.
Hazardous decomposition products will be formed at elevated temperatures. |
| Conditions to avoid | : | Heat, flames and sparks.
Protect from contamination.
Temperatures greater than recommended storage temperature.
Contact with incompatible substances can cause decomposition at or below SADT. |
| Incompatible materials | : | Oxidizing agents
Avoid impurities (e.g. rust, dust, ash), risk of decomposition.
Flammable materials |

Hazardous decomposition products

- | | | |
|-----------------------|---|--|
| Thermal decomposition | : | Benzoic acid
Benzene
Phenyl benzoate
Biphenyl |
|-----------------------|---|--|

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Dibenzoyl peroxide:

- | | | |
|---------------------------|---|---|
| Acute oral toxicity | : | LD50 (Mouse): > 2,000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity |
| Acute inhalation toxicity | : | LC0 (Rat): 24.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist |

Dimethyl phthalate:

- | | | |
|---------------------------|---|---------------------------|
| Acute oral toxicity | : | LD50 (Rat): > 5,000 mg/kg |
| Acute inhalation toxicity | : | LC50 (Rat): > 10.4 mg/l |

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/11/2023
8.1	09/16/2024	10644891-00016	Date of first issue: 01/29/2016

Exposure time: 6 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Dibenzoyl peroxide:

Species : Rabbit
Result : No skin irritation

Dimethyl phthalate:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Dibenzoyl peroxide:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Remarks : Based on national or regional regulation.

Dimethyl phthalate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Dibenzoyl peroxide:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : positive

Assessment : Probability or evidence of skin sensitization in humans

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/11/2023
8.1	09/16/2024	10644891-00016	Date of first issue: 01/29/2016

Dimethyl phthalate:

Test Type : Open epicutaneous test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Dibenzoyl peroxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Dimethyl phthalate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: positive

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version 8.1 Revision Date: 09/16/2024 SDS Number: 10644891-00016 Date of last issue: 10/11/2023
Date of first issue: 01/29/2016

Components:

Dibenzoyl peroxide:

Species : Rat
Application Route : Skin contact
Exposure time : 104 weeks
Result : negative

Dimethyl phthalate:

Species : Mouse, male
Application Route : Skin contact
Exposure time : 55 weeks
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Dibenzoyl peroxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Dimethyl phthalate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Test Type: Embryo-fetal development
Species: Rat
Application Route: Skin contact
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version 8.1 Revision Date: 09/16/2024 SDS Number: 10644891-00016 Date of last issue: 10/11/2023
Date of first issue: 01/29/2016

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Dibenzoyl peroxide:

Species : Rat
NOAEL : 500 mg/kg
Application Route : Ingestion
Exposure time : 54 Days
Method : OECD Test Guideline 422

Dimethyl phthalate:

Species : Rat
NOAEL : 1,000 mg/kg
LOAEL : 2,000 mg/kg
Application Route : Ingestion
Exposure time : 2 y

Species : Mouse
NOAEL : 2,700 mg/kg
Application Route : Skin contact
Exposure time : 1 y

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Dibenzoyl peroxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.0602 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.11 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.0711 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.02

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version 8.1 Revision Date: 09/16/2024 SDS Number: 10644891-00016 Date of last issue: 10/11/2023
Date of first issue: 01/29/2016

mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Daphnia magna (Water flea)): 0.001 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: 35 mg/l
Exposure time: 0.5 h
Method: OECD Test Guideline 209

Dimethyl phthalate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 39 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 52 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 259.76 mg/l
Exposure time: 72 h

EC10 (Desmodesmus subspicatus (green algae)): 193.09 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 11 mg/l
Exposure time: 102 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 9.6 mg/l
Exposure time: 21 d

Persistence and degradability

Components:

Dibenzoyl peroxide:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 71 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Dimethyl phthalate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 11 d
Method: OECD Test Guideline 301E

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/11/2023
8.1	09/16/2024	10644891-00016	Date of first issue: 01/29/2016

Bioaccumulative potential

Components:

Dibenzoyl peroxide:

Partition coefficient: n-octanol/water : log Pow: 3.2

Dimethyl phthalate:

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)
Bioconcentration factor (BCF): 57

Partition coefficient: n-octanol/water : log Pow: 1.54

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3108
Proper shipping name : ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)
Class : 5.2
Packing group : Not assigned by regulation
Labels : 5.2
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3108
Proper shipping name : Organic peroxide type E, solid (Dibenzoyl peroxide)
Class : 5.2
Packing group : Not assigned by regulation
Labels : Organic Peroxides, Keep Away From Heat

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/11/2023
8.1	09/16/2024	10644891-00016	Date of first issue: 01/29/2016

Packing instruction (cargo aircraft) : 570

Packing instruction (passenger aircraft) : 570

IMDG-Code

UN number : UN 3108

Proper shipping name : ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2

EmS Code : F-J, S-R

Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 3108

Proper shipping name : ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)

Class : 5.2

Packing group : II

Labels : 5.2

ERG Code : 145

Marine pollutant : yes(DIBENZOYL PEROXIDE)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content : CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 0 % / 0 g/l

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/11/2023
8.1	09/16/2024	10644891-00016	Date of first issue: 01/29/2016

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA : 8-hour, time-weighted average
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA ON OEL / STEL : Short-Term Exposure Limit (STEL)
CA QC OEL / TWA/EV : Time-weighted average exposure value
CA QC OEL / STEV : Short-term exposure value

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU HARDENER, 40 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/11/2023
8.1	09/16/2024	10644891-00016	Date of first issue: 01/29/2016

Revision Date : 09/16/2024
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8