

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

SECTION 1. IDENTIFICATION

Product name : VAKU 20, Fine body filler, 2 kg
Product code : 892.60202
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Construction material
Body filler/stopper

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 3
Skin irritation : Category 2
Eye irritation : Category 2A
Carcinogenicity : Category 2

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

Reproductive toxicity : Category 1B

Specific target organ toxicity - repeated exposure : Category 1 (Auditory system)

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.
H360D May damage the unborn child.
H372 Causes damage to organs (Auditory system) through prolonged or repeated exposure.

Precautionary Statements :

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical attention.
P332 + P313 If skin irritation occurs: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Talc	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6	>= 30 - < 60 *
Styrene	Benzene, ethenyl-	100-42-5	>= 10 - < 30 *
Limestone	Calcium carbonate	1317-65-3	>= 10 - < 30 *
Titanium dioxide	Titanic anhydride	13463-67-7	>= 1 - < 5 *
Potassium 2-ethylhexanoate	Hexanoic acid, 2-ethyl-, potassium salt	3164-85-0	>= 0.1 - < 1 *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
Causes serious eye irritation.
Suspected of causing cancer.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version	Revision Date:	SDS Number:	Date of last issue: 03/30/2023
5.1	12/05/2023	10785585-00012	Date of first issue: 02/22/2017

May damage the unborn child.
Causes damage to organs through prolonged or repeated exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Metal oxides
Sulfur oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version	Revision Date:	SDS Number:	Date of last issue: 03/30/2023
5.1	12/05/2023	10785585-00012	Date of first issue: 02/22/2017

Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Do not get on skin or clothing.
Do not breathe vapors.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases
Very acutely toxic substances and mixtures

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Talc	14807-96-6	TWAEV (respirable dust)	2 mg/m ³	CA QC OEL
		TWA (Respirable particulates)	2 mg/m ³	CA AB OEL
		TWA (Respirable)	2 mg/m ³	CA BC OEL
		TWA	2 fibres per cubic centimeter	CA ON OEL
		TWA (Respirable fraction)	2 mg/m ³	CA ON OEL
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
Styrene	100-42-5	TWA	20 ppm 85 mg/m ³	CA AB OEL
		STEL	40 ppm 170 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		STEL	40 ppm	CA BC OEL
		TWA	35 ppm	CA ON OEL
		STEL	100 ppm	CA ON OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	75 ppm	CA QC OEL
		TWA	10 ppm	ACGIH
		STEL	20 ppm	ACGIH
Limestone	1317-65-3	TWA	10 mg/m ³	CA AB OEL
		TWAEV (total dust)	10 mg/m ³	CA QC OEL

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m ³	CA BC OEL
		STEL	20 mg/m ³	CA BC OEL
Titanium dioxide	13463-67-7	TWA	10 mg/m ³	CA AB OEL
		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m ³	CA BC OEL
		TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA (Respirable particulate matter)	2.5 mg/m ³ (Titanium dioxide)	ACGIH

This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Titanium dioxide

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Styrene	100-42-5	Mandelic acid plus phenylglyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g creatinine	ACGIH BEI
		Styrene	Urine	End of shift (As soon as possible after exposure ceases)	20 µg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

- Filter type : Combined particulates and organic vapor type
- Hand protection
- Material : Fluorinated rubber
Break through time : \geq 480 min
Glove thickness : \geq 0.7 mm
Protective index : Class 6
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : viscous
- Color : white
- Odor : characteristic
- Odor Threshold : No data available
- pH : Solvent mixture; pH value determination not possible, no aqueous solution
- Melting point/freezing point : No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

Initial boiling point and boiling range : 145.2 °C

Flash point : 34 °C
Method: DIN 53213

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : 8.9 %(V)

Lower explosion limit / Lower flammability limit : 1.2 %(V)

Vapor pressure : 6 hPa (20 °C)

Relative vapor density : No data available

Density : 1.744 g/cm³ (20 °C)
Method: DIN 53217

Solubility(ies)
Water solubility : partly miscible

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : 480 °C
Method: DIN 51794

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : 80,000 mPa.s (20 °C)
Viscosity, kinematic : > 20.5 mm²/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Flammable liquid and vapor.
Vapors may form explosive mixture with air.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:

Talc:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Styrene:

Acute oral toxicity : LD50 (Hamster): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 11.8 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Limestone:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Potassium 2-ethylhexanoate:

Acute oral toxicity : LD50 (Rat, female): > 2,000 - 5,000 mg/kg
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

Components:

Talc:

Species : Rabbit
Result : No skin irritation

Styrene:

Species : Rabbit
Result : Skin irritation

Limestone:

Species : Rabbit

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Titanium dioxide:

Species : Rabbit
Result : No skin irritation

Potassium 2-ethylhexanoate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Talc:

Species : Rabbit
Result : No eye irritation

Styrene:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Limestone:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Titanium dioxide:

Species : Rabbit
Result : No eye irritation

Potassium 2-ethylhexanoate:

Species : Bovine cornea
Method : OECD Test Guideline 437
Result : Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

Components:

Talc:

Routes of exposure : Skin contact
Species : Humans
Result : negative

Limestone:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative
Remarks : Based on data from similar materials

Titanium dioxide:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : negative

Potassium 2-ethylhexanoate:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Talc:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
Species: Rat
Application Route: Ingestion
Result: negative

Styrene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

Application Route: inhalation (vapor)
Method: OECD Test Guideline 474
Result: negative

Limestone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Result: negative

Potassium 2-ethylhexanoate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

Carcinogenicity

Suspected of causing cancer.

Components:

Talc:

Species : Mouse
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Result : negative

Styrene:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 104 weeks
Result : positive
Remarks : The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Titanium dioxide:

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Method : OECD Test Guideline 453
Result : positive
Remarks : The mechanism or mode of action may not be relevant in humans.
This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

Reproductive toxicity

May damage the unborn child.

Components:

Talc:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Styrene:

Effects on fertility : Test Type: Three-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

Limestone:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Potassium 2-ethylhexanoate:

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 443
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Clear evidence of adverse effects on development, based on animal experiments.
Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

Components:

Styrene:

Assessment : May cause respiratory irritation.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

STOT-repeated exposure

Causes damage to organs (Auditory system) through prolonged or repeated exposure.

Components:

Styrene:

Target Organs : Auditory system
Assessment : Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Styrene:

Species : Rat
NOAEL : 1.28 mg/l
Application Route : inhalation (vapor)
Exposure time : 4 Weeks

Species : Rat
NOAEL : 1,000 - 2,000 mg/kg
Application Route : Ingestion
Exposure time : 78 - 100 Weeks

Limestone:

Species : Rat
NOAEL : > 300 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 422
Remarks : Based on data from similar materials

Titanium dioxide:

Species : Rat
NOAEL : 24,000 mg/kg
Application Route : Ingestion
Exposure time : 28 Days

Species : Rat
NOAEL : 10 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 y

Potassium 2-ethylhexanoate:

Species : Rat
LOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

Aspiration toxicity

Not classified based on available information.

Components:

Styrene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Talc:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l
Exposure time: 24 h

Styrene:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 10 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.7 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 6.3 mg/l
Exposure time: 96 h

EC10 (Pseudokirchneriella subcapitata (green algae)): 0.28 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1.01 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Toxicity to microorganisms : NOEC (Pseudomonas putida): 72 mg/l
Exposure time: 16 h

Limestone:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

Toxicity to daphnia and other aquatic invertebrates : LL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 14 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials

EL10 (Desmodesmus subspicatus (green algae)): > 14 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Titanium dioxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Potassium 2-ethylhexanoate:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
Exposure time: 48 h
Method: Directive 67/548/EEC, Annex V, C.2.
Remarks: Based on data from similar materials

Toxicity to algae/aquatic : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version	Revision Date:	SDS Number:	Date of last issue: 03/30/2023
5.1	12/05/2023	10785585-00012	Date of first issue: 02/22/2017

plants	:	mg/l Exposure time: 72 h Remarks: Based on data from similar materials
	:	EC10 (Desmodesmus subspicatus (green algae)): > 1 mg/l Exposure time: 72 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): > 1 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
Toxicity to microorganisms	:	EC10 (Pseudomonas putida): > 1 mg/l Exposure time: 17 h Method: DIN 38 412 Part 8 Remarks: Based on data from similar materials

Persistence and degradability

Components:

Styrene:

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 100 % Exposure time: 28 d
------------------	---	--

Potassium 2-ethylhexanoate:

Biodegradability	:	Result: Readily biodegradable. Method: OECD Test Guideline 301E Remarks: Based on data from similar materials
------------------	---	---

Bioaccumulative potential

Components:

Styrene:

Partition coefficient: n-octanol/water	:	log Pow: 2.96
--	---	---------------

Potassium 2-ethylhexanoate:

Partition coefficient: n-octanol/water	:	log Pow: 2.96 Method: OECD Test Guideline 107
--	---	--

Mobility in soil

No data available

Other adverse effects

No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
-

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

- UN number : UN 1866
Proper shipping name : RESIN SOLUTION
Class : 3
Packing group : III
Labels : 3
Environmentally hazardous : no

IATA-DGR

- UN/ID No. : UN 1866
Proper shipping name : Resin solution
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

- UN number : UN 1866
Proper shipping name : RESIN SOLUTION
- Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no
Remarks : Complies with the chemical and physical criteria according to 2.3.2.5 of the International Maritime Code for Dangerous Goods (IMDG Code).

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version 5.1 Revision Date: 12/05/2023 SDS Number: 10785585-00012 Date of last issue: 03/30/2023
Date of first issue: 02/22/2017

Domestic regulation

TDG

UN number : UN 1866
Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : III
Labels : 3
ERG Code : 127
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content : CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 7 g/l

The ingredients of this product are reported in the following inventories:

NDSL : This product contains one or several components listed in the Canadian NDSL.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA ON OEL / STEL : Short-Term Exposure Limit (STEL)
CA QC OEL / TWAEV : Time-weighted average exposure value
CA QC OEL / STEV : Short-term exposure value

SAFETY DATA SHEET

according to the Hazardous Products Regulations



VAKU 20, Fine body filler, 2 kg

Version	Revision Date:	SDS Number:	Date of last issue: 03/30/2023
5.1	12/05/2023	10785585-00012	Date of first issue: 02/22/2017

AllC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 12/05/2023
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8