

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

---

### SECTION 1. IDENTIFICATION

Product name : VAKU 70, Glass fibre filler, 1.76 kg  
Product code : 892.60702  
Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : 1-800-263-5002  
Telefax : 1-905-564-3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300

Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300

E-mail address : prodsafe@wurth.ca

#### Recommended use of the chemical and restrictions on use

Recommended use : Correction of paintwork damage on motor vehicles  
Filler

Restrictions on use : Not applicable

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 3  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Skin sensitization : Sub-category 1A  
Carcinogenicity : Category 2  
Reproductive toxicity : Category 2  
Specific target organ toxicity : Category 1 (Auditory system)  
- repeated exposure

#### GHS label elements

Hazard pictograms :   

Signal Word : Danger

---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

---

**Hazard Statements** : H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.  
H361d Suspected of damaging the unborn child.  
H372 Causes damage to organs (Auditory system) through prolonged or repeated exposure.

**Precautionary Statements** : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe vapors.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.

**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P333 + P313 If skin irritation or rash occurs: Get medical attention.  
P337 + P313 If eye irritation persists: Get medical attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

**Storage:**  
P405 Store locked up.

**Disposal:**  
P501 Dispose of contents and container to an approved waste disposal plant.

### Other hazards

Vapors may form explosive mixture with air.

---

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

Chemical name	Common Name/Synonym	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Talc	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	14807-96-6*	>= 10 - <= 30	TSC
Limestone	Calcium carbonate	1317-65-3*	>= 10 - <= 30	TSC
Styrene	Benzene, ethenyl-	100-42-5*	>= 10 - <= 30	TSC
Glass, oxide, chemicals	No data available	65997-17-3*	>= 0.5 - <= 1.5	TSC
Reaction mass of 2-[(2-(2-hydroxyethoxy)ethyl)(4-methylphenyl)amino]ethanol and 2,2'-[(4-methylphenyl)imino]diethanol	No data available	Not Assigned	>= 0.1 - <= 1	TSC
Maleic anhydride	2,5-Furandione	108-31-6*	> 0 - <= 0.1	TSC

\* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

|| See Section 15 for HMIRA information.

### SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Suspected of causing cancer.  
Suspected of damaging the unborn child.  
Causes damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection,

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
3.0	04/04/2026	11590695-00003	Date of first issue: 10/31/2025

Notes to physician : and use the recommended personal protective equipment when the potential for exposure exists (see section 8).  
: Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Metal oxides  
Silicon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
3.0	04/04/2026	11590695-00003	Date of first issue: 10/31/2025

---

jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

- |                             |   |   |
|-----------------------------|---|---|
| Technical measures          | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.   |
| Local/Total ventilation     | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.<br>Use explosion-proof electrical, ventilating and lighting equipment.  |
| Advice on safe handling     | : | Do not get on skin or clothing.<br>Do not breathe vapors.<br>Do not swallow.<br>Do not get in eyes.<br>Wash skin thoroughly after handling.<br>Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment<br>Non-sparking tools should be used.<br>Keep container tightly closed.<br>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>Take precautionary measures against static discharges.<br>Do not eat, drink or smoke when using this product.<br>Take care to prevent spills, waste and minimize release to the environment. |
| Conditions for safe storage | : | Keep in properly labeled containers.<br>Store locked up.<br>Keep tightly closed.<br>Keep in a cool, well-ventilated place.<br>Store in accordance with the particular national regulations.<br>Keep away from heat and sources of ignition.   |
| Materials to avoid          | : | Do not store with the following product types:<br>Strong oxidizing agents<br>Self-reactive substances and mixtures<br>Organic peroxides<br>Flammable solids<br>Pyrophoric liquids<br>Pyrophoric solids<br>Self-heating substances and mixtures<br>Substances and mixtures which in contact with water emit  |

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

flammable gases  
Explosives  
Gases  
Very acutely toxic substances and mixtures

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Talc	14807-96-6	TWA (Respirable particulates)	2 mg/m <sup>3</sup>	CA AB OEL
		TWA (Respirable)	2 mg/m <sup>3</sup>	CA BC OEL
		TWA	2 fibres per cubic centimeter	CA ON OEL
		TWA (Respirable fraction)	2 mg/m <sup>3</sup>	CA ON OEL
		TWAEV (respirable aerosol fraction)	2 mg/m <sup>3</sup>	CA QC OEL
		TWA (Respirable particulate matter)	2 mg/m <sup>3</sup>	ACGIH
Limestone	1317-65-3	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		STEL	20 mg/m <sup>3</sup>	CA BC OEL
Styrene	100-42-5	TWA	20 ppm 85 mg/m <sup>3</sup>	CA AB OEL
		STEL	40 ppm 170 mg/m <sup>3</sup>	CA AB OEL
		TWA	10 ppm	CA BC OEL
		STEL	20 ppm	CA BC OEL
		TWA	35 ppm	CA ON OEL
		STEL	100 ppm	CA ON OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	75 ppm	CA QC OEL
		TWA	10 ppm	ACGIH
		STEL	20 ppm	ACGIH
Glass, oxide, chemicals	65997-17-3	TWA	1 fibres per cubic	CA ON OEL

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

II			centimeter	
Maleic anhydride	108-31-6	TWA	0.1 ppm 0.4 mg/m <sup>3</sup>	CA AB OEL
		TWA	0.1 ppm	CA BC OEL
		TWAEV (inhalable fraction and vapour)	0.01 mg/m <sup>3</sup>	CA QC OEL
		TWA (Inhalable fraction and vapor)	0.01 mg/m <sup>3</sup>	ACGIH

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Styrene	100-42-5	Mandelic acid plus phenylglyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g creatinine	ACGIH BEI
		Styrene	Urine	End of shift (As soon as possible after exposure ceases)	20 µg/l	ACGIH BEI

**Engineering measures** : Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection

Material : Fluorinated rubber

Break through time : > 60 min

Glove thickness : >= 0.7 mm

Protective index : Class 6

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

---

- chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:  
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Contaminated work clothing should not be allowed out of the workplace.  
Wash contaminated clothing before re-use.
- 

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : viscous liquid
- Color : green
- Odor : characteristic
- Odor Threshold : No data available
- pH : substance/mixture is non-soluble (in water)
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : 145.2 °C
- Flash point : 31 °C  
Method: DIN 53213  
(for a component of this mixture)
- Evaporation rate : No data available
- Flammability (solid, gas) : Not applicable
- Flammability (liquids) : No data available
- Upper explosion limit / Upper flammability limit : 8.9 %(V)  
(for a component of this mixture)
- Lower explosion limit / Lower

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
3.0	04/04/2026	11590695-00003	Date of first issue: 10/31/2025

---

flammability limit	(for a component of this mixture)
Vapor pressure	: No data available
Relative vapor density	: No data available
Density	: 1.635 g/cm <sup>3</sup> (20 °C)
Solubility(ies)	
Water solubility	: immiscible
Partition coefficient: n-octanol/water	: Not applicable
Autoignition temperature	: 480 °C Method: DIN 51794 (for a component of this mixture)
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: 60,000 - 80,000 mPa.s ( 20 °C)
Viscosity, kinematic	: > 20.5 mm <sup>2</sup> /s ( 40 °C)
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Particle characteristics	
Particle size	: Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

---

Ingestion  
Eye contact

### Acute toxicity

Not classified based on available information.

### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

### Components:

#### Talc:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

#### Limestone:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

#### Styrene:

Acute oral toxicity : LD50 (Hamster): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 11.8 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

### Glass, oxide, chemicals:

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

---

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Remarks: Based on data from similar materials

### Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Acute oral toxicity : LD50 (Rat, male): 619 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402

### Maleic anhydride:

Acute oral toxicity : LD50 (Rat): 1,090 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 4.35 mg/l  
Exposure time: 1 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 2,620 mg/kg

### Skin corrosion/irritation

Causes skin irritation.

### Components:

#### Talc:

Species : Rabbit  
Result : No skin irritation

#### Limestone:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

#### Styrene:

Species : Rabbit  
Result : Skin irritation

#### Glass, oxide, chemicals:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

### Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Species : reconstructed human epidermis (RhE)  
Method : OECD Test Guideline 431

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

---

Species : reconstructed human epidermis (RhE)  
Method : OECD Test Guideline 439

Result : Skin irritation

### Maleic anhydride:

Species : in vitro membrane barrier  
Method : OECD Test Guideline 435  
Remarks : Based on data from similar materials

Result : Corrosive after 3 minutes to 1 hour of exposure

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Components:

#### Talc:

Species : Rabbit  
Result : No eye irritation

#### Limestone:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

#### Styrene:

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

#### Glass, oxide, chemicals:

Species : Human  
Result : No eye irritation

#### Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Species : Rabbit  
Result : Irreversible effects on the eye  
Method : OECD Test Guideline 405

#### Maleic anhydride:

Species : Rabbit  
Result : Irreversible effects on the eye

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

---

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified based on available information.

#### Components:

##### Talc:

Routes of exposure : Skin contact  
Species : Humans  
Result : negative

##### Limestone:

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative  
Remarks : Based on data from similar materials

#### Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : positive

Assessment : Probability or evidence of skin sensitization in humans

##### Maleic anhydride:

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Result : positive

Assessment : Probability or evidence of high skin sensitization rate in humans

Routes of exposure : inhalation (dust/mist/fume)  
Species : Rat  
Result : positive

Assessment : Probability of respiratory sensitization in humans based on animal testing

#### Germ cell mutagenicity

Not classified based on available information.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

---

### Components:

#### **Talc:**

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro  
Species: Rat  
Application Route: Ingestion  
Result: negative

#### **Limestone:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

#### **Styrene:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 474  
Result: negative

#### **Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[(4-methylphenyl)imino]diethanol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: positive

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

---

Genotoxicity in vivo : Test Type: In vivo mammalian alkaline comet assay  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 489  
Result: negative

### Maleic anhydride:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow  
cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### Carcinogenicity

Suspected of causing cancer.

### Components:

#### Talc:

Species : Mouse  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years  
Result : negative

#### Styrene:

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 104 weeks  
Result : positive  
Remarks : The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

### Glass, oxide, chemicals:

Species : Rat  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years  
Result : negative

### Maleic anhydride:

Species : Rat

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
3.0	04/04/2026	11590695-00003	Date of first issue: 10/31/2025

---

Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative

### Reproductive toxicity

Suspected of damaging the unborn child.

### Components:

#### Talc:

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

#### Limestone:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

#### Styrene:

Effects on fertility : Test Type: Three-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

### Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

---

Method: OECD Test Guideline 414  
Result: negative

### Maleic anhydride:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

### STOT-single exposure

Not classified based on available information.

### Components:

#### Styrene:

Assessment : May cause respiratory irritation.

### STOT-repeated exposure

Causes damage to organs (Auditory system) through prolonged or repeated exposure.

### Components:

#### Styrene:

Target Organs : Auditory system  
Assessment : Causes damage to organs through prolonged or repeated exposure.

### Maleic anhydride:

Routes of exposure : inhalation (vapor)  
Target Organs : Respiratory Tract  
Assessment : Shown to produce significant health effects in animals at concentrations of 0.2 mg/l/6h/d or less.

### Repeated dose toxicity

### Components:

#### Limestone:

Species : Rat  
NOAEL : > 300 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days  
Method : OECD Test Guideline 422  
Remarks : Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
3.0	04/04/2026	11590695-00003	Date of first issue: 10/31/2025

---

### Styrene:

Species	: Rat
NOAEL	: 1.28 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 4 Weeks

Species	: Rat
NOAEL	: 1,000 - 2,000 mg/kg
Application Route	: Ingestion
Exposure time	: 78 - 100 Weeks

### Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Species	: Rat, female
NOAEL	: 100 mg/kg
LOAEL	: 300 mg/kg
Application Route	: Ingestion
Exposure time	: 28 Days
Method	: OECD Test Guideline 407

### Maleic anhydride:

Species	: Rat
LOAEL	: 100 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

  

Species	: Rat
LOAEL	: 0.01 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 28 Days

### Aspiration toxicity

Not classified based on available information.

### Components:

#### Styrene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### Talc:

Toxicity to fish	: LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l Exposure time: 24 h
------------------	---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

---

### Limestone:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : LL50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 14 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: No toxicity at the limit of solubility.  
Based on data from similar materials
- EL10 (Desmodesmus subspicatus (green algae)): > 14 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: No toxicity at the limit of solubility.  
Based on data from similar materials
- Toxicity to microorganisms : EC50: > 100 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials

### Styrene:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 10 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.7 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 6.3 mg/l  
Exposure time: 96 h
- EC10 (Pseudokirchneriella subcapitata (green algae)): 0.28 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1.01 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

---

Toxicity to microorganisms : NOEC (Pseudomonas putida): 72 mg/l  
Exposure time: 16 h

### Glass, oxide, chemicals:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC10 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

### Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 48 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

### Maleic anhydride:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 115 mg/l  
Exposure time: 48 h  
Test substance: Neutralized product  
Method: DIN 38412

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

---

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l  
Exposure time: 48 h  
Test substance: Neutralized product  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (microalgae)): 150 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

ErC50 (Pseudokirchneriella subcapitata (microalgae)): > 150 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 21 d

Toxicity to microorganisms : EC10 (Pseudomonas putida): 44.6 mg/l  
Exposure time: 18 h  
Test substance: Neutralized product  
Method: DIN 38 412 Part 8

### Persistence and degradability

#### Components:

##### **Styrene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 28 d

#### **Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 1.5 %  
Exposure time: 29 d  
Method: OECD Test Guideline 301B

##### **Maleic anhydride:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 93.2 %  
Exposure time: 11 d  
Method: OECD Test Guideline 301B

### Bioaccumulative potential

#### Components:

##### **Styrene:**

Partition coefficient: n- : log Pow: 2.96

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
3.0	04/04/2026	11590695-00003	Date of first issue: 10/31/2025

octanol/water

### Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Partition coefficient: n-octanol/water : log Pow: 2.17  
Method: OECD Test Guideline 117

### Maleic anhydride:

Partition coefficient: n-octanol/water : log Pow: -2.61

### Mobility in soil

No data available

### Other adverse effects

No data available

### Endocrine disrupting properties

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
Class : 3  
Packing group : III  
Labels : 3  
Environmentally hazardous : no

#### IATA-DGR

UN/ID No. : UN 1866  
Proper shipping name : Resin solution  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
3.0	04/04/2026	11590695-00003	Date of first issue: 10/31/2025

Packing instruction (passenger aircraft) : 355

### IMDG-Code

UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### TDG

UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
Class : 3  
Packing group : III  
Labels : 3  
ERG Code : 128  
Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

**Volatile organic compounds (VOC) content** Canada - Volatile Organic Compound (VOC) Concentration Limits for Automotive Refinishing Products Regulations  
VOC content: 0.92 % / 5 g/l

### The ingredients of this product are reported in the following inventories:

CA. DSL : This product contains one or several components that are not on the Canadian DSL nor NDSL.

### Canadian lists

No substances are subject to CEPA Section 84 Ministerial Conditions.

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL : Canada. British Columbia OEL

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version 3.0      Revision Date: 04/04/2026      SDS Number: 11590695-00003      Date of last issue: 12/09/2025  
Date of first issue: 10/31/2025

CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA ON OEL / STEL	:	Short-Term Exposure Limit (STEL)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 04/04/2026

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## VAKU 70, Glass fibre filler, 1.76 kg

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
3.0	04/04/2026	11590695-00003	Date of first issue: 10/31/2025

---

Date format : mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8