

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version 2.0      Revision Date: 06/19/2025      SDS Number: 11532173-00002      Date of last issue: 05/02/2025  
Date of first issue: 05/02/2025

---

### SECTION 1. IDENTIFICATION

Product name : LEAK STOP FOR 1234YF, 52 g  
Product code : 892.764332  
Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : 1-800-263-5002  
Telefax : 1-905-564-3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300  
E-mail address : prodsafe@wurth.ca

#### Recommended use of the chemical and restrictions on use

Recommended use : Automotive  
Sealant  
Restrictions on use : Not applicable

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 3  
Reproductive toxicity : Category 2

#### GHS label elements

Hazard pictograms :   
Signal Word : Warning  
Hazard Statements : H229 Pressurised container: May burst if heated.

---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version 2.0      Revision Date: 06/19/2025      SDS Number: 11532173-00002      Date of last issue: 05/02/2025  
Date of first issue: 05/02/2025

H361 Suspected of damaging fertility or the unborn child.

### Precautionary Statements

#### Prevention:

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P251 Do not pierce or burn, even after use.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.

#### Response:

P308 + P313 IF exposed or concerned: Get medical attention.

#### Storage:

P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

#### Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy paraffinic	No data available	Not Assigned	$\geq 10 - < 30$ *
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	4-(2,2,3-Trimethylbut-3-en-1-yl)-N-[4-(2,2,3-trimethylbut-3-en-1-yl)phenyl]aniline	68411-46-1	$\geq 0.1 - < 1$ *
Phenol, isopropylated, phosphate (3:1)	Isopropylated Triaryl Phosphate	68937-41-7	$\geq 0.1 - < 1$ *

\* Actual concentration or concentration range is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2025
2.0	06/19/2025	11532173-00002	Date of first issue: 05/02/2025

---

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Suspected of damaging fertility or the unborn child.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2025
2.0	06/19/2025	11532173-00002	Date of first issue: 05/02/2025

---

Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid inhalation of vapor or mist.  
Do not swallow.  
Avoid contact with eyes.  
Avoid prolonged or repeated contact with skin.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from heat, hot surfaces, sparks, open flames and

---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version 2.0      Revision Date: 06/19/2025      SDS Number: 11532173-00002      Date of last issue: 05/02/2025  
Date of first issue: 05/02/2025

- other ignition sources. No smoking.  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Do not pierce or burn, even after use.  
Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases
- Recommended storage temperature : < 40 °C

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy paraffinic	Not Assigned	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m <sup>3</sup>	CA QC OEL
		TWA (Mist)	1 mg/m <sup>3</sup>	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH

- Engineering measures : Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

#### Personal protective equipment

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

- Filter type : Combined particulates and organic vapor type

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2025
2.0	06/19/2025	11532173-00002	Date of first issue: 05/02/2025

---

### Hand protection

Material : Nitrile rubber  
Break through time : < 240 min  
Glove thickness : 0.12 mm

### Remarks

: Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

### Eye protection

: Please follow all applicable local/national requirements when selecting protective measures for a specific workplace. Wear the following personal protective equipment:  
Safety glasses  
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.

### Skin and body protection

: Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

### Hygiene measures

: If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Propellant : Air

Color : Greenish yellow

Odor : characteristic

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2025
2.0	06/19/2025	11532173-00002	Date of first issue: 05/02/2025

---

Initial boiling point and boiling range : Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Flammability (liquids) : Not applicable

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Density : 0.9578 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : emulsifiable

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version 2.0      Revision Date: 06/19/2025      SDS Number: 11532173-00002      Date of last issue: 05/02/2025  
Date of first issue: 05/02/2025

---

Possibility of hazardous reactions : If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402  
Remarks: Based on data from similar materials

##### **Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

##### **Phenol, isopropylated, phosphate (3:1):**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2025
2.0	06/19/2025	11532173-00002	Date of first issue: 05/02/2025

---

Acute inhalation toxicity : LC50 (Rat): > 200 mg/l  
Exposure time: 1 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 10,000 mg/kg

### **Skin corrosion/irritation**

Not classified based on available information.

### **Components:**

#### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

#### **Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Mild skin irritation

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Components:**

#### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

#### **Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

#### **Phenol, isopropylated, phosphate (3:1):**

Species : Rabbit  
Result : No eye irritation

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version 2.0      Revision Date: 06/19/2025      SDS Number: 11532173-00002      Date of last issue: 05/02/2025  
Date of first issue: 05/02/2025

---

### Components:

#### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative  
Remarks : Based on data from similar materials

#### **Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### **Phenol, isopropylated, phosphate (3:1):**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : equivocal

### **Germ cell mutagenicity**

Not classified based on available information.

### Components:

#### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

#### **Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

#### **Phenol, isopropylated, phosphate (3:1):**

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2025
2.0	06/19/2025	11532173-00002	Date of first issue: 05/02/2025

---

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Hamster  
Application Route: Ingestion  
Method: OECD Test Guideline 475  
Result: negative

### Carcinogenicity

Not classified based on available information.

### Components:

#### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 78 weeks  
Method : OECD Test Guideline 451  
Result : negative  
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

### Reproductive toxicity

Suspected of damaging fertility or the unborn child.

### Components:

#### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Skin contact

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2025
2.0	06/19/2025	11532173-00002	Date of first issue: 05/02/2025

---

Method: OECD Test Guideline 414  
Result: negative  
Remarks: Based on data from similar materials

### **Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 443  
Result: positive

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

### **Phenol, isopropylated, phosphate (3:1):**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 421  
Result: positive

Effects on fetal development : Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

### **STOT-single exposure**

Not classified based on available information.

### **STOT-repeated exposure**

Not classified based on available information.

### **Components:**

#### **Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:**

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

#### **Phenol, isopropylated, phosphate (3:1):**

Routes of exposure : Ingestion

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version 2.0      Revision Date: 06/19/2025      SDS Number: 11532173-00002      Date of last issue: 05/02/2025  
Date of first issue: 05/02/2025

---

Target Organs : Adrenal gland  
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

### Repeated dose toxicity

#### Components:

##### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Rabbit  
NOAEL : 1,000 mg/kg  
Application Route : Skin contact  
Exposure time : 4 Weeks  
Method : OECD Test Guideline 410  
Remarks : Based on data from similar materials

Species : Rat  
NOAEL : > 980 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 4 Weeks

##### **Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:**

Species : Rat  
NOAEL : 25 mg/kg  
LOAEL : 75 mg/kg  
Application Route : Ingestion  
Exposure time : 53 Days  
Method : OECD Test Guideline 422

##### **Phenol, isopropylated, phosphate (3:1):**

Species : Rat  
NOAEL : < 25 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408

### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version 2.0      Revision Date: 06/19/2025      SDS Number: 11532173-00002      Date of last issue: 05/02/2025  
Date of first issue: 05/02/2025

---

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l  
Exposure time: 10 min  
Method: DIN 38 412 Part 8  
Remarks: Based on data from similar materials

### **Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:**

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 51 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOELR (Desmodesmus subspicatus (green algae)): > 1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

EL50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10 (Daphnia magna (Water flea)): 1.69 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 211

### **Phenol, isopropylated, phosphate (3:1):**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 1.6 mg/l  
Exposure time: 96 h

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2025
2.0	06/19/2025	11532173-00002	Date of first issue: 05/02/2025

---

- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 1.5 mg/l  
Exposure time: 48 h
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 2.5 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- NOELR (Pseudokirchneriella subcapitata (green algae)): 0.31 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 0.0031 mg/l  
Exposure time: 33 d  
Method: OECD Test Guideline 210
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.0415 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211
- Toxicity to microorganisms : EC50: > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

### Persistence and degradability

#### Components:

##### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 31 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 1 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

##### **Phenol, isopropylated, phosphate (3:1):**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 17.9 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

### Bioaccumulative potential

#### Components:

##### **Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:**

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2025
2.0	06/19/2025	11532173-00002	Date of first issue: 05/02/2025

---

Partition coefficient: n-octanol/water : log Pow: > 4  
Remarks: Calculation

### Phenol, isopropylated, phosphate (3:1):

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)  
Bioconcentration factor (BCF): 776  
Method: OECD Test Guideline 305

Partition coefficient: n-octanol/water : log Pow: > 4

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Please ensure aerosol cans are sprayed completely empty (including propellant)  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.2  
Packing group : Not assigned by regulation  
Labels : 2.2  
Environmentally hazardous : yes

#### IATA-DGR

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, non-flammable  
Class : 2.2  
Packing group : Not assigned by regulation  
Labels : Non-flammable, non-toxic Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version 2.0      Revision Date: 06/19/2025      SDS Number: 11532173-00002      Date of last issue: 05/02/2025  
Date of first issue: 05/02/2025

---

||ger aircraft)

### IMDG-Code

||UN number : UN 1950  
||Proper shipping name : AEROSOLS  
(Phenol, isopropylated, phosphate (3:1))  
||Class : 2.2  
||Packing group : Not assigned by regulation  
||Labels : 2.2  
||EmS Code : F-D, S-U  
||Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### TDG

||UN number : UN 1950  
||Proper shipping name : AEROSOLS  
||Class : 2.2  
||Packing group : Not assigned by regulation  
||Labels : 2.2  
||ERG Code : 126  
||Marine pollutant : yes(Phenol, isopropylated, phosphate (3:1))

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

### The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

---

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL : Canada. British Columbia OEL  
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants  
ACGIH / TWA : 8-hour, time-weighted average  
CA AB OEL / TWA : 8-hour Occupational exposure limit

---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2025
2.0	06/19/2025	11532173-00002	Date of first issue: 05/02/2025

---

CA AB OEL / STEL : 15-minute occupational exposure limit  
CA BC OEL / TWA : 8-hour time weighted average  
CA QC OEL / TWAEV : Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/19/2025  
Date format : mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## LEAK STOP FOR 1234YF, 52 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2025
2.0	06/19/2025	11532173-00002	Date of first issue: 05/02/2025

---

intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8