according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 1.2 10/16/2024 10870221-00003 Date of first issue: 10/14/2022

SECTION 1. IDENTIFICATION

Product name : SALT STAIN REMOVER, 3.78 L

Product code : 893.033122 Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd

GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225 Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:

CHEMTREC (24/7): 1-800-424-9300 Transport related emergencies:

CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou

exposition:

CHEMTREC (24/7): 1-800-424-9300

Urgences liées au transport:

CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Automotive

Detergent

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Eye irritation : Category 2A

Specific target organ toxicity

- repeated exposure

Category 2 (Respiratory Tract)

GHS label elements

Hazard pictograms



Signal Word : Warning

Hazard Statements : H319 Causes serious eye irritation.

H373 May cause damage to organs (Respiratory Tract) through

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 1.2 10/16/2024 10870221-00003 Date of first issue: 10/14/2022

prolonged or repeated exposure.

Precautionary Statements : Prevention:

P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling. P280 Wear eye protection and face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P314 Get medical attention if you feel unwell.

P337 + P313 If eye irritation persists: Get medical attention.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
2-Butoxyethanol	1-Butoxy-2- hydroxyethan	111-76-2	>= 1 - < 5 *
Sodium Xylene Sul- fonate	Benzenesulfonic acid, dimethyl-, sodium salt	1300-72-7	>= 1 - < 5 *
Alcohols, C8-10, eth- oxylated propoxylated	No data availa- ble	68603-25-8	>= 1 - < 5 *
Tetrasodium ethylene- diaminetetraacetate	Glycine, N,N'- 1,2- ethanediylbis[N- (carboxyme- thyl)-, sodium salt	64-02-8	>= 1 - < 5 *

^{*} Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 1.2 10/16/2024 10870221-00003 Date of first issue: 10/14/2022

Remove contaminated clothing and shoes.

Get medical attention.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated

exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides Metal oxides

Nitrogen oxides (NOx)

Sulfur oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 1.2 10/16/2024 10870221-00003 Date of first issue: 10/14/2022

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers)

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe mist or vapors.

Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-Butoxyethanol	111-76-2	TWA	20 ppm 97 mg/m³	CA AB OEL
		TWA	20 ppm	CA BC OEL

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 10/16/2024 10870221-00003 Date of first issue: 10/14/2022 1.2

	TWAEV	20 ppm	CA QC OEL
	TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra-tion	Basis
2-Butoxyethanol	111-76-2	Butoxyaceti c acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g creatinine	ACGIH BEI

Engineering measures Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection If adequate local exhaust ventilation is not available or

exposure assessment demonstrates exposures outside the

recommended guidelines, use respiratory protection. Combined particulates and organic vapor type

Filter type Hand protection

Material

PVC Break through time > 480 min Glove thickness 0.35 mm

Remarks Choose gloves to protect hands against chemicals depending

> on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the

end of workday.

Eye protection Wear the following personal protective equipment:

Safety goggles

Skin and body protection Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

If exposure to chemical is likely during typical use, provide Hygiene measures

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Color colorless

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 1.2 10/16/2024 10870221-00003 Date of first issue: 10/14/2022

Odor : perfumed

Odor Threshold : No data available

pH : 10.9

Concentration: 100 % (as aqueous solution)

Melting point/freezing point : No data available

Initial boiling point and boiling

range

100 °C

Flash point : does not flash

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 1.01

Solubility(ies)

Water solubility : completely miscible

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : 10 mm²/s

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size : Not applicable

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 1.2 10/16/2024 10870221-00003 Date of first issue: 10/14/2022

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

Possibility of hazardous reac- : None known.

tions

Conditions to avoid : None known. Incompatible materials : Acids

Hazardous decomposition : No h

products

: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:

2-Butoxyethanol:

Acute oral toxicity : LD50 (Guinea pig): 1,200 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment

Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg

Sodium Xylene Sulfonate:

Acute oral toxicity : LD50 (Rat): > 7,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 6.41 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 1.2 10/16/2024 10870221-00003 Date of first issue: 10/14/2022

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Alcohols, C8-10, ethoxylated propoxylated:

Acute oral toxicity : Acute toxicity estimate: 2,500 mg/kg

Method: Expert judgment

Tetrasodium ethylenediaminetetraacetate:

Acute oral toxicity : LD50 (Rat): 1,780 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 1 mg/l

Exposure time: 6 h

Test atmosphere: dust/mist

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

2-Butoxyethanol:

Species : Rabbit

Method : Directive 67/548/EEC, Annex V, B.4.

Result : Skin irritation

Sodium Xylene Sulfonate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Alcohols, C8-10, ethoxylated propoxylated:

Result : Skin irritation

Tetrasodium ethylenediaminetetraacetate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 1.2 10/16/2024 10870221-00003 Date of first issue: 10/14/2022

Components:

2-Butoxyethanol:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

Sodium Xylene Sulfonate:

Species : Rabbit

Result : Irritation to eyes, reversing within 7 days

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Alcohols, C8-10, ethoxylated propoxylated:

Result : Irritation to eyes, reversing within 21 days

Tetrasodium ethylenediaminetetraacetate:

Result : Irreversible effects on the eye

Remarks : Based on national or regional regulation.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

2-Butoxyethanol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Sodium Xylene Sulfonate:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Remarks : Based on data from similar materials

Tetrasodium ethylenediaminetetraacetate:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 1.2 10/16/2024 10870221-00003 Date of first issue: 10/14/2022

Result : negative

Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

2-Butoxyethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-

malian cells Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: Intraperitoneal injection

Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Sodium Xylene Sulfonate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Tetrasodium ethylenediaminetetraacetate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 1.2 10/16/2024 10870221-00003 Date of first issue: 10/14/2022

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

2-Butoxyethanol:

Species : Rat

Application Route : inhalation (vapor)

Exposure time : 2 Years
Result : negative

Sodium Xylene Sulfonate:

Species : Mouse
Application Route : Skin contact
Exposure time : 2 Years
Result : negative

Tetrasodium ethylenediaminetetraacetate:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Remarks : Based on data from similar materials

Species : Mouse
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

2-Butoxyethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Mouse

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 1.2 10/16/2024 10870221-00003 Date of first issue: 10/14/2022

Result: negative

Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Sodium Xylene Sulfonate:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Tetrasodium ethylenediaminetetraacetate:

Effects on fertility : Test Type: Four-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs (Respiratory Tract) through prolonged or repeated exposure.

Components:

Tetrasodium ethylenediaminetetraacetate:

Routes of exposure : inhalation (dust/mist/fume)

Target Organs : Respiratory Tract

Assessment : Shown to produce significant health effects in animals at con-

centrations of >0.02 to 0.2 mg/l/6h/d.

Repeated dose toxicity

Components:

Sodium Xylene Sulfonate:

Species : Mouse
NOAEL : >= 440 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks

Remarks : Based on data from similar materials

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 10/16/2024 10870221-00003 Date of first issue: 10/14/2022 1.2

Tetrasodium ethylenediaminetetraacetate:

Species Mouse **NOAEL** >= 938 mg/kgApplication Route Ingestion Exposure time 103 Weeks

Remarks Based on data from similar materials

Species Rat LOAEL : 0.03 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 4 Weeks

Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2-Butoxyethanol:

LC50 (Oncorhynchus mykiss (rainbow trout)): 1,464 mg/l Toxicity to fish

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1,800 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 1,840

Exposure time: 72 h

Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 679

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 21 d

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

EC10 (Daphnia magna (Water flea)): 134 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Sodium Xylene Sulfonate:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 10/16/2024 10870221-00003 Date of first issue: 10/14/2022 1.2

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1,020 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 230

mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 31

mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to microorganisms EC10: >= 1,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Alcohols, C8-10, ethoxylated propoxylated:

Ecotoxicology Assessment

Acute aquatic toxicity Toxic effects cannot be excluded

Toxic effects cannot be excluded Chronic aquatic toxicity

Tetrasodium ethylenediaminetetraacetate:

Toxicity to fish LC50 (Lepomis macrochirus (Bluegill sunfish)): 121 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 140 mg/l

Exposure time: 48 h Method: DIN 38412

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

NOEC (Desmodesmus subspicatus (green algae)): 100 mg/l

Exposure time: 72 h

Method: Directive 67/548/EEC, Annex V, C.3.

Toxicity to fish (Chronic tox-

icity)

NOEC (Danio rerio (zebra fish)): > 25.7 mg/l

Exposure time: 35 d

Method: OECD Test Guideline 210

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

NOEC (Daphnia magna (Water flea)): 25 mg/l

Exposure time: 21 d ic toxicity)

Remarks: Based on data from similar materials

Toxicity to microorganisms EC10: > 1,000 mg/l

> Exposure time: 30 min Method: ISO 8192

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 1.2 10/16/2024 10870221-00003 Date of first issue: 10/14/2022

Persistence and degradability

Components:

2-Butoxyethanol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 90.4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Sodium Xylene Sulfonate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 100 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Remarks: Based on data from similar materials

Tetrasodium ethylenediaminetetraacetate:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 - 10 % Exposure time: 28 d

Method: OECD Test Guideline 301E

Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

2-Butoxyethanol:

Partition coefficient: n-

octanol/water

log Pow: 0.81

Sodium Xylene Sulfonate:

Partition coefficient: n-

octanol/water

log Pow: -3.12

Tetrasodium ethylenediaminetetraacetate:

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)

Bioconcentration factor (BCF): 1.8

Mobility in soil
No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 1.2 10/16/2024 10870221-00003 Date of first issue: 10/14/2022

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds

(VOC) content

CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 -

Guidelines for VOC in Consumer Products

VOC content: 1 %

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada, British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average CA AB OEL / TWA : 8-hour Occupational exposure limit CA BC OEL / TWA : 8-hour time weighted average

CA QC OEL / TWAEV : Time-weighted average exposure value

according to the Hazardous Products Regulations



SALT STAIN REMOVER, 3.78 L

Version Revision Date: SDS Number: Date of last issue: 06/19/2024 1.2 10/16/2024 10870221-00003 Date of first issue: 10/14/2022

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 10/16/2024 Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8