

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/23/2026	11667305-00001	Date of first issue: 03/23/2026

SECTION 1. IDENTIFICATION

Product name : CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L
Product code : 893.050035
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : 1-800-263-5002

Telefax : 1-905-564-3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300

Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Anti-friction agent and lubricant

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Serious eye damage : Category 1

Skin sensitization : Sub-category 1A

Flammable liquids : Category 4

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H227 Combustible liquid.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

Precautionary Statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version 1.0 Revision Date: 03/23/2026 SDS Number: 11667305-00001 Date of last issue: -
Date of first issue: 03/23/2026

and other ignition sources. No smoking.
P261 Avoid breathing mist or vapors.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified	Mineral oil, petroleum distillates, solvent-dewaxed light paraffinic	64742-56-9*	>= 30 - <= 60	TSC
2-Phenoxyethanol	Ethanol, 2-phenoxy-	122-99-6*	>= 5 - <= 10	TSC
Rape oil	No data available	8002-13-9*	>= 1 - <= 5	TSC
Sodium petroleum sulfonate	No data available	68608-26-4*	>= 1 - <= 5	TSC
Propylene glycol	1,2-Propanediol	57-55-6*	>= 0.5 - <= 1.5	TSC
Alcohols, C16-18 and C18-unsaturated, ethoxylated	No data available	68920-66-1*	>= 0.5 - <= 1.5	TSC
1,2-Benzisothiazol-3(2H)-one	No data available	2634-33-5*	> 0 - <= 0.1	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version 1.0	Revision Date: 03/23/2026	SDS Number: 11667305-00001	Date of last issue: - Date of first issue: 03/23/2026
----------------	------------------------------	-------------------------------	--

See Section 15 for HMIRA information.

SECTION 4. FIRST AID MEASURES

General advice	: In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention immediately.
If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	: May cause an allergic skin reaction. Causes serious eye damage.
Protection of first-aiders	: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
Notes to physician	: Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Water spray Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire fighting	: Do not use a solid water stream as it may scatter and spread fire. Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Exposure to combustion products may be a hazard to health.
Hazardous combustion products	: Carbon oxides Sulfur oxides Metal oxides
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version 1.0	Revision Date: 03/23/2026	SDS Number: 11667305-00001	Date of last issue: - Date of first issue: 03/23/2026
----------------	------------------------------	-------------------------------	--

Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Avoid breathing mist or vapors.
Do not swallow.
Do not get in eyes.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version 1.0 Revision Date: 03/23/2026 SDS Number: 11667305-00001 Date of last issue: -
Date of first issue: 03/23/2026

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Explosives
Gases

Recommended storage temperature : 5 - 40 °C
Storage period : 12 Months

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified	64742-56-9	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
2-Phenoxyethanol	122-99-6	TWA	25 ppm 141 mg/m ³	CA ON OEL
Rape oil	8002-13-9	TWAEV (Mist)	10 mg/m ³	CA QC OEL
Propylene glycol	57-55-6	TWA (Vapour and aerosols)	50 ppm 155 mg/m ³	CA ON OEL
		TWA (aerosol)	10 mg/m ³	CA ON OEL

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version 1.0	Revision Date: 03/23/2026	SDS Number: 11667305-00001	Date of last issue: - Date of first issue: 03/23/2026
----------------	------------------------------	-------------------------------	--

- Engineering measures** : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.
- Personal protective equipment**
- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Combined particulates and organic vapor type
- Hand protection
- Material : Nitrile rubber
- Break through time : > 480 min
- Glove thickness : 0.9 - 1 mm
- Protective index : Class 6
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment: Chemical resistant goggles must be worn. If splashes are likely to occur, wear: Face-shield
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : amber
- Odor : characteristic
- Odor Threshold : No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version 1.0	Revision Date: 03/23/2026	SDS Number: 11667305-00001	Date of last issue: - Date of first issue: 03/23/2026
----------------	------------------------------	-------------------------------	--

pH	:	8.9 Concentration: 5 % Method: DIN 51369
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	80 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	0.94 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	completely soluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	76 mm ² /s (20 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/23/2026	11667305-00001	Date of first issue: 03/23/2026

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Combustible liquid. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
---------------------	---	--

Components:

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Method: OECD Test Guideline 402

2-Phenoxyethanol:

Acute oral toxicity	:	LD50 (Rat, male): 1,394 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 1 mg/l Exposure time: 6 h Test atmosphere: dust/mist Method: OECD Test Guideline 412

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version 1.0	Revision Date: 03/23/2026	SDS Number: 11667305-00001	Date of last issue: - Date of first issue: 03/23/2026
----------------	------------------------------	-------------------------------	--

Acute dermal toxicity : LD50 (Rat): 14,391 mg/kg

Rape oil:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Sodium petroleum sulfonate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 1.9 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: Based on data from similar materials

Propylene glycol:

Acute oral toxicity : LD50 (Rat): 22,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 44.9 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Alcohols, C16-18 and C18-unsaturated, ethoxylated:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

1,2-Benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat, male): 450 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male): 0.21 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/23/2026	11667305-00001	Date of first issue: 03/23/2026

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Species	: Rabbit
Result	: No skin irritation

2-Phenoxyethanol:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Rape oil:

Species	: Rabbit
Result	: No skin irritation
Remarks	: Based on data from similar materials

Sodium petroleum sulfonate:

Species	: Rabbit
Result	: No skin irritation

Propylene glycol:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Alcohols, C16-18 and C18-unsaturated, ethoxylated:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: Skin irritation

1,2-Benzisothiazol-3(2H)-one:

Result	: Skin irritation
--------	-------------------

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/23/2026	11667305-00001	Date of first issue: 03/23/2026

2-Phenoxyethanol:

Species	:	Rabbit
Result	:	Irreversible effects on the eye
Method	:	OECD Test Guideline 405

Rape oil:

Species	:	Rabbit
Result	:	No eye irritation
Remarks	:	Based on data from similar materials

Sodium petroleum sulfonate:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Remarks	:	Based on data from similar materials

Propylene glycol:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

Alcohols, C16-18 and C18-unsaturated, ethoxylated:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

1,2-Benzisothiazol-3(2H)-one:

Species	:	Rabbit
Result	:	Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

2-Phenoxyethanol:

Test Type	:	Maximization Test
-----------	---	-------------------

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/23/2026	11667305-00001	Date of first issue: 03/23/2026

Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

Rape oil:

Test Type	:	Human repeat insult patch test (HRIPT)
Routes of exposure	:	Skin contact
Species	:	Humans
Result	:	negative
Remarks	:	Based on data from similar materials

Sodium petroleum sulfonate:

Test Type	:	Human repeat insult patch test (HRIPT)
Routes of exposure	:	Skin contact
Result	:	negative
Remarks	:	Based on data from similar materials

Propylene glycol:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

1,2-Benzisothiazol-3(2H)-one:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	positive

Assessment	:	Probability or evidence of high skin sensitization rate in humans
------------	---	---

Germ cell mutagenicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Remarks: Based on data from similar materials
-----------------------	---	--

Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection
----------------------	---	--

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version 1.0	Revision Date: 03/23/2026	SDS Number: 11667305-00001	Date of last issue: - Date of first issue: 03/23/2026
----------------	------------------------------	-------------------------------	--

Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

2-Phenoxyethanol:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
Genotoxicity in vivo	:	Test Type: Unscheduled DNA synthesis (UDS) test with mammalian liver cells in vivo Species: Rat Application Route: Ingestion Method: OECD Test Guideline 486 Result: negative Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat Application Route: Ingestion Result: negative

Rape oil:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Remarks: Based on data from similar materials Test Type: Chromosome aberration test in vitro Result: negative Remarks: Based on data from similar materials
-----------------------	---	---

Sodium petroleum sulfonate:

Genotoxicity in vitro	:	Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473
-----------------------	---	---

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version 1.0	Revision Date: 03/23/2026	SDS Number: 11667305-00001	Date of last issue: - Date of first issue: 03/23/2026
----------------	------------------------------	-------------------------------	--

Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Propylene glycol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Alcohols, C16-18 and C18-unsaturated, ethoxylated:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

1,2-Benzisothiazol-3(2H)-one:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with mammalian liver cells in vivo
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 486
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/23/2026	11667305-00001	Date of first issue: 03/23/2026

Carcinogenicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Species	:	Mouse
Application Route	:	Skin contact
Exposure time	:	78 weeks
Method	:	OECD Test Guideline 451
Result	:	negative
Remarks	:	Based on data from similar materials

2-Phenoxyethanol:

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	2 Years
Method	:	OECD Test Guideline 451
Result	:	negative

Propylene glycol:

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	2 Years
Result	:	negative

Reproductive toxicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Effects on fertility	:	Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: Ingestion Result: negative Remarks: Based on data from similar materials
----------------------	---	--

Effects on fetal development	:	Test Type: Embryo-fetal development Species: Rat Application Route: Skin contact Method: OECD Test Guideline 414 Result: negative Remarks: Based on data from similar materials
------------------------------	---	--

2-Phenoxyethanol:

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Mouse Application Route: Ingestion
----------------------	---	---

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/23/2026	11667305-00001	Date of first issue: 03/23/2026

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Rape oil:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Sodium petroleum sulfonate:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 415
Result: negative
Remarks: Based on data from similar materials

Propylene glycol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Result: negative

1,2-Benzisothiazol-3(2H)-one:

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: Ingestion
Method: OPPTS 870.3800

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version 1.0	Revision Date: 03/23/2026	SDS Number: 11667305-00001	Date of last issue: - Date of first issue: 03/23/2026
----------------	------------------------------	-------------------------------	--

Result: negative

STOT-single exposure

Not classified based on available information.

Components:

2-Phenoxyethanol:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Components:

1,2-Benzisothiazol-3(2H)-one:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Species	: Rat
NOAEL	: 1,000 mg/kg
Application Route	: Skin contact
Exposure time	: 4 Weeks
Method	: OECD Test Guideline 410
Remarks	: Based on data from similar materials

Species	: Rat
NOAEL	: > 980 mg/m ³
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 4 Weeks
Remarks	: Based on data from similar materials

2-Phenoxyethanol:

Species	: Rat
NOAEL	: 396 mg/kg
Application Route	: Ingestion
Exposure time	: 13 Weeks
Method	: OECD Test Guideline 408

Species	: Rabbit
NOAEL	: 500 mg/kg
Application Route	: Skin contact
Exposure time	: 13 Weeks

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/23/2026	11667305-00001	Date of first issue: 03/23/2026

Rape oil:

Species	:	Rat
NOAEL	:	> 100 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days
Remarks	:	Based on data from similar materials

Sodium petroleum sulfonate:

Species	:	Rat
NOAEL	:	> 1,000 mg/kg
Application Route	:	Skin contact
Exposure time	:	28 Days
Method	:	OECD Test Guideline 410
Remarks	:	Based on data from similar materials

Propylene glycol:

Species	:	Rat, male
NOAEL	:	>= 1,700 mg/kg
Application Route	:	Ingestion
Exposure time	:	2 y

1,2-Benzisothiazol-3(2H)-one:

Species	:	Dog
NOAEL	:	5 mg/kg
LOAEL	:	20 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days
Method	:	Directive 67/548/EEC, Annex V, B.27.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
		Exposure time: 96 h
		Method: OECD Test Guideline 203
		Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
		Exposure time: 48 h
		Method: OECD Test Guideline 202
		Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version 1.0	Revision Date: 03/23/2026	SDS Number: 11667305-00001	Date of last issue: - Date of first issue: 03/23/2026
----------------	------------------------------	-------------------------------	--

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

2-Phenoxyethanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 344 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): >= 500 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 625 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.

EC10 (Desmodesmus subspicatus (green algae)): 333 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 24 mg/l
Exposure time: 34 d
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 9.43 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: >= 1,000 mg/l
Exposure time: 30 min
Method: OECD Test Guideline 209

Rape oil:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: ISO 7346/1
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 96.72 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version 1.0	Revision Date: 03/23/2026	SDS Number: 11667305-00001	Date of last issue: - Date of first issue: 03/23/2026
----------------	------------------------------	-------------------------------	--

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Desmodesmus subspicatus (green algae)): > 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC (Pseudomonas putida): > 100 mg/l
Exposure time: 16 h
Remarks: Based on data from similar materials

Sodium petroleum sulfonate:

Toxicity to fish : LL50 (Cyprinodon variegatus (sheepshead minnow)): > 10,000 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: 3,200 - 5,000 mg/l
Exposure time: 8 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Propylene glycol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 40,613 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version 1.0	Revision Date: 03/23/2026	SDS Number: 11667305-00001	Date of last issue: - Date of first issue: 03/23/2026
----------------	------------------------------	-------------------------------	--

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Ceriodaphnia dubia (water flea)): 18,340 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	ErC50 (Skeletonema costatum (marine diatom)): 19,300 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Ceriodaphnia dubia (water flea)): 13,020 mg/l Exposure time: 7 d
Toxicity to microorganisms	:	NOEC (Pseudomonas putida): > 20,000 mg/l Exposure time: 18 h

Alcohols, C16-18 and C18-unsaturated, ethoxylated:

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): > 10 - 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
M-Factor (Acute aquatic toxicity)	:	1
Toxicity to microorganisms	:	EC50: > 10,000 mg/l Method: OECD Test Guideline 209

Ecotoxicology Assessment

Acute aquatic toxicity	:	Very toxic to aquatic life., M-factor: 1
------------------------	---	--

1,2-Benzisothiazol-3(2H)-one:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 0.74 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 2.24 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.1087 mg/l Exposure time: 24 h EC10 (Pseudokirchneriella subcapitata (green algae)): 0.0268 mg/l Exposure time: 24 h
Toxicity to fish (Chronic toxicity)	:	NOEC (Pimephales promelas (fathead minnow)): 0.28 mg/l Exposure time: 33 d Method: OECD Test Guideline 210
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 0.91 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to microorganisms	:	NOEC: 10.3 mg/l

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/23/2026	11667305-00001	Date of first issue: 03/23/2026

Exposure time: 3 h
Method: OECD Test Guideline 209

Persistence and degradability

Components:

Distillates (petroleum), solvent dewaxed light paraffinic; baseoil - unspecified:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

2-Phenoxyethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 98 %
Exposure time: 3 d
Method: OECD Test Guideline 301A

Rape oil:

Biodegradability : Result: Readily biodegradable.
Remarks: Based on data from similar materials

Sodium petroleum sulfonate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
Remarks: Based on data from similar materials

Propylene glycol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 98.3 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Alcohols, C16-18 and C18-unsaturated, ethoxylated:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential

Components:

2-Phenoxyethanol:

Partition coefficient: n- : log Pow: 1.2

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version 1.0	Revision Date: 03/23/2026	SDS Number: 11667305-00001	Date of last issue: - Date of first issue: 03/23/2026
----------------	------------------------------	-------------------------------	--

octanol/water

Rape oil:

Partition coefficient: n-octanol/water	: log Pow: > 4
Remarks: Expert judgment	

Propylene glycol:

Partition coefficient: n-octanol/water	: log Pow: -1.07
Method: Regulation (EC) No. 440/2008, Annex, A.8	

Alcohols, C16-18 and C18-unsaturated, ethoxylated:

Partition coefficient: n-octanol/water	: log Pow: 6.13
Remarks: Calculation	

1,2-Benzisothiazol-3(2H)-one:

Bioaccumulation	: Species: Lepomis macrochirus (Bluegill sunfish)
Bioconcentration factor (BCF): 6.62	

Partition coefficient: n-octanol/water	: log Pow: 0.7
--	----------------

Mobility in soil

No data available

Other adverse effects

No data available

Endocrine disrupting properties

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	: Do not dispose of waste into sewer. Dispose of in accordance with local regulations.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/23/2026	11667305-00001	Date of first issue: 03/23/2026

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content

Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations
VOC content: 1.42 %

The ingredients of this product are reported in the following inventories:

CA. DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

Canadian lists

No substances are subject to CEPA Section 84 Ministerial Conditions.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV	:	Time-weighted average exposure value

SAFETY DATA SHEET

according to the Hazardous Products Regulations



CUT+COOL COOLING LUBRICANT HD, High-performance concentrate, 5 L

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/23/2026	11667305-00001	Date of first issue: 03/23/2026

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 03/23/2026
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8