

## KLEBFIX, 18 mL

Version 2.19      Revision Date: 07/26/2023      SDS Number: 10625424-00013      Date of last issue: 04/24/2023  
Date of first issue: 03/25/2014

---

**SECTION 1. IDENTIFICATION**

Product name : KLEBFIX, 18 mL

Product code : 893.09

Other means of identification : No data available

**Manufacturer or supplier's details**

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:

CHEMTREC (24/7): 1-800-424-9300

Urgences liées au transport:

CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

**Recommended use of the chemical and restrictions on use**

Recommended use : Adhesives

Restrictions on use : Not applicable

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Flammable liquids : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity : Category 3  
- single exposure

**KLEBFIX, 18 mL**

Version 2.19      Revision Date: 07/26/2023      SDS Number: 10625424-00013      Date of last issue: 04/24/2023  
 Date of first issue: 03/25/2014

**GHS label elements**

Hazard pictograms



Signal Word

: Warning

Hazard Statements

: H227 Combustible liquid.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H335 May cause respiratory irritation.

Precautionary Statements

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P261 Avoid breathing mist or vapors.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves, protective clothing, eye protection and face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P332 + P313 If skin irritation occurs: Get medical attention.  
 P337 + P313 If eye irritation persists: Get medical attention.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents and container to an approved waste disposal plant.

**Other hazards**

Vapors may form explosive mixture with air.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Ethyl 2-cyanoacrylate	1-mmethyl-1-	7085-85-0	>= 80 - <= 100 *

**KLEBFIX, 18 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2023
2.19	07/26/2023	10625424-00013	Date of first issue: 03/25/2014

	phenylethylhydroperoxide		
--	--------------------------	--	--

\* Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- |   |   |  |
|---|---|--|
| General advice  | : | In the case of accident or if you feel unwell, seek medical advice immediately.<br>When symptoms persist or in all cases of doubt seek medical advice.   |
| If inhaled  | : | If inhaled, remove to fresh air.<br>Get medical attention if symptoms occur.   |
| In case of skin contact                                     | : | In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.<br>Get medical attention.<br>Wash clothing before reuse.<br>Thoroughly clean shoes before reuse. |
| In case of eye contact                                      | : | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.<br>If easy to do, remove contact lens, if worn.<br>Get medical attention.<br>Eyelid bonding: see a doctor.                                      |
| If swallowed  | : | If swallowed, DO NOT induce vomiting.<br>Get medical attention if symptoms occur.<br>Rinse mouth thoroughly with water.  |
| Most important symptoms and effects, both acute and delayed | : | Causes skin irritation.<br>Causes serious eye irritation.<br>May cause respiratory irritation.   |
| Protection of first-aiders                                  | : | First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).  |
| Notes to physician  | : | Treat symptomatically and supportively.  |

**SECTION 5. FIRE-FIGHTING MEASURES**

- |                                       |   |  |
|---------------------------------------|---|--|
| Suitable extinguishing media          | : | Water spray<br>Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical |
| Unsuitable extinguishing media        | : | High volume water jet  |
| Specific hazards during fire fighting | : | Do not use a solid water stream as it may scatter and spread fire.                         |

**KLEBFIX, 18 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2023
2.19	07/26/2023	10625424-00013	Date of first issue: 03/25/2014

---

Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.

- Hazardous combustion products : Carbon oxides  
Nitrogen oxides (NO<sub>x</sub>)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

**KLEBFIX, 18 mL**

Version 2.19      Revision Date: 07/26/2023      SDS Number: 10625424-00013      Date of last issue: 04/24/2023  
 Date of first issue: 03/25/2014

- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
 Avoid breathing mist or vapors.  
 Do not swallow.  
 Do not get in eyes.  
 Wash skin thoroughly after handling.  
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
 Keep container tightly closed.  
 Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Take precautionary measures against static discharges.  
 Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
 Store locked up.  
 Keep tightly closed.  
 Keep in a cool, well-ventilated place.  
 Store in accordance with the particular national regulations.  
 Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:  
 Strong oxidizing agents  
 Explosives  
 Gases

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethyl 2-cyanoacrylate	7085-85-0	TWA	0.2 ppm 1 mg/m <sup>3</sup>	CA AB OEL
		TWA	0.2 ppm	CA BC OEL
		TWA	0.2 ppm	ACGIH
		STEL	1 ppm	ACGIH

- Engineering measures** : Minimize workplace exposure concentrations.  
 If sufficient ventilation is unavailable, use with local exhaust ventilation.

**Personal protective equipment**

- Respiratory protection : If adequate local exhaust ventilation is not available or expo-

**KLEBFIX, 18 mL**

Version 2.19      Revision Date: 07/26/2023      SDS Number: 10625424-00013      Date of last issue: 04/24/2023  
Date of first issue: 03/25/2014

---

sure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Organic vapor Type

**Hand protection**

Material : butyl-rubber  
Break through time : 60 min  
Glove thickness : > 0.6 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : colorless

Odor : irritating

Odor Threshold : No data available

pH : substance/mixture reacts with water

Melting point/freezing point : No data available

**KLEBFIX, 18 mL**

Version            Revision Date:            SDS Number:            Date of last issue: 04/24/2023  
2.19                07/26/2023                10625424-00013            Date of first issue: 03/25/2014

---

Initial boiling point and boiling range : No data available

Flash point : 70 - < 90 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 1.05 g/cm<sup>3</sup> (20 °C)  
Method: DIN 51757

Solubility(ies)  
Water solubility : hydrolyzes

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : 20 - 40 mPa.s ( 25 °C)  
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

## KLEBFIX, 18 mL

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2023
2.19	07/26/2023	10625424-00013	Date of first issue: 03/25/2014

---

Possibility of hazardous reactions : Combustible liquid.  
Vapors may form explosive mixture with air.  
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Components:****Ethyl 2-cyanoacrylate:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**Skin corrosion/irritation**

Causes skin irritation.

**Components:****Ethyl 2-cyanoacrylate:**

Species : Rabbit  
Result : Skin irritation

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Components:****Ethyl 2-cyanoacrylate:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.



## KLEBFIX, 18 mL

Version 2.19      Revision Date: 07/26/2023      SDS Number: 10625424-00013      Date of last issue: 04/24/2023  
Date of first issue: 03/25/2014

---

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Ethyl 2-cyanoacrylate:**

Genotoxicity in vitro                   : Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

May cause respiratory irritation.

**Components:****Ethyl 2-cyanoacrylate:**

Assessment                               : May cause respiratory irritation.

**STOT-repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability****Components:****Ethyl 2-cyanoacrylate:**

Biodegradability                       : Remarks: No data available

**Bioaccumulative potential****Components:****Ethyl 2-cyanoacrylate:**

Partition coefficient: n-               : Pow: 0.776  
octanol/water

## KLEBFIX, 18 mL

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2023
2.19	07/26/2023	10625424-00013	Date of first issue: 03/25/2014

---

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**UN/ID No. : UN 3334  
Proper shipping name : Aviation regulated liquid, n.o.s.  
(Ethyl 2-cyanoacrylate)  
Class : 9  
Packing group : III  
Labels : Miscellaneous  
Packing instruction (cargo aircraft) : 964  
Packing instruction (passenger aircraft) : 964**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

Not regulated as a dangerous good

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

## KLEBFIX, 18 mL

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2023
2.19	07/26/2023	10625424-00013	Date of first issue: 03/25/2014

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION****The ingredients of this product are reported in the following inventories:**

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

**Additional regulatory information**

1,4-Benzenediol 123-31-9

This product contains CAS 123-31-9, which is subject to a Significant New Activity No. 123-31-9 S', per Canada Gazette December 21, 2011

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation,

## KLEBFIX, 18 mL

Version	Revision Date:	SDS Number:	Date of last issue: 04/24/2023
2.19	07/26/2023	10625424-00013	Date of first issue: 03/25/2014

---

Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 07/26/2023  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8