according to the Hazardous Products Regulations



## FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

#### **SECTION 1. IDENTIFICATION**

Product name : FLEXIBLE FOAM, Component B, 110 ml

Product code : 893.100080B

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd

GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:

CHEMTREC (24/7): 1-800-424-9300

Transport related emergencies:

CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou

exposition:

CHEMTREC (24/7): 1-800-424-9300

Urgences liées au transport:

CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Polymer

**Paints** 

Restrictions on use : Not applicable

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the Hazardous Products Regulations

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Respiratory sensitization : Category 1

according to the Hazardous Products Regulations



## FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 06/19/2024 5246574-00006 Date of first issue: 11/04/2019 2.2

Skin sensitization Category 1

Carcinogenicity Category 2

Specific target organ toxicity

- single exposure

Category 3

Specific target organ toxicity - repeated exposure (Inhala-

tion)

Category 2 (Respiratory Tract)

#### **GHS** label elements

Hazard pictograms





Signal Word Danger

**Hazard Statements** H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing diffi-

culties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs (Respiratory Tract) through

prolonged or repeated exposure if inhaled.

#### **Precautionary Statements** Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe mist or vapors.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves, protective clothing, eye protection

and face protection.

P284 Wear respiratory protection.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical attention.

according to the Hazardous Products Regulations



## FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

P333 + P313 If skin irritation or rash occurs: Get medical atten-

tion.

P337 + P313 If eye irritation persists: Get medical attention. P342 + P311 If experiencing respiratory symptoms: Call a doc-

tor.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

#### Other hazards

Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### Components

| Chemical name        | Common           | CAS-No.    | Concentration (% w/w) |  |
|----------------------|------------------|------------|-----------------------|--|
|                      | Name/Synonym     |            |                       |  |
| 4,4'-Diphenylmethane | Benzene, 1,1'-   | 101-68-8   |                       |  |
| diisocyanate         | methylenebis[4-  |            | >= 10 - < 30 *        |  |
|                      | isocyanato-      |            |                       |  |
| Methylenediphenyl    | Benzene, 1,1'-   | 26447-40-5 |                       |  |
| diisocyanate         | meth-            |            | >= 10 - < 30 *        |  |
|                      | ylenebis[isocyan |            | >= 10 - < 30          |  |
|                      | ato-             |            |                       |  |

<sup>\*</sup> Actual concentration or concentration range is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

according to the Hazardous Products Regulations



## FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention.

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Respiratory symptoms, including pulmonary edema, may be

delayed.

Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reac-

tive airways dysfunction syndrome).

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Water spray in large fire situations

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod-

ucts

Carbon oxides

Nitrogen oxides (NOx)

Hydrogen cyanide (hydrocyanic acid)

Isocyanates

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

according to the Hazardous Products Regulations



## FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions

Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent

After approximately one hour, transfer to waste container and

do not seal, due to evolution of carbon dioxide.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

### **SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe mist or vapors.

Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety

according to the Hazardous Products Regulations



# FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

practice, based on the results of the workplace exposure as-

sessment

Keep container tightly closed.

Protect from moisture.

Already sensitized individuals, and those susceptible

to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respira-

tory irritants or sensitizers.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store locked up.
Protect from moisture.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Gases

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Ingredients with workplace control parameters

| Components                          | CAS-No.    | Value type<br>(Form of<br>exposure) | Control parameters / Permissible concentration | Basis     |
|-------------------------------------|------------|-------------------------------------|--|-----------|
| 4,4'-Diphenylmethane diisocyanate   | 101-68-8   | TWA                                 | 0.005 ppm                                      | CA BC OEL |
|                                     |            | С                                   | 0.01 ppm                                       | CA BC OEL |
|                                     |            | TWA                                 | 0.005 ppm                                      | CA ON OEL |
|                                     |            | С                                   | 0.02 ppm                                       | CA ON OEL |
|                                     |            | TWAEV                               | 0.005 ppm<br>0.051 mg/m <sup>3</sup>           | CA QC OEL |
|                                     |            | TWA                                 | 0.005 ppm                                      | ACGIH     |
| Methylenediphenyl diisocyana-<br>te | 26447-40-5 | TWAEV                               | 0.005 ppm<br>0.051 mg/m <sup>3</sup>           | CA QC OEL |
|                                     |            | TWA                                 | 0.005 ppm                                      | CA BC OEL |
|                                     |            | С                                   | 0.01 ppm                                       | CA BC OEL |
|                                     |            | TWA                                 | 0.005 ppm                                      | ACGIH     |

**Engineering measures** : Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the re-

commended guidelines, use respiratory protection.

according to the Hazardous Products Regulations



## FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 06/19/2024 5246574-00006 Date of first issue: 11/04/2019 2.2

Filter type Combined particulates and organic vapor type

Hand protection

Material Chemical-resistant gloves

Remarks Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks

and at the end of workday.

Eye protection Wear the following personal protective equipment:

Safety goggles

Skin and body protection Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

workplace.

Wash contaminated clothing before re-use.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance** liquid

Color light yellow

Odor slight, aromatic

Odor Threshold No data available

No data available рΗ

Melting point/freezing point No data available

Initial boiling point and boiling : No data available

range

according to the Hazardous Products Regulations



# FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

Flash point : 188 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : 1.241 g/cm<sup>3</sup>

Solubility(ies)

Water solubility : Reacts with water.

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : > 500 °C

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size : Not applicable

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable if used as directed. Follow precautionary advice and

avoid incompatible materials and conditions.

Polymerizes at high temperatures with evolution of carbon

dioxide.

according to the Hazardous Products Regulations



# FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

Possibility of hazardous reac-

tions

Isocyanates react with many materials and the rate of reaction increases with temperature as well as increased contact; these reactions can become violent. Contact is increased by stirging or if the other material mixes with the increased.

ring or if the other material mixes with the isocyanate. Exothermic reaction with acids, amines and alcohols Reacts with water to form carbon dioxide and heat

Isocyanates are not soluble in water and sink to the bottom, but react slowly at the interface. The reaction forms carbon

dioxide gas and a layer of solid polyurea.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Acids
Bases
Water
Alcohols
Amines
Ammonia
Aluminum
Zinc
Brass
Tin
Copper

Galvanized metals

Humid air

Hazardous decomposition

products

No hazardous decomposition products are known.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

#### **Acute toxicity**

Harmful if inhaled.

### **Product:**

Acute inhalation toxicity : Assessment: The substance/mixture is not toxic on inhalation

as defined by dangerous goods regulations.

Acute toxicity estimate: 2.63 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

according to the Hazardous Products Regulations



## FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

#### **Components:**

4,4'-Diphenylmethane diisocyanate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 2.24 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: Based on data from similar materials

Methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.49 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Remarks: Based on data from similar materials

Acute toxicity estimate: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgment

Remarks: Based on national or regional regulation.

LC50 (Rat): > 2.24 mg/l Exposure time: 1 h

Test atmosphere: dust/mist

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

#### **Components:**

## 4,4'-Diphenylmethane diisocyanate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Remarks : Based on data from similar materials

#### Methylenediphenyl diisocyanate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

according to the Hazardous Products Regulations



## FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### **Components:**

### 4,4'-Diphenylmethane diisocyanate:

Result : Irritation to eyes, reversing within 7 days Remarks : Based on national or regional regulation.

#### Methylenediphenyl diisocyanate:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Result : Irritation to eyes, reversing within 21 days Remarks : Based on national or regional regulation.

#### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

### Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### **Components:**

### 4,4'-Diphenylmethane diisocyanate:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : positive

Assessment : Probability or evidence of skin sensitization in humans

Routes of exposure : Inhalation Species : Rat Result : positive

Remarks : Based on data from similar materials

Assessment : Probability of respiratory sensitization in humans based on

animal testing

### Methylenediphenyl diisocyanate:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : positive

Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitization in humans

according to the Hazardous Products Regulations



## FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

Routes of exposure : Inhalation Species : Rat Result : positive

Remarks : Based on data from similar materials

Assessment : Probability of respiratory sensitization in humans based on

animal testing

Germ cell mutagenicity

Not classified based on available information.

**Components:** 

4,4'-Diphenylmethane diisocyanate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (dust/mist/fume)

Method: OECD Test Guideline 474

Result: negative

Methylenediphenyl diisocyanate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Suspected of causing cancer.

**Components:** 

4,4'-Diphenylmethane diisocyanate:

Species : Rat

Application Route : inhalation (dust/mist/fume)

Exposure time : 2 Years Result : positive

Remarks : Based on data from similar materials

Carcinogenicity - Assess-

ment

: Limited evidence of carcinogenicity in animal studies

according to the Hazardous Products Regulations



## FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

### Methylenediphenyl diisocyanate:

Species : Ra

Application Route : inhalation (dust/mist/fume)

Exposure time : 2 Years Result : positive

Remarks : Based on data from similar materials

Carcinogenicity - Assess-

ment

: Limited evidence of carcinogenicity in animal studies

#### Reproductive toxicity

Not classified based on available information.

#### Components:

### 4,4'-Diphenylmethane diisocyanate:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (dust/mist/fume)

Result: negative

Remarks: Based on data from similar materials

#### Methylenediphenyl diisocyanate:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (dust/mist/fume)

Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

### STOT-single exposure

May cause respiratory irritation.

#### **Components:**

### 4,4'-Diphenylmethane diisocyanate:

Assessment : May cause respiratory irritation.

#### Methylenediphenyl diisocyanate:

Assessment : May cause respiratory irritation.

#### STOT-repeated exposure

May cause damage to organs (Respiratory Tract) through prolonged or repeated exposure if inhaled.

#### **Components:**

### 4,4'-Diphenylmethane diisocyanate:

Routes of exposure : inhalation (dust/mist/fume)

Target Organs : Respiratory Tract

Assessment : Shown to produce significant health effects in animals at con-

according to the Hazardous Products Regulations



## FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

centrations of >0.02 to 0.2 mg/l/6h/d.

### Methylenediphenyl diisocyanate:

Routes of exposure : inhalation (dust/mist/fume)

Target Organs : Respiratory Tract

Assessment : May cause damage to organs through prolonged or repeated

exposure.

#### Repeated dose toxicity

#### **Components:**

### 4,4'-Diphenylmethane diisocyanate:

Species : Rat

NOAEL : 0,2 mg/m3 LOAEL : 1 mg/m3

Application Route : inhalation (dust/mist/fume)

Exposure time : 2 y

Remarks : Based on data from similar materials

### Methylenediphenyl diisocyanate:

Species : Rat

NOAEL : 0.0002 mg/l LOAEL : 0.001 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 2 y

Remarks : Based on data from similar materials

### **Aspiration toxicity**

Not classified based on available information.

#### **Experience with human exposure**

### **Components:**

### Methylenediphenyl diisocyanate:

Inhalation : Symptoms: Sensitization, respiratory tract irritation

Skin contact : Symptoms: Skin irritation

Eye contact : Symptoms: Eye irritation

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

#### **Components:**

#### 4,4'-Diphenylmethane diisocyanate:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 3,000 mg/l

Exposure time: 96 h

according to the Hazardous Products Regulations



## FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 129.7 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 1,640

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): 1,640 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Methylenediphenyl diisocyanate:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 1,000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 24 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EL50 (Scenedesmus subspicatus): > 1,640 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOELR (Scenedesmus subspicatus): 1,640 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOELR (Daphnia): >= 10 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l

according to the Hazardous Products Regulations



## FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

### Persistence and degradability

### Components:

### 4,4'-Diphenylmethane diisocyanate:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 302

Remarks: Based on data from similar materials

### Methylenediphenyl diisocyanate:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Remarks: Based on data from similar materials

#### **Bioaccumulative potential**

### Components:

### 4,4'-Diphenylmethane diisocyanate:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 200

Partition coefficient: n-

octanol/water

log Pow: 4.51

### Methylenediphenyl diisocyanate:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 200

Remarks: Based on data from similar materials

Partition coefficient: n-

octanol/water

log Pow: 4.51

### Mobility in soil

No data available

#### Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal methods**

Waste from residues : Do not dispose of waste into sewer.

according to the Hazardous Products Regulations



## FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

#### **UNRTDG**

Not regulated as a dangerous good

**IATA-DGR** 

UN/ID No. : UN 3334

Proper shipping name : Aviation regulated liquid, n.o.s.

(4,4'-Diphenylmethane diisocyanate, Methylenediphenyl dii-

socyanate)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

: 964

Packing instruction (passen- :

ger aircraft)

964

### **IMDG-Code**

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **Domestic regulation**

### **TDG**

Not regulated as a dangerous good

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### **SECTION 15. REGULATORY INFORMATION**

Volatile organic compounds

(VOC) content

CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 -

Guidelines for VOC in Consumer Products

VOC content: 0 % / 0 g/l

#### The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).

according to the Hazardous Products Regulations



## FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 06/19/2024 5246574-00006 Date of first issue: 11/04/2019 2.2

#### **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations

**ACGIH** USA. ACGIH Threshold Limit Values (TLV)

CA BC OEL Canada. British Columbia OEL

CA ON OEL Ontario Table of Occupational Exposure Limits made under

the Occupational Health and Safety Act.

Québec. Regulation respecting occupational health and safe-CA QC OEL

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA 8-hour, time-weighted average CA BC OEL / TWA 8-hour time weighted average

CA BC OEL / C ceiling limit CA ON OEL / C : Ceiling Limit (C)

CA ON OEL / TWA Time-Weighted Average Limit (TWA) CA QC OEL / TWAEV Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships: n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

compile the Material Safety

Sources of key data used to : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

according to the Hazardous Products Regulations



# FLEXIBLE FOAM, Component B, 110 ml

Version Revision Date: SDS Number: Date of last issue: 11/10/2022 2.2 06/19/2024 5246574-00006 Date of first issue: 11/04/2019

Data Sheet cy, http://echa.europa.eu/

Revision Date : 06/19/2024 Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8