

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version 4.5      Revision Date: 06/24/2024      SDS Number: 10693562-00008      Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

---

### SECTION 1. IDENTIFICATION

Product name : WEATHERSTRIP ADHESIVE, 148 mL  
Product code : 893.100095  
Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : +1 (905) 564 6225  
Telefax : +1 (905) 564 3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)  
  
Urgences impliquant un déversement, incendie, explosion ou exposition:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences liées au transport:  
CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)  
  
E-mail address : prodsafe@wurth.ca

#### Recommended use of the chemical and restrictions on use

Recommended use : Adhesives  
Restrictions on use : Not applicable

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 2  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Reproductive toxicity : Category 2  
Specific target organ toxicity : Category 3  
- single exposure  
Specific target organ toxicity : Category 2 (Central nervous system)  
- repeated exposure

#### GHS label elements

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version 4.5      Revision Date: 06/24/2024      SDS Number: 10693562-00008      Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

---

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.  
H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements

:

**Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P332 + P313 If skin irritation occurs: Get medical attention.  
P337 + P313 If eye irritation persists: Get medical attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents and container to an approved waste disposal plant.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version 4.5      Revision Date: 06/24/2024      SDS Number: 10693562-00008      Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

### Other hazards

Vapors may form explosive mixture with air.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
Chemical nature : Adhesives

#### Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Toluene	Benzene, methyl-	108-88-3	$\geq 10 - < 30$ *
Butanone	Ethyl methyl ketone	78-93-3	$\geq 10 - < 30$ *
Acetone	2-Propanone	67-64-1	$\geq 10 - < 30$ *
n-Hexane	Hexyl hydride	110-54-3	$\geq 10 - < 30$ *

\* Actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of damaging fertility. Suspected of damaging the unborn child.  
May cause damage to organs through prolonged or repeated exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2023
4.5	06/24/2024	10693562-00008	Date of first issue: 06/28/2017

---

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Chlorine compounds  
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Ventilate the area.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2023
4.5	06/24/2024	10693562-00008	Date of first issue: 06/28/2017

determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not get on skin or clothing.  
Do not breathe mist or vapors.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Non-sparking tools should be used.  
Keep container tightly closed.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Self-reactive substances and mixtures  
Organic peroxides  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases  
Very acutely toxic substances and mixtures
- Storage period : 18 Months

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version  
4.5

Revision Date:  
06/24/2024

SDS Number:  
10693562-00008

Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Toluene	108-88-3	TWA	50 ppm 188 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		TWA	20 ppm	ACGIH
Butanone	78-93-3	TWA	200 ppm 590 mg/m <sup>3</sup>	CA AB OEL
		STEL	300 ppm 885 mg/m <sup>3</sup>	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	50 ppm 150 mg/m <sup>3</sup>	CA QC OEL
		STEV	100 ppm 300 mg/m <sup>3</sup>	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m <sup>3</sup>	CA AB OEL
		STEL	750 ppm 1,800 mg/m <sup>3</sup>	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	250 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
n-Hexane	110-54-3	TWA	50 ppm 176 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 176 mg/m <sup>3</sup>	CA QC OEL
		TWA	50 ppm	ACGIH

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure)	0.03 mg/l	ACGIH BEI

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version 4.5      Revision Date: 06/24/2024      SDS Number: 10693562-00008      Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI
Butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
n-Hexane	110-54-3	2,5-Hexanedione	Urine	End of shift	0.5 mg/l	ACGIH BEI

**Engineering measures** : Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often!  
For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2023
4.5	06/24/2024	10693562-00008	Date of first issue: 06/28/2017

---

potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).  
Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	black
Odor	:	characteristic
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	56 °C
Flash point	:	< -20 °C
Evaporation rate	:	> 1
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	233 hPa (20 °C)
Relative vapor density	:	> 1
Relative density	:	No data available
Density	:	0.895 - 0.905 g/cm <sup>3</sup> (20 °C)
Solubility(ies)	:	



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2023
4.5	06/24/2024	10693562-00008	Date of first issue: 06/28/2017

---

Water solubility	:	partly miscible
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	8,400 - 9,400 mPa.s
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s ( 40 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics		
Particle size	:	Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Highly flammable liquid and vapor. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### **Product:**

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method

---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version 4.5      Revision Date: 06/24/2024      SDS Number: 10693562-00008      Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

---

### Components:

#### **Toluene:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

#### **Butanone:**

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 25.5 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 436  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

#### **Acetone:**

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

#### **n-Hexane:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 31.86 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

### **Skin corrosion/irritation**

Causes skin irritation.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version 4.5      Revision Date: 06/24/2024      SDS Number: 10693562-00008      Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

---

### Components:

#### **Toluene:**

Species : Rabbit  
Method : Directive 67/548/EEC, Annex V, B.4.  
Result : Skin irritation

#### **Butanone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

#### **Acetone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

#### **n-Hexane:**

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### Components:

#### **Toluene:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

#### **Butanone:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Method : OECD Test Guideline 405

#### **Acetone:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Method : OECD Test Guideline 405

#### **n-Hexane:**

Species : Rabbit  
Result : No eye irritation

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version 4.5      Revision Date: 06/24/2024      SDS Number: 10693562-00008      Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

---

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

#### Components:

##### Toluene:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : Directive 67/548/EEC, Annex V, B.6.  
Result : negative

##### Butanone:

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

##### Acetone:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

##### n-Hexane:

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Result : negative

### Germ cell mutagenicity

Not classified based on available information.

#### Components:

##### Toluene:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: Intraperitoneal injection

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version 4.5      Revision Date: 06/24/2024      SDS Number: 10693562-00008      Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

---

Result: negative

Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 478  
Result: negative

### Butanone:

Genotoxicity in vitro

: Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

Test Type: Saccharomyces cerevisiae, gene mutation assay (in vitro)  
Result: negative

Genotoxicity in vivo

: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

### Acetone:

Genotoxicity in vitro

: Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo

: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

### n-Hexane:

Genotoxicity in vitro

: Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version 4.5      Revision Date: 06/24/2024      SDS Number: 10693562-00008      Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

---

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: inhalation (vapor)  
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow  
cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

### Carcinogenicity

Not classified based on available information.

### Components:

#### Toluene:

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 103 weeks  
Result : negative

Species : Mouse  
Application Route : Skin contact  
Exposure time : 24 Months  
Result : negative

#### Acetone:

Species : Mouse  
Application Route : Skin contact  
Exposure time : 424 days  
Result : negative

#### n-Hexane:

Species : Mouse  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : negative  
Remarks : Based on data from similar materials

### Reproductive toxicity

Suspected of damaging fertility. Suspected of damaging the unborn child.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version 4.5      Revision Date: 06/24/2024      SDS Number: 10693562-00008      Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

---

### Components:

#### **Toluene:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 416  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

#### **Butanone:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Inhalation  
Method: OECD Test Guideline 414  
Result: negative

#### **Acetone:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

#### **n-Hexane:**

Effects on fertility : Test Type: Fertility/early embryonic development  
Application Route: inhalation (vapor)  
Result: positive

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Mouse  
Application Route: inhalation (vapor)  
Result: negative

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and





# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version 4.5      Revision Date: 06/24/2024      SDS Number: 10693562-00008      Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

---

### Butanone:

Species : Rat  
NOAEL : 14.84 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days  
Method : OECD Test Guideline 413

### Acetone:

Species : Rat  
NOAEL : 900 mg/kg  
LOAEL : 1,700 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
NOAEL : 45 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 8 Weeks

### n-Hexane:

Species : Mouse  
LOAEL : 1.76 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks

Species : Rat, male  
NOAEL : 568 mg/kg  
LOAEL : 3,973 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

### Aspiration toxicity

Not classified based on available information.

### Components:

#### Toluene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### Butanone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

#### Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version 4.5      Revision Date: 06/24/2024      SDS Number: 10693562-00008      Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

---

### n-Hexane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### Experience with human exposure

#### Components:

#### **Toluene:**

Inhalation : Target Organs: Central nervous system  
Symptoms: Neurological disorders

#### **n-Hexane:**

Inhalation : Target Organs: Central nervous system  
Symptoms: Central nervous system depression

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### **Toluene:**

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Skeletonema costatum (marine diatom)): 10 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l  
Exposure time: 40 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): 0.74 mg/l  
Exposure time: 7 d

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 84 mg/l  
Exposure time: 24 h

#### **Butanone:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 2,029 mg/l  
Exposure time: 96 h

---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version 4.5      Revision Date: 06/24/2024      SDS Number: 10693562-00008      Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

---

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 1,240 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

### Acetone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 8,800 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 79 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: 61,150 mg/l  
Exposure time: 30 min  
Method: ISO 8192

### n-Hexane:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.5 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3.88 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 55 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEL (Pseudokirchneriella subcapitata (green algae)): 30 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

### Persistence and degradability

#### Components:

#### **Toluene:**

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version 4.5      Revision Date: 06/24/2024      SDS Number: 10693562-00008      Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

---

**Biodegradability** : Result: Readily biodegradable.  
Biodegradation: 80 %  
Exposure time: 20 d

### **Butanone:**

**Biodegradability** : Result: Readily biodegradable.  
Biodegradation: 98 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

### **Acetone:**

**Biodegradability** : Result: Readily biodegradable.  
Biodegradation: 91 %  
Exposure time: 28 d

### **n-Hexane:**

**Biodegradability** : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

## **Bioaccumulative potential**

### **Components:**

#### **Toluene:**

**Bioaccumulation** : Species: Leuciscus idus (Golden orfe)  
Bioconcentration factor (BCF): 90

**Partition coefficient: n-octanol/water** : log Pow: 2.73

#### **Butanone:**

**Partition coefficient: n-octanol/water** : log Pow: 0.3

#### **Acetone:**

**Partition coefficient: n-octanol/water** : log Pow: -0.27 - -0.23

#### **n-Hexane:**

**Partition coefficient: n-octanol/water** : log Pow: 4

### **Mobility in soil**

No data available

### **Other adverse effects**

No data available

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version 4.5      Revision Date: 06/24/2024      SDS Number: 10693562-00008      Date of last issue: 05/29/2023  
Date of first issue: 06/28/2017

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

UN number : UN 1133  
Proper shipping name : ADHESIVES  
Class : 3  
Packing group : II  
Labels : 3  
Environmentally hazardous : no

##### IATA-DGR

UN/ID No. : UN 1133  
Proper shipping name : Adhesives  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

##### IMDG-Code

UN number : UN 1133  
Proper shipping name : ADHESIVES  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-D  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### TDG

UN number : UN 1133  
Proper shipping name : ADHESIVES  
Class : 3

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2023
4.5	06/24/2024	10693562-00008	Date of first issue: 06/28/2017

Packing group : II  
Labels : 3  
ERG Code : 128  
Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

**Volatile organic compounds (VOC) content** CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products  
VOC content: 52 % / 575 g/l

### The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL : Canada. British Columbia OEL  
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants  
ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
CA AB OEL / TWA : 8-hour Occupational exposure limit  
CA AB OEL / STEL : 15-minute occupational exposure limit  
CA BC OEL / TWA : 8-hour time weighted average  
CA BC OEL / STEL : short-term exposure limit  
CA QC OEL / TWA EV : Time-weighted average exposure value  
CA QC OEL / STEV : Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory con-

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## WEATHERSTRIP ADHESIVE, 148 mL

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2023
4.5	06/24/2024	10693562-00008	Date of first issue: 06/28/2017

---

centration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/24/2024  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8