

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

SECTION 1. IDENTIFICATION

Product name : HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Product code : 893.10633

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 1

Skin irritation : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 2

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version 1.0	Revision Date: 03/22/2024	SDS Number: 11365647-00001	Date of last issue: - Date of first issue: 03/22/2024
----------------	------------------------------	-------------------------------	--

Specific target organ toxicity : Category 3
- single exposure

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.

Precautionary Statements :

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical attention.
P332 + P313 If skin irritation occurs: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version
1.0

Revision Date:
03/22/2024

SDS Number:
11365647-00001

Date of last issue: -
Date of first issue: 03/22/2024

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy paraffinic	Mineral oil, petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	$\geq 10 - < 30$ *
Acetone	2-Propanone	67-64-1	$\geq 10 - < 30$ *
Isobutane	Propane, 2-methyl-	75-28-5	$\geq 10 - < 30$ *
Distillates (petroleum), hydrotreated heavy paraffinic	Mineral oil, petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	$\geq 5 - < 10$ *
Distillates (petroleum), hydrotreated heavy paraffinic	Mineral oil, petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	$\geq 5 - < 10$ *
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Naphtha (petroleum), hydrotreated light	92128-66-0	$\geq 1 - < 5$ *
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Heptane, branched, cyclic and linear	64742-49-0	$\geq 1 - < 5$ *
Carbon dioxide	Carbonic anhydride	124-38-9	$\geq 1 - < 5$ *
Propane	Dimethylmethane	74-98-6	$\geq 1 - < 5$ *
C11-14-branched alkyl monohexyl and dihexyl phosphate amines	Alkyl-(C11-C14)-monohexyl/dihexyl phosphate amine	80939-62-4	$\geq 1 - < 5$ *
Benzenamine, N-phenyl-, reaction products with 2,4,4-	4-(2,2,3-Trimethylbut-3-en-1-yl)-N-[4-	68411-46-1	$\geq 0.1 - < 1$ *

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version 1.0 Revision Date: 03/22/2024 SDS Number: 11365647-00001 Date of last issue: -
Date of first issue: 03/22/2024

trimethylpentene	(2,2,3-trimethylbut-3-en-1-yl)phenyl]aniline		
------------------	--	--	--

* Actual concentration or concentration range is withheld as a trade secret

Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0

SECTION 4. FIRST AID MEASURES

General advice	: In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	: If inhaled, remove to fresh air. Get medical attention.
In case of skin contact	: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention.
If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	: Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility.
Protection of first-aiders	: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
Notes to physician	: Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Water spray Alcohol-resistant foam
------------------------------	---

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version 1.0	Revision Date: 03/22/2024	SDS Number: 11365647-00001	Date of last issue: - Date of first issue: 03/22/2024
----------------	------------------------------	-------------------------------	--

	Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire fighting	: Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Hazardous combustion products	: Carbon oxides Nitrogen oxides (NO _x) Oxides of phosphorus
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
Environmental precautions	: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	: Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapors/mists with a water spray jet. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version 1.0	Revision Date: 03/22/2024	SDS Number: 11365647-00001	Date of last issue: - Date of first issue: 03/22/2024
----------------	------------------------------	-------------------------------	--

sal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- | | |
|-----------------------------|---|
| Technical measures | : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation. |
| Advice on safe handling | : Do not get on skin or clothing.
Avoid breathing spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source. |
| Conditions for safe storage | : Store locked up.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight. |
| Materials to avoid | : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases |
| Recommended storage tem- | : < 40 °C |

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version 1.0 Revision Date: 03/22/2024 SDS Number: 11365647-00001 Date of last issue: -
Date of first issue: 03/22/2024

perature

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m ³	CA AB OEL
		STEL	750 ppm 1,800 mg/m ³	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	250 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Isobutane	75-28-5	TWA	1,000 ppm	CA AB OEL
		STEL	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	92128-66-0	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version 1.0 Revision Date: 03/22/2024 SDS Number: 11365647-00001 Date of last issue: -
Date of first issue: 03/22/2024

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	TWA	400 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWA	400 ppm 1,640 mg/m ³	CA AB OEL
		STEL	500 ppm 2,050 mg/m ³	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Carbon dioxide	124-38-9	TWA	5,000 ppm 9,000 mg/m ³	CA AB OEL
		STEL	30,000 ppm 54,000 mg/m ³	CA AB OEL
		TWA	5,000 ppm	CA BC OEL
		STEL	15,000 ppm	CA BC OEL
		STEV	30,000 ppm 54,000 mg/m ³	CA QC OEL
		TWAEV	5,000 ppm 9,000 mg/m ³	CA QC OEL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the re-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version 1.0	Revision Date: 03/22/2024	SDS Number: 11365647-00001	Date of last issue: - Date of first issue: 03/22/2024
----------------	------------------------------	-------------------------------	--

commended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0.45 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a dissolved gas

Propellant : Isobutane, Carbon dioxide, Propane, Butane

Color : brown

Odor : characteristic

Odor Threshold : No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version 1.0	Revision Date: 03/22/2024	SDS Number: 11365647-00001	Date of last issue: - Date of first issue: 03/22/2024
----------------	------------------------------	-------------------------------	--

pH	:	substance/mixture is non-soluble (in water)
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	-40 °C
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	14.3 %(V)
Lower explosion limit / Lower flammability limit	:	0.6 %(V)
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Density	:	0.773 g/cm ³ (20 °C) Method: DIN 51757
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version 1.0	Revision Date: 03/22/2024	SDS Number: 11365647-00001	Date of last issue: - Date of first issue: 03/22/2024
----------------	------------------------------	-------------------------------	--

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity	: Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
---------------------------	--

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
Acute inhalation toxicity	: LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Remarks: Based on data from similar materials
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Method: OECD Test Guideline 402 Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

Acetone:

Acute oral toxicity	:	LD50 (Rat): 5,800 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 76 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	:	LD50 (Rabbit): 7,426 mg/kg

Isobutane:

Acute inhalation toxicity	:	LC50 (Mouse): 260200 ppm Exposure time: 4 h Test atmosphere: gas
---------------------------	---	--

Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Method: OECD Test Guideline 402 Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Method: OECD Test Guideline 402 Remarks: Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version 1.0	Revision Date: 03/22/2024	SDS Number: 11365647-00001	Date of last issue: - Date of first issue: 03/22/2024
----------------	------------------------------	-------------------------------	--

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25.2 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 (Rat): > 5,840 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 23.3 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,800 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Carbon dioxide:

Acute inhalation toxicity : LC50 (Rat): 40000 - 50000 ppm
Exposure time: 30 min
Test atmosphere: vapor

Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min
Test atmosphere: gas

C11-14-branched alkyl monoheptyl and diheptyl phosphate amines:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

Skin corrosion/irritation

Causes skin irritation.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Species	:	Rabbit
Result	:	No skin irritation
Remarks	:	Based on data from similar materials

Acetone:

Assessment	:	Repeated exposure may cause skin dryness or cracking.
------------	---	---

Distillates (petroleum), hydrotreated heavy paraffinic:

Species	:	Rabbit
Result	:	No skin irritation
Remarks	:	Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species	:	Rabbit
Result	:	No skin irritation
Remarks	:	Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	Skin irritation

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species	:	Rabbit
Result	:	Skin irritation
Remarks	:	Based on data from similar materials

C11-14-branched alkyl monoheptyl and diheptyl phosphate amines:

Species	:	Rabbit
Result	:	Skin irritation

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	Mild skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

Acetone:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Method	:	OECD Test Guideline 405

Distillates (petroleum), hydrotreated heavy paraffinic:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species	:	Rabbit
Result	:	No eye irritation

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species	:	Rabbit
Result	:	No eye irritation
Remarks	:	Based on data from similar materials

C11-14-branched alkyl monoethyl and diethyl phosphate amines:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative
Remarks	: Based on data from similar materials

Acetone:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative

Distillates (petroleum), hydrotreated heavy paraffinic:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative
Remarks	: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative
Remarks	: Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Test Type	: Maximization Test
Routes of exposure	: Skin contact

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

C11-14-branched alkyl monoheptyl and diheptyl phosphate amines:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Result: negative
Remarks: Based on data from similar materials

Acetone:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

Isobutane:

- | | |
|-----------------------|---|
| Genotoxicity in vitro | : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials |
| Genotoxicity in vivo | : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials |

Distillates (petroleum), hydrotreated heavy paraffinic:

- | | |
|-----------------------|--|
| Genotoxicity in vitro | : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative |
| Genotoxicity in vivo | : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials |

Distillates (petroleum), hydrotreated heavy paraffinic:

- | | |
|-----------------------|--|
| Genotoxicity in vitro | : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative |
| Genotoxicity in vivo | : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials |

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

- | | |
|-----------------------|---|
| Genotoxicity in vitro | : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative |
| Genotoxicity in vivo | : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (vapor)
Method: OPPTS 870.5395
Result: negative |

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

C11-14-branched alkyl monoheptyl and diheptyl phosphate amines:

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Acetone:

Species : Mouse
Application Route : Skin contact
Exposure time : 424 days
Result : negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

Distillates (petroleum), hydrotreated heavy paraffinic:

Species	:	Mouse
Application Route	:	Skin contact
Exposure time	:	78 weeks
Method	:	OECD Test Guideline 451
Result	:	negative
Remarks	:	Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species	:	Mouse
Application Route	:	Skin contact
Exposure time	:	78 weeks
Method	:	OECD Test Guideline 451
Result	:	negative
Remarks	:	Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species	:	Mouse
Application Route	:	Skin contact
Exposure time	:	102 weeks
Result	:	negative

Reproductive toxicity

Suspected of damaging fertility.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Effects on fertility	:	Test Type: Reproduction/Developmental toxicity screening test
		Species: Rat
		Application Route: Ingestion
		Method: OECD Test Guideline 421
		Result: negative
		Remarks: Based on data from similar materials

Acetone:

Effects on fertility	:	Test Type: One-generation reproduction toxicity study
		Species: Rat
		Application Route: Ingestion
		Result: negative

Effects on fetal development	:	Test Type: Embryo-fetal development
		Species: Rat
		Application Route: inhalation (vapor)
		Result: negative

Isobutane:

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the
----------------------	---	---

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

reproduction/developmental toxicity screening test
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Distillates (petroleum), hydrotreated heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version 1.0	Revision Date: 03/22/2024	SDS Number: 11365647-00001	Date of last issue: - Date of first issue: 03/22/2024
----------------	------------------------------	-------------------------------	--

Species: Rat
Application Route: inhalation (vapor)
Result: negative

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

C11-14-branched alkyl monoheptyl and diheptyl phosphate amines:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Effects on fertility : Test Type: One-generation reproduction toxicity study

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 443
Result: positive

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

STOT-single exposure

May cause drowsiness or dizziness.

Components:

Acetone:

Assessment : May cause drowsiness or dizziness.

Isobutane:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Assessment : May cause drowsiness or dizziness.

Propane:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Components:

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

Repeated dose toxicity

Components:

Acetone:

Species	: Rat
NOAEL	: 900 mg/kg
LOAEL	: 1,700 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days
Species	: Rat
NOAEL	: 45 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 8 Weeks

Isobutane:

Species	: Rat
NOAEL	: 9000 ppm
Application Route	: inhalation (gas)
Exposure time	: 6 Weeks
Method	: OECD Test Guideline 422

Distillates (petroleum), hydrotreated heavy paraffinic:

Species	: Rabbit
NOAEL	: 1,000 mg/kg
Application Route	: Skin contact
Exposure time	: 4 Weeks
Method	: OECD Test Guideline 410
Remarks	: Based on data from similar materials

Species	: Rat
NOAEL	: > 980 mg/m ³
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 4 Weeks

Distillates (petroleum), hydrotreated heavy paraffinic:

Species	: Rabbit
NOAEL	: 1,000 mg/kg
Application Route	: Skin contact
Exposure time	: 4 Weeks
Method	: OECD Test Guideline 410
Remarks	: Based on data from similar materials

Species	: Rat
NOAEL	: > 980 mg/m ³
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 4 Weeks

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species	: Rat
NOAEL	: > 20 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 13 Weeks

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species	: Rat
NOAEL	: 12.47 mg/l
Application Route	: Inhalation
Exposure time	: 90 Days
Remarks	: Based on data from similar materials

Propane:

Species	: Rat
NOAEL	: 7.214 mg/l
Application Route	: inhalation (gas)
Exposure time	: 6 Weeks
Method	: OECD Test Guideline 422

C11-14-branched alkyl monoheptyl and diheptyl phosphate amines:

Species	: Rat
LOAEL	: 10 mg/kg
Application Route	: Ingestion
Exposure time	: 29 - 54 Days
Method	: OECD Test Guideline 422

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Species	: Rat
NOAEL	: 25 mg/kg
LOAEL	: 75 mg/kg
Application Route	: Ingestion
Exposure time	: 53 Days
Method	: OECD Test Guideline 422

Aspiration toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): > 1 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Method: DIN 38 412 Part 8

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version 1.0	Revision Date: 03/22/2024	SDS Number: 11365647-00001	Date of last issue: - Date of first issue: 03/22/2024
----------------	------------------------------	-------------------------------	--

Remarks: Based on data from similar materials

Acetone:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia pulex (Water flea)): 8,800 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): >= 79 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to microorganisms	:	EC50: 61,150 mg/l Exposure time: 30 min Method: ISO 8192

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 10 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
Toxicity to microorganisms	:	NOEC: > 1.93 mg/l Exposure time: 10 min Method: DIN 38 412 Part 8 Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
------------------	---	---

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version 1.0	Revision Date: 03/22/2024	SDS Number: 11365647-00001	Date of last issue: - Date of first issue: 03/22/2024
----------------	------------------------------	-------------------------------	--

Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.5 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic) : NOELR (Daphnia magna (Water flea)): 2.6 mg/l
Exposure time: 21 d

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

ic toxicity)

Method: OECD Test Guideline 211

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 13.4 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Selenastrum capricornutum (green algae)): 0.1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.17 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Carbon dioxide:

Toxicity to fish : NOEC (Lepomis macrochirus (Bluegill sunfish)): > 100 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : NOEC (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

C11-14-branched alkyl monoethyl and diethyl phosphate amines:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 10 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

Method: OECD Test Guideline 201

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Acetone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 28 d

Isobutane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 77.05 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Propane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

C11-14-branched alkyl monoethyl and diethyl phosphate amines:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 12 %
Exposure time: 28 d

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential

Components:

Acetone:

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

Isobutane:

Partition coefficient: n-octanol/water : log Pow: 2.8

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Partition coefficient: n-octanol/water : log Pow: 4
Remarks: Based on data from similar materials

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Partition coefficient: n-octanol/water : log Pow: > 4
Remarks: Based on data from similar materials

Carbon dioxide:

Partition coefficient: n-octanol/water : log Pow: 0.83

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version 1.0	Revision Date: 03/22/2024	SDS Number: 11365647-00001	Date of last issue: - Date of first issue: 03/22/2024
----------------	------------------------------	-------------------------------	--

Partition coefficient: n-octanol/water : log Pow: > 4
Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.

Contaminated packaging : Please ensure aerosol cans are sprayed completely empty (including propellant)
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1

EmS Code : F-D, S-U

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 1950

Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1

ERG Code : 126

Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations
VOC content: 25 % / 386.5 g/l
Remarks: VOC content excluding water and exempt compounds

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)

CA BC OEL : Canada. British Columbia OEL

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
--	---	---

Revision Date	:	03/22/2024
Date format	:	mm/dd/yyyy

SAFETY DATA SHEET

according to the Hazardous Products Regulations



HHS 5000, High-temperature adhesive synthetic lubricating oil, 386.5 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/22/2024	11365647-00001	Date of first issue: 03/22/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8