

**LMS FLUID, Food grade lubricant, 344 g**

Version 2.16      Revision Date: 06/06/2023      SDS Number: 10709319-00011      Date of last issue: 01/26/2023  
Date of first issue: 12/23/2009

---

**SECTION 1. IDENTIFICATION**

Product name : LMS FLUID, Food grade lubricant, 344 g  
Product code : 893.107001  
Other means of identification : No data available

**Manufacturer or supplier's details**

Company name of supplier : Würth Canada Limited  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : +1 (905) 564 6225  
Telefax : +1 (905) 564 3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)  
  
Urgences impliquant un déversement, incendie, explosion ou exposition:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences liées au transport:  
CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)  
  
E-mail address : prodsafe@wurth.ca

**Recommended use of the chemical and restrictions on use**

Recommended use : Anti-friction agent and lubricant

Restrictions on use : Not applicable

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Gases under pressure : Compressed gas

**GHS label elements**

Hazard pictograms :



**LMS FLUID, Food grade lubricant, 344 g**

Version 2.16      Revision Date: 06/06/2023      SDS Number: 10709319-00011      Date of last issue: 01/26/2023  
 Date of first issue: 12/23/2009

Signal Word : Warning

Hazard Statements : H280 Contains gas under pressure; may explode if heated.

Precautionary Statements : **Storage:**  
 P410 + P403 Protect from sunlight. Store in a well-ventilated place.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
White mineral oil (petroleum)	Paraffinum liquidum	8042-47-5	>= 80 - <= 100 *

\* Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

If inhaled : If inhaled, remove to fresh air.  
 Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.  
 Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.  
 Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.  
 Get medical attention if symptoms occur.  
 Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : None known.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically and supportively.

**SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray  
 Alcohol-resistant foam  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry chemical

**LMS FLUID, Food grade lubricant, 344 g**

Version	Revision Date:	SDS Number:	Date of last issue: 01/26/2023
2.16	06/06/2023	10709319-00011	Date of first issue: 12/23/2009

---

- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
- 

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
-

**LMS FLUID, Food grade lubricant, 344 g**

Version            Revision Date:            SDS Number:            Date of last issue: 01/26/2023  
2.16                06/06/2023                10709319-00011            Date of first issue: 12/23/2009

- Local/Total ventilation            :    Use only with adequate ventilation.
- Advice on safe handling            :    Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage        :    Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Do not pierce or burn, even after use.  
Keep cool. Protect from sunlight.
- Materials to avoid                 :    Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases
- Recommended storage temperature    :    10 - 40 °C

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Mist)	1 mg/m <sup>3</sup>	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH

- Engineering measures**            :    Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

**LMS FLUID, Food grade lubricant, 344 g**

Version 2.16      Revision Date: 06/06/2023      SDS Number: 10709319-00011      Date of last issue: 01/26/2023  
Date of first issue: 12/23/2009

---

**Personal protective equipment**

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Combined particulates and organic vapor type
- Hand protection
- Material : Nitrile rubber
  - Break through time : 480 min
  - Glove thickness : 0.45 mm
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:  
Safety glasses  
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.  
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.
- Skin and body protection : Skin should be washed after contact.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : Aerosol containing a compressed gas
- Propellant : Air
- Color : colorless
- Odor : odorless
- Odor Threshold : No data available
- pH : substance/mixture is non-soluble (in water)
- Melting point/freezing point : No data available

**LMS FLUID, Food grade lubricant, 344 g**

Version	Revision Date:	SDS Number:	Date of last issue: 01/26/2023
2.16	06/06/2023	10709319-00011	Date of first issue: 12/23/2009

---

Initial boiling point and boiling range : > 250 °C

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Density : 0.81 g/cm<sup>3</sup> (20 °C)

Solubility(ies)  
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : 250 °C

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

**LMS FLUID, Food grade lubricant, 344 g**

Version	Revision Date:	SDS Number:	Date of last issue: 01/26/2023
2.16	06/06/2023	10709319-00011	Date of first issue: 12/23/2009

---

Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Components:****White mineral oil (petroleum):**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****White mineral oil (petroleum):**

Species	:	Rabbit
Result	:	No skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:****White mineral oil (petroleum):**

Species	:	Rabbit
Result	:	No eye irritation

**LMS FLUID, Food grade lubricant, 344 g**

Version            Revision Date:            SDS Number:            Date of last issue: 01/26/2023  
2.16                06/06/2023                10709319-00011            Date of first issue: 12/23/2009

---

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Components:****White mineral oil (petroleum):**

Test Type                                : Buehler Test  
Routes of exposure                    : Skin contact  
Species                                    : Guinea pig  
Result                                      : negative

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****White mineral oil (petroleum):**

Genotoxicity in vitro                : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Genotoxicity in vivo                 : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Carcinogenicity**

Not classified based on available information.

**Components:****White mineral oil (petroleum):**

Species                                    : Rat  
Application Route                      : Ingestion  
Exposure time                          : 24 Months  
Result                                      : negative

**Reproductive toxicity**

Not classified based on available information.

**Components:****White mineral oil (petroleum):**

Effects on fertility                    : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Skin contact  
Result: negative



**LMS FLUID, Food grade lubricant, 344 g**

Version 2.16      Revision Date: 06/06/2023      SDS Number: 10709319-00011      Date of last issue: 01/26/2023  
Date of first issue: 12/23/2009

---

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.

**Repeated dose toxicity****Components:****White mineral oil (petroleum):**

Species : Rat  
LOAEL : > 160 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
LOAEL : >= 1 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 4 Weeks  
Method : OECD Test Guideline 412

**Aspiration toxicity**

Not classified based on available information.

**Components:****White mineral oil (petroleum):**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****White mineral oil (petroleum):**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : NOEC (Pseudokirchneriella subcapitata (green algae)): 100  
plants : mg/l  
Exposure time: 72 h

**LMS FLUID, Food grade lubricant, 344 g**

Version	Revision Date:	SDS Number:	Date of last issue: 01/26/2023
2.16	06/06/2023	10709319-00011	Date of first issue: 12/23/2009

---

Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l  
Exposure time: 28 dToxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1,000 mg/l  
Exposure time: 21 d**Persistence and degradability****Components:****White mineral oil (petroleum):**Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 31 %  
Exposure time: 28 d**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.  
Please ensure aerosol cans are sprayed completely empty (including propellant)

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.2  
Packing group : Not assigned by regulation  
Labels : 2.2**IATA-DGR**

UN/ID No. : UN 1950

**LMS FLUID, Food grade lubricant, 344 g**

Version	Revision Date:	SDS Number:	Date of last issue: 01/26/2023
2.16	06/06/2023	10709319-00011	Date of first issue: 12/23/2009

---

Proper shipping name : Aerosols, non-flammable  
 Class : 2.2  
 Packing group : Not assigned by regulation  
 Labels : Non-flammable, non-toxic Gas  
 Packing instruction (cargo aircraft) : 203  
 Packing instruction (passenger aircraft) : 203

**IMDG-Code**

UN number : UN 1950  
 Proper shipping name : AEROSOLS

Class : 2.2  
 Packing group : Not assigned by regulation  
 Labels : 2.2  
 EmS Code : F-D, S-U  
 Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation**
**TDG**

UN number : UN 1950  
 Proper shipping name : AEROSOLS

Class : 2.2  
 Packing group : Not assigned by regulation  
 Labels : 2.2  
 ERG Code : 126  
 Marine pollutant : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

**SECTION 15. REGULATORY INFORMATION**
**The ingredients of this product are reported in the following inventories:**

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

---

**SECTION 16. OTHER INFORMATION**
**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)

**LMS FLUID, Food grade lubricant, 344 g**

Version	Revision Date:	SDS Number:	Date of last issue: 01/26/2023
2.16	06/06/2023	10709319-00011	Date of first issue: 12/23/2009

CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <a href="http://echa.europa.eu/">http://echa.europa.eu/</a>
--	---	---

Revision Date	:	06/06/2023
Date format	:	mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be

**LMS FLUID, Food grade lubricant, 344 g**

Version	Revision Date:	SDS Number:	Date of last issue: 01/26/2023
2.16	06/06/2023	10709319-00011	Date of first issue: 12/23/2009

---

considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8