

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

SECTION 1. IDENTIFICATION

Product name : PERFECT LIGHT ZINC SPRAY, 325 g
Product code : 893.114114
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : 1-800-263-5002
Telefax : 1-905-564-3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Urgences impliquant un déversement, incendie, explosion ou
exposition: CHEMTREC (24/7): 1-800-424-9300
E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Solvent-borne coatings
Compressed Gas (Aerosol cans)
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 1
Specific target organ toxicity : Category 2 (Auditory system)
- repeated exposure
Specific target organ toxicity : Category 3
- single exposure
Eye irritation : Category 2A
Skin irritation : Category 2

GHS label elements

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Hazard pictograms :   

Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, eye protection and face protection.

Response:
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical attention if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:
P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Dimethyl ether	Methane, 1,1'-oxybis-	115-10-6	$\geq 30 - < 60$ *
Xylene	Benzene, dimethyl-	1330-20-7	$\geq 5 - < 10$ *
Ethyl acetate	Ethyl ethanoate	141-78-6	$\geq 5 - < 10$ *
n-Butyl acetate	Acetic acid, butyl ester	123-86-4	$\geq 5 - < 10$ *
Acetone	2-Propanone	67-64-1	$\geq 1 - < 5$ *
Aluminium	No data available	7429-90-5	$\geq 1 - < 5$ *
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Naphtha (petroleum), hydrotreated heavy	64742-48-9	$\geq 1 - < 5$ *
Butan-1-ol	n-Butyl alcohol	71-36-3	$\geq 1 - < 5$ *
Quaternary ammonium compounds, cocoalkylethyldimethyl, Et sulfates	Cocoethyldimonium	68308-64-5	$\geq 0.1 - < 1$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/06/2024
9.1	11/14/2024	10770804-00012	Date of first issue: 12/23/2009

- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/06/2024
9.1	11/14/2024	10770804-00012	Date of first issue: 12/23/2009

- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.
- Conditions for safe storage : Store locked up.
Keep in a cool, well-ventilated place.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases

Recommended storage temperature : < 50 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Dimethyl ether	115-10-6	TWA	1,000 ppm	CA BC OEL
Xylene	1330-20-7	TWA	100 ppm 434 mg/m ³	CA AB OEL
		STEL	150 ppm 651 mg/m ³	CA AB OEL
		TWAEV	100 ppm 434 mg/m ³	CA QC OEL
		STEV	150 ppm 651 mg/m ³	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
Ethyl acetate	141-78-6	TWA	20 ppm	ACGIH
		TWA	400 ppm 1,440 mg/m ³	CA AB OEL
		TWA	150 ppm	CA BC OEL
		TWAEV	400 ppm 1,440 mg/m ³	CA QC OEL
		TWA	400 ppm	ACGIH
		STEL	200 ppm 950 mg/m ³	CA AB OEL
n-Butyl acetate	123-86-4	TWA	150 ppm 713 mg/m ³	CA AB OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	150 ppm	CA QC OEL
		TWA	50 ppm	CA BC OEL

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
 Date of first issue: 12/23/2009

		STEL	150 ppm	CA BC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m ³	CA AB OEL
		STEL	750 ppm 1,800 mg/m ³	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	250 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Aluminium	7429-90-5	TWA (Dust)	10 mg/m ³	CA AB OEL
		TWA (Respirable)	1 mg/m ³ (Aluminum)	CA BC OEL
		TWA (powder)	5 mg/m ³ (Aluminum)	CA AB OEL
		TWAEV (respirable dust)	5 mg/m ³	CA QC OEL
		TWA (Respirable particulate matter)	1 mg/m ³ (Aluminum)	ACGIH
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Butan-1-ol	71-36-3	TWA	20 ppm 60 mg/m ³	CA AB OEL
		TWA	15 ppm	CA BC OEL
		C	30 ppm	CA BC OEL
		C	50 ppm 152 mg/m ³	CA QC OEL
		TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene	1330-20-7	Methyl-hippuric acids	Urine	End of shift (As soon as possible)	0.3 g/g creatinine	ACGIH BEI

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

				after exposure ceases)		
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : butyl-rubber

Break through time : > 480 min

Glove thickness : 0.7 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/06/2024
9.1	11/14/2024	10770804-00012	Date of first issue: 12/23/2009

When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	aerosol
Propellant	:	Dimethyl ether
Color	:	silver
Odor	:	characteristic
Odor Threshold	:	No data available
pH	:	Solvent mixture; pH value determination not possible, no aqueous solution
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	-24 °C
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Density	:	0.81 g/cm ³ (20 °C)
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/06/2024
9.1	11/14/2024	10770804-00012	Date of first issue: 12/23/2009

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics
Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.
Vapors may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

Dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 164000 ppm
Exposure time: 4 h
Test atmosphere: gas

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): 27.571 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg

Ethyl acetate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 22.5 mg/l
Exposure time: 6 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 20,000 mg/kg

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Acetone:

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Aluminium:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 0.888 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 4,951 mg/m³
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rabbit): >= 3,160 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Butan-1-ol:

- Acute oral toxicity : LD50 (Rat, female): 790 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 17.76 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit, male): 3,430 mg/kg

Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates:

- Acute oral toxicity : LD50 (Rat): 570 mg/kg
Method: OECD Test Guideline 401
- Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.
- Acute dermal toxicity : LD50 (Rabbit, male): > 200 - 1,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Skin corrosion/irritation

Causes skin irritation.

Components:

Xylene:

Species : Rabbit
Result : Skin irritation

Ethyl acetate:

Species : Rabbit
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

n-Butyl acetate:

Species : Rabbit
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Acetone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Aluminium:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Species : Rabbit
Result : Mild skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Butan-1-ol:

Species : Rabbit
Result : Skin irritation

Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 1 to 4 hours of exposure

Serious eye damage/eye irritation

Causes serious eye irritation.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Components:

Xylene:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Ethyl acetate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

n-Butyl acetate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Acetone:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

Aluminium:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Butan-1-ol:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates:

Result : Irreversible effects on the eye
Remarks : Based on skin corrosivity.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Components:

Xylene:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : negative

Ethyl acetate:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

n-Butyl acetate:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Acetone:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Aluminium:

Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Butan-1-ol:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : negative

Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates:

Test Type : Buehler Test

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Dimethyl ether:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)
Application Route: inhalation (gas)
Result: negative

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Ethyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Hamster
Application Route: Ingestion
Result: negative

n-Butyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Acetone:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Aluminium:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Species: Mouse
Application Route: Ingestion
Result: negative

Butan-1-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Dimethyl ether:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 2 Years
Result : negative

Xylene:

Species : Rat
Application Route : Ingestion

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Exposure time : 103 weeks
Result : negative

Acetone:

Species : Mouse
Application Route : Skin contact
Exposure time : 424 days
Result : negative

Aluminium:

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 86 weeks
Result : negative

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 105 weeks
Result : negative
Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Dimethyl ether:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Ethyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Inhalation
Result: negative
Remarks: Based on data from similar materials

Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

n-Butyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Aluminium:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Result: negative

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Butan-1-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Skin contact
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Components:

Dimethyl ether:

Assessment : May cause drowsiness or dizziness.

Xylene:

Assessment : May cause respiratory irritation.

Ethyl acetate:

Assessment : May cause drowsiness or dizziness.

n-Butyl acetate:

Assessment : May cause drowsiness or dizziness.

Acetone:

Assessment : May cause drowsiness or dizziness.

Butan-1-ol:

Assessment : May cause respiratory irritation.

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Components:

Xylene:

Routes of exposure : inhalation (vapor)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Repeated dose toxicity

Components:

Dimethyl ether:

Species : Rat
NOAEL : 47.11 mg/l
Application Route : inhalation (vapor)
Exposure time : 2 y

Xylene:

Species : Rat
LOAEL : > 0.2 - 1 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Species : Rat
LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Ethyl acetate:

Species : Rat
NOAEL : 900 mg/kg
LOAEL : 3,600 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
NOAEL : 1.28 mg/l
LOAEL : 2.75 mg/kg
Application Route : inhalation (vapor)
Exposure time : 94 Days

n-Butyl acetate:

Species : Rat
NOAEL : 2.4 mg/l
Application Route : inhalation (vapor)
Exposure time : 90 Days

Acetone:

Species : Rat
NOAEL : 900 mg/kg
LOAEL : 1,700 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
NOAEL : 45 mg/l
Application Route : inhalation (vapor)
Exposure time : 8 Weeks

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Species : Rat
NOAEL : >= 1,000 mg/kg
Application Route : Ingestion
Exposure time : 54 Days
Remarks : Based on data from similar materials

Butan-1-ol:

Species : Rat
NOAEL : 125 mg/kg
LOAEL : 500 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/06/2024
9.1	11/14/2024	10770804-00012	Date of first issue: 12/23/2009

Species	:	Rat
NOAEL	:	> 1 mg/l
Application Route	:	inhalation (vapor)
Exposure time	:	13 Weeks
Remarks	:	Based on data from similar materials

Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates:

Species	:	Rat
NOAEL	:	> 100 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days
Method	:	OECD Test Guideline 408
Remarks	:	Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Components:

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Butan-1-ol:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Experience with human exposure

Components:

Ethyl acetate:

Eye contact	:	Target Organs: Eye Symptoms: Irritation
-------------	---	--

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Dimethyl ether:

- Toxicity to fish : LC50 (*Poecilia reticulata* (guppy)): > 4,100 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 4,400 mg/l
Exposure time: 48 h
- Toxicity to microorganisms : EC10 (*Pseudomonas putida*): > 1,600 mg/l

Xylene:

- Toxicity to fish : LC50 (*Oncorhynchus mykiss* (rainbow trout)): 13.5 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 1 - 10 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EC50 (*Skeletonema costatum* (marine diatom)): 10 mg/l
Exposure time: 72 h
- Toxicity to fish (Chronic toxicity) : NOEC (*Danio rerio* (zebra fish)): > 0.1 - < 1 mg/l
Exposure time: 35 d
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10 (*Daphnia magna* (Water flea)): > 1 - 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials
- Toxicity to microorganisms : NOEC: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Ethyl acetate:

- Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): 220 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 3,090 mg/l
Exposure time: 24 h
Method: DIN 38412
- Toxicity to algae/aquatic plants : NOEC (*Desmodesmus subspicatus* (green algae)): > 100 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): > 1 - 9.65 mg/l
Exposure time: 32 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 2.4 mg/l
Exposure time: 24 d

Toxicity to microorganisms : EC10 (Photobacterium phosphoreum): 1,650 mg/l
Exposure time: 0.25 h

n-Butyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp. (Water flea)): 44 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23.2 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

Acetone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 8,800 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): >= 79 mg/l

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/06/2024
9.1	11/14/2024	10770804-00012	Date of first issue: 12/23/2009

aquatic invertebrates (Chronic toxicity) : Exposure time: 21 d
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: 61,150 mg/l
Exposure time: 30 min
Method: ISO 8192

Aluminium:

Toxicity to fish : NOEC (Salmo trutta (brown trout)): > 80 µg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : NOEC (Daphnia magna (Water flea)): > 0.135 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Ecotoxicology Assessment

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): > 1 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Butan-1-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1,376 mg/l

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

- Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,328 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 225 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201
- EC10 (Raphidocelis subcapitata (freshwater green alga)): 134 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 4.1 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
- Toxicity to microorganisms : EC10 (Pseudomonas putida): 2,476 mg/l
Exposure time: 17 h
Method: DIN 38 412 Part 8

Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): 13.8 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.036 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.14 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- EC10 (Pseudokirchneriella subcapitata (green algae)): 0.01 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): > 0.01 - 0.1 mg/l
Exposure time: 28 d
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): > 0.001 - 0.01 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/06/2024
9.1	11/14/2024	10770804-00012	Date of first issue: 12/23/2009

Toxicity to microorganisms : EC10: 9 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Persistence and degradability

Components:

Dimethyl ether:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Xylene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Ethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 69 %
Exposure time: 20 d

n-Butyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Acetone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 28 d

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Butan-1-ol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 92 %
Exposure time: 20 d

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 67.77 %
Exposure time: 28 d
Method: OECD Test Guideline 310

Bioaccumulative potential

Components:

Dimethyl ether:

Partition coefficient: n-octanol/water : log Pow: 0.2

Xylene:

Partition coefficient: n-octanol/water : log Pow: 3.16
Remarks: Calculation

Ethyl acetate:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 30

Partition coefficient: n-octanol/water : log Pow: 0.68

n-Butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2.3

Acetone:

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

Butan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 1
Method: OECD Test Guideline 117

Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates:

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)
Bioconcentration factor (BCF): < 500
Remarks: Based on data from similar materials

Partition coefficient: n-octanol/water : log Pow: 3.26
Remarks: Calculation

Mobility in soil

No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/06/2024
9.1	11/14/2024	10770804-00012	Date of first issue: 12/23/2009

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

- UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
Environmentally hazardous : yes

IATA-DGR

- UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

- UN number : UN 1950
Proper shipping name : AEROSOLS
(Zinc, Quaternary ammonium compounds, coco alkylethyl-dimethyl, Et sulfates)
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : yes

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version 9.1 Revision Date: 11/14/2024 SDS Number: 10770804-00012 Date of last issue: 06/06/2024
Date of first issue: 12/23/2009

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
ERG Code : 126
Marine pollutant : yes(Zinc, Quaternary ammonium compounds, coco alkylethyl-dimethyl, Et sulfates)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 82.8 % / 679 g/l

The ingredients of this product are reported in the following inventories:

DSL : This product contains one or several components that are not on the Canadian DSL nor NDSL.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)

CA BC OEL : Canada. British Columbia OEL
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit
CA BC OEL / C : ceiling limit
CA QC OEL / TWAEV : Time-weighted average exposure value

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/06/2024
9.1	11/14/2024	10770804-00012	Date of first issue: 12/23/2009

CA QC OEL / STEV : Short-term exposure value
CA QC OEL / C : Ceiling

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/14/2024
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PERFECT LIGHT ZINC SPRAY, 325 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/06/2024
9.1	11/14/2024	10770804-00012	Date of first issue: 12/23/2009

CA / Z8